

TEST DATA OF DHS50B15

Regulated DC Power Supply
May 26, 2009

Approved by : Tatsuya Mano
Tatsuya Mano Design Manager

Prepared by : Shuuhei Sawada
Shuuhei Sawada Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)


Model DHS50B15

Item Input Current (by Input Voltage)

Object

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0	0.000	0.000	0.000
50	0.000	0.000	0.000
100	0.000	0.000	0.000
150	0.000	0.000	0.000
170	0.002	0.002	0.002
180	0.032	0.171	0.325
200	0.029	0.153	0.293
250	0.015	0.123	0.235
280	0.011	0.112	0.211
300	0.010	0.106	0.199
350	0.010	0.095	0.174
400	0.010	0.086	0.156
420	0.010	0.084	0.150
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model		DHS50B15																																																				
Item		Input Current (by Load Current)																																																				
Object																																																						
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>---□---</div><div>---○---</div></div><div><div>Input Volt.</div><div>Input Volt.</div><div>Input Volt.</div></div><div><div>200V</div><div>280V</div><div>400V</div></div></div> <p>Input Current [A]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>0.00</td><td>0.029</td><td>0.011</td><td>0.007</td></tr><tr><td>0.60</td><td>0.066</td><td>0.049</td><td>0.040</td></tr><tr><td>1.20</td><td>0.113</td><td>0.084</td><td>0.066</td></tr><tr><td>1.80</td><td>0.161</td><td>0.118</td><td>0.090</td></tr><tr><td>2.40</td><td>0.209</td><td>0.152</td><td>0.115</td></tr><tr><td>3.00</td><td>0.259</td><td>0.187</td><td>0.139</td></tr><tr><td>3.40</td><td>0.292</td><td>0.211</td><td>0.155</td></tr><tr><td>3.74</td><td>0.321</td><td>0.232</td><td>0.170</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	0.029	0.011	0.007	0.60	0.066	0.049	0.040	1.20	0.113	0.084	0.066	1.80	0.161	0.118	0.090	2.40	0.209	0.152	0.115	3.00	0.259	0.187	0.139	3.40	0.292	0.211	0.155	3.74	0.321	0.232	0.170	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0.00	0.029	0.011	0.007																																																			
0.60	0.066	0.049	0.040																																																			
1.20	0.113	0.084	0.066																																																			
1.80	0.161	0.118	0.090																																																			
2.40	0.209	0.152	0.115																																																			
3.00	0.259	0.187	0.139																																																			
3.40	0.292	0.211	0.155																																																			
3.74	0.321	0.232	0.170																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model		DHS50B15		Temperature		25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry		Figure A																																																				
Object																																																										
1.Graph				2.Values																																																						
<div><div><div>—△—</div><div>---□---</div><div>---○---</div></div><div><div>Input Volt.</div><div>Input Volt.</div><div>Input Volt.</div></div><div><div>200V</div><div>280V</div><div>400V</div></div></div> <div></div>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>0.00</td><td>6.00</td><td>3.10</td><td>2.80</td></tr><tr><td>0.60</td><td>13.30</td><td>13.90</td><td>16.20</td></tr><tr><td>1.20</td><td>22.80</td><td>23.50</td><td>26.60</td></tr><tr><td>1.80</td><td>32.30</td><td>33.10</td><td>36.30</td></tr><tr><td>2.40</td><td>41.90</td><td>42.80</td><td>46.10</td></tr><tr><td>3.00</td><td>51.80</td><td>52.50</td><td>55.90</td></tr><tr><td>3.40</td><td>58.50</td><td>59.20</td><td>62.40</td></tr><tr><td>3.74</td><td>64.30</td><td>64.90</td><td>68.00</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	6.00	3.10	2.80	0.60	13.30	13.90	16.20	1.20	22.80	23.50	26.60	1.80	32.30	33.10	36.30	2.40	41.90	42.80	46.10	3.00	51.80	52.50	55.90	3.40	58.50	59.20	62.40	3.74	64.30	64.90	68.00	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																									
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																							
0.00	6.00	3.10	2.80																																																							
0.60	13.30	13.90	16.20																																																							
1.20	22.80	23.50	26.60																																																							
1.80	32.30	33.10	36.30																																																							
2.40	41.90	42.80	46.10																																																							
3.00	51.80	52.50	55.90																																																							
3.40	58.50	59.20	62.40																																																							
3.74	64.30	64.90	68.00																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
Note: Slanted line shows the range of the rated load current.																																																										

Model	DHS50B15																																		
Item	Efficiency (by Input Voltage)	Temperature	25°C																																
		Testing Circuitry	Figure A																																
Object																																			
1.Graph		2.Values																																	
<div><div><div>---□--- Load 50%</div><div>—△— Load 100%</div></div><p>Efficiency [%]</p><p>Input Voltage [V]</p><p>Note: Slanted line shows the range of the rated input voltage.</p></div>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Efficiency [%]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>195</td><td>82.4</td><td>86.4</td></tr><tr><td>200</td><td>82.6</td><td>86.6</td></tr><tr><td>240</td><td>82.1</td><td>86.7</td></tr><tr><td>280</td><td>80.8</td><td>85.6</td></tr><tr><td>320</td><td>78.6</td><td>84.2</td></tr><tr><td>360</td><td>75.7</td><td>83.0</td></tr><tr><td>400</td><td>73.4</td><td>81.3</td></tr><tr><td>420</td><td>72.1</td><td>80.7</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	195	82.4	86.4	200	82.6	86.6	240	82.1	86.7	280	80.8	85.6	320	78.6	84.2	360	75.7	83.0	400	73.4	81.3	420	72.1	80.7	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
195	82.4	86.4																																	
200	82.6	86.6																																	
240	82.1	86.7																																	
280	80.8	85.6																																	
320	78.6	84.2																																	
360	75.7	83.0																																	
400	73.4	81.3																																	
420	72.1	80.7																																	
--	-	-																																	

COSEL

Model		DHS50B15		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object																																																								
1.Graph		<div><div>—△—</div>Input Volt. 200V</div> <div><div>---□---</div>Input Volt. 280V</div> <div><div>- -○- -</div>Input Volt. 400V</div>		2.Values																																																				
<div><div>Efficiency [%]</div><div><div>Load Current [A]</div></div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.60</td><td>66.7</td><td>63.9</td><td>53.8</td></tr><tr><td>1.20</td><td>78.3</td><td>76.5</td><td>67.1</td></tr><tr><td>1.80</td><td>82.6</td><td>80.8</td><td>73.4</td></tr><tr><td>2.40</td><td>85.1</td><td>83.4</td><td>77.8</td></tr><tr><td>3.00</td><td>86.1</td><td>84.9</td><td>80.1</td></tr><tr><td>3.40</td><td>86.6</td><td>85.6</td><td>81.3</td></tr><tr><td>3.74</td><td>86.6</td><td>85.7</td><td>82.0</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Efficiency [%]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	-	-	-	0.60	66.7	63.9	53.8	1.20	78.3	76.5	67.1	1.80	82.6	80.8	73.4	2.40	85.1	83.4	77.8	3.00	86.1	84.9	80.1	3.40	86.6	85.6	81.3	3.74	86.6	85.7	82.0	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.00	-	-	-																																																					
0.60	66.7	63.9	53.8																																																					
1.20	78.3	76.5	67.1																																																					
1.80	82.6	80.8	73.4																																																					
2.40	85.1	83.4	77.8																																																					
3.00	86.1	84.9	80.1																																																					
3.40	86.6	85.6	81.3																																																					
3.74	86.6	85.7	82.0																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								

COSEL

Model	DHS50B15																																
Item	Line Regulation	Temperature	25°C																														
Object	+15V3.4A	Testing Circuitry	Figure A																														
1.Graph		2.Values																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Output Voltage [V] Load 50%</th><th>Output Voltage [V] Load 100%</th></tr></thead><tbody><tr><td>195</td><td>14.981</td><td>14.980</td></tr><tr><td>200</td><td>14.981</td><td>14.980</td></tr><tr><td>240</td><td>14.981</td><td>14.980</td></tr><tr><td>280</td><td>14.981</td><td>14.980</td></tr><tr><td>320</td><td>14.981</td><td>14.980</td></tr><tr><td>360</td><td>14.981</td><td>14.980</td></tr><tr><td>400</td><td>14.981</td><td>14.981</td></tr><tr><td>420</td><td>14.982</td><td>14.981</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%	195	14.981	14.980	200	14.981	14.980	240	14.981	14.980	280	14.981	14.980	320	14.981	14.980	360	14.981	14.980	400	14.981	14.981	420	14.982	14.981	--	-	-		
Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%																															
195	14.981	14.980																															
200	14.981	14.980																															
240	14.981	14.980																															
280	14.981	14.980																															
320	14.981	14.980																															
360	14.981	14.980																															
400	14.981	14.981																															
420	14.982	14.981																															
--	-	-																															
Note: Slanted line shows the range of the rated input voltage.																																	

COSEL

Model	DHS50B15																																																					
Item	Load Regulation	Temperature	25°C																																																			
Object	+15V3.4A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div>—△— Input Volt. 200V</div><div>---□--- Input Volt. 280V</div><div>-·-○-·- Input Volt. 400V</div></div> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>0.00</td><td>14.991</td><td>14.991</td><td>14.991</td></tr><tr><td>0.60</td><td>14.980</td><td>14.980</td><td>14.981</td></tr><tr><td>1.20</td><td>14.980</td><td>14.980</td><td>14.980</td></tr><tr><td>1.80</td><td>14.980</td><td>14.980</td><td>14.980</td></tr><tr><td>2.40</td><td>14.980</td><td>14.980</td><td>14.980</td></tr><tr><td>3.00</td><td>14.980</td><td>14.980</td><td>14.980</td></tr><tr><td>3.40</td><td>14.980</td><td>14.980</td><td>14.980</td></tr><tr><td>3.74</td><td>14.980</td><td>14.979</td><td>14.979</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	14.991	14.991	14.991	0.60	14.980	14.980	14.981	1.20	14.980	14.980	14.980	1.80	14.980	14.980	14.980	2.40	14.980	14.980	14.980	3.00	14.980	14.980	14.980	3.40	14.980	14.980	14.980	3.74	14.980	14.979	14.979	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0.00	14.991	14.991	14.991																																																			
0.60	14.980	14.980	14.981																																																			
1.20	14.980	14.980	14.980																																																			
1.80	14.980	14.980	14.980																																																			
2.40	14.980	14.980	14.980																																																			
3.00	14.980	14.980	14.980																																																			
3.40	14.980	14.980	14.980																																																			
3.74	14.980	14.979	14.979																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						


- 7 -

BC-10331

COSEL


Model	DHS50B15	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+15V3.4A	

Input Volt. 280 V
Cycle 1000 ms


Load Current  3.4A / 20µs

Min. Load (0A) \longleftrightarrow
Load 100% (3.4A)

500mV/div




500 µs/div




5 ms/div

Min. Load (0A) \longleftrightarrow
Load 50% (1.7A)

500mV/div




500 µs/div




5 ms/div

Load 10% (0.34A) \longleftrightarrow
Load 100% (3.4A)

500mV/div





500 µs/div



5 ms/div

Model	DHS50B15																																																																												
Item	Ripple Voltage (by Load Current)	Temperature	25°C																																																																										
Object	+15V3.4A	Testing Circuitry	Figure B																																																																										
1.Graph		2.Values																																																																											
<div><div><div><div></div><div>Input Volt. 200V</div></div><div><div></div><div>Input Volt. 400V</div></div></div><div><table><thead><tr><th>Load Current [A]</th><th>Input Volt. 200 [V]</th><th>Input Volt. 400 [V]</th></tr></thead><tbody><tr><td>0.00</td><td>20</td><td>30</td></tr><tr><td>0.60</td><td>50</td><td>60</td></tr><tr><td>1.20</td><td>50</td><td>60</td></tr><tr><td>1.80</td><td>50</td><td>60</td></tr><tr><td>2.40</td><td>50</td><td>60</td></tr><tr><td>3.00</td><td>50</td><td>60</td></tr><tr><td>3.40</td><td>50</td><td>60</td></tr><tr><td>3.74</td><td>50</td><td>60</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table></div></div> <div><div>Measured by 100 MHz Oscilloscope.</div><div>Ripple Voltage is shown as p-p in the figure below.</div><div>Note: Slanted line shows the range of the rated load current.</div></div> <div><div>Ripple [mVp-p]</div><div></div><div>Fig.Complex Ripple Wave Form</div></div>		Load Current [A]	Input Volt. 200 [V]	Input Volt. 400 [V]	0.00	20	30	0.60	50	60	1.20	50	60	1.80	50	60	2.40	50	60	3.00	50	60	3.40	50	60	3.74	50	60	--	-	-	--	-	-	--	-	-	<table><thead><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 200 [V]</th><th>Input Volt. 400 [V]</th></tr></thead><tbody><tr><td>0.00</td><td>20</td><td>30</td></tr><tr><td>0.60</td><td>50</td><td>60</td></tr><tr><td>1.20</td><td>50</td><td>60</td></tr><tr><td>1.80</td><td>50</td><td>60</td></tr><tr><td>2.40</td><td>50</td><td>60</td></tr><tr><td>3.00</td><td>50</td><td>60</td></tr><tr><td>3.40</td><td>50</td><td>60</td></tr><tr><td>3.74</td><td>50</td><td>60</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.00	20	30	0.60	50	60	1.20	50	60	1.80	50	60	2.40	50	60	3.00	50	60	3.40	50	60	3.74	50	60	--	-	-	--	-	-	--	-	-
Load Current [A]	Input Volt. 200 [V]	Input Volt. 400 [V]																																																																											
0.00	20	30																																																																											
0.60	50	60																																																																											
1.20	50	60																																																																											
1.80	50	60																																																																											
2.40	50	60																																																																											
3.00	50	60																																																																											
3.40	50	60																																																																											
3.74	50	60																																																																											
--	-	-																																																																											
--	-	-																																																																											
--	-	-																																																																											
Load Current [A]	Ripple Voltage [mV]																																																																												
	Input Volt. 200 [V]	Input Volt. 400 [V]																																																																											
0.00	20	30																																																																											
0.60	50	60																																																																											
1.20	50	60																																																																											
1.80	50	60																																																																											
2.40	50	60																																																																											
3.00	50	60																																																																											
3.40	50	60																																																																											
3.74	50	60																																																																											
--	-	-																																																																											
--	-	-																																																																											
--	-	-																																																																											

		Temperature 25°C Testing Circuitry Figure B																																						
Model	DHS50B15																																							
Item	Ripple-Noise																																							
Object	+15V3.4A																																							
1.Graph <div style="text-align: right;"> —△— Input Volt. 200V - - -○- - - Input Volt. 400V </div>  <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <div style="text-align: center;">  <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p> </div>		2.Values <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th><th colspan="2">Ripple-Noise [mV]</th></tr> <tr> <th>Input Volt. 200 [V]</th><th>Input Volt. 400 [V]</th></tr> </thead> <tbody> <tr><td>0.00</td><td>25</td><td>35</td></tr> <tr><td>0.60</td><td>50</td><td>65</td></tr> <tr><td>1.20</td><td>50</td><td>65</td></tr> <tr><td>1.80</td><td>50</td><td>65</td></tr> <tr><td>2.40</td><td>50</td><td>65</td></tr> <tr><td>3.00</td><td>50</td><td>65</td></tr> <tr><td>3.40</td><td>50</td><td>65</td></tr> <tr><td>3.74</td><td>50</td><td>65</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.00	25	35	0.60	50	65	1.20	50	65	1.80	50	65	2.40	50	65	3.00	50	65	3.40	50	65	3.74	50	65	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 200 [V]	Input Volt. 400 [V]																																						
0.00	25	35																																						
0.60	50	65																																						
1.20	50	65																																						
1.80	50	65																																						
2.40	50	65																																						
3.00	50	65																																						
3.40	50	65																																						
3.74	50	65																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						

Model		DHS50B15
Item		Ripple Voltage (by Ambient Temp.)
Object		+15V3.4A

1.Graph

□

Load 50%

—

△

—

Load 100%

300

250

200

150

100

50

0

60

40

20

0

20

40

60

80

100

120

Ambient Temperature [°C]

300

250

200

150

100

50

0

60

40

20

0

20

40

60

80

100

120

Ambient Temperature [°C]

Input Volt. 280V

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	70	70
-40	70	70
-20	70	70
0	65	65
25	60	60
40	60	60
55	60	60
70	60	60
85	60	60
100	55	55
--	-	-

COSEL

Model		DHS50B15	Testing Circuitry Figure A																																																			
Item		Ambient Temperature Drift																																																				
Object		+15V3.4A																																																				
1.Graph		<div><div>—△—</div> Input Volt. 200V</div> <div><div>---□---</div> Input Volt. 280V</div> <div><div>-·-○-·-</div> Input Volt. 400V</div> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2.Values																																																			
		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>-50</td><td>14.905</td><td>14.907</td><td>14.909</td></tr><tr><td>-40</td><td>14.920</td><td>14.922</td><td>14.924</td></tr><tr><td>-20</td><td>14.946</td><td>14.947</td><td>14.949</td></tr><tr><td>0</td><td>14.966</td><td>14.966</td><td>14.968</td></tr><tr><td>25</td><td>14.980</td><td>14.980</td><td>14.980</td></tr><tr><td>40</td><td>14.985</td><td>14.984</td><td>14.983</td></tr><tr><td>55</td><td>14.987</td><td>14.985</td><td>14.985</td></tr><tr><td>70</td><td>14.986</td><td>14.984</td><td>14.984</td></tr><tr><td>85</td><td>14.984</td><td>14.982</td><td>14.981</td></tr><tr><td>100</td><td>14.979</td><td>14.977</td><td>14.976</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>	Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	-50	14.905	14.907	14.909	-40	14.920	14.922	14.924	-20	14.946	14.947	14.949	0	14.966	14.966	14.968	25	14.980	14.980	14.980	40	14.985	14.984	14.983	55	14.987	14.985	14.985	70	14.986	14.984	14.984	85	14.984	14.982	14.981	100	14.979	14.977	14.976	--	-	-	-	
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
-50	14.905	14.907	14.909																																																			
-40	14.920	14.922	14.924																																																			
-20	14.946	14.947	14.949																																																			
0	14.966	14.966	14.968																																																			
25	14.980	14.980	14.980																																																			
40	14.985	14.984	14.983																																																			
55	14.987	14.985	14.985																																																			
70	14.986	14.984	14.984																																																			
85	14.984	14.982	14.981																																																			
100	14.979	14.977	14.976																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated ambient temperature.																																																						



		Testing Circuitry Figure A
Model	DHS50B15	
Item	Output Voltage Accuracy	
Object	+15V3.4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 100°C

Input Voltage : 200 - 400V

Load Current : 0 - 3.4A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	70	200	0	15.004	±42	±0.3
Minimum Voltage	-40	200	3.4	14.920		

COSEL

Model		DHS50B15	
Item		Time Lapse Drift	
Object		+15V3.4A	

1.Graph


Output Voltage [V]

</

COSEL


Model	DHS50B15	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V3.4A		

1. Graph



2. Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	26.0	5.5	31.5	1.6	37.3
100 %	26.0	8.3	34.3	0.7	19.1



Model		DHS50B15
Item		Minimum Input Voltage for Regulated Output Voltage
Object		+15V3.4A

1.Graph

□

Load 50%

—

△

—

Load 100%

Input Voltage [V]

<

Model	DHS50B15																																																									
Item	Overcurrent Protection	Temperature	25°C																																																							
		Testing Circuitry	Figure A																																																							
Object	+15V3.4A																																																									
1.Graph		2.Values																																																								
<div><div>— Input Volt. 200V</div><div>— Input Volt. 280V</div><div>— Input Volt. 400V</div></div> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 6V to 0V.</p>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>15.0</td><td>3.42</td><td>3.42</td><td>3.42</td></tr><tr><td>14.3</td><td>4.22</td><td>4.32</td><td>4.49</td></tr><tr><td>13.5</td><td>4.25</td><td>4.36</td><td>4.52</td></tr><tr><td>12.0</td><td>4.31</td><td>4.44</td><td>4.58</td></tr><tr><td>10.5</td><td>4.39</td><td>4.51</td><td>4.61</td></tr><tr><td>9.0</td><td>4.46</td><td>4.58</td><td>4.66</td></tr><tr><td>7.5</td><td>4.53</td><td>4.62</td><td>4.64</td></tr><tr><td>6.0</td><td>4.66</td><td>4.70</td><td>4.59</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	15.0	3.42	3.42	3.42	14.3	4.22	4.32	4.49	13.5	4.25	4.36	4.52	12.0	4.31	4.44	4.58	10.5	4.39	4.51	4.61	9.0	4.46	4.58	4.66	7.5	4.53	4.62	4.64	6.0	4.66	4.70	4.59	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																							
15.0	3.42	3.42	3.42																																																							
14.3	4.22	4.32	4.49																																																							
13.5	4.25	4.36	4.52																																																							
12.0	4.31	4.44	4.58																																																							
10.5	4.39	4.51	4.61																																																							
9.0	4.46	4.58	4.66																																																							
7.5	4.53	4.62	4.64																																																							
6.0	4.66	4.70	4.59																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							

COSEL

Model		DHS50B15
Item		Overvoltage Protection
Object		+15V3.4A

1.Graph

—△—

Input Volt. 200V

---□---

Input Volt. 280V

---○---

Input Volt. 400V

Operating Point [V]

<




Figure A




Figure B