

TEST DATA OF DPG500

(200V INPUT)

AC-DC Front End Module
March.8. 2010

Approved by : Tatsuya Mano
Tatsuya Mano Design Manager

Prepared by : Satoshi Uetani
Satoshi Uetani Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ambient Temperature Drift	13
14.Output Voltage Accuracy	14
15.Time Lapse Drift	15
16.Rise and Fall Time	16
17.Minimum Input Voltage for Regulated Output Voltage	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 20)

COSEL

Model		DPG500																																																				
Item		Input Current (by Load Power)																																																				
Object																																																						
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt. 170V</div></div><div><div>---□---</div><div>Input Volt. 200V</div></div><div><div>---○---</div><div>Input Volt. 264V</div></div></div> <p>Input Current [A]</p> <p>Load Power [W]</p> <p>Note: Sianted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Power [W]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 170[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 264[V]</th></tr><tr><td>0</td><td>0.30</td><td>0.35</td><td>0.46</td></tr><tr><td>50</td><td>0.47</td><td>0.47</td><td>0.53</td></tr><tr><td>150</td><td>1.05</td><td>0.92</td><td>0.83</td></tr><tr><td>250</td><td>1.65</td><td>1.42</td><td>1.21</td></tr><tr><td>300</td><td>1.95</td><td>1.67</td><td>1.39</td></tr><tr><td>400</td><td>2.56</td><td>2.18</td><td>1.79</td></tr><tr><td>500</td><td>3.17</td><td>2.69</td><td>2.20</td></tr><tr><td>550</td><td>3.47</td><td>2.95</td><td>2.39</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Power [W]	Input Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	0.30	0.35	0.46	50	0.47	0.47	0.53	150	1.05	0.92	0.83	250	1.65	1.42	1.21	300	1.95	1.67	1.39	400	2.56	2.18	1.79	500	3.17	2.69	2.20	550	3.47	2.95	2.39	--	-	-	-	--	-	-	-	--	-	-	-
Load Power [W]	Input Current [A]																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
0	0.30	0.35	0.46																																																			
50	0.47	0.47	0.53																																																			
150	1.05	0.92	0.83																																																			
250	1.65	1.42	1.21																																																			
300	1.95	1.67	1.39																																																			
400	2.56	2.18	1.79																																																			
500	3.17	2.69	2.20																																																			
550	3.47	2.95	2.39																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			



Model

DPG500

Item

Input Power (by Load Power)

Object

1.Graph

—△—

Input Volt. 170V

---□---

Input Volt. 200V

---○---

Input Volt. 264V

Note: Slanted line shows the range of the rated load current.

Temperature

25°C

Testing Circuitry

Figure A

2.Values

Load Power [W]	Input Power [W]		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
0	3.8	4.1	4.0
50	55.3	55.1	59.1
150	159.1	158.5	160.1
250	262.7	261.5	259.2
300	314.7	313.1	311.8
400	418.8	416.6	414.8
500	524.5	521.3	520.5
550	575.5	571.8	570.8
--	-	-	-
--	-	-	-
--	-	-	-

2

BC-10386

COSEL

Model		DPG500																																	
Item		Efficiency (by Input Voltage)																																	
Object																																			
1.Graph		2.Values																																	
<div><div><div><div><div></div><div></div><div></div></div><div></div><div></div></div><div><div><div></div><div></div><div></div></div><div></div><div></div></div></div><div>Load 50%</div><div>Load 100%</div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Efficiency [%]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>150</td><td>95.4</td><td>95.7</td></tr><tr><td>170</td><td>95.9</td><td>96.1</td></tr><tr><td>180</td><td>96.1</td><td>96.4</td></tr><tr><td>200</td><td>96.3</td><td>96.7</td></tr><tr><td>220</td><td>96.6</td><td>97.0</td></tr><tr><td>240</td><td>96.7</td><td>97.3</td></tr><tr><td>255</td><td>96.8</td><td>97.3</td></tr><tr><td>264</td><td>96.8</td><td>97.3</td></tr><tr><td>280</td><td>97.8</td><td>97.9</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	150	95.4	95.7	170	95.9	96.1	180	96.1	96.4	200	96.3	96.7	220	96.6	97.0	240	96.7	97.3	255	96.8	97.3	264	96.8	97.3	280	97.8	97.9		
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
150	95.4	95.7																																	
170	95.9	96.1																																	
180	96.1	96.4																																	
200	96.3	96.7																																	
220	96.6	97.0																																	
240	96.7	97.3																																	
255	96.8	97.3																																	
264	96.8	97.3																																	
280	97.8	97.9																																	
		BC-10386																																	

COSEL

Model

DPG500

Item

Efficiency (by Load Power)

Object

1.Graph

—△—

Input Volt. 170V

---□---

Input Volt. 200V

---○---

Input Volt. 264V

Efficiency [%]

Load Power [W]

Note: Slanted line shows the range of the rated load current.

Temperature

25°C

Testing Circuitry

Figure A

2.Values

Load Power [W]	Efficiency [%]		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
0	-	-	-
50	92.2	92.4	92.6
150	95.3	95.6	96.1
250	95.9	96.3	96.8
300	95.9	96.5	97.1
400	96.1	96.7	97.2
500	96.1	96.7	97.3
550	96.1	96.7	97.5
--	-	-	-
--	-	-	-
--	-	-	-

4

BC-10386

COSEL

LOREL

Model	DPG500
Item	Power Factor (by Input Voltage)
Object	_____

1.Graph

□

Load 50%

△

Load 100%

Note: Slanted line shows the range of the rated input voltage.

Temperature25°C

Testing CircuitryFigure A

2.Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
150	0.946	0.976
170	0.938	0.973
180	0.934	0.971
200	0.922	0.968
220	0.908	0.961
240	0.890	0.956
255	0.880	0.952
264	0.874	0.950
270	0.855	0.940
280	0.384	0.602

- 5 -

BC-10386

COSEL

LOREL

Model	DPG500
Item	Power Factor (by Load Power)
Object	

1.Graph

—△—

Input Volt. 170V

---□---

Input Volt. 200V

---○---

Input Volt. 264V

Power Factor

Load Power [W]

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values


Load Power [W]	Power Factor		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
50	0.690	0.589	0.426
150	0.894	0.859	0.766
250	0.938	0.922	0.874
300	0.949	0.938	0.901
400	0.964	0.957	0.932
500	0.973	0.968	0.950
550	0.976	0.971	0.956
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

- 6 -

BC-10386


COSEL

Model	DPG500	Temperature 25°C Testing Circuitry Figure A
Item	Inrush Current	
Object	_____	



Input Voltage 200 V
Frequency 60 Hz
Load 0 %

Primary inrush current 28.8 A
Secondary inrush current 16.0 A





COSEL		Temperature 25°C Testing Circuitry Figure B
Model	DPG500	
Item	Leakage Current	
Object	_____	

1.Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A)DEN-AN	-	-	-
(B)IEC60950-1	-	-	-

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B)IEC60950-1	0.25	0.31	0.42

2.Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model		DPG500	
Item		Line Regulation	
Object		+360V 500W	
1.Graph		2.Values	

---□---

Load 50%

—△—

Load 100%

Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%
150	360.89	360.88
170	360.89	360.88
180	360.90	360.89
200	360.90	360.89
220	360.91	360.90
240	360.91	360.91
255	375.02	374.73
264	384.11	384.01
280	387.90	386.06

Note: Slanted line shows the range of the rated input voltage.

9


BC-10386

COSEL

Model	DPG500																																																					
Item	Load Regulation	Temperature	25°C																																																			
Object	+360V 500W	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>---□---</div><div>-·○-·-</div></div><div><div>Input Volt. 170V</div><div>Input Volt. 200V</div><div>Input Volt. 264V</div></div></div> <p>Output Voltage [V]</p> <p>Load Power [W]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Power [W]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 170[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 264[V]</th></tr><tr><td>0</td><td>360.89</td><td>360.91</td><td>384.81</td></tr><tr><td>50</td><td>360.88</td><td>360.90</td><td>384.80</td></tr><tr><td>150</td><td>360.88</td><td>360.89</td><td>384.80</td></tr><tr><td>250</td><td>360.88</td><td>360.89</td><td>384.79</td></tr><tr><td>300</td><td>360.87</td><td>360.89</td><td>384.79</td></tr><tr><td>400</td><td>360.87</td><td>360.88</td><td>384.79</td></tr><tr><td>500</td><td>360.87</td><td>360.88</td><td>384.79</td></tr><tr><td>550</td><td>360.87</td><td>360.88</td><td>384.79</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Power [W]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	360.89	360.91	384.81	50	360.88	360.90	384.80	150	360.88	360.89	384.80	250	360.88	360.89	384.79	300	360.87	360.89	384.79	400	360.87	360.88	384.79	500	360.87	360.88	384.79	550	360.87	360.88	384.79	--	-	-	-	--	-	-	-	--	-	-	-
Load Power [W]	Output Voltage [V]																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
0	360.89	360.91	384.81																																																			
50	360.88	360.90	384.80																																																			
150	360.88	360.89	384.80																																																			
250	360.88	360.89	384.79																																																			
300	360.87	360.89	384.79																																																			
400	360.87	360.88	384.79																																																			
500	360.87	360.88	384.79																																																			
550	360.87	360.88	384.79																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

- 10 -

BC-10386



Model		DPG500	
Item		Ripple Voltage (by Load Current)	
Object		+360V500W	
1.Graph		2.Values	


Testing Circuitry Figure A



Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
-50	359.87	359.88	384.89
-40	360.14	360.15	384.70
-20	360.53	360.54	384.38
0	360.76	360.77	384.32
25	360.86	360.86	383.60
40	360.78	360.79	383.46
55	360.66	360.66	383.33
70	360.49	360.48	383.12
85	360.21	360.22	382.81
100	359.92	359.92	384.27
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.


COSEL

Model	DPG500																								
Item	Time Lapse Drift	Temperature	25°C																						
		Testing Circuitry	Figure A																						
Object	+360V 500W																								
1.Graph		2.Values																							
<div><p>Output Voltage [V]</p><p>Time [H]</p><p>Input Volt. 200V</p><p>Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>360.85</td></tr><tr><td>0.5</td><td>360.89</td></tr><tr><td>1.0</td><td>360.89</td></tr><tr><td>2.0</td><td>360.88</td></tr><tr><td>3.0</td><td>360.88</td></tr><tr><td>4.0</td><td>360.88</td></tr><tr><td>5.0</td><td>360.88</td></tr><tr><td>6.0</td><td>360.88</td></tr><tr><td>7.0</td><td>360.88</td></tr><tr><td>8.0</td><td>360.88</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	360.85	0.5	360.89	1.0	360.89	2.0	360.88	3.0	360.88	4.0	360.88	5.0	360.88	6.0	360.88	7.0	360.88	8.0	360.88
Time since start [H]	Output Voltage [V]																								
0.0	360.85																								
0.5	360.89																								
1.0	360.89																								
2.0	360.88																								
3.0	360.88																								
4.0	360.88																								
5.0	360.88																								
6.0	360.88																								
7.0	360.88																								
8.0	360.88																								

- 15 -

BC-10386

COSEL



COSEL

Model		DPG500																																					
Item		Minimum Input Voltage for Regulated Output Voltage																																					
Object		+360V 500W																																					
1.Graph		Testing Circuitry Figure A																																					
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Ambient Temperature [°C]</th><th>Load 50% [V]</th><th>Load 100% [V]</th></tr></thead><tbody><tr><td>-50</td><td>73</td><td>88</td></tr><tr><td>-40</td><td>73</td><td>88</td></tr><tr><td>-20</td><td>73</td><td>89</td></tr><tr><td>0</td><td>73</td><td>89</td></tr><tr><td>25</td><td>73</td><td>89</td></tr><tr><td>40</td><td>73</td><td>90</td></tr><tr><td>55</td><td>73</td><td>90</td></tr><tr><td>70</td><td>73</td><td>90</td></tr><tr><td>85</td><td>72</td><td>90</td></tr><tr><td>100</td><td>72</td><td>91</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Load 50% [V]	Load 100% [V]	-50	73	88	-40	73	88	-20	73	89	0	73	89	25	73	89	40	73	90	55	73	90	70	73	90	85	72	90	100	72	91	--	-	-	2.Values	
Ambient Temperature [°C]	Load 50% [V]	Load 100% [V]																																					
-50	73	88																																					
-40	73	88																																					
-20	73	89																																					
0	73	89																																					
25	73	89																																					
40	73	90																																					
55	73	90																																					
70	73	90																																					
85	72	90																																					
100	72	91																																					
--	-	-																																					
Note: Slanted line shows the range of the rated ambient temperature.																																							

Testing Circuitry Figure A



Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
-50	412.00	412.00	412.00
-40	416.00	416.00	416.00
-20	416.00	416.00	416.00
0	420.00	420.00	420.00
25	424.00	424.00	424.00
40	424.00	424.00	424.00
55	424.00	424.00	424.00
70	424.00	424.00	424.00
85	424.00	424.00	424.00
100	424.00	424.00	424.00
-	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)