

# TEST DATA OF G1W-12

Regulated DC Power Supply  
October 13, 2010

Approved by : Eiyoshi Wakamatsu  
Eiyoshi Wakamatsu Design Manager

Prepared by : Satoshi Kinoshita  
Satoshi Kinoshita Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Load Current) . . . . .	1
2.Input Power (by Load Current) . . . . .	2
3.Efficiency (by Input Voltage) . . . . .	3
4.Efficiency (by Load Current) . . . . .	4
5.Power Factor (by Input Voltage) . . . . .	5
6.Power Factor (by Load Current) . . . . .	6
7.Inrush Current . . . . .	7
8.Line Regulation . . . . .	8
9.Load Regulation . . . . .	9
10.Dynamic Load Response . . . . .	10
11.Ripple Voltage (by Load Current) . . . . .	12
12.Ripple Voltage (by Ambient Temperature) . . . . .	14
13.Ambient Temperature Drift . . . . .	15
14.Output Voltage Accuracy . . . . .	16
15.Time Lapse Drift . . . . .	17
16.Rise and Fall Time . . . . .	18
17.Hold-Up Time . . . . .	20
18.Instantaneous Interruption Compensation . . . . .	22
19.Minimum Input Voltage for Regulated Output Voltage . . . . .	24
20.Overcurrent Protection . . . . .	25
21.Figure of Testing Circuitry . . . . .	26

(Final Page 26)

# COSEL

Model		G1W-12		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph				2.Values																																																				
<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>—△—</div><div>---□---</div><div>-·-○-·-</div></div><div><div>Input Volt.</div><div>Input Volt.</div><div>Input Volt.</div></div><div><div>90V</div><div>100V</div><div>110V</div></div></div><div><div><div>0.25</div><div>0.20</div><div>0.15</div><div>0.10</div><div>0.05</div><div>0.00</div></div><div><div>0</div><div>20</div><div>40</div><div>60</div><div>80</div><div>100</div><div>120</div></div></div><div><div>Input Current [A]</div><div>Load Ration [%]</div></div></div>				<table><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0</td><td>0.015</td><td>0.016</td><td>0.017</td></tr><tr><td>20</td><td>0.056</td><td>0.058</td><td>0.059</td></tr><tr><td>40</td><td>0.091</td><td>0.093</td><td>0.095</td></tr><tr><td>60</td><td>0.123</td><td>0.125</td><td>0.128</td></tr><tr><td>80</td><td>0.153</td><td>0.156</td><td>0.159</td></tr><tr><td>100</td><td>0.182</td><td>0.186</td><td>0.190</td></tr><tr><td>110</td><td>0.196</td><td>0.200</td><td>0.204</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Ration [%]	Input Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	0.015	0.016	0.017	20	0.056	0.058	0.059	40	0.091	0.093	0.095	60	0.123	0.125	0.128	80	0.153	0.156	0.159	100	0.182	0.186	0.190	110	0.196	0.200	0.204	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																							
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																					
0	0.015	0.016	0.017																																																					
20	0.056	0.058	0.059																																																					
40	0.091	0.093	0.095																																																					
60	0.123	0.125	0.128																																																					
80	0.153	0.156	0.159																																																					
100	0.182	0.186	0.190																																																					
110	0.196	0.200	0.204																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					

-

1

-

BC-10211

# COSEL

Model		G1W-12		Temperature 25°C																																																	
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																	
Object		_____																																																			
1.Graph				2.Values																																																	
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th>Load Ratio [%]</th><th>Input Power [W] (90V)</th><th>Input Power [W] (100V)</th><th>Input Power [W] (110V)</th></tr></thead><tbody><tr><td>0</td><td>0.80</td><td>0.90</td><td>1.10</td></tr><tr><td>20</td><td>3.40</td><td>3.80</td><td>4.30</td></tr><tr><td>40</td><td>5.90</td><td>6.60</td><td>7.30</td></tr><tr><td>60</td><td>8.40</td><td>9.40</td><td>10.40</td></tr><tr><td>80</td><td>10.80</td><td>12.10</td><td>13.40</td></tr><tr><td>100</td><td>13.20</td><td>14.80</td><td>16.40</td></tr><tr><td>110</td><td>14.40</td><td>16.10</td><td>17.90</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>				Load Ratio [%]	Input Power [W] (90V)	Input Power [W] (100V)	Input Power [W] (110V)	0	0.80	0.90	1.10	20	3.40	3.80	4.30	40	5.90	6.60	7.30	60	8.40	9.40	10.40	80	10.80	12.10	13.40	100	13.20	14.80	16.40	110	14.40	16.10	17.90	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Ratio [%]	Input Power [W] (90V)	Input Power [W] (100V)	Input Power [W] (110V)																																																		
0	0.80	0.90	1.10																																																		
20	3.40	3.80	4.30																																																		
40	5.90	6.60	7.30																																																		
60	8.40	9.40	10.40																																																		
80	10.80	12.10	13.40																																																		
100	13.20	14.80	16.40																																																		
110	14.40	16.10	17.90																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

# COSEL

Model		G1W-12																																	
Item		Efficiency (by Input Voltage)																																	
Object		_____																																	
1.Graph		2.Values																																	
<div><div><div><div><div>---</div><div>□</div><div>---</div></div><div>Load 50%</div></div><div><div>—</div><div>△</div><div>—</div></div><div>Load 100%</div></div></div> <div><div><div>Efficiency [%]</div><div><div><div>70</div><div>62</div><div>54</div><div>46</div><div>38</div><div>30</div><div>22</div><div>14</div></div><div><div><div>80</div><div>90</div><div>100</div><div>110</div><div>120</div></div></div></div><div><div><div>Input Voltage [V]</div><div></div></div></div></div></div> <div><div>Note: Slanted line shows the range of the rated input voltage.</div></div>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Efficiency [%]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>85</td><td>54.0</td><td>58.2</td></tr><tr><td>90</td><td>50.9</td><td>54.7</td></tr><tr><td>100</td><td>45.2</td><td>48.8</td></tr><tr><td>110</td><td>40.6</td><td>44.0</td></tr><tr><td>115</td><td>38.9</td><td>42.0</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	85	54.0	58.2	90	50.9	54.7	100	45.2	48.8	110	40.6	44.0	115	38.9	42.0	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
85	54.0	58.2																																	
90	50.9	54.7																																	
100	45.2	48.8																																	
110	40.6	44.0																																	
115	38.9	42.0																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
		- 3 -																																	
		BC-10211																																	

# COSEL

Model		G1W-12		Temperature 25°C																																																	
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																	
Object																																																					
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th>Load Ration [%]</th><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>20</td><td>42.7</td><td>38.1</td><td>33.7</td></tr><tr><td>40</td><td>49.0</td><td>43.8</td><td>39.6</td></tr><tr><td>60</td><td>51.6</td><td>46.1</td><td>41.7</td></tr><tr><td>80</td><td>53.5</td><td>47.8</td><td>43.1</td></tr><tr><td>100</td><td>54.7</td><td>48.8</td><td>44.0</td></tr><tr><td>110</td><td>55.2</td><td>49.3</td><td>44.4</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Ration [%]	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	42.7	38.1	33.7	40	49.0	43.8	39.6	60	51.6	46.1	41.7	80	53.5	47.8	43.1	100	54.7	48.8	44.0	110	55.2	49.3	44.4	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	2.Values	
Load Ration [%]	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																		
0	-	-	-																																																		
20	42.7	38.1	33.7																																																		
40	49.0	43.8	39.6																																																		
60	51.6	46.1	41.7																																																		
80	53.5	47.8	43.1																																																		
100	54.7	48.8	44.0																																																		
110	55.2	49.3	44.4																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		


Model	G1W-12																																
Item	Power Factor (by Input Voltage)	Temperature	25°C																														
		Testing Circuitry	Figure A																														
Object																																	
1.Graph		2.Values																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>0.744</td><td>0.810</td></tr><tr><td>90</td><td>0.740</td><td>0.810</td></tr><tr><td>100</td><td>0.734</td><td>0.796</td></tr><tr><td>110</td><td>0.724</td><td>0.788</td></tr><tr><td>115</td><td>0.715</td><td>0.785</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Load 50%	Load 100%	85	0.744	0.810	90	0.740	0.810	100	0.734	0.796	110	0.724	0.788	115	0.715	0.785	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Load 50%	Load 100%																															
85	0.744	0.810																															
90	0.740	0.810																															
100	0.734	0.796																															
110	0.724	0.788																															
115	0.715	0.785																															
--	-	-																															
--	-	-																															
--	-	-																															
--	-	-																															

Model	G1W-12																																																					
Item	Power Factor (by Load Current)	Temperature	25°C																																																			
		Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <p>Power Factor</p> <p>Load Ratio [%]</p>		<table><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Power Factor</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>20</td><td>0.680</td><td>0.655</td><td>0.662</td></tr><tr><td>40</td><td>0.720</td><td>0.710</td><td>0.702</td></tr><tr><td>60</td><td>0.764</td><td>0.752</td><td>0.738</td></tr><tr><td>80</td><td>0.788</td><td>0.776</td><td>0.766</td></tr><tr><td>100</td><td>0.810</td><td>0.796</td><td>0.788</td></tr><tr><td>110</td><td>0.818</td><td>0.805</td><td>0.799</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Ration [%]	Power Factor			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	0.680	0.655	0.662	40	0.720	0.710	0.702	60	0.764	0.752	0.738	80	0.788	0.776	0.766	100	0.810	0.796	0.788	110	0.818	0.805	0.799	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Power Factor																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0	-	-	-																																																			
20	0.680	0.655	0.662																																																			
40	0.720	0.710	0.702																																																			
60	0.764	0.752	0.738																																																			
80	0.788	0.776	0.766																																																			
100	0.810	0.796	0.788																																																			
110	0.818	0.805	0.799																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			








Model	G1W-12	Temperature     25°C Testing Circuitry   Figure A	
Item	Inrush Current		
Object	_____		



Input Voltage	100 V
Frequency	60 Hz
Load	100 %
Primary inrush current	2.1 A



Model	G1W-12																																		
Item	Line Regulation	Temperature	25°C																																
		Testing Circuitry	Figure A																																
Object	+12V0.3A																																		
1.Graph		2.Values																																	
<div><div>---□--- Load 50%</div><div>—△— Load 100%</div></div>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>85</td><td>12.032</td><td>12.031</td></tr><tr><td>90</td><td>12.032</td><td>12.031</td></tr><tr><td>100</td><td>12.031</td><td>12.031</td></tr><tr><td>110</td><td>12.032</td><td>12.031</td></tr><tr><td>115</td><td>12.032</td><td>12.031</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	12.032	12.031	90	12.032	12.031	100	12.031	12.031	110	12.032	12.031	115	12.032	12.031	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	12.032	12.031																																	
90	12.032	12.031																																	
100	12.031	12.031																																	
110	12.032	12.031																																	
115	12.032	12.031																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
Object	-12V0.3A																																		
1.Graph		2.Values																																	
<div><div>---□--- Load 50%</div><div>—△— Load 100%</div></div> <div>Note: Slanted line shows the range of the rated input voltage.</div>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>85</td><td>-12.032</td><td>-12.032</td></tr><tr><td>90</td><td>-12.032</td><td>-12.032</td></tr><tr><td>100</td><td>-12.032</td><td>-12.032</td></tr><tr><td>110</td><td>-12.032</td><td>-12.032</td></tr><tr><td>115</td><td>-12.032</td><td>-12.032</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	-12.032	-12.032	90	-12.032	-12.032	100	-12.032	-12.032	110	-12.032	-12.032	115	-12.032	-12.032	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	-12.032	-12.032																																	
90	-12.032	-12.032																																	
100	-12.032	-12.032																																	
110	-12.032	-12.032																																	
115	-12.032	-12.032																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	



Model	G1W-12																																																					
Item	Load Regulation	Temperature	25°C																																																			
		Testing Circuitry	Figure A																																																			
Object	+12V0.3A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt. 90V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 110V</div></div></div> <table><thead><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0.00</td><td>12.032</td><td>12.032</td><td>12.032</td></tr><tr><td>0.06</td><td>12.032</td><td>12.032</td><td>12.032</td></tr><tr><td>0.12</td><td>12.031</td><td>12.032</td><td>12.031</td></tr><tr><td>0.18</td><td>12.031</td><td>12.032</td><td>12.032</td></tr><tr><td>0.24</td><td>12.031</td><td>12.031</td><td>12.031</td></tr><tr><td>0.30</td><td>12.031</td><td>12.031</td><td>12.031</td></tr><tr><td>0.33</td><td>12.031</td><td>12.031</td><td>12.031</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	12.032	12.032	12.032	0.06	12.032	12.032	12.032	0.12	12.031	12.032	12.031	0.18	12.031	12.032	12.032	0.24	12.031	12.031	12.031	0.30	12.031	12.031	12.031	0.33	12.031	12.031	12.031	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	12.032	12.032	12.032																																																			
0.06	12.032	12.032	12.032																																																			
0.12	12.031	12.032	12.031																																																			
0.18	12.031	12.032	12.032																																																			
0.24	12.031	12.031	12.031																																																			
0.30	12.031	12.031	12.031																																																			
0.33	12.031	12.031	12.031																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-12V0.3A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt. 90V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 110V</div></div></div> <table><thead><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0.00</td><td>-12.032</td><td>-12.032</td><td>-12.032</td></tr><tr><td>0.06</td><td>-12.032</td><td>-12.032</td><td>-12.032</td></tr><tr><td>0.12</td><td>-12.032</td><td>-12.032</td><td>-12.032</td></tr><tr><td>0.18</td><td>-12.032</td><td>-12.032</td><td>-12.032</td></tr><tr><td>0.24</td><td>-12.032</td><td>-12.032</td><td>-12.032</td></tr><tr><td>0.30</td><td>-12.032</td><td>-12.032</td><td>-12.032</td></tr><tr><td>0.33</td><td>-12.032</td><td>-12.032</td><td>-12.032</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-12.032	-12.032	-12.032	0.06	-12.032	-12.032	-12.032	0.12	-12.032	-12.032	-12.032	0.18	-12.032	-12.032	-12.032	0.24	-12.032	-12.032	-12.032	0.30	-12.032	-12.032	-12.032	0.33	-12.032	-12.032	-12.032	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-12.032	-12.032	-12.032																																																			
0.06	-12.032	-12.032	-12.032																																																			
0.12	-12.032	-12.032	-12.032																																																			
0.18	-12.032	-12.032	-12.032																																																			
0.24	-12.032	-12.032	-12.032																																																			
0.30	-12.032	-12.032	-12.032																																																			
0.33	-12.032	-12.032	-12.032																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

-9-

BC-10211



Model	G1W-12		
Item	Dynamic Load Response	Temperature	25°C
Object	+12V0.3A	Testing Circuitry	Figure A

Input Volt. 100 V  
Cycle 1000 ms


Load Current




Min. Load (0A) ←→

Load 100% (0.3A)

50 mV/div



100 μs/div




100 μs/div


Load 50% (0.15A) ←→

Load 100% (0.3A)

50 mV/div



100 μs/div



100 μs/div



Model	G1W-12	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Response		
Object	-12V0.3A		


Input Volt. 100 V  
Cycle 1000 ms

Load Current




Min. Load (0A) ←→  
Load 100% (0.3A)

50 mV/div




100  $\mu$ s/div




100  $\mu$ s/div

Load 50% (0.15A) ←→  
Load 100% (0.3A)

50 mV/div



100  $\mu$ s/div



100  $\mu$ s/div

Model	G1W-12																																											
Item	Ripple Voltage (by Load Current)	Temperature	25°C																																									
		Testing Circuitry	Figure A																																									
Object	+12V0.3A																																											
1.Graph		2.Values																																										
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 90 [V]</th><th>Input Volt. 110 [V]</th></tr><tr><td>0.00</td><td>0.7</td><td>0.7</td></tr><tr><td>0.15</td><td>0.7</td><td>0.7</td></tr><tr><td>0.30</td><td>0.8</td><td>0.8</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.00	0.7	0.7	0.15	0.7	0.7	0.30	0.8	0.8	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																											
	Input Volt. 90 [V]	Input Volt. 110 [V]																																										
0.00	0.7	0.7																																										
0.15	0.7	0.7																																										
0.30	0.8	0.8																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										


Model	G1W-12																																											
Item	Ripple Voltage (by Load Current)	Temperature	25°C																																									
		Testing Circuitry	Figure A																																									
Object	-12V0.3A																																											
1.Graph		2.Values																																										
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 90 [V]</th><th>Input Volt. 110 [V]</th></tr><tr><td>0.00</td><td>0.5</td><td>0.5</td></tr><tr><td>0.15</td><td>0.6</td><td>0.6</td></tr><tr><td>0.30</td><td>0.6</td><td>0.6</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.00	0.5	0.5	0.15	0.6	0.6	0.30	0.6	0.6	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																											
	Input Volt. 90 [V]	Input Volt. 110 [V]																																										
0.00	0.5	0.5																																										
0.15	0.6	0.6																																										
0.30	0.6	0.6																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										

- 13 -


BC-10211

Testing Circuitry Figure A

## 2.Values





## 2.Values



Note: Slanted line shows the range of the rated ambient temperature.





Model	G1W-12																																																						
Item	Ambient Temperature Drift		Testing Circuitry    Figure A																																																				
Object	+12V0.3A																																																						
1.Graph		2.Values																																																					
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div>  <div><div>Output Voltage [V]</div><div>Ambient Temperature [°C]</div><div>Load 100%</div></div>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>-20</td><td>12.004</td><td>12.004</td><td>12.004</td></tr><tr><td>-10</td><td>12.011</td><td>12.011</td><td>12.011</td></tr><tr><td>0</td><td>12.018</td><td>12.018</td><td>12.018</td></tr><tr><td>10</td><td>12.023</td><td>12.023</td><td>12.023</td></tr><tr><td>20</td><td>12.027</td><td>12.026</td><td>12.027</td></tr><tr><td>25</td><td>12.027</td><td>12.027</td><td>12.027</td></tr><tr><td>30</td><td>12.029</td><td>12.029</td><td>12.029</td></tr><tr><td>40</td><td>12.031</td><td>12.031</td><td>12.031</td></tr><tr><td>50</td><td>12.030</td><td>12.030</td><td>12.030</td></tr><tr><td>60</td><td>12.030</td><td>12.030</td><td>12.030</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-20	12.004	12.004	12.004	-10	12.011	12.011	12.011	0	12.018	12.018	12.018	10	12.023	12.023	12.023	20	12.027	12.026	12.027	25	12.027	12.027	12.027	30	12.029	12.029	12.029	40	12.031	12.031	12.031	50	12.030	12.030	12.030	60	12.030	12.030	12.030	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																				
-20	12.004	12.004	12.004																																																				
-10	12.011	12.011	12.011																																																				
0	12.018	12.018	12.018																																																				
10	12.023	12.023	12.023																																																				
20	12.027	12.026	12.027																																																				
25	12.027	12.027	12.027																																																				
30	12.029	12.029	12.029																																																				
40	12.031	12.031	12.031																																																				
50	12.030	12.030	12.030																																																				
60	12.030	12.030	12.030																																																				
--	-	-	-																																																				
Object	-12V0.3A																																																						
1.Graph		2.Values																																																					
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div>  <div><div>Output Voltage [V]</div><div>Ambient Temperature [°C]</div><div>Load 100%</div></div>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>-20</td><td>-12.016</td><td>-12.016</td><td>-12.016</td></tr><tr><td>-10</td><td>-12.022</td><td>-12.022</td><td>-12.022</td></tr><tr><td>0</td><td>-12.026</td><td>-12.026</td><td>-12.026</td></tr><tr><td>10</td><td>-12.029</td><td>-12.029</td><td>-12.029</td></tr><tr><td>20</td><td>-12.030</td><td>-12.030</td><td>-12.030</td></tr><tr><td>25</td><td>-12.030</td><td>-12.030</td><td>-12.030</td></tr><tr><td>30</td><td>-12.030</td><td>-12.030</td><td>-12.030</td></tr><tr><td>40</td><td>-12.030</td><td>-12.030</td><td>-12.029</td></tr><tr><td>50</td><td>-12.027</td><td>-12.027</td><td>-12.026</td></tr><tr><td>60</td><td>-12.022</td><td>-12.022</td><td>-12.022</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-20	-12.016	-12.016	-12.016	-10	-12.022	-12.022	-12.022	0	-12.026	-12.026	-12.026	10	-12.029	-12.029	-12.029	20	-12.030	-12.030	-12.030	25	-12.030	-12.030	-12.030	30	-12.030	-12.030	-12.030	40	-12.030	-12.030	-12.029	50	-12.027	-12.027	-12.026	60	-12.022	-12.022	-12.022	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																				
-20	-12.016	-12.016	-12.016																																																				
-10	-12.022	-12.022	-12.022																																																				
0	-12.026	-12.026	-12.026																																																				
10	-12.029	-12.029	-12.029																																																				
20	-12.030	-12.030	-12.030																																																				
25	-12.030	-12.030	-12.030																																																				
30	-12.030	-12.030	-12.030																																																				
40	-12.030	-12.030	-12.029																																																				
50	-12.027	-12.027	-12.026																																																				
60	-12.022	-12.022	-12.022																																																				
--	-	-	-																																																				
Note: Slanted line shows the range of the rated ambient temperature.																																																							

- 15 -

BC-10211



**COSEL**


Model	G1W-12																								
Item	Time Lapse Drift	Temperature	25°C																						
Object	+12V0.3A	Testing Circuitry	Figure A																						
1.Graph		2.Values																							
<div></div> <div>Output Voltage [V]</div> <div>Time [H]</div> <div>Input Volt. 100V</div> <div>Load 100%</div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>12.032</td></tr><tr><td>0.5</td><td>12.031</td></tr><tr><td>1.0</td><td>12.031</td></tr><tr><td>2.0</td><td>12.031</td></tr><tr><td>3.0</td><td>12.031</td></tr><tr><td>4.0</td><td>12.031</td></tr><tr><td>5.0</td><td>12.031</td></tr><tr><td>6.0</td><td>12.031</td></tr><tr><td>7.0</td><td>12.031</td></tr><tr><td>8.0</td><td>12.031</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	12.032	0.5	12.031	1.0	12.031	2.0	12.031	3.0	12.031	4.0	12.031	5.0	12.031	6.0	12.031	7.0	12.031	8.0	12.031
Time since start [H]	Output Voltage [V]																								
0.0	12.032																								
0.5	12.031																								
1.0	12.031																								
2.0	12.031																								
3.0	12.031																								
4.0	12.031																								
5.0	12.031																								
6.0	12.031																								
7.0	12.031																								
8.0	12.031																								
Object	-12V0.3A																								
1.Graph		2.Values																							
<div></div> <div>Output Voltage [V]</div> <div>Time [H]</div> <div>Input Volt. 100V</div> <div>Load 100%</div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>-12.032</td></tr><tr><td>0.5</td><td>-12.031</td></tr><tr><td>1.0</td><td>-12.031</td></tr><tr><td>2.0</td><td>-12.031</td></tr><tr><td>3.0</td><td>-12.031</td></tr><tr><td>4.0</td><td>-12.031</td></tr><tr><td>5.0</td><td>-12.031</td></tr><tr><td>6.0</td><td>-12.031</td></tr><tr><td>7.0</td><td>-12.031</td></tr><tr><td>8.0</td><td>-12.031</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	-12.032	0.5	-12.031	1.0	-12.031	2.0	-12.031	3.0	-12.031	4.0	-12.031	5.0	-12.031	6.0	-12.031	7.0	-12.031	8.0	-12.031
Time since start [H]	Output Voltage [V]																								
0.0	-12.032																								
0.5	-12.031																								
1.0	-12.031																								
2.0	-12.031																								
3.0	-12.031																								
4.0	-12.031																								
5.0	-12.031																								
6.0	-12.031																								
7.0	-12.031																								
8.0	-12.031																								

- 17 -

BC-10211


Model	G1W-12	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V0.3A		

## 1.Graph




## 2.Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	13.8	23.3	37.1	57.0	201.0
100 %	14.0	23.0	37.0	23.0	104.0




Model	G1W-12	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-12V0.3A		

## 1.Graph



## 2.Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		13.5	24.0	37.5	56.0	197.0
100 %		13.5	24.0	37.5	22.5	103.5



# COSEL



Model	G1W-12																																		
Item	Hold-Up Time	Temperature	25°C																																
		Testing Circuitry	Figure A																																
Object	+12V0.3A																																		
1.Graph		2.Values																																	
<div><div><div>---□--- Load 50%</div><div>—△— Load 100%</div></div><div>Hold-Up Time [ms]</div><div>Input Voltage [V]</div></div> <div><p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p><p>Note: Slanted line shows the range of the rated input voltage.</p></div>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Hold-Up Time [ms]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>85</td><td>26</td><td>7</td></tr><tr><td>90</td><td>34</td><td>11</td></tr><tr><td>100</td><td>49</td><td>19</td></tr><tr><td>110</td><td>65</td><td>27</td></tr><tr><td>115</td><td>73</td><td>30</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	26	7	90	34	11	100	49	19	110	65	27	115	73	30	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	26	7																																	
90	34	11																																	
100	49	19																																	
110	65	27																																	
115	73	30																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	

Model	G1W-12																																		
Item	Hold-Up Time	Temperature	25°C																																
		Testing Circuitry	Figure A																																
Object	-12V0.3A																																		
1.Graph		2.Values																																	
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <p>Hold-Up Time [ms]</p> <p>Input Voltage [V]</p> <p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Hold-Up Time [ms]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>85</td><td>26</td><td>7</td></tr><tr><td>90</td><td>34</td><td>11</td></tr><tr><td>100</td><td>49</td><td>19</td></tr><tr><td>110</td><td>64</td><td>26</td></tr><tr><td>115</td><td>72</td><td>30</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	26	7	90	34	11	100	49	19	110	64	26	115	72	30	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	26	7																																	
90	34	11																																	
100	49	19																																	
110	64	26																																	
115	72	30																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	

Model	G1W-12																																																					
Item	Instantaneous Interruption Compensation	Temperature	25°C																																																			
Object	+12V0.3A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <div><div><div>Instantaneous Compensation Time [ms]</div><div>1000</div><div>100</div><div>10</div><div>1</div></div><div><div>0.00</div><div>0.10</div><div>0.20</div><div>0.30</div></div><div><div>Load Current [A]</div></div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.06</td><td>91</td><td>128</td><td>165</td></tr><tr><td>0.12</td><td>42</td><td>61</td><td>80</td></tr><tr><td>0.18</td><td>21</td><td>37</td><td>51</td></tr><tr><td>0.24</td><td>16</td><td>24</td><td>35</td></tr><tr><td>0.30</td><td>6</td><td>19</td><td>24</td></tr><tr><td>0.33</td><td>5</td><td>16</td><td>23</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-	-	-	0.06	91	128	165	0.12	42	61	80	0.18	21	37	51	0.24	16	24	35	0.30	6	19	24	0.33	5	16	23	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-	-	-																																																			
0.06	91	128	165																																																			
0.12	42	61	80																																																			
0.18	21	37	51																																																			
0.24	16	24	35																																																			
0.30	6	19	24																																																			
0.33	5	16	23																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						





Model	G1W-12																																																					
Item	Instantaneous Interruption Compensation	Temperature	25°C																																																			
Object	-12V0.3A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-</div><div>Input Volt.</div><div>110V</div></div></div> <div><div><div>Instantaneous Compensation Time [ms]</div><div>1000</div><div>100</div><div>10</div><div>1</div></div><div><div>0.00</div><div>0.10</div><div>0.20</div><div>0.30</div></div><div><div>Load Current [A]</div></div></div> <div>Note: Slanted line shows the range of the rated load current.</div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.06</td><td>90</td><td>126</td><td>162</td></tr><tr><td>0.12</td><td>41</td><td>61</td><td>80</td></tr><tr><td>0.18</td><td>21</td><td>37</td><td>50</td></tr><tr><td>0.24</td><td>16</td><td>24</td><td>35</td></tr><tr><td>0.30</td><td>6</td><td>19</td><td>24</td></tr><tr><td>0.33</td><td>5</td><td>16</td><td>23</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-	-	-	0.06	90	126	162	0.12	41	61	80	0.18	21	37	50	0.24	16	24	35	0.30	6	19	24	0.33	5	16	23	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-	-	-																																																			
0.06	90	126	162																																																			
0.12	41	61	80																																																			
0.18	21	37	50																																																			
0.24	16	24	35																																																			
0.30	6	19	24																																																			
0.33	5	16	23																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	G1W-12	Testing Circuitry    Figure A																																							
Item	Minimum Input Voltage for Regulated Output Voltage																																								
Object	+12V0.3A																																								
1.Graph		2.Values																																							
<div><div>---□---</div> Load 50%</div> <div><div>—△—</div> Load 100%</div> 		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>-20</td><td>67</td><td>74</td></tr><tr><td>-10</td><td>67</td><td>74</td></tr><tr><td>0</td><td>67</td><td>74</td></tr><tr><td>10</td><td>67</td><td>75</td></tr><tr><td>20</td><td>67</td><td>75</td></tr><tr><td>25</td><td>67</td><td>75</td></tr><tr><td>30</td><td>67</td><td>75</td></tr><tr><td>40</td><td>67</td><td>75</td></tr><tr><td>50</td><td>69</td><td>77</td></tr><tr><td>60</td><td>69</td><td>77</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	67	74	-10	67	74	0	67	74	10	67	75	20	67	75	25	67	75	30	67	75	40	67	75	50	69	77	60	69	77	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	67	74																																							
-10	67	74																																							
0	67	74																																							
10	67	75																																							
20	67	75																																							
25	67	75																																							
30	67	75																																							
40	67	75																																							
50	69	77																																							
60	69	77																																							
--	-	-																																							
Object	-12V0.3A																																								
1.Graph		2.Values																																							
<div><div>---□---</div> Load 50%</div> <div><div>—△—</div> Load 100%</div> 		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>-20</td><td>67</td><td>74</td></tr><tr><td>-10</td><td>67</td><td>74</td></tr><tr><td>0</td><td>67</td><td>74</td></tr><tr><td>10</td><td>67</td><td>74</td></tr><tr><td>20</td><td>67</td><td>75</td></tr><tr><td>25</td><td>67</td><td>75</td></tr><tr><td>30</td><td>67</td><td>75</td></tr><tr><td>40</td><td>67</td><td>75</td></tr><tr><td>50</td><td>69</td><td>77</td></tr><tr><td>60</td><td>69</td><td>77</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	67	74	-10	67	74	0	67	74	10	67	74	20	67	75	25	67	75	30	67	75	40	67	75	50	69	77	60	69	77	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	67	74																																							
-10	67	74																																							
0	67	74																																							
10	67	74																																							
20	67	75																																							
25	67	75																																							
30	67	75																																							
40	67	75																																							
50	69	77																																							
60	69	77																																							
--	-	-																																							
Note: Slanted line shows the range of the rated ambient temperature.																																									

- 24 -

BC-10211

Model	G1W-12																																																									
Item	Overcurrent Protection	Temperature	25°C																																																							
Object	+12V0.3A	Testing Circuitry	Figure A																																																							
1.Graph		2.Values																																																								
<div><div></div>Input Volt. 90V</div> <div><div></div>Input Volt. 100V</div> <div><div></div>Input Volt. 110V</div> 		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>12.0</td><td>0.38</td><td>0.38</td><td>0.38</td></tr><tr><td>11.4</td><td>0.37</td><td>0.37</td><td>0.37</td></tr><tr><td>10.8</td><td>0.36</td><td>0.36</td><td>0.36</td></tr><tr><td>9.6</td><td>0.34</td><td>0.34</td><td>0.34</td></tr><tr><td>8.4</td><td>0.32</td><td>0.32</td><td>0.32</td></tr><tr><td>7.2</td><td>0.30</td><td>0.30</td><td>0.30</td></tr><tr><td>6.0</td><td>0.27</td><td>0.27</td><td>0.27</td></tr><tr><td>4.8</td><td>0.25</td><td>0.25</td><td>0.25</td></tr><tr><td>3.6</td><td>0.23</td><td>0.23</td><td>0.23</td></tr><tr><td>2.4</td><td>0.20</td><td>0.20</td><td>0.20</td></tr><tr><td>1.2</td><td>0.18</td><td>0.18</td><td>0.18</td></tr><tr><td>0.0</td><td>0.16</td><td>0.16</td><td>0.16</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	12.0	0.38	0.38	0.38	11.4	0.37	0.37	0.37	10.8	0.36	0.36	0.36	9.6	0.34	0.34	0.34	8.4	0.32	0.32	0.32	7.2	0.30	0.30	0.30	6.0	0.27	0.27	0.27	4.8	0.25	0.25	0.25	3.6	0.23	0.23	0.23	2.4	0.20	0.20	0.20	1.2	0.18	0.18	0.18	0.0	0.16	0.16	0.16
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
12.0	0.38	0.38	0.38																																																							
11.4	0.37	0.37	0.37																																																							
10.8	0.36	0.36	0.36																																																							
9.6	0.34	0.34	0.34																																																							
8.4	0.32	0.32	0.32																																																							
7.2	0.30	0.30	0.30																																																							
6.0	0.27	0.27	0.27																																																							
4.8	0.25	0.25	0.25																																																							
3.6	0.23	0.23	0.23																																																							
2.4	0.20	0.20	0.20																																																							
1.2	0.18	0.18	0.18																																																							
0.0	0.16	0.16	0.16																																																							
Object	-12V0.3A																																																									
1.Graph		2.Values																																																								
<div><div></div>Input Volt. 90V</div> <div><div></div>Input Volt. 100V</div> <div><div></div>Input Volt. 110V</div>  <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>-12.0</td><td>0.38</td><td>0.38</td><td>0.38</td></tr><tr><td>-11.4</td><td>0.37</td><td>0.37</td><td>0.37</td></tr><tr><td>-10.8</td><td>0.36</td><td>0.36</td><td>0.36</td></tr><tr><td>-9.6</td><td>0.34</td><td>0.34</td><td>0.34</td></tr><tr><td>-8.4</td><td>0.32</td><td>0.32</td><td>0.32</td></tr><tr><td>-7.2</td><td>0.29</td><td>0.29</td><td>0.29</td></tr><tr><td>-6.0</td><td>0.27</td><td>0.27</td><td>0.27</td></tr><tr><td>-4.8</td><td>0.25</td><td>0.25</td><td>0.25</td></tr><tr><td>-3.6</td><td>0.23</td><td>0.23</td><td>0.23</td></tr><tr><td>-2.4</td><td>0.20</td><td>0.20</td><td>0.20</td></tr><tr><td>-1.2</td><td>0.18</td><td>0.18</td><td>0.18</td></tr><tr><td>0.0</td><td>0.16</td><td>0.16</td><td>0.16</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-12.0	0.38	0.38	0.38	-11.4	0.37	0.37	0.37	-10.8	0.36	0.36	0.36	-9.6	0.34	0.34	0.34	-8.4	0.32	0.32	0.32	-7.2	0.29	0.29	0.29	-6.0	0.27	0.27	0.27	-4.8	0.25	0.25	0.25	-3.6	0.23	0.23	0.23	-2.4	0.20	0.20	0.20	-1.2	0.18	0.18	0.18	0.0	0.16	0.16	0.16
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
-12.0	0.38	0.38	0.38																																																							
-11.4	0.37	0.37	0.37																																																							
-10.8	0.36	0.36	0.36																																																							
-9.6	0.34	0.34	0.34																																																							
-8.4	0.32	0.32	0.32																																																							
-7.2	0.29	0.29	0.29																																																							
-6.0	0.27	0.27	0.27																																																							
-4.8	0.25	0.25	0.25																																																							
-3.6	0.23	0.23	0.23																																																							
-2.4	0.20	0.20	0.20																																																							
-1.2	0.18	0.18	0.18																																																							
0.0	0.16	0.16	0.16																																																							

- 25 -

BC-10211




Figure A