

## Temperature increase of main components: 主要部品温度上昇


Model: G2

## 1. Conditions

- (1) Input :AC 90 ~ 110 [V]  
 (2) Output :Rated output  
 (3) Mounting method :Shown as Fig.1.1

## 2. Result

No.	Parts name	Symbol No.	Increase ( $\Delta T$ )						Rated temp. [°C]	Reference
			[deg]							
			5V	12V	15V	24V				
1	Rectifier(Main-Input)	SS1	54	59	51	37			150	Junction Temp.
2	Rectifier(Sub-Input)	SS21	38	38	34	29			150	Junction Temp.
3	Transformer	T1	37	40	35	30			120	
4	Input Capacitor(Main)	C2	30	31	27	23			105	
5	Input Capacitor(Sub)	C21	34	35	32	27			105	
6	Fet(Main)	TR1	51	53	44	39			150	Junction Temp.
7	Transistor(Sub)	TR21	36	37	34	30			150	Junction Temp.
8	Voltage Regulator	IC21	35	37	33	29			150	Junction Temp.
9	Power Control Ic	IC22	46	47	44	40			150	Junction Temp.
10	Output Capacitor	C6	25	25	26	22			105	
11										
12										
13										
14										
15										
16										
17										
18										
19										
20										

Fig.1.1 Mounting method  
(Normal position)

\*All information presented herein are not guaranteed.

\*本資料は参考資料であり、その内容を保証するものではありません。