

TEST DATA OF G2W-12

Regulated DC Power Supply
October 19, 2010

Approved by : Eiyoshi Wakamatsu
Design Manager

Prepared by : Satoshi Kinoshita
Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Line Regulation	8
9.Load Regulation	9
10.Dynamic Load Response	10
11.Ripple Voltage (by Load Current)	12
12.Ripple Voltage (by Ambient Temperature)	14
13.Ambient Temperature Drift	15
14.Output Voltage Accuracy	16
15.Time Lapse Drift	17
16.Rise and Fall Time	18
17.Hold-Up Time	20
18.Instantaneous Interruption Compensation	22
19.Minimum Input Voltage for Regulated Output Voltage	24
20.Overcurrent Protection	25
21.Figure of Testing Circuitry	26

(Final Page 26)



Model	G2W-12																																																																																					
Item	Input Current (by Load Current)	Temperature	25°C																																																																																			
Object	_____	Testing Circuitry	Figure A																																																																																			
1.Graph		2.Values																																																																																				
<div><div><div><div></div><div>△</div></div><div>Input Volt. 90V</div></div><div><div><div></div><div>□</div></div><div>Input Volt. 100V</div></div><div><div><div></div><div>○</div></div><div>Input Volt. 110V</div></div></div> <div><table><thead><tr><th>Load Ratio [%]</th><th>90V [A]</th><th>100V [A]</th><th>110V [A]</th></tr></thead><tbody><tr><td>0</td><td>0.016</td><td>0.017</td><td>0.019</td></tr><tr><td>20</td><td>0.097</td><td>0.100</td><td>0.102</td></tr><tr><td>40</td><td>0.164</td><td>0.168</td><td>0.171</td></tr><tr><td>60</td><td>0.226</td><td>0.231</td><td>0.235</td></tr><tr><td>80</td><td>0.284</td><td>0.290</td><td>0.295</td></tr><tr><td>100</td><td>0.340</td><td>0.347</td><td>0.353</td></tr><tr><td>110</td><td>0.367</td><td>0.375</td><td>0.381</td></tr></tbody></table></div>		Load Ratio [%]	90V [A]	100V [A]	110V [A]	0	0.016	0.017	0.019	20	0.097	0.100	0.102	40	0.164	0.168	0.171	60	0.226	0.231	0.235	80	0.284	0.290	0.295	100	0.340	0.347	0.353	110	0.367	0.375	0.381	<table><thead><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0</td><td>0.016</td><td>0.017</td><td>0.019</td></tr><tr><td>20</td><td>0.097</td><td>0.100</td><td>0.102</td></tr><tr><td>40</td><td>0.164</td><td>0.168</td><td>0.171</td></tr><tr><td>60</td><td>0.226</td><td>0.231</td><td>0.235</td></tr><tr><td>80</td><td>0.284</td><td>0.290</td><td>0.295</td></tr><tr><td>100</td><td>0.340</td><td>0.347</td><td>0.353</td></tr><tr><td>110</td><td>0.367</td><td>0.375</td><td>0.381</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Ration [%]	Input Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	0.016	0.017	0.019	20	0.097	0.100	0.102	40	0.164	0.168	0.171	60	0.226	0.231	0.235	80	0.284	0.290	0.295	100	0.340	0.347	0.353	110	0.367	0.375	0.381	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ratio [%]	90V [A]	100V [A]	110V [A]																																																																																			
0	0.016	0.017	0.019																																																																																			
20	0.097	0.100	0.102																																																																																			
40	0.164	0.168	0.171																																																																																			
60	0.226	0.231	0.235																																																																																			
80	0.284	0.290	0.295																																																																																			
100	0.340	0.347	0.353																																																																																			
110	0.367	0.375	0.381																																																																																			
Load Ration [%]	Input Current [A]																																																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																																																			
0	0.016	0.017	0.019																																																																																			
20	0.097	0.100	0.102																																																																																			
40	0.164	0.168	0.171																																																																																			
60	0.226	0.231	0.235																																																																																			
80	0.284	0.290	0.295																																																																																			
100	0.340	0.347	0.353																																																																																			
110	0.367	0.375	0.381																																																																																			
--	-	-	-																																																																																			
--	-	-	-																																																																																			
--	-	-	-																																																																																			
--	-	-	-																																																																																			

COSEL

Model		G2W-12		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <div><div><div>Input Power [W]</div><div>50</div><div>40</div><div>30</div><div>20</div><div>10</div><div>0</div></div><div><div>0</div><div>40</div><div>80</div><div>120</div></div></div>		2.Values																																																				
		<table><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0</td><td>0.90</td><td>1.10</td><td>1.20</td></tr><tr><td>20</td><td>5.50</td><td>6.20</td><td>7.00</td></tr><tr><td>40</td><td>10.10</td><td>11.30</td><td>12.60</td></tr><tr><td>60</td><td>14.70</td><td>16.40</td><td>18.10</td></tr><tr><td>80</td><td>19.20</td><td>21.40</td><td>23.70</td></tr><tr><td>100</td><td>23.60</td><td>26.40</td><td>29.10</td></tr><tr><td>110</td><td>25.80</td><td>28.80</td><td>31.90</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Ration [%]	Input Power [W]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	0.90	1.10	1.20	20	5.50	6.20	7.00	40	10.10	11.30	12.60	60	14.70	16.40	18.10	80	19.20	21.40	23.70	100	23.60	26.40	29.10	110	25.80	28.80	31.90	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																							
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																					
0	0.90	1.10	1.20																																																					
20	5.50	6.20	7.00																																																					
40	10.10	11.30	12.60																																																					
60	14.70	16.40	18.10																																																					
80	19.20	21.40	23.70																																																					
100	23.60	26.40	29.10																																																					
110	25.80	28.80	31.90																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
		</																																																						

Model	G2W-12																																		
Item	Efficiency (by Input Voltage)	Temperature	25°C																																
Object		Testing Circuitry	Figure A																																
1.Graph		2.Values																																	
<div><div><div>---</div><div>□</div><div>---</div></div><div>Load 50%</div></div> <div><div>—</div><div>△</div><div>—</div></div> <div>Load 100%</div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Efficiency [%]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>62.3</td><td>65.1</td></tr><tr><td>90</td><td>58.2</td><td>61.2</td></tr><tr><td>100</td><td>51.9</td><td>54.9</td></tr><tr><td>110</td><td>47.2</td><td>49.5</td></tr><tr><td>115</td><td>44.8</td><td>47.4</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	85	62.3	65.1	90	58.2	61.2	100	51.9	54.9	110	47.2	49.5	115	44.8	47.4	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
85	62.3	65.1																																	
90	58.2	61.2																																	
100	51.9	54.9																																	
110	47.2	49.5																																	
115	44.8	47.4																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	

COSEL


Model		G2W-12		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<div><div><div>—△—</div><div>Input Volt. 90V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 110V</div></div></div> <div><div>Efficiency [%]</div><div>Load Ration [%]</div></div>		2.Values																																																				
		<table><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>20</td><td>52.6</td><td>46.6</td><td>41.3</td></tr><tr><td>40</td><td>57.2</td><td>51.1</td><td>45.9</td></tr><tr><td>60</td><td>59.0</td><td>52.8</td><td>47.9</td></tr><tr><td>80</td><td>60.2</td><td>54.0</td><td>48.8</td></tr><tr><td>100</td><td>61.2</td><td>54.7</td><td>49.6</td></tr><tr><td>110</td><td>61.6</td><td>55.2</td><td>49.8</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Ration [%]	Efficiency [%]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	52.6	46.6	41.3	40	57.2	51.1	45.9	60	59.0	52.8	47.9	80	60.2	54.0	48.8	100	61.2	54.7	49.6	110	61.6	55.2	49.8	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																							
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																					
0	-	-	-																																																					
20	52.6	46.6	41.3																																																					
40	57.2	51.1	45.9																																																					
60	59.0	52.8	47.9																																																					
80	60.2	54.0	48.8																																																					
100	61.2	54.7	49.6																																																					
110	61.6	55.2	49.8																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Model	G2W-12																																
Item	Power Factor (by Input Voltage)	Temperature	25°C																														
		Testing Circuitry	Figure A																														
Object																																	
1.Graph		2.Values																															
<div><div><div>---</div><div>□</div><div>---</div></div><div>Load 50%</div></div> <div><div>—</div><div>△</div><div>—</div></div> <div>Load 100%</div> <table><thead><tr><th>Input Voltage [V]</th><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>0.707</td><td>0.776</td></tr><tr><td>90</td><td>0.705</td><td>0.771</td></tr><tr><td>100</td><td>0.695</td><td>0.758</td></tr><tr><td>110</td><td>0.683</td><td>0.751</td></tr><tr><td>115</td><td>0.682</td><td>0.746</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Load 50%	Load 100%	85	0.707	0.776	90	0.705	0.771	100	0.695	0.758	110	0.683	0.751	115	0.682	0.746	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Load 50%	Load 100%																															
85	0.707	0.776																															
90	0.705	0.771																															
100	0.695	0.758																															
110	0.683	0.751																															
115	0.682	0.746																															
--	-	-																															
--	-	-																															
--	-	-																															
--	-	-																															


Model	G2W-12																																																					
Item	Power Factor (by Load Current)	Temperature	25°C																																																			
		Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt. 90V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>-·-○-·-</div><div>Input Volt. 110V</div></div></div> <p>Power Factor</p> <p>Load Ration [%]</p>		<table><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Power Factor</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>20</td><td>0.632</td><td>0.620</td><td>0.619</td></tr><tr><td>40</td><td>0.682</td><td>0.673</td><td>0.667</td></tr><tr><td>60</td><td>0.724</td><td>0.710</td><td>0.699</td></tr><tr><td>80</td><td>0.750</td><td>0.738</td><td>0.729</td></tr><tr><td>100</td><td>0.771</td><td>0.761</td><td>0.750</td></tr><tr><td>110</td><td>0.782</td><td>0.768</td><td>0.761</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Ration [%]	Power Factor			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	0.632	0.620	0.619	40	0.682	0.673	0.667	60	0.724	0.710	0.699	80	0.750	0.738	0.729	100	0.771	0.761	0.750	110	0.782	0.768	0.761	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Power Factor																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0	-	-	-																																																			
20	0.632	0.620	0.619																																																			
40	0.682	0.673	0.667																																																			
60	0.724	0.710	0.699																																																			
80	0.750	0.738	0.729																																																			
100	0.771	0.761	0.750																																																			
110	0.782	0.768	0.761																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	G2W-12	Temperature 25°C Testing Circuitry Figure A	
Item	Inrush Current		
Object			



Input Voltage 100 V
Frequency 60 Hz
Load 100 %

Primary inrush current 4.8 A



Model	G2W-12																																		
Item	Line Regulation	Temperature	25°C																																
		Testing Circuitry	Figure A																																
Object	+12V0.6A																																		
1.Graph		2.Values																																	
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>12.032</td><td>12.031</td></tr><tr><td>90</td><td>12.032</td><td>12.031</td></tr><tr><td>100</td><td>12.032</td><td>12.031</td></tr><tr><td>110</td><td>12.032</td><td>12.031</td></tr><tr><td>115</td><td>12.032</td><td>12.031</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	12.032	12.031	90	12.032	12.031	100	12.032	12.031	110	12.032	12.031	115	12.032	12.031	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	12.032	12.031																																	
90	12.032	12.031																																	
100	12.032	12.031																																	
110	12.032	12.031																																	
115	12.032	12.031																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
Object	-12V0.6A																																		
1.Graph		2.Values																																	
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>-12.034</td><td>-12.033</td></tr><tr><td>90</td><td>-12.034</td><td>-12.033</td></tr><tr><td>100</td><td>-12.034</td><td>-12.033</td></tr><tr><td>110</td><td>-12.034</td><td>-12.033</td></tr><tr><td>115</td><td>-12.034</td><td>-12.033</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	-12.034	-12.033	90	-12.034	-12.033	100	-12.034	-12.033	110	-12.034	-12.033	115	-12.034	-12.033	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	-12.034	-12.033																																	
90	-12.034	-12.033																																	
100	-12.034	-12.033																																	
110	-12.034	-12.033																																	
115	-12.034	-12.033																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
Note: Slanted line shows the range of the rated input voltage.																																			



Model	G2W-12																																																					
Item	Load Regulation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+12V0.6A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt. 90V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 110V</div></div></div> <table><thead><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0.00</td><td>12.032</td><td>12.032</td><td>12.032</td></tr><tr><td>0.10</td><td>12.032</td><td>12.032</td><td>12.032</td></tr><tr><td>0.20</td><td>12.032</td><td>12.032</td><td>12.032</td></tr><tr><td>0.30</td><td>12.031</td><td>12.032</td><td>12.032</td></tr><tr><td>0.40</td><td>12.031</td><td>12.032</td><td>12.032</td></tr><tr><td>0.50</td><td>12.031</td><td>12.031</td><td>12.032</td></tr><tr><td>0.60</td><td>12.031</td><td>12.031</td><td>12.031</td></tr><tr><td>0.66</td><td>12.031</td><td>12.031</td><td>12.031</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	12.032	12.032	12.032	0.10	12.032	12.032	12.032	0.20	12.032	12.032	12.032	0.30	12.031	12.032	12.032	0.40	12.031	12.032	12.032	0.50	12.031	12.031	12.032	0.60	12.031	12.031	12.031	0.66	12.031	12.031	12.031	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	12.032	12.032	12.032																																																			
0.10	12.032	12.032	12.032																																																			
0.20	12.032	12.032	12.032																																																			
0.30	12.031	12.032	12.032																																																			
0.40	12.031	12.032	12.032																																																			
0.50	12.031	12.031	12.032																																																			
0.60	12.031	12.031	12.031																																																			
0.66	12.031	12.031	12.031																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-12V0.6A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt. 90V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 110V</div></div></div> <table><thead><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0.00</td><td>-12.035</td><td>-12.035</td><td>-12.034</td></tr><tr><td>0.10</td><td>-12.034</td><td>-12.034</td><td>-12.034</td></tr><tr><td>0.20</td><td>-12.034</td><td>-12.034</td><td>-12.034</td></tr><tr><td>0.30</td><td>-12.034</td><td>-12.034</td><td>-12.034</td></tr><tr><td>0.40</td><td>-12.034</td><td>-12.034</td><td>-12.034</td></tr><tr><td>0.50</td><td>-12.034</td><td>-12.033</td><td>-12.033</td></tr><tr><td>0.60</td><td>-12.033</td><td>-12.033</td><td>-12.033</td></tr><tr><td>0.66</td><td>-12.033</td><td>-12.033</td><td>-12.033</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-12.035	-12.035	-12.034	0.10	-12.034	-12.034	-12.034	0.20	-12.034	-12.034	-12.034	0.30	-12.034	-12.034	-12.034	0.40	-12.034	-12.034	-12.034	0.50	-12.034	-12.033	-12.033	0.60	-12.033	-12.033	-12.033	0.66	-12.033	-12.033	-12.033	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-12.035	-12.035	-12.034																																																			
0.10	-12.034	-12.034	-12.034																																																			
0.20	-12.034	-12.034	-12.034																																																			
0.30	-12.034	-12.034	-12.034																																																			
0.40	-12.034	-12.034	-12.034																																																			
0.50	-12.034	-12.033	-12.033																																																			
0.60	-12.033	-12.033	-12.033																																																			
0.66	-12.033	-12.033	-12.033																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

-9-

BC-10213



Model	G2W-12		
Item	Dynamic Load Response	Temperature	25°C
Object	+12V0.6A	Testing Circuitry	Figure A


Input Volt. 100 V
Cycle 1000 ms

Load Current




Min. Load (0A) ←→
Load 100% (0.6A)

50 mV/div




100 μ s/div




100 μ s/div

Load 50% (0.3A) ←→
Load 100% (0.6A)

50 mV/div



100 μ s/div




100 μ s/div



Model	G2W-12	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Response		
Object	-12V0.6A		


Input Volt. 100 V
Cycle 1000 ms

Load Current




Min. Load (0A) ←→
Load 100% (0.6A)

50 mV/div




100 μ s/div




100 μ s/div

Load 50% (0.3A) ←→
Load 100% (0.6A)

50 mV/div



100 μ s/div



100 μ s/div

Model	G2W-12																																											
Item	Ripple Voltage (by Load Current)	Temperature	25°C																																									
		Testing Circuitry	Figure A																																									
Object	+12V0.6A																																											
1.Graph		2.Values																																										
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 90 [V]</th><th>Input Volt. 110 [V]</th></tr><tr><td>0.0</td><td>0.6</td><td>0.6</td></tr><tr><td>0.3</td><td>0.7</td><td>0.7</td></tr><tr><td>0.6</td><td>0.8</td><td>0.8</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.0	0.6	0.6	0.3	0.7	0.7	0.6	0.8	0.8	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																											
	Input Volt. 90 [V]	Input Volt. 110 [V]																																										
0.0	0.6	0.6																																										
0.3	0.7	0.7																																										
0.6	0.8	0.8																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										

- 12 -

BC-10213

Model	G2W-12	Temperature 25°C Testing Circuitry Figure A																																										
Item	Ripple Voltage (by Load Current)																																											
Object	-12V0.6A																																											
1.Graph		2.Values																																										
<div><div><div>—△— Input Volt. 90V</div><div>-·-○-·- Input Volt. 110V</div></div><div>Ripple Voltage [mV]</div><div>Load Current [A]</div></div> <div>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.</div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 90 [V]</th><th>Input Volt. 110 [V]</th></tr><tr><td>0.0</td><td>0.6</td><td>0.6</td></tr><tr><td>0.3</td><td>0.8</td><td>0.8</td></tr><tr><td>0.6</td><td>0.8</td><td>0.8</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.0	0.6	0.6	0.3	0.8	0.8	0.6	0.8	0.8	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																											
	Input Volt. 90 [V]	Input Volt. 110 [V]																																										
0.0	0.6	0.6																																										
0.3	0.8	0.8																																										
0.6	0.8	0.8																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										

- 13 -

BC-10213



Model	G2W-12																																											
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure A																																										
Object	+12V0.6A																																											
1.Graph		2.Values																																										
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <p>Input Volt. 100V</p>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>-20</td><td>0.8</td><td>0.9</td></tr><tr><td>-10</td><td>0.8</td><td>0.8</td></tr><tr><td>25</td><td>0.7</td><td>0.8</td></tr><tr><td>50</td><td>0.7</td><td>0.8</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-20	0.8	0.9	-10	0.8	0.8	25	0.7	0.8	50	0.7	0.8	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																											
	Load 50%	Load 100%																																										
-20	0.8	0.9																																										
-10	0.8	0.8																																										
25	0.7	0.8																																										
50	0.7	0.8																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
Object	-12V0.6A																																											
1.Graph		2.Values																																										
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <p>Input Volt. 100V</p> <p>Measured by 20 MHz Oscilloscope.</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>-20</td><td>1.0</td><td>1.0</td></tr><tr><td>-10</td><td>0.9</td><td>0.9</td></tr><tr><td>25</td><td>0.8</td><td>0.8</td></tr><tr><td>50</td><td>0.7</td><td>0.8</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-20	1.0	1.0	-10	0.9	0.9	25	0.8	0.8	50	0.7	0.8	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																											
	Load 50%	Load 100%																																										
-20	1.0	1.0																																										
-10	0.9	0.9																																										
25	0.8	0.8																																										
50	0.7	0.8																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										

Model	G2W-12																																																					
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																				
Object	+12V0.6A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>-20</td><td>12.014</td><td>12.014</td><td>12.014</td></tr><tr><td>-10</td><td>12.021</td><td>12.021</td><td>12.021</td></tr><tr><td>0</td><td>12.027</td><td>12.027</td><td>12.027</td></tr><tr><td>10</td><td>12.030</td><td>12.030</td><td>12.030</td></tr><tr><td>20</td><td>12.032</td><td>12.032</td><td>12.032</td></tr><tr><td>25</td><td>12.032</td><td>12.032</td><td>12.032</td></tr><tr><td>30</td><td>12.032</td><td>12.032</td><td>12.032</td></tr><tr><td>40</td><td>12.030</td><td>12.030</td><td>12.030</td></tr><tr><td>50</td><td>12.026</td><td>12.026</td><td>12.026</td></tr><tr><td>60</td><td>12.020</td><td>12.020</td><td>12.020</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-20	12.014	12.014	12.014	-10	12.021	12.021	12.021	0	12.027	12.027	12.027	10	12.030	12.030	12.030	20	12.032	12.032	12.032	25	12.032	12.032	12.032	30	12.032	12.032	12.032	40	12.030	12.030	12.030	50	12.026	12.026	12.026	60	12.020	12.020	12.020	--	-	-	-		
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
-20	12.014	12.014	12.014																																																			
-10	12.021	12.021	12.021																																																			
0	12.027	12.027	12.027																																																			
10	12.030	12.030	12.030																																																			
20	12.032	12.032	12.032																																																			
25	12.032	12.032	12.032																																																			
30	12.032	12.032	12.032																																																			
40	12.030	12.030	12.030																																																			
50	12.026	12.026	12.026																																																			
60	12.020	12.020	12.020																																																			
--	-	-	-																																																			
Object	-12V0.6A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>-20</td><td>-12.013</td><td>-12.013</td><td>-12.013</td></tr><tr><td>-10</td><td>-12.021</td><td>-12.021</td><td>-12.021</td></tr><tr><td>0</td><td>-12.026</td><td>-12.026</td><td>-12.026</td></tr><tr><td>10</td><td>-12.030</td><td>-12.030</td><td>-12.030</td></tr><tr><td>20</td><td>-12.032</td><td>-12.032</td><td>-12.032</td></tr><tr><td>25</td><td>-12.032</td><td>-12.032</td><td>-12.032</td></tr><tr><td>30</td><td>-12.032</td><td>-12.032</td><td>-12.032</td></tr><tr><td>40</td><td>-12.031</td><td>-12.032</td><td>-12.031</td></tr><tr><td>50</td><td>-12.029</td><td>-12.029</td><td>-12.029</td></tr><tr><td>60</td><td>-12.026</td><td>-12.026</td><td>-12.026</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-20	-12.013	-12.013	-12.013	-10	-12.021	-12.021	-12.021	0	-12.026	-12.026	-12.026	10	-12.030	-12.030	-12.030	20	-12.032	-12.032	-12.032	25	-12.032	-12.032	-12.032	30	-12.032	-12.032	-12.032	40	-12.031	-12.032	-12.031	50	-12.029	-12.029	-12.029	60	-12.026	-12.026	-12.026	--	-	-	-		
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
-20	-12.013	-12.013	-12.013																																																			
-10	-12.021	-12.021	-12.021																																																			
0	-12.026	-12.026	-12.026																																																			
10	-12.030	-12.030	-12.030																																																			
20	-12.032	-12.032	-12.032																																																			
25	-12.032	-12.032	-12.032																																																			
30	-12.032	-12.032	-12.032																																																			
40	-12.031	-12.032	-12.031																																																			
50	-12.029	-12.029	-12.029																																																			
60	-12.026	-12.026	-12.026																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated ambient temperature.																																																						

- 15 -

BC-10213

COSEL


Model	G2W-12																								
Item	Time Lapse Drift	Temperature	25°C																						
Object	+12V0.6A	Testing Circuitry	Figure A																						
1.Graph		2.Values																							
<div></div> <div>Input Volt. 100V Load 100%</div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>12.031</td></tr><tr><td>0.5</td><td>12.032</td></tr><tr><td>1.0</td><td>12.032</td></tr><tr><td>2.0</td><td>12.032</td></tr><tr><td>3.0</td><td>12.032</td></tr><tr><td>4.0</td><td>12.032</td></tr><tr><td>5.0</td><td>12.032</td></tr><tr><td>6.0</td><td>12.032</td></tr><tr><td>7.0</td><td>12.032</td></tr><tr><td>8.0</td><td>12.032</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	12.031	0.5	12.032	1.0	12.032	2.0	12.032	3.0	12.032	4.0	12.032	5.0	12.032	6.0	12.032	7.0	12.032	8.0	12.032
Time since start [H]	Output Voltage [V]																								
0.0	12.031																								
0.5	12.032																								
1.0	12.032																								
2.0	12.032																								
3.0	12.032																								
4.0	12.032																								
5.0	12.032																								
6.0	12.032																								
7.0	12.032																								
8.0	12.032																								
Object	-12V0.6A																								
1.Graph		2.Values																							
<div></div> <div>Input Volt. 100V Load 100%</div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>-12.033</td></tr><tr><td>0.5</td><td>-12.033</td></tr><tr><td>1.0</td><td>-12.033</td></tr><tr><td>2.0</td><td>-12.033</td></tr><tr><td>3.0</td><td>-12.033</td></tr><tr><td>4.0</td><td>-12.033</td></tr><tr><td>5.0</td><td>-12.033</td></tr><tr><td>6.0</td><td>-12.033</td></tr><tr><td>7.0</td><td>-12.033</td></tr><tr><td>8.0</td><td>-12.033</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	-12.033	0.5	-12.033	1.0	-12.033	2.0	-12.033	3.0	-12.033	4.0	-12.033	5.0	-12.033	6.0	-12.033	7.0	-12.033	8.0	-12.033
Time since start [H]	Output Voltage [V]																								
0.0	-12.033																								
0.5	-12.033																								
1.0	-12.033																								
2.0	-12.033																								
3.0	-12.033																								
4.0	-12.033																								
5.0	-12.033																								
6.0	-12.033																								
7.0	-12.033																								
8.0	-12.033																								

- 17 -

BC-10213


Model	G2W-12	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V0.6A		

1.Graph




2.Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	12.8	23.3	36.1	49.0	203.5
100 %	12.8	23.3	36.1	20.0	106.0




Model	G2W-12	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-12V0.6A		

1.Graph



2.Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		12.8	23.8	36.6	48.0	202.0
100 %		12.8	23.8	36.6	19.5	103.5



Model	G2W-12																																		
Item	Hold-Up Time	Temperature	25°C																																
		Testing Circuitry	Figure A																																
Object	+12V0.6A																																		
1.Graph		2.Values																																	
<div><div><div>---</div><div>□</div><div>---</div><div>Load 50%</div></div><div><div>—</div><div>△</div><div>—</div><div>Load 100%</div></div></div> <p>Hold-Up Time [ms]</p> <p>Input Voltage [V]</p> <p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Hold-Up Time [ms]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>85</td><td>19</td><td>5</td></tr><tr><td>90</td><td>27</td><td>9</td></tr><tr><td>100</td><td>41</td><td>16</td></tr><tr><td>110</td><td>56</td><td>23</td></tr><tr><td>115</td><td>63</td><td>27</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	19	5	90	27	9	100	41	16	110	56	23	115	63	27	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	19	5																																	
90	27	9																																	
100	41	16																																	
110	56	23																																	
115	63	27																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	

Model	G2W-12																																		
Item	Hold-Up Time	Temperature	25°C																																
		Testing Circuitry	Figure A																																
Object	-12V0.6A																																		
1.Graph		2.Values																																	
<div><div><div>---</div><div>□---</div><div>Load 50%</div></div><div><div>—</div><div>△—</div><div>Load 100%</div></div></div> <p>Hold-Up Time [ms]</p> <p>Input Voltage [V]</p>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Hold-Up Time [ms]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>85</td><td>19</td><td>5</td></tr><tr><td>90</td><td>26</td><td>9</td></tr><tr><td>100</td><td>41</td><td>16</td></tr><tr><td>110</td><td>55</td><td>23</td></tr><tr><td>115</td><td>62</td><td>26</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	19	5	90	26	9	100	41	16	110	55	23	115	62	26	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	19	5																																	
90	26	9																																	
100	41	16																																	
110	55	23																																	
115	62	26																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																			



Model	G2W-12	Temperature25°C Testing CircuitryFigure A																																																				
Item	Instantaneous Interruption Compensation																																																					
Object	+12V0.6A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.10</td><td>91</td><td>133</td><td>176</td></tr><tr><td>0.20</td><td>40</td><td>63</td><td>85</td></tr><tr><td>0.30</td><td>21</td><td>38</td><td>54</td></tr><tr><td>0.40</td><td>17</td><td>23</td><td>38</td></tr><tr><td>0.50</td><td>5</td><td>21</td><td>23</td></tr><tr><td>0.60</td><td>5</td><td>16</td><td>23</td></tr><tr><td>0.66</td><td>4</td><td>6</td><td>20</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated load current.</p>		Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-	-	-	0.10	91	133	176	0.20	40	63	85	0.30	21	38	54	0.40	17	23	38	0.50	5	21	23	0.60	5	16	23	0.66	4	6	20	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-	-	-																																																			
0.10	91	133	176																																																			
0.20	40	63	85																																																			
0.30	21	38	54																																																			
0.40	17	23	38																																																			
0.50	5	21	23																																																			
0.60	5	16	23																																																			
0.66	4	6	20																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	G2W-12																																																					
Item	Instantaneous Interruption Compensation	Temperature	25°C																																																			
Object	-12V0.6A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div> <div>Instantaneous Compensation Time [ms]</div> <div>Load Current [A]</div> <div>Note: Slanted line shows the range of the rated load current.</div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.10</td><td>91</td><td>132</td><td>174</td></tr><tr><td>0.20</td><td>40</td><td>63</td><td>85</td></tr><tr><td>0.30</td><td>21</td><td>38</td><td>54</td></tr><tr><td>0.40</td><td>17</td><td>23</td><td>38</td></tr><tr><td>0.50</td><td>5</td><td>20</td><td>23</td></tr><tr><td>0.60</td><td>5</td><td>16</td><td>23</td></tr><tr><td>0.66</td><td>4</td><td>6</td><td>20</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-	-	-	0.10	91	132	174	0.20	40	63	85	0.30	21	38	54	0.40	17	23	38	0.50	5	20	23	0.60	5	16	23	0.66	4	6	20	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-	-	-																																																			
0.10	91	132	174																																																			
0.20	40	63	85																																																			
0.30	21	38	54																																																			
0.40	17	23	38																																																			
0.50	5	20	23																																																			
0.60	5	16	23																																																			
0.66	4	6	20																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	G2W-12																																								
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																							
Object	+12V0.6A																																								
1.Graph		2.Values																																							
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-20</td><td>70</td><td>76</td></tr><tr><td>-10</td><td>71</td><td>77</td></tr><tr><td>0</td><td>71</td><td>77</td></tr><tr><td>10</td><td>71</td><td>77</td></tr><tr><td>20</td><td>71</td><td>77</td></tr><tr><td>25</td><td>71</td><td>77</td></tr><tr><td>30</td><td>71</td><td>77</td></tr><tr><td>40</td><td>71</td><td>77</td></tr><tr><td>50</td><td>71</td><td>77</td></tr><tr><td>60</td><td>71</td><td>77</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	70	76	-10	71	77	0	71	77	10	71	77	20	71	77	25	71	77	30	71	77	40	71	77	50	71	77	60	71	77	--	-	-		
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	70	76																																							
-10	71	77																																							
0	71	77																																							
10	71	77																																							
20	71	77																																							
25	71	77																																							
30	71	77																																							
40	71	77																																							
50	71	77																																							
60	71	77																																							
--	-	-																																							
Object	-12V0.6A																																								
1.Graph		2.Values																																							
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-20</td><td>70</td><td>76</td></tr><tr><td>-10</td><td>71</td><td>77</td></tr><tr><td>0</td><td>71</td><td>77</td></tr><tr><td>10</td><td>71</td><td>77</td></tr><tr><td>20</td><td>71</td><td>77</td></tr><tr><td>25</td><td>71</td><td>77</td></tr><tr><td>30</td><td>71</td><td>77</td></tr><tr><td>40</td><td>71</td><td>77</td></tr><tr><td>50</td><td>71</td><td>78</td></tr><tr><td>60</td><td>71</td><td>79</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	70	76	-10	71	77	0	71	77	10	71	77	20	71	77	25	71	77	30	71	77	40	71	77	50	71	78	60	71	79	--	-	-		
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	70	76																																							
-10	71	77																																							
0	71	77																																							
10	71	77																																							
20	71	77																																							
25	71	77																																							
30	71	77																																							
40	71	77																																							
50	71	78																																							
60	71	79																																							
--	-	-																																							
Note: Slanted line shows the range of the rated ambient temperature.																																									

- 24 -

BC-10213

Model	G2W-12																																																									
Item	Overcurrent Protection	Temperature	25°C																																																							
Object	+12V0.6A	Testing Circuitry	Figure A																																																							
1.Graph		2.Values																																																								
<div><div><div></div>Input Volt. 90V</div><div><div></div>Input Volt. 100V</div><div><div></div>Input Volt. 110V</div></div> 		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>12.0</td><td>0.77</td><td>0.77</td><td>0.77</td></tr><tr><td>11.4</td><td>0.75</td><td>0.75</td><td>0.75</td></tr><tr><td>10.8</td><td>0.73</td><td>0.73</td><td>0.73</td></tr><tr><td>9.6</td><td>0.69</td><td>0.69</td><td>0.69</td></tr><tr><td>8.4</td><td>0.64</td><td>0.64</td><td>0.64</td></tr><tr><td>7.2</td><td>0.60</td><td>0.60</td><td>0.60</td></tr><tr><td>6.0</td><td>0.56</td><td>0.56</td><td>0.56</td></tr><tr><td>4.8</td><td>0.51</td><td>0.51</td><td>0.51</td></tr><tr><td>3.6</td><td>0.47</td><td>0.47</td><td>0.47</td></tr><tr><td>2.4</td><td>0.43</td><td>0.43</td><td>0.43</td></tr><tr><td>1.2</td><td>0.38</td><td>0.38</td><td>0.38</td></tr><tr><td>0.0</td><td>0.33</td><td>0.33</td><td>0.33</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	12.0	0.77	0.77	0.77	11.4	0.75	0.75	0.75	10.8	0.73	0.73	0.73	9.6	0.69	0.69	0.69	8.4	0.64	0.64	0.64	7.2	0.60	0.60	0.60	6.0	0.56	0.56	0.56	4.8	0.51	0.51	0.51	3.6	0.47	0.47	0.47	2.4	0.43	0.43	0.43	1.2	0.38	0.38	0.38	0.0	0.33	0.33	0.33
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
12.0	0.77	0.77	0.77																																																							
11.4	0.75	0.75	0.75																																																							
10.8	0.73	0.73	0.73																																																							
9.6	0.69	0.69	0.69																																																							
8.4	0.64	0.64	0.64																																																							
7.2	0.60	0.60	0.60																																																							
6.0	0.56	0.56	0.56																																																							
4.8	0.51	0.51	0.51																																																							
3.6	0.47	0.47	0.47																																																							
2.4	0.43	0.43	0.43																																																							
1.2	0.38	0.38	0.38																																																							
0.0	0.33	0.33	0.33																																																							
Object	-12V0.6A																																																									
1.Graph		2.Values																																																								
<div><div><div></div>Input Volt. 90V</div><div><div></div>Input Volt. 100V</div><div><div></div>Input Volt. 110V</div></div>  <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>-12.0</td><td>0.78</td><td>0.78</td><td>0.78</td></tr><tr><td>-11.4</td><td>0.76</td><td>0.76</td><td>0.76</td></tr><tr><td>-10.8</td><td>0.73</td><td>0.73</td><td>0.73</td></tr><tr><td>-9.6</td><td>0.69</td><td>0.69</td><td>0.69</td></tr><tr><td>-8.4</td><td>0.65</td><td>0.65</td><td>0.65</td></tr><tr><td>-7.2</td><td>0.60</td><td>0.60</td><td>0.60</td></tr><tr><td>-6.0</td><td>0.56</td><td>0.56</td><td>0.56</td></tr><tr><td>-4.8</td><td>0.51</td><td>0.51</td><td>0.51</td></tr><tr><td>-3.6</td><td>0.47</td><td>0.47</td><td>0.47</td></tr><tr><td>-2.4</td><td>0.43</td><td>0.43</td><td>0.43</td></tr><tr><td>-1.2</td><td>0.39</td><td>0.39</td><td>0.39</td></tr><tr><td>0.0</td><td>0.34</td><td>0.34</td><td>0.34</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-12.0	0.78	0.78	0.78	-11.4	0.76	0.76	0.76	-10.8	0.73	0.73	0.73	-9.6	0.69	0.69	0.69	-8.4	0.65	0.65	0.65	-7.2	0.60	0.60	0.60	-6.0	0.56	0.56	0.56	-4.8	0.51	0.51	0.51	-3.6	0.47	0.47	0.47	-2.4	0.43	0.43	0.43	-1.2	0.39	0.39	0.39	0.0	0.34	0.34	0.34
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
-12.0	0.78	0.78	0.78																																																							
-11.4	0.76	0.76	0.76																																																							
-10.8	0.73	0.73	0.73																																																							
-9.6	0.69	0.69	0.69																																																							
-8.4	0.65	0.65	0.65																																																							
-7.2	0.60	0.60	0.60																																																							
-6.0	0.56	0.56	0.56																																																							
-4.8	0.51	0.51	0.51																																																							
-3.6	0.47	0.47	0.47																																																							
-2.4	0.43	0.43	0.43																																																							
-1.2	0.39	0.39	0.39																																																							
0.0	0.34	0.34	0.34																																																							

- 25 -

BC-10213




Figure A