

TEST DATA OF GT3.5W-15

Regulated DC Power Supply
October 26, 2010

Approved by : Eiyoshi Wakamatsu
Eiyoshi Wakamatsu Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Line Regulation	8
9.Load Regulation	9
10.Dynamic Load Response	10
11.Ripple Voltage (by Load Current)	12
12.Ripple Voltage (by Ambient Temperature)	14
13.Ambient Temperature Drift	15
14.Output Voltage Accuracy	16
15.Time Lapse Drift	17
16.Rise and Fall Time	18
17.Hold-Up Time	20
18.Instantaneous Interruption Compensation	22
19.Minimum Input Voltage for Regulated Output Voltage	24
20.Overcurrent Protection	25
21.Figure of Testing Circuitry	26

(Final Page 26)

COSEL

Model	GT3.5W-15																																																					
Item	Input Current (by Load Current)																																																					
Object	_____																																																					
1.Graph		2.Values																																																				
<div><div>—△—</div><div>Input Volt.</div><div>90V</div></div> <div><div>---□---</div><div>Input Volt.</div><div>100V</div></div> <div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div> <p>Input Current [A]</p> <p>Load Ration [%]</p>		<table><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0</td><td>0.037</td><td>0.044</td><td>0.051</td></tr><tr><td>20</td><td>0.345</td><td>0.353</td><td>0.361</td></tr><tr><td>40</td><td>0.603</td><td>0.615</td><td>0.627</td></tr><tr><td>60</td><td>0.840</td><td>0.855</td><td>0.872</td></tr><tr><td>80</td><td>1.062</td><td>1.083</td><td>1.102</td></tr><tr><td>100</td><td>1.276</td><td>1.300</td><td>1.323</td></tr><tr><td>110</td><td>1.380</td><td>1.406</td><td>1.430</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Ration [%]	Input Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	0.037	0.044	0.051	20	0.345	0.353	0.361	40	0.603	0.615	0.627	60	0.840	0.855	0.872	80	1.062	1.083	1.102	100	1.276	1.300	1.323	110	1.380	1.406	1.430	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0	0.037	0.044	0.051																																																			
20	0.345	0.353	0.361																																																			
40	0.603	0.615	0.627																																																			
60	0.840	0.855	0.872																																																			
80	1.062	1.083	1.102																																																			
100	1.276	1.300	1.323																																																			
110	1.380	1.406	1.430																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model		GT3.5W-15		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <div><div><div>Input Power [W]</div><div>200</div><div>150</div><div>100</div><div>50</div><div>0</div></div><div><div>0</div><div>40</div><div>80</div><div>120</div></div><div><div>Load Ration [%]</div></div></div>		2.Values																																																				
		<table><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0</td><td>1.9</td><td>2.3</td><td>2.7</td></tr><tr><td>20</td><td>18.5</td><td>20.7</td><td>23.0</td></tr><tr><td>40</td><td>35.0</td><td>39.0</td><td>43.1</td></tr><tr><td>60</td><td>51.3</td><td>57.1</td><td>63.2</td></tr><tr><td>80</td><td>67.3</td><td>75.1</td><td>82.9</td></tr><tr><td>100</td><td>83.3</td><td>92.9</td><td>102.6</td></tr><tr><td>110</td><td>91.2</td><td>101.7</td><td>112.3</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Ration [%]	Input Power [W]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	1.9	2.3	2.7	20	18.5	20.7	23.0	40	35.0	39.0	43.1	60	51.3	57.1	63.2	80	67.3	75.1	82.9	100	83.3	92.9	102.6	110	91.2	101.7	112.3	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																							
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																					
0	1.9	2.3	2.7																																																					
20	18.5	20.7	23.0																																																					
40	35.0	39.0	43.1																																																					
60	51.3	57.1	63.2																																																					
80	67.3	75.1	82.9																																																					
100	83.3	92.9	102.6																																																					
110	91.2	101.7	112.3																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					

Model	GT3.5W-15																																
Item	Efficiency (by Input Voltage)	Temperature	25°C																														
Object		Testing Circuitry	Figure A																														
1.Graph		2.Values																															
<div><div><div>---</div><div>□</div><div>---</div></div><div>Load 50%</div></div> <div><div>—</div><div>△</div><div>—</div></div> <div>Load 100%</div> <table><thead><tr><th>Input Voltage [V]</th><th>Efficiency [%] Load 50%</th><th>Efficiency [%] Load 100%</th></tr></thead><tbody><tr><td>85</td><td>70.4</td><td>72.9</td></tr><tr><td>90</td><td>66.3</td><td>68.7</td></tr><tr><td>100</td><td>59.4</td><td>61.5</td></tr><tr><td>110</td><td>53.8</td><td>55.7</td></tr><tr><td>115</td><td>51.3</td><td>53.2</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Efficiency [%] Load 50%	Efficiency [%] Load 100%	85	70.4	72.9	90	66.3	68.7	100	59.4	61.5	110	53.8	55.7	115	51.3	53.2	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Efficiency [%] Load 50%	Efficiency [%] Load 100%																															
85	70.4	72.9																															
90	66.3	68.7																															
100	59.4	61.5																															
110	53.8	55.7																															
115	51.3	53.2																															
--	-	-																															
--	-	-																															
--	-	-																															
--	-	-																															

COSEL

Model	GT3.5W-15																																																																																	
Item	Efficiency (by Load Current)	Temperature	25°C																																																																															
Object		Testing Circuitry	Figure A																																																																															
1.Graph <div> —△— Input Volt. 90V ---□--- Input Volt. 100V -·-○-·- Input Volt. 110V </div> <table border="1"> <caption>Efficiency Data from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>90V Efficiency [%]</th> <th>100V Efficiency [%]</th> <th>110V Efficiency [%]</th> </tr> </thead> <tbody> <tr><td>20</td><td>61.8</td><td>55.2</td><td>49.7</td></tr> <tr><td>40</td><td>65.3</td><td>58.6</td><td>53.0</td></tr> <tr><td>60</td><td>66.9</td><td>60.1</td><td>54.3</td></tr> <tr><td>80</td><td>68.0</td><td>60.9</td><td>55.2</td></tr> <tr><td>100</td><td>68.6</td><td>61.5</td><td>55.7</td></tr> <tr><td>110</td><td>69.0</td><td>61.8</td><td>56.0</td></tr> </tbody> </table>		Load Ration [%]	90V Efficiency [%]	100V Efficiency [%]	110V Efficiency [%]	20	61.8	55.2	49.7	40	65.3	58.6	53.0	60	66.9	60.1	54.3	80	68.0	60.9	55.2	100	68.6	61.5	55.7	110	69.0	61.8	56.0	2.Values <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th><th colspan="3">Efficiency [%]</th></tr> <tr> <th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>61.8</td><td>55.2</td><td>49.7</td></tr> <tr><td>40</td><td>65.3</td><td>58.6</td><td>53.0</td></tr> <tr><td>60</td><td>66.9</td><td>60.1</td><td>54.3</td></tr> <tr><td>80</td><td>68.0</td><td>60.9</td><td>55.2</td></tr> <tr><td>100</td><td>68.6</td><td>61.5</td><td>55.7</td></tr> <tr><td>110</td><td>69.0</td><td>61.8</td><td>56.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Efficiency [%]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	61.8	55.2	49.7	40	65.3	58.6	53.0	60	66.9	60.1	54.3	80	68.0	60.9	55.2	100	68.6	61.5	55.7	110	69.0	61.8	56.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	90V Efficiency [%]	100V Efficiency [%]	110V Efficiency [%]																																																																															
20	61.8	55.2	49.7																																																																															
40	65.3	58.6	53.0																																																																															
60	66.9	60.1	54.3																																																																															
80	68.0	60.9	55.2																																																																															
100	68.6	61.5	55.7																																																																															
110	69.0	61.8	56.0																																																																															
Load Ration [%]	Efficiency [%]																																																																																	
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																																															
0	-	-	-																																																																															
20	61.8	55.2	49.7																																																																															
40	65.3	58.6	53.0																																																																															
60	66.9	60.1	54.3																																																																															
80	68.0	60.9	55.2																																																																															
100	68.6	61.5	55.7																																																																															
110	69.0	61.8	56.0																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															


COSEL

Model	GT3.5W-15																																
Item	Power Factor (by Input Voltage)	Temperature	25°C																														
		Testing Circuitry	Figure A																														
Object																																	
1.Graph		2.Values																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>0.669</td><td>0.731</td></tr><tr><td>90</td><td>0.663</td><td>0.726</td></tr><tr><td>100</td><td>0.654</td><td>0.716</td></tr><tr><td>110</td><td>0.644</td><td>0.706</td></tr><tr><td>115</td><td>0.640</td><td>0.702</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Load 50%	Load 100%	85	0.669	0.731	90	0.663	0.726	100	0.654	0.716	110	0.644	0.706	115	0.640	0.702	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Load 50%	Load 100%																															
85	0.669	0.731																															
90	0.663	0.726																															
100	0.654	0.716																															
110	0.644	0.706																															
115	0.640	0.702																															
--	-	-																															
--	-	-																															
--	-	-																															
--	-	-																															

Model	GT3.5W-15																																																		
Item	Power Factor (by Load Current)	Temperature	25°C																																																
		Testing Circuitry	Figure A																																																
Object																																																			
1.Graph		2.Values																																																	
<div><div><div>—△—</div><div>---□---</div><div>-·-○-·-</div></div><div><div>Input Volt.</div><div>Input Volt.</div><div>Input Volt.</div></div><div><div>90V</div><div>100V</div><div>110V</div></div></div> <table><thead><tr><th>Load Ration [%]</th><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>20</td><td>0.595</td><td>0.586</td><td>0.579</td></tr><tr><td>40</td><td>0.646</td><td>0.634</td><td>0.626</td></tr><tr><td>60</td><td>0.679</td><td>0.669</td><td>0.660</td></tr><tr><td>80</td><td>0.705</td><td>0.694</td><td>0.685</td></tr><tr><td>100</td><td>0.726</td><td>0.715</td><td>0.706</td></tr><tr><td>110</td><td>0.735</td><td>0.724</td><td>0.714</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Ration [%]	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	0.595	0.586	0.579	40	0.646	0.634	0.626	60	0.679	0.669	0.660	80	0.705	0.694	0.685	100	0.726	0.715	0.706	110	0.735	0.724	0.714	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Ration [%]	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																
0	-	-	-																																																
20	0.595	0.586	0.579																																																
40	0.646	0.634	0.626																																																
60	0.679	0.669	0.660																																																
80	0.705	0.694	0.685																																																
100	0.726	0.715	0.706																																																
110	0.735	0.724	0.714																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																


COSEL

<div>COSEL</div>		<div>Temperature 25°C Testing Circuitry Figure A</div>
Model	GT3.5W-15	
Item	Inrush Current	
Object	<div></div>	





Input Voltage	100 V
Frequency	60 Hz
Load	100 %

Primary inrush current	22.9 A
------------------------	--------



Model	GT3.5W-15																																
Item	Line Regulation	Temperature	25°C																														
Object	+15V1.9A	Testing Circuitry	Figure A																														
1.Graph		2.Values																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Output Voltage [V] Load 50%</th><th>Output Voltage [V] Load 100%</th></tr></thead><tbody><tr><td>85</td><td>15.035</td><td>15.035</td></tr><tr><td>90</td><td>15.035</td><td>15.035</td></tr><tr><td>100</td><td>15.035</td><td>15.035</td></tr><tr><td>110</td><td>15.036</td><td>15.036</td></tr><tr><td>115</td><td>15.036</td><td>15.036</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%	85	15.035	15.035	90	15.035	15.035	100	15.035	15.035	110	15.036	15.036	115	15.036	15.036	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%																															
85	15.035	15.035																															
90	15.035	15.035																															
100	15.035	15.035																															
110	15.036	15.036																															
115	15.036	15.036																															
--	-	-																															
--	-	-																															
--	-	-																															
--	-	-																															
Object	-15V1.9A																																
1.Graph		2.Values																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Output Voltage [V] Load 50%</th><th>Output Voltage [V] Load 100%</th></tr></thead><tbody><tr><td>85</td><td>-15.046</td><td>-15.046</td></tr><tr><td>90</td><td>-15.046</td><td>-15.046</td></tr><tr><td>100</td><td>-15.047</td><td>-15.047</td></tr><tr><td>110</td><td>-15.047</td><td>-15.047</td></tr><tr><td>115</td><td>-15.047</td><td>-15.047</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%	85	-15.046	-15.046	90	-15.046	-15.046	100	-15.047	-15.047	110	-15.047	-15.047	115	-15.047	-15.047	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%																															
85	-15.046	-15.046																															
90	-15.046	-15.046																															
100	-15.047	-15.047																															
110	-15.047	-15.047																															
115	-15.047	-15.047																															
--	-	-																															
--	-	-																															
--	-	-																															
--	-	-																															
Note: Slanted line shows the range of the rated input voltage.																																	



Model	GT3.5W-15																																																						
Item	Load Regulation	Temperature 25°C Testing Circuitry Figure A																																																					
Object	+15V1.9A																																																						
1.Graph		2.Values																																																					
<div><div><div>—△—</div><div>Input Volt. 90V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 110V</div></div></div> 		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>15.035</td><td>15.035</td><td>15.035</td></tr><tr><td>0.30</td><td>15.035</td><td>15.035</td><td>15.035</td></tr><tr><td>0.60</td><td>15.035</td><td>15.035</td><td>15.035</td></tr><tr><td>0.90</td><td>15.035</td><td>15.035</td><td>15.035</td></tr><tr><td>1.20</td><td>15.035</td><td>15.035</td><td>15.035</td></tr><tr><td>1.50</td><td>15.035</td><td>15.035</td><td>15.035</td></tr><tr><td>1.80</td><td>15.035</td><td>15.035</td><td>15.035</td></tr><tr><td>1.90</td><td>15.035</td><td>15.035</td><td>15.035</td></tr><tr><td>2.09</td><td>15.035</td><td>15.035</td><td>15.035</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>			Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	15.035	15.035	15.035	0.30	15.035	15.035	15.035	0.60	15.035	15.035	15.035	0.90	15.035	15.035	15.035	1.20	15.035	15.035	15.035	1.50	15.035	15.035	15.035	1.80	15.035	15.035	15.035	1.90	15.035	15.035	15.035	2.09	15.035	15.035	15.035	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																				
0.00	15.035	15.035	15.035																																																				
0.30	15.035	15.035	15.035																																																				
0.60	15.035	15.035	15.035																																																				
0.90	15.035	15.035	15.035																																																				
1.20	15.035	15.035	15.035																																																				
1.50	15.035	15.035	15.035																																																				
1.80	15.035	15.035	15.035																																																				
1.90	15.035	15.035	15.035																																																				
2.09	15.035	15.035	15.035																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Object	-15V1.9A																																																						
1.Graph		2.Values																																																					
<div><div><div>—△—</div><div>Input Volt. 90V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 110V</div></div></div> 		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>-15.046</td><td>-15.047</td><td>-15.047</td></tr><tr><td>0.30</td><td>-15.046</td><td>-15.047</td><td>-15.047</td></tr><tr><td>0.60</td><td>-15.046</td><td>-15.047</td><td>-15.047</td></tr><tr><td>0.90</td><td>-15.046</td><td>-15.047</td><td>-15.047</td></tr><tr><td>1.20</td><td>-15.046</td><td>-15.047</td><td>-15.047</td></tr><tr><td>1.50</td><td>-15.046</td><td>-15.047</td><td>-15.047</td></tr><tr><td>1.80</td><td>-15.046</td><td>-15.047</td><td>-15.047</td></tr><tr><td>1.90</td><td>-15.046</td><td>-15.047</td><td>-15.047</td></tr><tr><td>2.09</td><td>-15.046</td><td>-15.047</td><td>-15.047</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>			Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-15.046	-15.047	-15.047	0.30	-15.046	-15.047	-15.047	0.60	-15.046	-15.047	-15.047	0.90	-15.046	-15.047	-15.047	1.20	-15.046	-15.047	-15.047	1.50	-15.046	-15.047	-15.047	1.80	-15.046	-15.047	-15.047	1.90	-15.046	-15.047	-15.047	2.09	-15.046	-15.047	-15.047	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																				
0.00	-15.046	-15.047	-15.047																																																				
0.30	-15.046	-15.047	-15.047																																																				
0.60	-15.046	-15.047	-15.047																																																				
0.90	-15.046	-15.047	-15.047																																																				
1.20	-15.046	-15.047	-15.047																																																				
1.50	-15.046	-15.047	-15.047																																																				
1.80	-15.046	-15.047	-15.047																																																				
1.90	-15.046	-15.047	-15.047																																																				
2.09	-15.046	-15.047	-15.047																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note: Slanted line shows the range of the rated load current.																																																							

- 9 -


BC-10222



Model	GT3.5W-15		
Item	Dynamic Load Response	Temperature	25°C
Object	+15V1.9A	Testing Circuitry	Figure A


Input Volt. 100 V
Cycle 1000 ms

Load Current




Min. Load (0A) \longleftrightarrow
Load 100% (1.9A)

50 mV/div




100 μ s/div




100 μ s/div

Load 50% (0.95A) \longleftrightarrow
Load 100% (1.9A)

50 mV/div



100 μ s/div



100 μ s/div




Model	GT3.5W-15	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Response		
Object	-15V1.9A		

Input Volt. 100 V
Cycle 1000 ms


Load Current

Min. Load (0A) ←→
Load 100% (1.9A)

50 mV/div




100 μ s/div




100 μ s/div

Load 50% (0.95A) ←→
Load 100% (1.9A)

50 mV/div



100 μ s/div



100 μ s/div

Model	GT3.5W-15																																											
Item	Ripple Voltage (by Load Current)	Temperature	25°C																																									
		Testing Circuitry	Figure A																																									
Object	+15V1.9A																																											
1.Graph		2.Values																																										
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 90 [V]</th><th>Input Volt. 110 [V]</th></tr><tr><td>0.00</td><td>1.0</td><td>1.0</td></tr><tr><td>0.95</td><td>1.0</td><td>1.0</td></tr><tr><td>1.90</td><td>1.0</td><td>1.0</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.00	1.0	1.0	0.95	1.0	1.0	1.90	1.0	1.0	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																											
	Input Volt. 90 [V]	Input Volt. 110 [V]																																										
0.00	1.0	1.0																																										
0.95	1.0	1.0																																										
1.90	1.0	1.0																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.																																												

Model	GT3.5W-15	Temperature Testing Circuitry	25°C Figure A																																									
Item	Ripple Voltage (by Load Current)																																											
Object	-15V1.9A																																											
1.Graph		2.Values																																										
<div><div><div><div></div><div>Input Volt. 90V</div></div><div><div></div><div>Input Volt. 110V</div></div></div><p>Ripple Voltage [mV]</p><p>Load Current [A]</p></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 90 [V]</th><th>Input Volt. 110 [V]</th></tr><tr><td>0.00</td><td>1.2</td><td>1.2</td></tr><tr><td>0.95</td><td>1.2</td><td>1.2</td></tr><tr><td>1.90</td><td>1.2</td><td>1.2</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.00	1.2	1.2	0.95	1.2	1.2	1.90	1.2	1.2	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																											
	Input Volt. 90 [V]	Input Volt. 110 [V]																																										
0.00	1.2	1.2																																										
0.95	1.2	1.2																																										
1.90	1.2	1.2																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.																																												

- 13 -

BC-10222



Model	GT3.5W-15																																									
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure A																																								
Object	+15V1.9A																																									
1.Graph		2.Values																																								
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Ambient Temperature [°C]</th><th>Load 50% [mV]</th><th>Load 100% [mV]</th></tr></thead><tbody><tr><td>-20</td><td>1.4</td><td>1.4</td></tr><tr><td>-10</td><td>1.0</td><td>1.0</td></tr><tr><td>25</td><td>1.0</td><td>1.0</td></tr><tr><td>50</td><td>1.0</td><td>1.0</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Input Volt. 100V</p>		Ambient Temperature [°C]	Load 50% [mV]	Load 100% [mV]	-20	1.4	1.4	-10	1.0	1.0	25	1.0	1.0	50	1.0	1.0	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-		
Ambient Temperature [°C]	Load 50% [mV]	Load 100% [mV]																																								
-20	1.4	1.4																																								
-10	1.0	1.0																																								
25	1.0	1.0																																								
50	1.0	1.0																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
Object	-15V1.9A																																									
1.Graph		2.Values																																								
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Ambient Temperature [°C]</th><th>Load 50% [mV]</th><th>Load 100% [mV]</th></tr></thead><tbody><tr><td>-20</td><td>1.2</td><td>1.2</td></tr><tr><td>-10</td><td>0.8</td><td>0.8</td></tr><tr><td>25</td><td>0.8</td><td>0.8</td></tr><tr><td>50</td><td>0.8</td><td>0.8</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Input Volt. 100V</p> <p>Measured by 20 MHz Oscilloscope.</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		Ambient Temperature [°C]	Load 50% [mV]	Load 100% [mV]	-20	1.2	1.2	-10	0.8	0.8	25	0.8	0.8	50	0.8	0.8	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-		
Ambient Temperature [°C]	Load 50% [mV]	Load 100% [mV]																																								
-20	1.2	1.2																																								
-10	0.8	0.8																																								
25	0.8	0.8																																								
50	0.8	0.8																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
		BC-10222																																								

Model	GT3.5W-15																																																					
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																				
Object	+15V1.9A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>-20</td><td>15.028</td><td>15.028</td><td>15.028</td></tr><tr><td>-10</td><td>15.034</td><td>15.034</td><td>15.035</td></tr><tr><td>0</td><td>15.040</td><td>15.041</td><td>15.041</td></tr><tr><td>10</td><td>15.040</td><td>15.040</td><td>15.041</td></tr><tr><td>20</td><td>15.043</td><td>15.043</td><td>15.044</td></tr><tr><td>25</td><td>15.041</td><td>15.041</td><td>15.041</td></tr><tr><td>30</td><td>15.042</td><td>15.042</td><td>15.043</td></tr><tr><td>40</td><td>15.039</td><td>15.039</td><td>15.039</td></tr><tr><td>50</td><td>15.032</td><td>15.032</td><td>15.033</td></tr><tr><td>60</td><td>15.025</td><td>15.026</td><td>15.026</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-20	15.028	15.028	15.028	-10	15.034	15.034	15.035	0	15.040	15.041	15.041	10	15.040	15.040	15.041	20	15.043	15.043	15.044	25	15.041	15.041	15.041	30	15.042	15.042	15.043	40	15.039	15.039	15.039	50	15.032	15.032	15.033	60	15.025	15.026	15.026	--	-	-	-		
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
-20	15.028	15.028	15.028																																																			
-10	15.034	15.034	15.035																																																			
0	15.040	15.041	15.041																																																			
10	15.040	15.040	15.041																																																			
20	15.043	15.043	15.044																																																			
25	15.041	15.041	15.041																																																			
30	15.042	15.042	15.043																																																			
40	15.039	15.039	15.039																																																			
50	15.032	15.032	15.033																																																			
60	15.025	15.026	15.026																																																			
--	-	-	-																																																			
Object	-15V1.9A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>-20</td><td>-15.024</td><td>-15.024</td><td>-15.024</td></tr><tr><td>-10</td><td>-15.032</td><td>-15.032</td><td>-15.033</td></tr><tr><td>0</td><td>-15.039</td><td>-15.039</td><td>-15.040</td></tr><tr><td>10</td><td>-15.044</td><td>-15.044</td><td>-15.045</td></tr><tr><td>20</td><td>-15.046</td><td>-15.046</td><td>-15.046</td></tr><tr><td>25</td><td>-15.046</td><td>-15.047</td><td>-15.047</td></tr><tr><td>30</td><td>-15.046</td><td>-15.047</td><td>-15.047</td></tr><tr><td>40</td><td>-15.044</td><td>-15.044</td><td>-15.044</td></tr><tr><td>50</td><td>-15.039</td><td>-15.039</td><td>-15.039</td></tr><tr><td>60</td><td>-15.033</td><td>-15.034</td><td>-15.034</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-20	-15.024	-15.024	-15.024	-10	-15.032	-15.032	-15.033	0	-15.039	-15.039	-15.040	10	-15.044	-15.044	-15.045	20	-15.046	-15.046	-15.046	25	-15.046	-15.047	-15.047	30	-15.046	-15.047	-15.047	40	-15.044	-15.044	-15.044	50	-15.039	-15.039	-15.039	60	-15.033	-15.034	-15.034	--	-	-	-		
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
-20	-15.024	-15.024	-15.024																																																			
-10	-15.032	-15.032	-15.033																																																			
0	-15.039	-15.039	-15.040																																																			
10	-15.044	-15.044	-15.045																																																			
20	-15.046	-15.046	-15.046																																																			
25	-15.046	-15.047	-15.047																																																			
30	-15.046	-15.047	-15.047																																																			
40	-15.044	-15.044	-15.044																																																			
50	-15.039	-15.039	-15.039																																																			
60	-15.033	-15.034	-15.034																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated ambient temperature.																																																						

- 15 -

BC-10222

COSEL


Model	GT3.5W-15																								
Item	Time Lapse Drift	Temperature	25°C																						
Object	+15V1.9A	Testing Circuitry	Figure A																						
1.Graph		2.Values																							
<div><p>Input Volt. 100V Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>15.035</td></tr><tr><td>0.5</td><td>15.034</td></tr><tr><td>1.0</td><td>15.034</td></tr><tr><td>2.0</td><td>15.034</td></tr><tr><td>3.0</td><td>15.033</td></tr><tr><td>4.0</td><td>15.033</td></tr><tr><td>5.0</td><td>15.033</td></tr><tr><td>6.0</td><td>15.033</td></tr><tr><td>7.0</td><td>15.033</td></tr><tr><td>8.0</td><td>15.033</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	15.035	0.5	15.034	1.0	15.034	2.0	15.034	3.0	15.033	4.0	15.033	5.0	15.033	6.0	15.033	7.0	15.033	8.0	15.033
Time since start [H]	Output Voltage [V]																								
0.0	15.035																								
0.5	15.034																								
1.0	15.034																								
2.0	15.034																								
3.0	15.033																								
4.0	15.033																								
5.0	15.033																								
6.0	15.033																								
7.0	15.033																								
8.0	15.033																								
Object	-15V1.9A																								
1.Graph		2.Values																							
<div><p>Input Volt. 100V Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>-15.047</td></tr><tr><td>0.5</td><td>-15.046</td></tr><tr><td>1.0</td><td>-15.046</td></tr><tr><td>2.0</td><td>-15.046</td></tr><tr><td>3.0</td><td>-15.046</td></tr><tr><td>4.0</td><td>-15.046</td></tr><tr><td>5.0</td><td>-15.046</td></tr><tr><td>6.0</td><td>-15.046</td></tr><tr><td>7.0</td><td>-15.046</td></tr><tr><td>8.0</td><td>-15.046</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	-15.047	0.5	-15.046	1.0	-15.046	2.0	-15.046	3.0	-15.046	4.0	-15.046	5.0	-15.046	6.0	-15.046	7.0	-15.046	8.0	-15.046
Time since start [H]	Output Voltage [V]																								
0.0	-15.047																								
0.5	-15.046																								
1.0	-15.046																								
2.0	-15.046																								
3.0	-15.046																								
4.0	-15.046																								
5.0	-15.046																								
6.0	-15.046																								
7.0	-15.046																								
8.0	-15.046																								

- 17 -

BC-10222


Model	GT3.5W-15	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V1.9A		

1.Graph




2.Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		12.3	26.5	38.8	52.0	278.5
100 %		12.0	26.5	38.5	22.5	138.5




Model	GT3.5W-15	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-15V1.9A		

1.Graph



2.Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	12.3	26.5	38.8	53.0	272.5
100 %	12.0	26.5	38.5	22.0	137.5



Model	GT3.5W-15																																																				
Item	Hold-Up Time	Temperature	25°C																																																		
		Testing Circuitry	Figure A																																																		
Object	+15V1.9A																																																				
1.Graph		2.Values																																																			
<div><div><div>---</div><div>□---</div><div>Load 50%</div></div><div><div>—</div><div>△—</div><div>Load 100%</div></div></div> <p>The graph shows Hold-Up Time [ms] on a logarithmic y-axis (1 to 1000) versus Input Voltage [V] on a linear x-axis (80 to 120). Two data series are plotted: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show an increasing trend in hold-up time as input voltage increases. A vertical slanted line is drawn at 90V, indicating the rated input voltage range.</p> <table><caption>Data points estimated from the graph</caption><tr><th>Input Voltage [V]</th><th>Load 50% Hold-Up Time [ms]</th><th>Load 100% Hold-Up Time [ms]</th></tr><tr><td>85</td><td>18</td><td>4</td></tr><tr><td>90</td><td>26</td><td>9</td></tr><tr><td>100</td><td>43</td><td>17</td></tr><tr><td>110</td><td>60</td><td>25</td></tr><tr><td>115</td><td>69</td><td>30</td></tr></table>		Input Voltage [V]	Load 50% Hold-Up Time [ms]	Load 100% Hold-Up Time [ms]	85	18	4	90	26	9	100	43	17	110	60	25	115	69	30	<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Hold-Up Time [ms]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>85</td><td>18</td><td>4</td></tr><tr><td>90</td><td>26</td><td>9</td></tr><tr><td>100</td><td>43</td><td>17</td></tr><tr><td>110</td><td>60</td><td>25</td></tr><tr><td>115</td><td>69</td><td>30</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	18	4	90	26	9	100	43	17	110	60	25	115	69	30	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Load 50% Hold-Up Time [ms]	Load 100% Hold-Up Time [ms]																																																			
85	18	4																																																			
90	26	9																																																			
100	43	17																																																			
110	60	25																																																			
115	69	30																																																			
Input Voltage [V]	Hold-Up Time [ms]																																																				
	Load 50%	Load 100%																																																			
85	18	4																																																			
90	26	9																																																			
100	43	17																																																			
110	60	25																																																			
115	69	30																																																			
--	-	-																																																			
--	-	-																																																			
--	-	-																																																			
--	-	-																																																			
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																																					

Model		GT3.5W-15	
Item		Hold-Up Time	
Object		-15V1.9A	
1.Graph		2.Values	

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	17	4
90	26	8
100	42	17
110	60	25
115	69	30
--	-	-
--	-	-
--	-	-
--	-	-

1000

100

10

1

80 90 100 110 120

Input Voltage [V]

Hold-Up Time [ms]

---□--- Load 50%



—△— Load 100%

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

Model	GT3.5W-15																																																					
Item	Instantaneous Interruption Compensation	Temperature	25°C																																																			
Object	+15V1.9A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div> <div>Instantaneous Compensation Time [ms]</div> <div>Load Current [A]</div> <div>Note: Slanted line shows the range of the rated load current.</div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.30</td><td>96</td><td>151</td><td>205</td></tr><tr><td>0.60</td><td>39</td><td>71</td><td>99</td></tr><tr><td>0.90</td><td>22</td><td>39</td><td>63</td></tr><tr><td>1.20</td><td>6</td><td>23</td><td>45</td></tr><tr><td>1.50</td><td>5</td><td>22</td><td>23</td></tr><tr><td>1.80</td><td>5</td><td>19</td><td>23</td></tr><tr><td>1.90</td><td>5</td><td>6</td><td>22</td></tr><tr><td>2.09</td><td>4</td><td>6</td><td>22</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-	-	-	0.30	96	151	205	0.60	39	71	99	0.90	22	39	63	1.20	6	23	45	1.50	5	22	23	1.80	5	19	23	1.90	5	6	22	2.09	4	6	22	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-	-	-																																																			
0.30	96	151	205																																																			
0.60	39	71	99																																																			
0.90	22	39	63																																																			
1.20	6	23	45																																																			
1.50	5	22	23																																																			
1.80	5	19	23																																																			
1.90	5	6	22																																																			
2.09	4	6	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	GT3.5W-15																																																					
Item	Instantaneous Interruption Compensation	Temperature	25°C																																																			
Object	-15V1.9A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <div><div><div>Instantaneous Compensation Time [ms]</div><div>1000</div><div>100</div><div>10</div><div>1</div></div><div><div>0.0</div><div>1.0</div><div>2.0</div></div><div><div>Load Current [A]</div></div></div> <div>Note: Slanted line shows the range of the rated load current.</div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.30</td><td>96</td><td>146</td><td>202</td></tr><tr><td>0.60</td><td>38</td><td>71</td><td>98</td></tr><tr><td>0.90</td><td>21</td><td>39</td><td>63</td></tr><tr><td>1.20</td><td>6</td><td>23</td><td>45</td></tr><tr><td>1.50</td><td>5</td><td>21</td><td>23</td></tr><tr><td>1.80</td><td>5</td><td>19</td><td>22</td></tr><tr><td>1.90</td><td>4</td><td>6</td><td>22</td></tr><tr><td>2.09</td><td>4</td><td>5</td><td>22</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-	-	-	0.30	96	146	202	0.60	38	71	98	0.90	21	39	63	1.20	6	23	45	1.50	5	21	23	1.80	5	19	22	1.90	4	6	22	2.09	4	5	22	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-	-	-																																																			
0.30	96	146	202																																																			
0.60	38	71	98																																																			
0.90	21	39	63																																																			
1.20	6	23	45																																																			
1.50	5	21	23																																																			
1.80	5	19	22																																																			
1.90	4	6	22																																																			
2.09	4	5	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	GT3.5W-15	Testing Circuitry Figure A																																							
Item	Minimum Input Voltage for Regulated Output Voltage																																								
Object	+15V1.9A																																								
1.Graph		2.Values																																							
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> 		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>-20</td><td>75</td><td>78</td></tr><tr><td>-10</td><td>75</td><td>78</td></tr><tr><td>0</td><td>75</td><td>78</td></tr><tr><td>10</td><td>75</td><td>78</td></tr><tr><td>20</td><td>75</td><td>78</td></tr><tr><td>25</td><td>75</td><td>78</td></tr><tr><td>30</td><td>75</td><td>78</td></tr><tr><td>40</td><td>75</td><td>78</td></tr><tr><td>50</td><td>75</td><td>78</td></tr><tr><td>60</td><td>75</td><td>78</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	75	78	-10	75	78	0	75	78	10	75	78	20	75	78	25	75	78	30	75	78	40	75	78	50	75	78	60	75	78	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	75	78																																							
-10	75	78																																							
0	75	78																																							
10	75	78																																							
20	75	78																																							
25	75	78																																							
30	75	78																																							
40	75	78																																							
50	75	78																																							
60	75	78																																							
--	-	-																																							
Object	-15V1.9A																																								
1.Graph		2.Values																																							
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> 		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>-20</td><td>75</td><td>78</td></tr><tr><td>-10</td><td>75</td><td>78</td></tr><tr><td>0</td><td>75</td><td>78</td></tr><tr><td>10</td><td>75</td><td>78</td></tr><tr><td>20</td><td>75</td><td>78</td></tr><tr><td>25</td><td>75</td><td>78</td></tr><tr><td>30</td><td>75</td><td>78</td></tr><tr><td>40</td><td>75</td><td>78</td></tr><tr><td>50</td><td>75</td><td>78</td></tr><tr><td>60</td><td>75</td><td>78</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	75	78	-10	75	78	0	75	78	10	75	78	20	75	78	25	75	78	30	75	78	40	75	78	50	75	78	60	75	78	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	75	78																																							
-10	75	78																																							
0	75	78																																							
10	75	78																																							
20	75	78																																							
25	75	78																																							
30	75	78																																							
40	75	78																																							
50	75	78																																							
60	75	78																																							
--	-	-																																							
Note: Slanted line shows the range of the rated ambient temperature.																																									

- 24 -

BC-10222

Model	GT3.5W-15																																																									
Item	Overcurrent Protection	Temperature	25°C																																																							
Object	+15V1.9A	Testing Circuitry	Figure A																																																							
1.Graph		2.Values																																																								
<div><div></div>Input Volt. 90V</div> <div><div></div>Input Volt. 100V</div> <div><div></div>Input Volt. 110V</div> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>15.0</td><td>2.48</td><td>2.48</td><td>2.48</td></tr><tr><td>14.3</td><td>2.41</td><td>2.41</td><td>2.41</td></tr><tr><td>13.5</td><td>2.33</td><td>2.33</td><td>2.33</td></tr><tr><td>12.0</td><td>2.19</td><td>2.19</td><td>2.19</td></tr><tr><td>10.5</td><td>2.04</td><td>2.04</td><td>2.04</td></tr><tr><td>9.0</td><td>1.89</td><td>1.89</td><td>1.89</td></tr><tr><td>7.5</td><td>1.76</td><td>1.76</td><td>1.76</td></tr><tr><td>6.0</td><td>1.61</td><td>1.61</td><td>1.61</td></tr><tr><td>4.5</td><td>1.46</td><td>1.46</td><td>1.46</td></tr><tr><td>3.0</td><td>1.32</td><td>1.32</td><td>1.32</td></tr><tr><td>1.5</td><td>1.17</td><td>1.17</td><td>1.17</td></tr><tr><td>0.0</td><td>1.01</td><td>1.01</td><td>1.01</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	15.0	2.48	2.48	2.48	14.3	2.41	2.41	2.41	13.5	2.33	2.33	2.33	12.0	2.19	2.19	2.19	10.5	2.04	2.04	2.04	9.0	1.89	1.89	1.89	7.5	1.76	1.76	1.76	6.0	1.61	1.61	1.61	4.5	1.46	1.46	1.46	3.0	1.32	1.32	1.32	1.5	1.17	1.17	1.17	0.0	1.01	1.01	1.01
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
15.0	2.48	2.48	2.48																																																							
14.3	2.41	2.41	2.41																																																							
13.5	2.33	2.33	2.33																																																							
12.0	2.19	2.19	2.19																																																							
10.5	2.04	2.04	2.04																																																							
9.0	1.89	1.89	1.89																																																							
7.5	1.76	1.76	1.76																																																							
6.0	1.61	1.61	1.61																																																							
4.5	1.46	1.46	1.46																																																							
3.0	1.32	1.32	1.32																																																							
1.5	1.17	1.17	1.17																																																							
0.0	1.01	1.01	1.01																																																							
Object	-15V1.9A																																																									
1.Graph		2.Values																																																								
<div><div></div>Input Volt. 90V</div> <div><div></div>Input Volt. 100V</div> <div><div></div>Input Volt. 110V</div> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>-15.00</td><td>2.50</td><td>2.50</td><td>2.50</td></tr><tr><td>-14.25</td><td>2.43</td><td>2.43</td><td>2.43</td></tr><tr><td>-13.50</td><td>2.35</td><td>2.35</td><td>2.35</td></tr><tr><td>-12.00</td><td>2.21</td><td>2.21</td><td>2.21</td></tr><tr><td>-10.50</td><td>2.07</td><td>2.07</td><td>2.07</td></tr><tr><td>-9.00</td><td>1.92</td><td>1.92</td><td>1.92</td></tr><tr><td>-7.50</td><td>1.77</td><td>1.77</td><td>1.77</td></tr><tr><td>-6.00</td><td>1.63</td><td>1.63</td><td>1.63</td></tr><tr><td>-4.50</td><td>1.48</td><td>1.48</td><td>1.48</td></tr><tr><td>-3.00</td><td>1.33</td><td>1.33</td><td>1.33</td></tr><tr><td>-1.50</td><td>1.18</td><td>1.18</td><td>1.18</td></tr><tr><td>0.00</td><td>1.02</td><td>1.02</td><td>1.02</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-15.00	2.50	2.50	2.50	-14.25	2.43	2.43	2.43	-13.50	2.35	2.35	2.35	-12.00	2.21	2.21	2.21	-10.50	2.07	2.07	2.07	-9.00	1.92	1.92	1.92	-7.50	1.77	1.77	1.77	-6.00	1.63	1.63	1.63	-4.50	1.48	1.48	1.48	-3.00	1.33	1.33	1.33	-1.50	1.18	1.18	1.18	0.00	1.02	1.02	1.02
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
-15.00	2.50	2.50	2.50																																																							
-14.25	2.43	2.43	2.43																																																							
-13.50	2.35	2.35	2.35																																																							
-12.00	2.21	2.21	2.21																																																							
-10.50	2.07	2.07	2.07																																																							
-9.00	1.92	1.92	1.92																																																							
-7.50	1.77	1.77	1.77																																																							
-6.00	1.63	1.63	1.63																																																							
-4.50	1.48	1.48	1.48																																																							
-3.00	1.33	1.33	1.33																																																							
-1.50	1.18	1.18	1.18																																																							
0.00	1.02	1.02	1.02																																																							

- 25 -

BC-10222




Figure A