

TEST DATA OF GT3W-12

Regulated DC Power Supply
November 1, 2010

Approved by : Eiyoshi Wakamatsu
Eiyoshi Wakamatsu Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Line Regulation	8
9.Load Regulation	9
10.Dynamic Load Response	10
11.Ripple Voltage (by Load Current)	12
12.Ripple Voltage (by Ambient Temperature)	14
13.Ambient Temperature Drift	15
14.Output Voltage Accuracy	16
15.Time Lapse Drift	17
16.Rise and Fall Time	18
17.Hold-Up Time	20
18.Instantaneous Interruption Compensation	22
19.Minimum Input Voltage for Regulated Output Voltage	24
20.Overcurrent Protection	25
21.Figure of Testing Circuitry	26

(Final Page 26)

COSEL

Model		GT3W-12		Temperature 25°C																																																	
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																	
Object																																																					
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th>Load Ration [%]</th><th>Input Current [A] (90V)</th><th>Input Current [A] (100V)</th><th>Input Current [A] (110V)</th></tr></thead><tbody><tr><td>0</td><td>0.027</td><td>0.033</td><td>0.041</td></tr><tr><td>20</td><td>0.228</td><td>0.233</td><td>0.239</td></tr><tr><td>40</td><td>0.396</td><td>0.405</td><td>0.412</td></tr><tr><td>60</td><td>0.552</td><td>0.563</td><td>0.573</td></tr><tr><td>80</td><td>0.698</td><td>0.712</td><td>0.725</td></tr><tr><td>100</td><td>0.839</td><td>0.855</td><td>0.870</td></tr><tr><td>110</td><td>0.907</td><td>0.925</td><td>0.940</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Ration [%]	Input Current [A] (90V)	Input Current [A] (100V)	Input Current [A] (110V)	0	0.027	0.033	0.041	20	0.228	0.233	0.239	40	0.396	0.405	0.412	60	0.552	0.563	0.573	80	0.698	0.712	0.725	100	0.839	0.855	0.870	110	0.907	0.925	0.940	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	2.Values	
Load Ration [%]	Input Current [A] (90V)	Input Current [A] (100V)	Input Current [A] (110V)																																																		
0	0.027	0.033	0.041																																																		
20	0.228	0.233	0.239																																																		
40	0.396	0.405	0.412																																																		
60	0.552	0.563	0.573																																																		
80	0.698	0.712	0.725																																																		
100	0.839	0.855	0.870																																																		
110	0.907	0.925	0.940																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

COSEL

Model		GT3W-12		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object																																																								
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <div><table><thead><tr><th>Load Ration [%]</th><th>90V [W]</th><th>100V [W]</th><th>110V [W]</th></tr></thead><tbody><tr><td>0</td><td>1.40</td><td>1.70</td><td>2.00</td></tr><tr><td>20</td><td>12.20</td><td>13.70</td><td>15.20</td></tr><tr><td>40</td><td>22.90</td><td>25.60</td><td>28.30</td></tr><tr><td>60</td><td>33.50</td><td>37.40</td><td>41.30</td></tr><tr><td>80</td><td>44.00</td><td>49.10</td><td>54.20</td></tr><tr><td>100</td><td>54.40</td><td>60.70</td><td>67.10</td></tr><tr><td>110</td><td>59.60</td><td>66.50</td><td>73.40</td></tr></tbody></table></div>		Load Ration [%]	90V [W]	100V [W]	110V [W]	0	1.40	1.70	2.00	20	12.20	13.70	15.20	40	22.90	25.60	28.30	60	33.50	37.40	41.30	80	44.00	49.10	54.20	100	54.40	60.70	67.10	110	59.60	66.50	73.40	2.Values																				
Load Ration [%]	90V [W]	100V [W]	110V [W]																																																					
0	1.40	1.70	2.00																																																					
20	12.20	13.70	15.20																																																					
40	22.90	25.60	28.30																																																					
60	33.50	37.40	41.30																																																					
80	44.00	49.10	54.20																																																					
100	54.40	60.70	67.10																																																					
110	59.60	66.50	73.40																																																					
		<table><thead><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0</td><td>1.40</td><td>1.70</td><td>2.00</td></tr><tr><td>20</td><td>12.20</td><td>13.70</td><td>15.20</td></tr><tr><td>40</td><td>22.90</td><td>25.60</td><td>28.30</td></tr><tr><td>60</td><td>33.50</td><td>37.40</td><td>41.30</td></tr><tr><td>80</td><td>44.00</td><td>49.10</td><td>54.20</td></tr><tr><td>100</td><td>54.40</td><td>60.70</td><td>67.10</td></tr><tr><td>110</td><td>59.60</td><td>66.50</td><td>73.40</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>				Load Ration [%]	Input Power [W]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	1.40	1.70	2.00	20	12.20	13.70	15.20	40	22.90	25.60	28.30	60	33.50	37.40	41.30	80	44.00	49.10	54.20	100	54.40	60.70	67.10	110	59.60	66.50	73.40	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																							
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																					
0	1.40	1.70	2.00																																																					
20	12.20	13.70	15.20																																																					
40	22.90	25.60	28.30																																																					
60	33.50	37.40	41.30																																																					
80	44.00	49.10	54.20																																																					
100	54.40	60.70	67.10																																																					
110	59.60	66.50	73.40																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					

Model	GT3W-12																																
Item	Efficiency (by Input Voltage)	Temperature	25°C																														
		Testing Circuitry	Figure A																														
Object																																	
1.Graph		2.Values																															
<div><div><div>---</div><div>□</div><div>---</div></div><div>Load 50%</div></div> <div><div>—</div><div>△</div><div>—</div></div> <div>Load 100%</div> <table><thead><tr><th>Input Voltage [V]</th><th>Efficiency [%] Load 50%</th><th>Efficiency [%] Load 100%</th></tr></thead><tbody><tr><td>85</td><td>67.9</td><td>70.4</td></tr><tr><td>90</td><td>64.0</td><td>66.4</td></tr><tr><td>100</td><td>57.3</td><td>59.4</td></tr><tr><td>110</td><td>51.9</td><td>53.8</td></tr><tr><td>115</td><td>49.3</td><td>51.4</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Efficiency [%] Load 50%	Efficiency [%] Load 100%	85	67.9	70.4	90	64.0	66.4	100	57.3	59.4	110	51.9	53.8	115	49.3	51.4	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Efficiency [%] Load 50%	Efficiency [%] Load 100%																															
85	67.9	70.4																															
90	64.0	66.4																															
100	57.3	59.4																															
110	51.9	53.8																															
115	49.3	51.4																															
--	-	-																															
--	-	-																															
--	-	-																															
--	-	-																															


COSEL

Model		GT3W-12		Temperature 25°C																																																	
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																	
Object		_____																																																			
1.Graph				2.Values																																																	
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th>Load Ration [%]</th><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>20</td><td>59.2</td><td>52.7</td><td>47.5</td></tr><tr><td>40</td><td>63.1</td><td>56.4</td><td>51.0</td></tr><tr><td>60</td><td>64.7</td><td>57.9</td><td>52.5</td></tr><tr><td>80</td><td>65.7</td><td>58.8</td><td>53.3</td></tr><tr><td>100</td><td>66.4</td><td>59.5</td><td>53.8</td></tr><tr><td>110</td><td>66.6</td><td>59.7</td><td>54.1</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>				Load Ration [%]	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	59.2	52.7	47.5	40	63.1	56.4	51.0	60	64.7	57.9	52.5	80	65.7	58.8	53.3	100	66.4	59.5	53.8	110	66.6	59.7	54.1	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Ration [%]	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																		
0	-	-	-																																																		
20	59.2	52.7	47.5																																																		
40	63.1	56.4	51.0																																																		
60	64.7	57.9	52.5																																																		
80	65.7	58.8	53.3																																																		
100	66.4	59.5	53.8																																																		
110	66.6	59.7	54.1																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Model	GT3W-12																																
Item	Power Factor (by Input Voltage)	Temperature	25°C																														
Object		Testing Circuitry	Figure A																														
1.Graph		2.Values																															
<div><div><div>---</div><div>□</div><div>---</div></div><div>Load 50%</div></div> <div><div>—</div><div>△</div><div>—</div></div> <div>Load 100%</div> <table><thead><tr><th>Input Voltage [V]</th><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>0.667</td><td>0.728</td></tr><tr><td>90</td><td>0.660</td><td>0.721</td></tr><tr><td>100</td><td>0.649</td><td>0.712</td></tr><tr><td>110</td><td>0.640</td><td>0.701</td></tr><tr><td>115</td><td>0.639</td><td>0.696</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Load 50%	Load 100%	85	0.667	0.728	90	0.660	0.721	100	0.649	0.712	110	0.640	0.701	115	0.639	0.696	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Load 50%	Load 100%																															
85	0.667	0.728																															
90	0.660	0.721																															
100	0.649	0.712																															
110	0.640	0.701																															
115	0.639	0.696																															
--	-	-																															
--	-	-																															
--	-	-																															
--	-	-																															


Model	GT3W-12																																																					
Item	Power Factor (by Load Current)	Temperature	25°C																																																			
		Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
<div><div>—△— Input Volt. 90V</div><div>---□--- Input Volt. 100V</div><div>-·-○-·- Input Volt. 110V</div></div> <p>Power Factor</p> <p>Load Ration [%]</p>		<table><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Power Factor</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>20</td><td>0.595</td><td>0.588</td><td>0.578</td></tr><tr><td>40</td><td>0.641</td><td>0.634</td><td>0.623</td></tr><tr><td>60</td><td>0.675</td><td>0.664</td><td>0.656</td></tr><tr><td>80</td><td>0.701</td><td>0.690</td><td>0.680</td></tr><tr><td>100</td><td>0.721</td><td>0.711</td><td>0.701</td></tr><tr><td>110</td><td>0.731</td><td>0.720</td><td>0.711</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Ration [%]	Power Factor			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	0.595	0.588	0.578	40	0.641	0.634	0.623	60	0.675	0.664	0.656	80	0.701	0.690	0.680	100	0.721	0.711	0.701	110	0.731	0.720	0.711	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Power Factor																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0	-	-	-																																																			
20	0.595	0.588	0.578																																																			
40	0.641	0.634	0.623																																																			
60	0.675	0.664	0.656																																																			
80	0.701	0.690	0.680																																																			
100	0.721	0.711	0.701																																																			
110	0.731	0.720	0.711																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

		Temperature 25°C Testing Circuitry Figure A
Model	GT3W-12	
Item	Inrush Current	
Object		



Input Voltage	100 V
Frequency	60 Hz
Load	100 %

Primary inrush current	15.8 A
------------------------	--------



Model	GT3W-12																																		
Item	Line Regulation	Temperature	25°C																																
Object	+12V1.5A	Testing Circuitry	Figure A																																
1.Graph		2.Values																																	
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>12.031</td><td>12.030</td></tr><tr><td>90</td><td>12.031</td><td>12.030</td></tr><tr><td>100</td><td>12.031</td><td>12.030</td></tr><tr><td>110</td><td>12.031</td><td>12.030</td></tr><tr><td>115</td><td>12.031</td><td>12.030</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	12.031	12.030	90	12.031	12.030	100	12.031	12.030	110	12.031	12.030	115	12.031	12.030	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	12.031	12.030																																	
90	12.031	12.030																																	
100	12.031	12.030																																	
110	12.031	12.030																																	
115	12.031	12.030																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
Object	-12V1.5A																																		
1.Graph		2.Values																																	
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>-12.025</td><td>-12.023</td></tr><tr><td>90</td><td>-12.025</td><td>-12.023</td></tr><tr><td>100</td><td>-12.025</td><td>-12.023</td></tr><tr><td>110</td><td>-12.025</td><td>-12.023</td></tr><tr><td>115</td><td>-12.025</td><td>-12.023</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	-12.025	-12.023	90	-12.025	-12.023	100	-12.025	-12.023	110	-12.025	-12.023	115	-12.025	-12.023	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	-12.025	-12.023																																	
90	-12.025	-12.023																																	
100	-12.025	-12.023																																	
110	-12.025	-12.023																																	
115	-12.025	-12.023																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
Note: Slanted line shows the range of the rated input voltage.																																			



Model	GT3W-12																																																					
Item	Load Regulation	Temperature	25°C																																																			
		Testing Circuitry	Figure A																																																			
Object	+12V1.5A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt. 90V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 110V</div></div></div> <table><thead><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0.00</td><td>12.033</td><td>12.033</td><td>12.033</td></tr><tr><td>0.30</td><td>12.032</td><td>12.032</td><td>12.033</td></tr><tr><td>0.60</td><td>12.032</td><td>12.032</td><td>12.032</td></tr><tr><td>0.90</td><td>12.031</td><td>12.031</td><td>12.031</td></tr><tr><td>1.20</td><td>12.030</td><td>12.030</td><td>12.030</td></tr><tr><td>1.50</td><td>12.029</td><td>12.030</td><td>12.030</td></tr><tr><td>1.65</td><td>12.029</td><td>12.029</td><td>12.029</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	12.033	12.033	12.033	0.30	12.032	12.032	12.033	0.60	12.032	12.032	12.032	0.90	12.031	12.031	12.031	1.20	12.030	12.030	12.030	1.50	12.029	12.030	12.030	1.65	12.029	12.029	12.029	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	12.033	12.033	12.033																																																			
0.30	12.032	12.032	12.033																																																			
0.60	12.032	12.032	12.032																																																			
0.90	12.031	12.031	12.031																																																			
1.20	12.030	12.030	12.030																																																			
1.50	12.029	12.030	12.030																																																			
1.65	12.029	12.029	12.029																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-12V1.5A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt. 90V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 110V</div></div></div> <table><thead><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0.00</td><td>-12.027</td><td>-12.027</td><td>-12.027</td></tr><tr><td>0.30</td><td>-12.026</td><td>-12.026</td><td>-12.026</td></tr><tr><td>0.60</td><td>-12.025</td><td>-12.026</td><td>-12.026</td></tr><tr><td>0.90</td><td>-12.025</td><td>-12.025</td><td>-12.025</td></tr><tr><td>1.20</td><td>-12.024</td><td>-12.024</td><td>-12.024</td></tr><tr><td>1.50</td><td>-12.023</td><td>-12.023</td><td>-12.023</td></tr><tr><td>1.65</td><td>-12.023</td><td>-12.023</td><td>-12.023</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-12.027	-12.027	-12.027	0.30	-12.026	-12.026	-12.026	0.60	-12.025	-12.026	-12.026	0.90	-12.025	-12.025	-12.025	1.20	-12.024	-12.024	-12.024	1.50	-12.023	-12.023	-12.023	1.65	-12.023	-12.023	-12.023	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-12.027	-12.027	-12.027																																																			
0.30	-12.026	-12.026	-12.026																																																			
0.60	-12.025	-12.026	-12.026																																																			
0.90	-12.025	-12.025	-12.025																																																			
1.20	-12.024	-12.024	-12.024																																																			
1.50	-12.023	-12.023	-12.023																																																			
1.65	-12.023	-12.023	-12.023																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

-9-

BC-10219




Model	GT3W-12		
Item	Dynamic Load Response	Temperature	25°C
Object	+12V1.5A	Testing Circuitry	Figure A

Input Volt. 100 V
Cycle 1000 ms


Load Current

Min. Load (0A) ←→
Load 100% (1.5A)

50 mV/div




100 μs/div




100 μs/div

Load 50% (0.75A) ←→
Load 100% (1.5A)

50 mV/div



100 μs/div



100 μs/div




Model	GT3W-12		
Item	Dynamic Load Response	Temperature	25°C
Object	-12V1.5A	Testing Circuitry	Figure A

Input Volt. 100 V
Cycle 1000 ms


Load Current

Min. Load (0A) \longleftrightarrow
Load 100% (1.5A)

50 mV/div




100 μs/div




100 μs/div

Load 50% (0.75A) \longleftrightarrow
Load 100% (1.5A)

50 mV/div



100 μs/div



100 μs/div

Model	GT3W-12																																											
Item	Ripple Voltage (by Load Current)	Temperature	25°C																																									
		Testing Circuitry	Figure A																																									
Object	+12V1.5A																																											
1.Graph		2.Values																																										
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 90 [V]</th><th>Input Volt. 110 [V]</th></tr><tr><td>0.00</td><td>0.6</td><td>0.6</td></tr><tr><td>0.75</td><td>0.6</td><td>0.6</td></tr><tr><td>1.50</td><td>0.6</td><td>0.6</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.00	0.6	0.6	0.75	0.6	0.6	1.50	0.6	0.6	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																											
	Input Volt. 90 [V]	Input Volt. 110 [V]																																										
0.00	0.6	0.6																																										
0.75	0.6	0.6																																										
1.50	0.6	0.6																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										

Model	GT3W-12																																											
Item	Ripple Voltage (by Load Current)	Temperature	25°C																																									
		Testing Circuitry	Figure A																																									
Object	-12V1.5A																																											
1.Graph		2.Values																																										
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 90 [V]</th><th>Input Volt. 110 [V]</th></tr><tr><td>0.00</td><td>0.6</td><td>0.6</td></tr><tr><td>0.75</td><td>0.6</td><td>0.6</td></tr><tr><td>1.50</td><td>0.6</td><td>0.6</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.00	0.6	0.6	0.75	0.6	0.6	1.50	0.6	0.6	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																											
	Input Volt. 90 [V]	Input Volt. 110 [V]																																										
0.00	0.6	0.6																																										
0.75	0.6	0.6																																										
1.50	0.6	0.6																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										

- 13 -



BC-10219



Model	GT3W-12																																											
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure A																																										
Object	+12V1.5A																																											
1.Graph		2.Values																																										
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <p>Ripple Voltage [mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 100V</p>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>-20</td><td>0.8</td><td>0.8</td></tr><tr><td>-10</td><td>0.8</td><td>0.8</td></tr><tr><td>25</td><td>0.6</td><td>0.6</td></tr><tr><td>50</td><td>0.6</td><td>0.6</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-20	0.8	0.8	-10	0.8	0.8	25	0.6	0.6	50	0.6	0.6	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																											
	Load 50%	Load 100%																																										
-20	0.8	0.8																																										
-10	0.8	0.8																																										
25	0.6	0.6																																										
50	0.6	0.6																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
Object	-12V1.5A																																											
1.Graph		2.Values																																										
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <p>Ripple Voltage [mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 100V</p>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>-20</td><td>0.8</td><td>0.8</td></tr><tr><td>-10</td><td>0.8</td><td>0.8</td></tr><tr><td>25</td><td>0.6</td><td>0.6</td></tr><tr><td>50</td><td>0.6</td><td>0.6</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-20	0.8	0.8	-10	0.8	0.8	25	0.6	0.6	50	0.6	0.6	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																											
	Load 50%	Load 100%																																										
-20	0.8	0.8																																										
-10	0.8	0.8																																										
25	0.6	0.6																																										
50	0.6	0.6																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
Measured by 20 MHz Oscilloscope.																																												
Note: Slanted line shows the range of the rated ambient temperature.																																												

- 14 -



BC-10219

Model	GT3W-12																																																						
Item	Ambient Temperature Drift		Testing Circuitry Figure A																																																				
Object	+12V1.5A																																																						
1.Graph		2.Values																																																					
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div>  <div><div>Output Voltage [V]</div><div>Ambient Temperature [°C]</div><div>Load 100%</div></div>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>-20</td><td>11.995</td><td>11.995</td><td>11.995</td></tr><tr><td>-10</td><td>12.007</td><td>12.007</td><td>12.007</td></tr><tr><td>0</td><td>12.016</td><td>12.016</td><td>12.016</td></tr><tr><td>10</td><td>12.022</td><td>12.022</td><td>12.022</td></tr><tr><td>20</td><td>12.028</td><td>12.028</td><td>12.028</td></tr><tr><td>25</td><td>12.031</td><td>12.031</td><td>12.031</td></tr><tr><td>30</td><td>12.033</td><td>12.033</td><td>12.033</td></tr><tr><td>40</td><td>12.035</td><td>12.035</td><td>12.035</td></tr><tr><td>50</td><td>12.033</td><td>12.033</td><td>12.033</td></tr><tr><td>60</td><td>12.031</td><td>12.031</td><td>12.031</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-20	11.995	11.995	11.995	-10	12.007	12.007	12.007	0	12.016	12.016	12.016	10	12.022	12.022	12.022	20	12.028	12.028	12.028	25	12.031	12.031	12.031	30	12.033	12.033	12.033	40	12.035	12.035	12.035	50	12.033	12.033	12.033	60	12.031	12.031	12.031	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																				
-20	11.995	11.995	11.995																																																				
-10	12.007	12.007	12.007																																																				
0	12.016	12.016	12.016																																																				
10	12.022	12.022	12.022																																																				
20	12.028	12.028	12.028																																																				
25	12.031	12.031	12.031																																																				
30	12.033	12.033	12.033																																																				
40	12.035	12.035	12.035																																																				
50	12.033	12.033	12.033																																																				
60	12.031	12.031	12.031																																																				
--	-	-	-																																																				
Object	-12V1.5A																																																						
1.Graph		2.Values																																																					
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div>  <div><div>Output Voltage [V]</div><div>Ambient Temperature [°C]</div><div>Load 100%</div></div>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>-20</td><td>-12.017</td><td>-12.017</td><td>-12.017</td></tr><tr><td>-10</td><td>-12.022</td><td>-12.022</td><td>-12.022</td></tr><tr><td>0</td><td>-12.026</td><td>-12.026</td><td>-12.026</td></tr><tr><td>10</td><td>-12.029</td><td>-12.029</td><td>-12.029</td></tr><tr><td>20</td><td>-12.030</td><td>-12.030</td><td>-12.030</td></tr><tr><td>25</td><td>-12.030</td><td>-12.029</td><td>-12.030</td></tr><tr><td>30</td><td>-12.029</td><td>-12.029</td><td>-12.029</td></tr><tr><td>40</td><td>-12.025</td><td>-12.025</td><td>-12.025</td></tr><tr><td>50</td><td>-12.021</td><td>-12.021</td><td>-12.021</td></tr><tr><td>60</td><td>-12.014</td><td>-12.014</td><td>-12.014</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-20	-12.017	-12.017	-12.017	-10	-12.022	-12.022	-12.022	0	-12.026	-12.026	-12.026	10	-12.029	-12.029	-12.029	20	-12.030	-12.030	-12.030	25	-12.030	-12.029	-12.030	30	-12.029	-12.029	-12.029	40	-12.025	-12.025	-12.025	50	-12.021	-12.021	-12.021	60	-12.014	-12.014	-12.014	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																				
-20	-12.017	-12.017	-12.017																																																				
-10	-12.022	-12.022	-12.022																																																				
0	-12.026	-12.026	-12.026																																																				
10	-12.029	-12.029	-12.029																																																				
20	-12.030	-12.030	-12.030																																																				
25	-12.030	-12.029	-12.030																																																				
30	-12.029	-12.029	-12.029																																																				
40	-12.025	-12.025	-12.025																																																				
50	-12.021	-12.021	-12.021																																																				
60	-12.014	-12.014	-12.014																																																				
--	-	-	-																																																				
Note: Slanted line shows the range of the rated ambient temperature.																																																							

- 15 -

BC-10219

COSEL


Model	GT3W-12																								
Item	Time Lapse Drift	Temperature	25°C																						
Object	+12V1.5A	Testing Circuitry	Figure A																						
1.Graph		2.Values																							
<div><p>Output Voltage [V]</p><p>Time [H]</p><p>Input Volt. 100V</p><p>Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>12.029</td></tr><tr><td>0.5</td><td>12.030</td></tr><tr><td>1.0</td><td>12.030</td></tr><tr><td>2.0</td><td>12.030</td></tr><tr><td>3.0</td><td>12.030</td></tr><tr><td>4.0</td><td>12.030</td></tr><tr><td>5.0</td><td>12.030</td></tr><tr><td>6.0</td><td>12.030</td></tr><tr><td>7.0</td><td>12.030</td></tr><tr><td>8.0</td><td>12.030</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	12.029	0.5	12.030	1.0	12.030	2.0	12.030	3.0	12.030	4.0	12.030	5.0	12.030	6.0	12.030	7.0	12.030	8.0	12.030
Time since start [H]	Output Voltage [V]																								
0.0	12.029																								
0.5	12.030																								
1.0	12.030																								
2.0	12.030																								
3.0	12.030																								
4.0	12.030																								
5.0	12.030																								
6.0	12.030																								
7.0	12.030																								
8.0	12.030																								
Object	-12V1.5A																								
1.Graph		2.Values																							
<div><p>Output Voltage [V]</p><p>Time [H]</p><p>Input Volt. 100V</p><p>Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>-12.024</td></tr><tr><td>0.5</td><td>-12.024</td></tr><tr><td>1.0</td><td>-12.024</td></tr><tr><td>2.0</td><td>-12.024</td></tr><tr><td>3.0</td><td>-12.024</td></tr><tr><td>4.0</td><td>-12.024</td></tr><tr><td>5.0</td><td>-12.024</td></tr><tr><td>6.0</td><td>-12.024</td></tr><tr><td>7.0</td><td>-12.024</td></tr><tr><td>8.0</td><td>-12.024</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	-12.024	0.5	-12.024	1.0	-12.024	2.0	-12.024	3.0	-12.024	4.0	-12.024	5.0	-12.024	6.0	-12.024	7.0	-12.024	8.0	-12.024
Time since start [H]	Output Voltage [V]																								
0.0	-12.024																								
0.5	-12.024																								
1.0	-12.024																								
2.0	-12.024																								
3.0	-12.024																								
4.0	-12.024																								
5.0	-12.024																								
6.0	-12.024																								
7.0	-12.024																								
8.0	-12.024																								

- 17 -

BC-10219


Model	GT3W-12	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V1.5A		

1.Graph




2.Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	10.0	27.5	37.5	56.0	276.5
100 %	10.5	27.0	37.5	23.5	142.0




Model	GT3W-12	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-12V1.5A		

1.Graph



2.Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	10.0	27.8	37.8	55.5	275.5
100 %	10.0	27.8	37.8	23.5	139.0



Model	GT3W-12																																
Item	Hold-Up Time	Temperature	25°C																														
		Testing Circuitry	Figure A																														
Object	+12V1.5A																																
1.Graph		2.Values																															
<div><div><div>---</div><div>□</div><div>---</div></div><div>Load 50%</div></div> <div><div>—</div><div>△</div><div>—</div></div> <div>Load 100%</div> <p>The graph shows Hold-Up Time [ms] on a logarithmic y-axis (1 to 1000) versus Input Voltage [V] on a linear x-axis (80 to 120). Two data series are plotted: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show an increasing trend. A slanted shaded region indicates the rated input voltage range from approximately 90V to 115V.</p> <table border="1"><thead><tr><th>Input Voltage [V]</th><th>Load 50% [ms]</th><th>Load 100% [ms]</th></tr></thead><tbody><tr><td>85</td><td>18</td><td>4</td></tr><tr><td>90</td><td>27</td><td>9</td></tr><tr><td>100</td><td>44</td><td>18</td></tr><tr><td>110</td><td>63</td><td>27</td></tr><tr><td>115</td><td>72</td><td>31</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Input Voltage [V]	Load 50% [ms]	Load 100% [ms]	85	18	4	90	27	9	100	44	18	110	63	27	115	72	31	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Load 50% [ms]	Load 100% [ms]																															
85	18	4																															
90	27	9																															
100	44	18																															
110	63	27																															
115	72	31																															
--	-	-																															
--	-	-																															
--	-	-																															
--	-	-																															
This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.																																	

COSEL

Model	GT3W-12																																
Item	Hold-Up Time	Temperature	25°C																														
		Testing Circuitry	Figure A																														
Object	-12V1.5A																																
1.Graph		2.Values																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <p>The graph shows Hold-Up Time [ms] on a logarithmic y-axis (1 to 1000) versus Input Voltage [V] on a linear x-axis (80 to 120). Two data series are plotted: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show an increasing trend in hold-up time as input voltage increases. A vertical slanted line is drawn at 90V, indicating the rated input voltage range.</p> <table border="1"><thead><tr><th>Input Voltage [V]</th><th>Load 50% [ms]</th><th>Load 100% [ms]</th></tr></thead><tbody><tr><td>85</td><td>19</td><td>5</td></tr><tr><td>90</td><td>27</td><td>10</td></tr><tr><td>100</td><td>45</td><td>18</td></tr><tr><td>110</td><td>64</td><td>27</td></tr><tr><td>115</td><td>73</td><td>32</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Input Voltage [V]	Load 50% [ms]	Load 100% [ms]	85	19	5	90	27	10	100	45	18	110	64	27	115	73	32	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Load 50% [ms]	Load 100% [ms]																															
85	19	5																															
90	27	10																															
100	45	18																															
110	64	27																															
115	73	32																															
--	-	-																															
--	-	-																															
--	-	-																															
--	-	-																															
This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.																																	



Model	GT3W-12																																																					
Item	Instantaneous Interruption Compensation	Temperature	25°C																																																			
Object	+12V1.5A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <div>Instantaneous Compensation Time [ms]</div> <div>Load Current [A]</div> <div>Note: Slanted line shows the range of the rated load current.</div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.30</td><td>73</td><td>123</td><td>169</td></tr><tr><td>0.60</td><td>23</td><td>56</td><td>73</td></tr><tr><td>0.90</td><td>21</td><td>23</td><td>50</td></tr><tr><td>1.20</td><td>5</td><td>22</td><td>36</td></tr><tr><td>1.50</td><td>5</td><td>6</td><td>23</td></tr><tr><td>1.65</td><td>4</td><td>6</td><td>22</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-	-	-	0.30	73	123	169	0.60	23	56	73	0.90	21	23	50	1.20	5	22	36	1.50	5	6	23	1.65	4	6	22	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-	-	-																																																			
0.30	73	123	169																																																			
0.60	23	56	73																																																			
0.90	21	23	50																																																			
1.20	5	22	36																																																			
1.50	5	6	23																																																			
1.65	4	6	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	GT3W-12																																																					
Item	Instantaneous Interruption Compensation	Temperature	25°C																																																			
Object	-12V1.5A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <div>Instantaneous Compensation Time [ms]</div> <div>Load Current [A]</div> <div>Note: Slanted line shows the range of the rated load current.</div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.30</td><td>73</td><td>123</td><td>169</td></tr><tr><td>0.60</td><td>23</td><td>56</td><td>74</td></tr><tr><td>0.90</td><td>21</td><td>24</td><td>51</td></tr><tr><td>1.20</td><td>5</td><td>22</td><td>36</td></tr><tr><td>1.50</td><td>5</td><td>6</td><td>23</td></tr><tr><td>1.65</td><td>4</td><td>6</td><td>22</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-	-	-	0.30	73	123	169	0.60	23	56	74	0.90	21	24	51	1.20	5	22	36	1.50	5	6	23	1.65	4	6	22	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-	-	-																																																			
0.30	73	123	169																																																			
0.60	23	56	74																																																			
0.90	21	24	51																																																			
1.20	5	22	36																																																			
1.50	5	6	23																																																			
1.65	4	6	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	GT3W-12	Testing Circuitry Figure A																																					
Item	Minimum Input Voltage for Regulated Output Voltage																																						
Object	+12V1.5A																																						
1.Graph		2.Values																																					
<div><div>---□---</div> Load 50%</div> <div><div>—△—</div> Load 100%</div> <table><thead><tr><th>Ambient Temperature [°C]</th><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-20</td><td>75</td><td>78</td></tr><tr><td>-10</td><td>73</td><td>78</td></tr><tr><td>0</td><td>73</td><td>78</td></tr><tr><td>10</td><td>73</td><td>78</td></tr><tr><td>20</td><td>73</td><td>78</td></tr><tr><td>25</td><td>73</td><td>78</td></tr><tr><td>30</td><td>74</td><td>78</td></tr><tr><td>40</td><td>74</td><td>78</td></tr><tr><td>50</td><td>75</td><td>78</td></tr><tr><td>60</td><td>75</td><td>78</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Load 50%	Load 100%	-20	75	78	-10	73	78	0	73	78	10	73	78	20	73	78	25	73	78	30	74	78	40	74	78	50	75	78	60	75	78	--	-	-		
Ambient Temperature [°C]	Load 50%	Load 100%																																					
-20	75	78																																					
-10	73	78																																					
0	73	78																																					
10	73	78																																					
20	73	78																																					
25	73	78																																					
30	74	78																																					
40	74	78																																					
50	75	78																																					
60	75	78																																					
--	-	-																																					
Object	-12V1.5A																																						
1.Graph		2.Values																																					
<div><div>---□---</div> Load 50%</div> <div><div>—△—</div> Load 100%</div> <table><thead><tr><th>Ambient Temperature [°C]</th><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-20</td><td>75</td><td>78</td></tr><tr><td>-10</td><td>73</td><td>78</td></tr><tr><td>0</td><td>73</td><td>78</td></tr><tr><td>10</td><td>73</td><td>78</td></tr><tr><td>20</td><td>73</td><td>78</td></tr><tr><td>25</td><td>74</td><td>78</td></tr><tr><td>30</td><td>74</td><td>78</td></tr><tr><td>40</td><td>74</td><td>78</td></tr><tr><td>50</td><td>75</td><td>78</td></tr><tr><td>60</td><td>75</td><td>78</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Load 50%	Load 100%	-20	75	78	-10	73	78	0	73	78	10	73	78	20	73	78	25	74	78	30	74	78	40	74	78	50	75	78	60	75	78	--	-	-		
Ambient Temperature [°C]	Load 50%	Load 100%																																					
-20	75	78																																					
-10	73	78																																					
0	73	78																																					
10	73	78																																					
20	73	78																																					
25	74	78																																					
30	74	78																																					
40	74	78																																					
50	75	78																																					
60	75	78																																					
--	-	-																																					
Note: Slanted line shows the range of the rated ambient temperature.																																							

- 24 -

BC-10219

Model	GT3W-12																																																									
Item	Overcurrent Protection	Temperature	25°C																																																							
Object	+12V1.5A	Testing Circuitry	Figure A																																																							
1.Graph		2.Values																																																								
<div><div><div></div>Input Volt. 90V</div><div><div></div>Input Volt. 100V</div><div><div></div>Input Volt. 110V</div></div> 		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>12.0</td><td>1.96</td><td>1.96</td><td>1.96</td></tr><tr><td>11.4</td><td>1.90</td><td>1.90</td><td>1.90</td></tr><tr><td>10.8</td><td>1.84</td><td>1.84</td><td>1.84</td></tr><tr><td>9.6</td><td>1.73</td><td>1.73</td><td>1.73</td></tr><tr><td>8.4</td><td>1.61</td><td>1.61</td><td>1.61</td></tr><tr><td>7.2</td><td>1.50</td><td>1.50</td><td>1.50</td></tr><tr><td>6.0</td><td>1.38</td><td>1.38</td><td>1.38</td></tr><tr><td>4.8</td><td>1.28</td><td>1.28</td><td>1.28</td></tr><tr><td>3.6</td><td>1.16</td><td>1.16</td><td>1.16</td></tr><tr><td>2.4</td><td>1.04</td><td>1.04</td><td>1.04</td></tr><tr><td>1.2</td><td>0.93</td><td>0.93</td><td>0.93</td></tr><tr><td>0.0</td><td>0.80</td><td>0.80</td><td>0.80</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	12.0	1.96	1.96	1.96	11.4	1.90	1.90	1.90	10.8	1.84	1.84	1.84	9.6	1.73	1.73	1.73	8.4	1.61	1.61	1.61	7.2	1.50	1.50	1.50	6.0	1.38	1.38	1.38	4.8	1.28	1.28	1.28	3.6	1.16	1.16	1.16	2.4	1.04	1.04	1.04	1.2	0.93	0.93	0.93	0.0	0.80	0.80	0.80
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
12.0	1.96	1.96	1.96																																																							
11.4	1.90	1.90	1.90																																																							
10.8	1.84	1.84	1.84																																																							
9.6	1.73	1.73	1.73																																																							
8.4	1.61	1.61	1.61																																																							
7.2	1.50	1.50	1.50																																																							
6.0	1.38	1.38	1.38																																																							
4.8	1.28	1.28	1.28																																																							
3.6	1.16	1.16	1.16																																																							
2.4	1.04	1.04	1.04																																																							
1.2	0.93	0.93	0.93																																																							
0.0	0.80	0.80	0.80																																																							
Object	-12V1.5A																																																									
1.Graph		2.Values																																																								
<div><div><div></div>Input Volt. 90V</div><div><div></div>Input Volt. 100V</div><div><div></div>Input Volt. 110V</div></div>  <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>-12.0</td><td>1.94</td><td>1.94</td><td>1.94</td></tr><tr><td>-11.4</td><td>1.88</td><td>1.88</td><td>1.88</td></tr><tr><td>-10.8</td><td>1.82</td><td>1.82</td><td>1.82</td></tr><tr><td>-9.6</td><td>1.71</td><td>1.71</td><td>1.71</td></tr><tr><td>-8.4</td><td>1.60</td><td>1.60</td><td>1.60</td></tr><tr><td>-7.2</td><td>1.48</td><td>1.48</td><td>1.48</td></tr><tr><td>-6.0</td><td>1.37</td><td>1.37</td><td>1.37</td></tr><tr><td>-4.8</td><td>1.25</td><td>1.25</td><td>1.25</td></tr><tr><td>-3.6</td><td>1.14</td><td>1.14</td><td>1.14</td></tr><tr><td>-2.4</td><td>1.02</td><td>1.02</td><td>1.02</td></tr><tr><td>-1.2</td><td>0.91</td><td>0.91</td><td>0.91</td></tr><tr><td>0.0</td><td>0.78</td><td>0.78</td><td>0.78</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-12.0	1.94	1.94	1.94	-11.4	1.88	1.88	1.88	-10.8	1.82	1.82	1.82	-9.6	1.71	1.71	1.71	-8.4	1.60	1.60	1.60	-7.2	1.48	1.48	1.48	-6.0	1.37	1.37	1.37	-4.8	1.25	1.25	1.25	-3.6	1.14	1.14	1.14	-2.4	1.02	1.02	1.02	-1.2	0.91	0.91	0.91	0.0	0.78	0.78	0.78
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
-12.0	1.94	1.94	1.94																																																							
-11.4	1.88	1.88	1.88																																																							
-10.8	1.82	1.82	1.82																																																							
-9.6	1.71	1.71	1.71																																																							
-8.4	1.60	1.60	1.60																																																							
-7.2	1.48	1.48	1.48																																																							
-6.0	1.37	1.37	1.37																																																							
-4.8	1.25	1.25	1.25																																																							
-3.6	1.14	1.14	1.14																																																							
-2.4	1.02	1.02	1.02																																																							
-1.2	0.91	0.91	0.91																																																							
0.0	0.78	0.78	0.78																																																							

- 25 -

BC-10219




Figure A