



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|------------|
| Model | JAC-50-155 |
|-------|------------|

| No. | P a r t s | | Q'ty of Device | Failure rate [10 ⁻⁶ /H] | R e f e r e n c e |
|--|------------------------|------------|----------------|------------------------------------|-------------------|
| 1 | I C | Monolithic | 0 | 0.0000 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 0 | 0.0000 | |
| 4 | D i o d e s | | 0 | 0.0000 | |
| 5 | LED•Optocouplers | | 0 | 0.0000 | |
| 6 | R e s i s t o r s | | 7 | 0.0217 | |
| 7 | C a p a c i t o r s | | 7 | 0.0581 | |
| 8 | Transformer•Choke Coil | | 1 | 0.0230 | |
| 9 | C o n n e c t o r s | | 51 | 0.2301 | |
| 10 | O t h e r s | | 1 | 0.0030 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 0.3359 | |

| | | |
|---------------------|-----|-----------|
| M T B F | [H] | 2,977,000 |
| Ambient Temperature | [℃] | — |
| Load Factor | [%] | — |