

Date : Aug.3,2012

Temperature increase of main components: 主要部品温度上昇


Model: KHNA120F

## 1. Conditions

- (1) Input : AC 85 ~ 264 [V]  
 (2) Output : Rated output  
 (3) Mounting method : Shown as Fig.1.1

## 2. Result

No.	Parts name	Symbol No.	Increase ( $\Delta T$ )						Rated temp. [°C]	Reference
			[deg]							
			24V							
1	Line Filter	L101	52.2						130	
2	Rectifier(Input)	SS101	51.6						150	Junction Temp.
3	Choke Coil(Pfc)	L105	45.9						130	
4	Input Capacitor	C109	28.8						105	
5	Rectified Diode(Pfc)	D101	56.7						150	Junction Temp.
6	Switching Moss-Fet(Pfc)	TR101	35.3						150	Junction Temp.
7	Switching Moss-Fet	TR402	30.0						150	Junction Temp.
8	Transformer	T401	49.5						130	
9	Rectified Moss-Fet	TR501	27.0						150	Junction Temp.
10	Output Choke	L501	24.1						120	
11	Output Capacitor	C501	32.2						105	
12										
13										
14										
15										
16										
17										
18										
19										
20										



(Front view)

Fig.1.1 Mounting method  
(Normal position)