



M T B F (E I A J R C R - 9 1 0 2)

| | |
|-------|------------|
| Model | LDA300W-12 |
|-------|------------|

| No. | P a r t s | | Q'ty of Device | Failure rate [10 ⁻⁶ /H] | R e f e r e n c e |
|--|------------------------|------------|----------------|------------------------------------|-------------------|
| 1 | I C | Monolithic | 2 | 0.0650 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 7 | 0.3423 | |
| 4 | D i o d e s | | 23 | 0.5685 | |
| 5 | LED・Optocouplers | | 3 | 0.2100 | |
| 6 | R e s i s t o r s | | 82 | 0.5275 | |
| 7 | C a p a c i t o r s | | 35 | 0.6025 | |
| 8 | Transformer・Choke Coil | | 12 | 0.1311 | |
| 9 | C o n n e c t o r s | | 412 | 0.2127 | |
| 10 | O t h e r s | | 4 | 0.2740 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 2.9336 | |

| | | |
|---------------------|------|---------|
| M T B F | [H] | 341,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |