



M T B F (E I A J R C R - 9 1 0 2)

| | |
|-------|-----------|
| Model | LHA50F-36 |
|-------|-----------|

| No. | P a r t s | | Q'ty of Device | Failure rate [10 ⁻⁶ /H] | R e f e r e n c e |
|--|------------------------|---------------------|----------------|------------------------------------|-------------------|
| 1 | I C | M o n o l i t h i c | 2 | 0.0980 | |
| 2 | | H y b r i d | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 4 | 0.2002 | |
| 4 | D i o d e s | | 13 | 0.3160 | |
| 5 | LED・Optocouplers | | 2 | 0.1400 | |
| 6 | R e s i s t o r s | | 52 | 0.3302 | |
| 7 | C a p a c i t o r s | | 27 | 0.2468 | |
| 8 | Transformer・Choke Coil | | 3 | 0.0690 | |
| 9 | C o n n e c t o r s | | 198 | 0.0471 | |
| 10 | O t h e r s | | 4 | 0.1580 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 1.6053 | |

| | |
|--------------------------|---------|
| M T B F [H] | 623,000 |
| Ambient Temperature [°C] | — |
| Load Factor [%] | — |