

# TEST DATA OF MGFW302415

Regulated DC Power Supply  
November 22, 2010

Approved by : Kazunari Asano  
Kazunari Asano Design Manager

Prepared by : Masashi Ueda  
Masashi Ueda Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	10
10.Ripple-Noise . . . . .	12
11.Ripple Voltage (by Ambient Temperature) . . . . .	14
12.Ambient Temperature Drift . . . . .	15
13.Output Voltage Accuracy . . . . .	16
14.Time Lapse Drift . . . . .	17
15.Rise and Fall Time . . . . .	18
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17.Overcurrent Protection . . . . .	21
18.Overvoltage Protection . . . . .	22
19.Figure of Testing Circuitry . . . . .	23

(Final Page 23)

Model	MGFW302415																																																																																	
Item	Input Current (by Input Voltage)	Temperature	25°C																																																																															
Object		Testing Circuitry	Figure A																																																																															
1.Graph		2.Values																																																																																
<div><div><div><div></div></div><div></div><div>Load 100%</div></div><div><div><div></div></div><div></div><div>Load 50%</div></div><div><div><div></div></div><div></div><div>Load 0%</div></div></div> <div><p>Note: Slanted line shows the range of the rated input voltage.</p></div>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Load 0%</th><th>Load 50%</th><th>Load 100%</th></tr><tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>2.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>6.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>7.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>8.0</td><td>0.002</td><td>0.002</td><td>0.000</td></tr><tr><td>8.2</td><td>0.045</td><td>0.006</td><td>0.004</td></tr><tr><td>8.5</td><td>0.044</td><td>1.969</td><td>4.085</td></tr><tr><td>8.6</td><td>0.044</td><td>1.958</td><td>4.010</td></tr><tr><td>9.0</td><td>0.044</td><td>1.887</td><td>3.859</td></tr><tr><td>12.0</td><td>0.041</td><td>1.408</td><td>2.877</td></tr><tr><td>18.0</td><td>0.033</td><td>0.955</td><td>1.938</td></tr><tr><td>24.0</td><td>0.030</td><td>0.737</td><td>1.471</td></tr><tr><td>36.0</td><td>0.028</td><td>0.515</td><td>1.021</td></tr><tr><td>40.0</td><td>0.028</td><td>0.472</td><td>0.925</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	6.0	0.000	0.000	0.000	7.0	0.000	0.000	0.000	8.0	0.002	0.002	0.000	8.2	0.045	0.006	0.004	8.5	0.044	1.969	4.085	8.6	0.044	1.958	4.010	9.0	0.044	1.887	3.859	12.0	0.041	1.408	2.877	18.0	0.033	0.955	1.938	24.0	0.030	0.737	1.471	36.0	0.028	0.515	1.021	40.0	0.028	0.472	0.925	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
2.0	0.000	0.000	0.000																																																																															
4.0	0.000	0.000	0.000																																																																															
6.0	0.000	0.000	0.000																																																																															
7.0	0.000	0.000	0.000																																																																															
8.0	0.002	0.002	0.000																																																																															
8.2	0.045	0.006	0.004																																																																															
8.5	0.044	1.969	4.085																																																																															
8.6	0.044	1.958	4.010																																																																															
9.0	0.044	1.887	3.859																																																																															
12.0	0.041	1.408	2.877																																																																															
18.0	0.033	0.955	1.938																																																																															
24.0	0.030	0.737	1.471																																																																															
36.0	0.028	0.515	1.021																																																																															
40.0	0.028	0.472	0.925																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															



BC-10532



Model	MGFW302415																																
Item	Efficiency (by Input Voltage)	Temperature	25°C																														
		Testing Circuitry	Figure A																														
Object																																	
1.Graph		2.Values																															
<div><div><div>---</div><div>□</div><div>---</div></div><div>Load 50%</div></div> <div><div>—</div><div>△</div><div>—</div></div> <div>Load 100%</div> <table><thead><tr><th>Input Voltage [V]</th><th>Load 50% Efficiency [%]</th><th>Load 100% Efficiency [%]</th></tr></thead><tbody><tr><td>8.5</td><td>87.6</td><td>87.0</td></tr><tr><td>9.0</td><td>88.1</td><td>87.4</td></tr><tr><td>12.0</td><td>88.2</td><td>87.7</td></tr><tr><td>15.0</td><td>87.4</td><td>87.4</td></tr><tr><td>18.0</td><td>86.5</td><td>86.8</td></tr><tr><td>24.0</td><td>84.7</td><td>86.0</td></tr><tr><td>30.0</td><td>82.6</td><td>84.6</td></tr><tr><td>36.0</td><td>80.3</td><td>83.0</td></tr><tr><td>40.0</td><td>78.7</td><td>81.9</td></tr></tbody></table>		Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]	8.5	87.6	87.0	9.0	88.1	87.4	12.0	88.2	87.7	15.0	87.4	87.4	18.0	86.5	86.8	24.0	84.7	86.0	30.0	82.6	84.6	36.0	80.3	83.0	40.0	78.7	81.9		
Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]																															
8.5	87.6	87.0																															
9.0	88.1	87.4																															
12.0	88.2	87.7																															
15.0	87.4	87.4																															
18.0	86.5	86.8																															
24.0	84.7	86.0																															
30.0	82.6	84.6																															
36.0	80.3	83.0																															
40.0	78.7	81.9																															
Note: Slanted line shows the range of the rated input voltage.																																	

Model	MGFW302415																																																																																	
Item	Efficiency (by Load Current)		Temperature		25°C																																																																													
			Testing Circuitry		Figure A																																																																													
Object																																																																																		
1.Graph			2.Values																																																																															
<div><div><div>—△—</div><div>Input Volt.</div><div>9V</div></div><div><div>---□---</div><div>Input Volt.</div><div>12V</div></div><div><div>---*---</div><div>Input Volt.</div><div>18V</div></div><div><div>---○---</div><div>Input Volt.</div><div>24V</div></div><div><div>---◇---</div><div>Input Volt.</div><div>36V</div></div></div> <p>Efficiency [%]</p> <p>Load Ration [%]</p>			<table><tr><th rowspan="2">Load Ration [%]</th><th colspan="5">Efficiency [%]</th></tr><tr><th>Input Volt. 9[V]</th><th>Input Volt. 12[V]</th><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>20</td><td>84.2</td><td>84.1</td><td>82.2</td><td>79.8</td><td>72.5</td></tr><tr><td>40</td><td>87.8</td><td>87.7</td><td>85.7</td><td>83.6</td><td>78.7</td></tr><tr><td>60</td><td>88.4</td><td>88.5</td><td>87.0</td><td>85.4</td><td>81.4</td></tr><tr><td>80</td><td>88.1</td><td>88.3</td><td>87.4</td><td>86.0</td><td>82.7</td></tr><tr><td>100</td><td>87.4</td><td>87.8</td><td>87.1</td><td>86.1</td><td>83.2</td></tr><tr><td>110</td><td>86.9</td><td>87.4</td><td>87.0</td><td>85.9</td><td>83.2</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr></table>			Load Ration [%]	Efficiency [%]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	-	-	20	84.2	84.1	82.2	79.8	72.5	40	87.8	87.7	85.7	83.6	78.7	60	88.4	88.5	87.0	85.4	81.4	80	88.1	88.3	87.4	86.0	82.7	100	87.4	87.8	87.1	86.1	83.2	110	86.9	87.4	87.0	85.9	83.2	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Efficiency [%]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0	-	-	-	-	-																																																																													
20	84.2	84.1	82.2	79.8	72.5																																																																													
40	87.8	87.7	85.7	83.6	78.7																																																																													
60	88.4	88.5	87.0	85.4	81.4																																																																													
80	88.1	88.3	87.4	86.0	82.7																																																																													
100	87.4	87.8	87.1	86.1	83.2																																																																													
110	86.9	87.4	87.0	85.9	83.2																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

Model	MGFW302415	Temperature 25°C Testing Circuitry Figure A																																	
Item	Line Regulation																																		
Object	+15V1A																																		
1.Graph		2.Values																																	
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>8.5</td><td>15.116</td><td>15.020</td></tr><tr><td>9.0</td><td>15.116</td><td>15.020</td></tr><tr><td>12.0</td><td>15.110</td><td>15.019</td></tr><tr><td>15.0</td><td>15.107</td><td>15.018</td></tr><tr><td>18.0</td><td>15.105</td><td>15.018</td></tr><tr><td>24.0</td><td>15.104</td><td>15.018</td></tr><tr><td>30.0</td><td>15.104</td><td>15.018</td></tr><tr><td>36.0</td><td>15.103</td><td>15.018</td></tr><tr><td>40.0</td><td>15.103</td><td>15.018</td></tr></tbody></table> <p>-15V: Rated output current</p>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8.5	15.116	15.020	9.0	15.116	15.020	12.0	15.110	15.019	15.0	15.107	15.018	18.0	15.105	15.018	24.0	15.104	15.018	30.0	15.104	15.018	36.0	15.103	15.018	40.0	15.103	15.018		
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
8.5	15.116	15.020																																	
9.0	15.116	15.020																																	
12.0	15.110	15.019																																	
15.0	15.107	15.018																																	
18.0	15.105	15.018																																	
24.0	15.104	15.018																																	
30.0	15.104	15.018																																	
36.0	15.103	15.018																																	
40.0	15.103	15.018																																	
Object	-15V1A																																		
1.Graph		2.Values																																	
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>8</td><td>-0.001</td><td>-0.001</td></tr><tr><td>9</td><td>-15.093</td><td>-14.978</td></tr><tr><td>12</td><td>-15.088</td><td>-14.980</td></tr><tr><td>15</td><td>-15.085</td><td>-14.981</td></tr><tr><td>18</td><td>-15.083</td><td>-14.981</td></tr><tr><td>24</td><td>-15.080</td><td>-14.981</td></tr><tr><td>30</td><td>-15.079</td><td>-14.980</td></tr><tr><td>36</td><td>-15.078</td><td>-14.980</td></tr><tr><td>40</td><td>-15.078</td><td>-14.979</td></tr></tbody></table> <p>+15V: Rated output current</p>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8	-0.001	-0.001	9	-15.093	-14.978	12	-15.088	-14.980	15	-15.085	-14.981	18	-15.083	-14.981	24	-15.080	-14.981	30	-15.079	-14.980	36	-15.078	-14.980	40	-15.078	-14.979		
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
8	-0.001	-0.001																																	
9	-15.093	-14.978																																	
12	-15.088	-14.980																																	
15	-15.085	-14.981																																	
18	-15.083	-14.981																																	
24	-15.080	-14.981																																	
30	-15.079	-14.980																																	
36	-15.078	-14.980																																	
40	-15.078	-14.979																																	
Note: Slanted line shows the range of the rated input voltage.																																			



# COSEL


Model	MGFW302415																																																																																	
Item	Load Regulation																																																																																	
Object	+15V1A																																																																																	
1.Graph		2.Values																																																																																
<div><div><div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div></div><div><div>Input Volt. 9V</div><div>Input Volt. 12V</div><div>Input Volt. 18V</div><div>Input Volt. 24V</div><div>Input Volt. 36V</div></div></div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="5">Output Voltage [V]</th></tr><tr><th>Input Volt. 9[V]</th><th>Input Volt. 12[V]</th><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>0.000</td><td>15.443</td><td>15.485</td><td>15.510</td><td>15.556</td><td>15.642</td></tr><tr><td>0.050</td><td>15.288</td><td>15.280</td><td>15.280</td><td>15.280</td><td>15.280</td></tr><tr><td>0.200</td><td>15.222</td><td>15.221</td><td>15.221</td><td>15.224</td><td>15.226</td></tr><tr><td>0.400</td><td>15.154</td><td>15.146</td><td>15.139</td><td>15.137</td><td>15.135</td></tr><tr><td>0.600</td><td>15.106</td><td>15.098</td><td>15.092</td><td>15.091</td><td>15.089</td></tr><tr><td>0.800</td><td>15.062</td><td>15.057</td><td>15.054</td><td>15.052</td><td>15.051</td></tr><tr><td>1.000</td><td>15.022</td><td>15.019</td><td>15.018</td><td>15.017</td><td>15.017</td></tr><tr><td>1.100</td><td>15.002</td><td>15.002</td><td>15.001</td><td>15.001</td><td>15.001</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	15.443	15.485	15.510	15.556	15.642	0.050	15.288	15.280	15.280	15.280	15.280	0.200	15.222	15.221	15.221	15.224	15.226	0.400	15.154	15.146	15.139	15.137	15.135	0.600	15.106	15.098	15.092	15.091	15.089	0.800	15.062	15.057	15.054	15.052	15.051	1.000	15.022	15.019	15.018	15.017	15.017	1.100	15.002	15.002	15.001	15.001	15.001	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.000	15.443	15.485	15.510	15.556	15.642																																																																													
0.050	15.288	15.280	15.280	15.280	15.280																																																																													
0.200	15.222	15.221	15.221	15.224	15.226																																																																													
0.400	15.154	15.146	15.139	15.137	15.135																																																																													
0.600	15.106	15.098	15.092	15.091	15.089																																																																													
0.800	15.062	15.057	15.054	15.052	15.051																																																																													
1.000	15.022	15.019	15.018	15.017	15.017																																																																													
1.100	15.002	15.002	15.001	15.001	15.001																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
		-15V: Rated output current																																																																																
Object	-15V1A																																																																																	
1.Graph		2.Values																																																																																
<div><div><div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div></div><div><div>Input Volt. 9V</div><div>Input Volt. 12V</div><div>Input Volt. 18V</div><div>Input Volt. 24V</div><div>Input Volt. 36V</div></div></div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="5">Output Voltage [V]</th></tr><tr><th>Input Volt. 9[V]</th><th>Input Volt. 12[V]</th><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>0.000</td><td>-15.360</td><td>-15.354</td><td>-15.350</td><td>-15.354</td><td>-15.366</td></tr><tr><td>0.05</td><td>-15.220</td><td>-15.220</td><td>-15.210</td><td>-15.200</td><td>-15.200</td></tr><tr><td>0.20</td><td>-15.180</td><td>-15.171</td><td>-15.163</td><td>-15.162</td><td>-15.160</td></tr><tr><td>0.40</td><td>-15.122</td><td>-15.114</td><td>-15.108</td><td>-15.106</td><td>-15.103</td></tr><tr><td>0.60</td><td>-15.070</td><td>-15.066</td><td>-15.062</td><td>-15.060</td><td>-15.058</td></tr><tr><td>0.80</td><td>-15.023</td><td>-15.022</td><td>-15.020</td><td>-15.018</td><td>-15.017</td></tr><tr><td>1.00</td><td>-14.977</td><td>-14.979</td><td>-14.980</td><td>-14.979</td><td>-14.978</td></tr><tr><td>1.10</td><td>-14.955</td><td>-14.958</td><td>-14.960</td><td>-14.960</td><td>-14.959</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	-15.360	-15.354	-15.350	-15.354	-15.366	0.05	-15.220	-15.220	-15.210	-15.200	-15.200	0.20	-15.180	-15.171	-15.163	-15.162	-15.160	0.40	-15.122	-15.114	-15.108	-15.106	-15.103	0.60	-15.070	-15.066	-15.062	-15.060	-15.058	0.80	-15.023	-15.022	-15.020	-15.018	-15.017	1.00	-14.977	-14.979	-14.980	-14.979	-14.978	1.10	-14.955	-14.958	-14.960	-14.960	-14.959	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.000	-15.360	-15.354	-15.350	-15.354	-15.366																																																																													
0.05	-15.220	-15.220	-15.210	-15.200	-15.200																																																																													
0.20	-15.180	-15.171	-15.163	-15.162	-15.160																																																																													
0.40	-15.122	-15.114	-15.108	-15.106	-15.103																																																																													
0.60	-15.070	-15.066	-15.062	-15.060	-15.058																																																																													
0.80	-15.023	-15.022	-15.020	-15.018	-15.017																																																																													
1.00	-14.977	-14.979	-14.980	-14.979	-14.978																																																																													
1.10	-14.955	-14.958	-14.960	-14.960	-14.959																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
		+15V: Rated output current																																																																																
Note: Slanted line shows the range of the rated load current.																																																																																		

Model	MGFW302415	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+15V1A	

Input Volt. 24 V

Other output current rated


Cycle 1000 ms




Min. Load (0A)  $\longleftrightarrow$

Load 100% (1A)

500mV/div



50ms/div




50ms/div


Min. Load (0A)  $\longleftrightarrow$

Load 50% (0.5A)

500mV/div



50ms/div




50ms/div


Load 50% (0.5A)  $\longleftrightarrow$

Load 100% (1A)

500mV/div



50ms/div



50ms/div



Model	MGFW302415		
Item	Dynamic Load Response	Temperature	25°C
Object	+15V1A	Testing Circuitry	Figure A

Input Volt. 24 V

Other output current rated

Cycle 1000 ms


$t_1, t_2 = 50\mu\text{s}$




Min. Load (0A)  $\longleftrightarrow$

Load 100% (1A)

500mV/div



50ms/div




50ms/div


Min. Load (0A)  $\longleftrightarrow$

Load 50% (0.5A)

500mV/div



50ms/div




50ms/div


Load 50% (0.5A)  $\longleftrightarrow$

Load 100% (1A)

500mV/div





50ms/div



50ms/div

Model	MGFW302415																																								
Item	Ripple Voltage (by Load Current)	Temperature	25°C																																						
		Testing Circuitry	Figure B																																						
Object	+15V1A																																								
1.Graph		2.Values																																							
<div><div><div><div><div></div><div>Input Volt. 9V</div></div><div><div></div><div>Input Volt. 36V</div></div></div><div><p>Ripple Voltage [mV]</p><p>Load Current [A]</p></div></div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 9 [V]</th><th>Input Volt. 36 [V]</th></tr><tr><td>0.0</td><td>9</td><td>16</td></tr><tr><td>0.2</td><td>8</td><td>9</td></tr><tr><td>0.4</td><td>8</td><td>9</td></tr><tr><td>0.6</td><td>8</td><td>9</td></tr><tr><td>0.8</td><td>6</td><td>6</td></tr><tr><td>1.0</td><td>6</td><td>6</td></tr><tr><td>1.1</td><td>6</td><td>6</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table> <p>-15V: Rated output current</p>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.0	9	16	0.2	8	9	0.4	8	9	0.6	8	9	0.8	6	6	1.0	6	6	1.1	6	6	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 9 [V]	Input Volt. 36 [V]																																							
0.0	9	16																																							
0.2	8	9																																							
0.4	8	9																																							
0.6	8	9																																							
0.8	6	6																																							
1.0	6	6																																							
1.1	6	6																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																									
<div><div><div><div></div><div>Ripple [mVp-p]</div></div><div><p>Fig.Complex Ripple Wave Form</p></div></div></div> <td colspan="2"></td>																																									

Model		MGFW302415																																							
Item		Ripple Voltage (by Load Current)																																							
Object		-15V1A																																							
1.Graph		2.Values																																							
<div><div><div>—△— Input Volt. 9V</div><div>-.-○-.- Input Volt. 36V</div></div></div> <div><p>Ripple Voltage is shown as p-p in the figure below.</p><p>Note: Slanted line shows the range of the rated load current.</p></div> <div><div>Ripple [mVp-p]</div><div>Fig.Complex Ripple Wave Form</div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 9 [V]</th><th>Input Volt. 36 [V]</th></tr><tr><td>0.0</td><td>11</td><td>17</td></tr><tr><td>0.2</td><td>15</td><td>26</td></tr><tr><td>0.4</td><td>15</td><td>26</td></tr><tr><td>0.6</td><td>15</td><td>26</td></tr><tr><td>0.8</td><td>13</td><td>24</td></tr><tr><td>1.0</td><td>13</td><td>24</td></tr><tr><td>1.1</td><td>13</td><td>24</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table> <div>+15V: Rated output current</div>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.0	11	17	0.2	15	26	0.4	15	26	0.6	15	26	0.8	13	24	1.0	13	24	1.1	13	24	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 9 [V]	Input Volt. 36 [V]																																							
0.0	11	17																																							
0.2	15	26																																							
0.4	15	26																																							
0.6	15	26																																							
0.8	13	24																																							
1.0	13	24																																							
1.1	13	24																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							

Model		MGFW302415																																							
Item		Ripple-Noise																																							
Object		+15V1A																																							
1.Graph		2.Values																																							
<div><div><div>—△— Input Volt. 9V</div><div>- -○- - Input Volt. 36V</div></div><div>Ripple Voltage [mV]</div><div>Load Current [A]</div></div> <div><p>Ripple-Noise is shown as p-p in the figure below.</p><p>Note: Slanted line shows the range of the rated load current.</p><div><div><div></div><div></div></div><div>Ripple Noise[mVp-p]</div></div><div>Fig.Complex Ripple Noise Wave Form</div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple-Noise [mV]</th></tr><tr><th>Input Volt. 9 [V]</th><th>Input Volt. 36 [V]</th></tr><tr><td>0.0</td><td>10</td><td>20</td></tr><tr><td>0.2</td><td>10</td><td>15</td></tr><tr><td>0.4</td><td>10</td><td>15</td></tr><tr><td>0.6</td><td>10</td><td>15</td></tr><tr><td>0.8</td><td>10</td><td>10</td></tr><tr><td>1.0</td><td>10</td><td>10</td></tr><tr><td>1.1</td><td>10</td><td>10</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table> <div>-15V: Rated output current</div>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.0	10	20	0.2	10	15	0.4	10	15	0.6	10	15	0.8	10	10	1.0	10	10	1.1	10	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 9 [V]	Input Volt. 36 [V]																																							
0.0	10	20																																							
0.2	10	15																																							
0.4	10	15																																							
0.6	10	15																																							
0.8	10	10																																							
1.0	10	10																																							
1.1	10	10																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							

Model		MGFW302415																																							
Item		Ripple-Noise																																							
Object		-15V1A																																							
1.Graph		2.Values																																							
<div><div><div>—△— Input Volt. 9V</div><div>- -○- - Input Volt. 36V</div></div><div>Ripple Voltage [mV]</div><div>Load Current [A]</div></div> <div><p>Ripple-Noise is shown as p-p in the figure below.</p><p>Note: Slanted line shows the range of the rated load current.</p><div><div>Ripple Noise[mVp-p]</div></div><div>Fig.Complex Ripple Noise Wave Form</div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple-Noise [mV]</th></tr><tr><th>Input Volt. 9 [V]</th><th>Input Volt. 36 [V]</th></tr><tr><td>0.0</td><td>15</td><td>20</td></tr><tr><td>0.2</td><td>20</td><td>30</td></tr><tr><td>0.4</td><td>20</td><td>30</td></tr><tr><td>0.6</td><td>20</td><td>30</td></tr><tr><td>0.8</td><td>15</td><td>30</td></tr><tr><td>1.0</td><td>15</td><td>30</td></tr><tr><td>1.1</td><td>15</td><td>30</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table> <div>+15V: Rated output current</div>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.0	15	20	0.2	20	30	0.4	20	30	0.6	20	30	0.8	15	30	1.0	15	30	1.1	15	30	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 9 [V]	Input Volt. 36 [V]																																							
0.0	15	20																																							
0.2	20	30																																							
0.4	20	30																																							
0.6	20	30																																							
0.8	15	30																																							
1.0	15	30																																							
1.1	15	30																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							



Model	MGFW302415																																						
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry    Figure A																																					
Object	+15V1A																																						
1.Graph		2.Values																																					
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Ambient Temperature [°C]</th><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-60</td><td>22</td><td>25</td></tr><tr><td>-40</td><td>21</td><td>21</td></tr><tr><td>-20</td><td>22</td><td>21</td></tr><tr><td>0</td><td>21</td><td>20</td></tr><tr><td>25</td><td>20</td><td>18</td></tr><tr><td>60</td><td>20</td><td>17</td></tr><tr><td>65</td><td>20</td><td>17</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>-15V: Rated output current</p>		Ambient Temperature [°C]	Load 50%	Load 100%	-60	22	25	-40	21	21	-20	22	21	0	21	20	25	20	18	60	20	17	65	20	17	--	-	-	--	-	-	--	-	-	--	-	-		
Ambient Temperature [°C]	Load 50%	Load 100%																																					
-60	22	25																																					
-40	21	21																																					
-20	22	21																																					
0	21	20																																					
25	20	18																																					
60	20	17																																					
65	20	17																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
Object	-15V1A																																						
1.Graph		2.Values																																					
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Ambient Temperature [°C]</th><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-60</td><td>56</td><td>53</td></tr><tr><td>-40</td><td>51</td><td>49</td></tr><tr><td>-20</td><td>45</td><td>44</td></tr><tr><td>0</td><td>44</td><td>43</td></tr><tr><td>25</td><td>42</td><td>41</td></tr><tr><td>60</td><td>41</td><td>38</td></tr><tr><td>65</td><td>41</td><td>38</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>+15V: Rated output current</p>		Ambient Temperature [°C]	Load 50%	Load 100%	-60	56	53	-40	51	49	-20	45	44	0	44	43	25	42	41	60	41	38	65	41	38	--	-	-	--	-	-	--	-	-	--	-	-		
Ambient Temperature [°C]	Load 50%	Load 100%																																					
-60	56	53																																					
-40	51	49																																					
-20	45	44																																					
0	44	43																																					
25	42	41																																					
60	41	38																																					
65	41	38																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
Measured by 100 MHz Oscilloscope.																																							
Note: Slanted line shows the range of the rated ambient temperature.																																							



Model	MGFW302415																																																																																		
Item	Ambient Temperature Drift																																																																																		
Object	+15V1A																																																																																		
1.Graph		2.Values																																																																																	
<div><div>—△—</div>Input Volt. 9V</div> <div><div>---□---</div>Input Volt. 12V</div> <div><div>-·-·*·-·-</div>Input Volt. 18V</div> <div><div>-·-○-·-</div>Input Volt. 24V</div> <div><div>---◇---</div>Input Volt. 36V</div>																																																																																			
<div>Output Voltage [V]</div> <div>Ambient Temperature [°C]</div> <div>Load 100%</div>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="5">Output Voltage [V]</th></tr><tr><th>Input Volt. 9[V]</th><th>Input Volt. 12[V]</th><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>-60</td><td>14.971</td><td>14.972</td><td>14.974</td><td>14.976</td><td>14.978</td></tr><tr><td>-40</td><td>14.991</td><td>14.992</td><td>14.993</td><td>14.995</td><td>14.996</td></tr><tr><td>-20</td><td>15.005</td><td>15.005</td><td>15.006</td><td>15.007</td><td>15.008</td></tr><tr><td>0</td><td>15.015</td><td>15.015</td><td>15.014</td><td>15.015</td><td>15.016</td></tr><tr><td>25</td><td>15.022</td><td>15.021</td><td>15.020</td><td>15.020</td><td>15.021</td></tr><tr><td>60</td><td>15.023</td><td>15.022</td><td>15.020</td><td>15.020</td><td>15.020</td></tr><tr><td>65</td><td>15.022</td><td>15.021</td><td>15.020</td><td>15.019</td><td>15.019</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr></table>					Ambient Temperature [°C]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-60	14.971	14.972	14.974	14.976	14.978	-40	14.991	14.992	14.993	14.995	14.996	-20	15.005	15.005	15.006	15.007	15.008	0	15.015	15.015	15.014	15.015	15.016	25	15.022	15.021	15.020	15.020	15.021	60	15.023	15.022	15.020	15.020	15.020	65	15.022	15.021	15.020	15.019	15.019	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																														
-60	14.971	14.972	14.974	14.976	14.978																																																																														
-40	14.991	14.992	14.993	14.995	14.996																																																																														
-20	15.005	15.005	15.006	15.007	15.008																																																																														
0	15.015	15.015	15.014	15.015	15.016																																																																														
25	15.022	15.021	15.020	15.020	15.021																																																																														
60	15.023	15.022	15.020	15.020	15.020																																																																														
65	15.022	15.021	15.020	15.019	15.019																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
Object	-15V1A																																																																																		
1.Graph		2.Values																																																																																	
<div><div>—△—</div>Input Volt. 9V</div> <div><div>---□---</div>Input Volt. 12V</div> <div><div>-·-·*·-·-</div>Input Volt. 18V</div> <div><div>-·-○-·-</div>Input Volt. 24V</div> <div><div>---◇---</div>Input Volt. 36V</div>																																																																																			
<div>Output Voltage [V]</div> <div>Ambient Temperature [°C]</div> <div>Load 100%</div>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="5">Output Voltage [V]</th></tr><tr><th>Input Volt. 9[V]</th><th>Input Volt. 12[V]</th><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>-60</td><td>-14.938</td><td>-14.942</td><td>-14.946</td><td>-14.947</td><td>-14.949</td></tr><tr><td>-40</td><td>-14.957</td><td>-14.960</td><td>-14.963</td><td>-14.963</td><td>-14.965</td></tr><tr><td>-20</td><td>-14.969</td><td>-14.972</td><td>-14.974</td><td>-14.974</td><td>-14.974</td></tr><tr><td>0</td><td>-14.977</td><td>-14.979</td><td>-14.980</td><td>-14.980</td><td>-14.980</td></tr><tr><td>25</td><td>-14.981</td><td>-14.983</td><td>-14.984</td><td>-14.984</td><td>-14.983</td></tr><tr><td>60</td><td>-14.978</td><td>-14.980</td><td>-14.980</td><td>-14.980</td><td>-14.979</td></tr><tr><td>65</td><td>-14.975</td><td>-14.977</td><td>-14.979</td><td>-14.978</td><td>-14.977</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr></table>					Ambient Temperature [°C]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-60	-14.938	-14.942	-14.946	-14.947	-14.949	-40	-14.957	-14.960	-14.963	-14.963	-14.965	-20	-14.969	-14.972	-14.974	-14.974	-14.974	0	-14.977	-14.979	-14.980	-14.980	-14.980	25	-14.981	-14.983	-14.984	-14.984	-14.983	60	-14.978	-14.980	-14.980	-14.980	-14.979	65	-14.975	-14.977	-14.979	-14.978	-14.977	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																														
-60	-14.938	-14.942	-14.946	-14.947	-14.949																																																																														
-40	-14.957	-14.960	-14.963	-14.963	-14.965																																																																														
-20	-14.969	-14.972	-14.974	-14.974	-14.974																																																																														
0	-14.977	-14.979	-14.980	-14.980	-14.980																																																																														
25	-14.981	-14.983	-14.984	-14.984	-14.983																																																																														
60	-14.978	-14.980	-14.980	-14.980	-14.979																																																																														
65	-14.975	-14.977	-14.979	-14.978	-14.977																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
Note: Slanted line shows the range of the rated ambient temperature.																																																																																			




# COSEL


Model	MGFW302415																								
Item	Time Lapse Drift		Temperature 25°C Testing Circuitry Figure A																						
Object	+15V1A																								
1.Graph		2.Values																							
<div></div> <div>Output Voltage [V]</div> <div>Time [H]</div> <div>Input Volt. 24V Load 100%</div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>15.002</td></tr><tr><td>0.5</td><td>15.016</td></tr><tr><td>1.0</td><td>15.016</td></tr><tr><td>2.0</td><td>15.016</td></tr><tr><td>3.0</td><td>15.016</td></tr><tr><td>4.0</td><td>15.016</td></tr><tr><td>5.0</td><td>15.016</td></tr><tr><td>6.0</td><td>15.016</td></tr><tr><td>7.0</td><td>15.016</td></tr><tr><td>8.0</td><td>15.016</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	15.002	0.5	15.016	1.0	15.016	2.0	15.016	3.0	15.016	4.0	15.016	5.0	15.016	6.0	15.016	7.0	15.016	8.0	15.016
Time since start [H]	Output Voltage [V]																								
0.0	15.002																								
0.5	15.016																								
1.0	15.016																								
2.0	15.016																								
3.0	15.016																								
4.0	15.016																								
5.0	15.016																								
6.0	15.016																								
7.0	15.016																								
8.0	15.016																								
Object	-15V1A																								
1.Graph		2.Values																							
<div></div> <div>Output Voltage [V]</div> <div>Time [H]</div> <div>Input Volt. 24V Load 100%</div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>-14.978</td></tr><tr><td>0.5</td><td>-14.981</td></tr><tr><td>1.0</td><td>-14.981</td></tr><tr><td>2.0</td><td>-14.981</td></tr><tr><td>3.0</td><td>-14.981</td></tr><tr><td>4.0</td><td>-14.981</td></tr><tr><td>5.0</td><td>-14.981</td></tr><tr><td>6.0</td><td>-14.981</td></tr><tr><td>7.0</td><td>-14.981</td></tr><tr><td>8.0</td><td>-14.981</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	-14.978	0.5	-14.981	1.0	-14.981	2.0	-14.981	3.0	-14.981	4.0	-14.981	5.0	-14.981	6.0	-14.981	7.0	-14.981	8.0	-14.981
Time since start [H]	Output Voltage [V]																								
0.0	-14.978																								
0.5	-14.981																								
1.0	-14.981																								
2.0	-14.981																								
3.0	-14.981																								
4.0	-14.981																								
5.0	-14.981																								
6.0	-14.981																								
7.0	-14.981																								
8.0	-14.981																								

- 17 -

BC-10532

# COSEL





Model	MGFW302415	Testing Circuitry    Figure A																																							
Item	Minimum Input Voltage for Regulated Output Voltage																																								
Object	+15V1A																																								
1.Graph		2.Values																																							
<div><div><div></div><div></div></div><div><div></div><div></div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-60</td><td>8.1</td><td>8.2</td></tr><tr><td>-40</td><td>8.1</td><td>8.1</td></tr><tr><td>-20</td><td>8.1</td><td>8.1</td></tr><tr><td>0</td><td>8.1</td><td>8.0</td></tr><tr><td>25</td><td>8.0</td><td>8.2</td></tr><tr><td>60</td><td>8.0</td><td>8.1</td></tr><tr><td>65</td><td>8.0</td><td>8.2</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	8.1	8.2	-40	8.1	8.1	-20	8.1	8.1	0	8.1	8.0	25	8.0	8.2	60	8.0	8.1	65	8.0	8.2	--	-	-	--	-	-	--	-	-	--	-	-		
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	8.1	8.2																																							
-40	8.1	8.1																																							
-20	8.1	8.1																																							
0	8.1	8.0																																							
25	8.0	8.2																																							
60	8.0	8.1																																							
65	8.0	8.2																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
Object	-15V1A																																								
1.Graph		2.Values																																							
<div><div><div></div><div></div></div><div><div></div><div></div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-60</td><td>8.0</td><td>8.1</td></tr><tr><td>-40</td><td>8.0</td><td>8.0</td></tr><tr><td>-20</td><td>8.0</td><td>8.0</td></tr><tr><td>0</td><td>7.9</td><td>7.9</td></tr><tr><td>25</td><td>7.9</td><td>8.1</td></tr><tr><td>60</td><td>7.9</td><td>8.3</td></tr><tr><td>65</td><td>7.9</td><td>8.0</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	8.0	8.1	-40	8.0	8.0	-20	8.0	8.0	0	7.9	7.9	25	7.9	8.1	60	7.9	8.3	65	7.9	8.0	--	-	-	--	-	-	--	-	-	--	-	-		
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	8.0	8.1																																							
-40	8.0	8.0																																							
-20	8.0	8.0																																							
0	7.9	7.9																																							
25	7.9	8.1																																							
60	7.9	8.3																																							
65	7.9	8.0																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
Note: Slanted line shows the range of the rated ambient temperature.																																									

- 20 -

BC-10532

BC-10532

Model	MGFW302415																																								
Item	Overvoltage Protection	Testing Circuitry    Figure A																																							
Object	+30V1A																																								
1.Graph		2.Values																																							
<div><div><div>—△—</div><div>Input Volt.</div><div>24V</div></div><div><div>---□---</div><div>Input Volt.</div><div>36V</div></div></div> <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>Measured as a single output(+30V).</p>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Operating Point [V]</th></tr><tr><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>-60</td><td>40.10</td><td>40.10</td></tr><tr><td>-40</td><td>40.03</td><td>40.03</td></tr><tr><td>-20</td><td>40.03</td><td>40.03</td></tr><tr><td>0</td><td>40.32</td><td>40.40</td></tr><tr><td>25</td><td>41.18</td><td>41.25</td></tr><tr><td>60</td><td>42.24</td><td>42.31</td></tr><tr><td>65</td><td>42.38</td><td>42.46</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Operating Point [V]		Input Volt. 24[V]	Input Volt. 36[V]	-60	40.10	40.10	-40	40.03	40.03	-20	40.03	40.03	0	40.32	40.40	25	41.18	41.25	60	42.24	42.31	65	42.38	42.46	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 24[V]	Input Volt. 36[V]																																							
-60	40.10	40.10																																							
-40	40.03	40.03																																							
-20	40.03	40.03																																							
0	40.32	40.40																																							
25	41.18	41.25																																							
60	42.24	42.31																																							
65	42.38	42.46																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							






Figure A




Figure B (Ripple and Ripple noise Characteristic)