



TEST DATA OF MGS6053R3

Regulated DC Power Supply
August 3, 2016

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager


Prepared by : Ryosuke Nakao
Ryosuke Nakao Design Engineer


COSEL CO.,LTD.


CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching Frequency (by Load Current)	18
19.Figure of Testing Circuitry	19

(Final Page 19)


Model		MGS6053R3		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object																																																																																				
1.Graph		<div><div><div>—△—</div><div>Load 100%</div></div><div><div>---□---</div><div>Load 50%</div></div><div><div>-·-○-·-</div><div>Load 0%</div></div></div>  <p>Note: Slanted line shows the range of the rated input voltage.</p>		2.Values																																																																																
		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Load 0%</th><th>Load 50%</th><th>Load 100%</th></tr><tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>3.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr><tr><td>3.8</td><td>0.003</td><td>0.003</td><td>0.003</td></tr><tr><td>3.9</td><td>0.014</td><td>0.002</td><td>0.003</td></tr><tr><td>4.0</td><td>0.014</td><td>0.828</td><td>1.674</td></tr><tr><td>4.1</td><td>0.013</td><td>0.807</td><td>1.618</td></tr><tr><td>4.2</td><td>0.013</td><td>0.787</td><td>1.585</td></tr><tr><td>4.3</td><td>0.012</td><td>0.772</td><td>1.540</td></tr><tr><td>4.5</td><td>0.012</td><td>0.732</td><td>1.520</td></tr><tr><td>5.0</td><td>0.010</td><td>0.657</td><td>1.342</td></tr><tr><td>6.0</td><td>0.008</td><td>0.547</td><td>1.079</td></tr><tr><td>7.0</td><td>0.004</td><td>0.472</td><td>0.937</td></tr><tr><td>8.0</td><td>0.006</td><td>0.415</td><td>0.816</td></tr><tr><td>9.0</td><td>0.006</td><td>0.378</td><td>0.720</td></tr><tr><td>10.0</td><td>0.006</td><td>0.345</td><td>0.656</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	3.0	0.002	0.002	0.002	3.8	0.003	0.003	0.003	3.9	0.014	0.002	0.003	4.0	0.014	0.828	1.674	4.1	0.013	0.807	1.618	4.2	0.013	0.787	1.585	4.3	0.012	0.772	1.540	4.5	0.012	0.732	1.520	5.0	0.010	0.657	1.342	6.0	0.008	0.547	1.079	7.0	0.004	0.472	0.937	8.0	0.006	0.415	0.816	9.0	0.006	0.378	0.720	10.0	0.006	0.345	0.656	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
3.0	0.002	0.002	0.002																																																																																	
3.8	0.003	0.003	0.003																																																																																	
3.9	0.014	0.002	0.003																																																																																	
4.0	0.014	0.828	1.674																																																																																	
4.1	0.013	0.807	1.618																																																																																	
4.2	0.013	0.787	1.585																																																																																	
4.3	0.012	0.772	1.540																																																																																	
4.5	0.012	0.732	1.520																																																																																	
5.0	0.010	0.657	1.342																																																																																	
6.0	0.008	0.547	1.079																																																																																	
7.0	0.004	0.472	0.937																																																																																	
8.0	0.006	0.415	0.816																																																																																	
9.0	0.006	0.378	0.720																																																																																	
10.0	0.006	0.345	0.656																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	

Model		MGS6053R3		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object																																																								
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>4.5V</div></div><div><div>---□---</div><div>Input Volt.</div><div>5V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>9V</div></div></div> 		2.Values																																																				
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 4.5[V]</th><th>Input Volt. 5[V]</th><th>Input Volt. 9[V]</th></tr><tr><td>0.00</td><td>0.012</td><td>0.010</td><td>0.006</td></tr><tr><td>0.32</td><td>0.310</td><td>0.282</td><td>0.177</td></tr><tr><td>0.64</td><td>0.589</td><td>0.529</td><td>0.309</td></tr><tr><td>0.96</td><td>0.885</td><td>0.789</td><td>0.445</td></tr><tr><td>1.28</td><td>1.184</td><td>1.059</td><td>0.588</td></tr><tr><td>1.60</td><td>1.520</td><td>1.342</td><td>0.720</td></tr><tr><td>1.76</td><td>1.675</td><td>1.490</td><td>0.803</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Input Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.00	0.012	0.010	0.006	0.32	0.310	0.282	0.177	0.64	0.589	0.529	0.309	0.96	0.885	0.789	0.445	1.28	1.184	1.059	0.588	1.60	1.520	1.342	0.720	1.76	1.675	1.490	0.803	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0.00	0.012	0.010	0.006																																																					
0.32	0.310	0.282	0.177																																																					
0.64	0.589	0.529	0.309																																																					
0.96	0.885	0.789	0.445																																																					
1.28	1.184	1.059	0.588																																																					
1.60	1.520	1.342	0.720																																																					
1.76	1.675	1.490	0.803																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								

Model		MGS6053R3		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object																																																								
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>4.5V</div></div><div><div>---□---</div><div>Input Volt.</div><div>5V</div></div><div><div>---○---</div><div>Input Volt.</div><div>9V</div></div></div> 		2.Values																																																				
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 4.5[V]</th><th>Input Volt. 5[V]</th><th>Input Volt. 9[V]</th></tr><tr><td>0.00</td><td>0.05</td><td>0.05</td><td>0.05</td></tr><tr><td>0.32</td><td>1.39</td><td>1.40</td><td>1.59</td></tr><tr><td>0.64</td><td>2.62</td><td>2.62</td><td>2.77</td></tr><tr><td>0.96</td><td>3.88</td><td>3.87</td><td>4.00</td></tr><tr><td>1.28</td><td>5.19</td><td>5.18</td><td>5.26</td></tr><tr><td>1.60</td><td>6.55</td><td>6.50</td><td>6.52</td></tr><tr><td>1.76</td><td>7.22</td><td>7.18</td><td>7.15</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Input Power [W]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.00	0.05	0.05	0.05	0.32	1.39	1.40	1.59	0.64	2.62	2.62	2.77	0.96	3.88	3.87	4.00	1.28	5.19	5.18	5.26	1.60	6.55	6.50	6.52	1.76	7.22	7.18	7.15	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0.00	0.05	0.05	0.05																																																					
0.32	1.39	1.40	1.59																																																					
0.64	2.62	2.62	2.77																																																					
0.96	3.88	3.87	4.00																																																					
1.28	5.19	5.18	5.26																																																					
1.60	6.55	6.50	6.52																																																					
1.76	7.22	7.18	7.15																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		MGS6053R3		Temperature 25°C																																	
Item		Efficiency (by Input Voltage)		Testing Circuitry Figure A																																	
Object																																					
1.Graph				2.Values																																	
<div><div><div><div></div><div></div><div></div></div><div><div></div><div></div><div></div></div></div><div><div>---</div><div>□</div><div>---</div></div><div>Load 50%</div></div> <div><div>---</div><div>△</div><div>---</div></div> <div>Load 100%</div> <div><div><div>Efficiency [%]</div><div>95</div><div>85</div><div>75</div><div>65</div><div>55</div></div><div><div>3</div><div>6</div><div>9</div><div>12</div></div><div><div>Input Voltage [V]</div></div></div>				<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Efficiency [%]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>4.4</td><td>81.5</td><td>80.9</td></tr><tr><td>4.5</td><td>81.6</td><td>81.0</td></tr><tr><td>4.8</td><td>81.4</td><td>81.3</td></tr><tr><td>5.0</td><td>81.2</td><td>81.5</td></tr><tr><td>7.0</td><td>80.1</td><td>81.9</td></tr><tr><td>9.0</td><td>77.9</td><td>81.4</td></tr><tr><td>10.0</td><td>76.5</td><td>80.8</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.4	81.5	80.9	4.5	81.6	81.0	4.8	81.4	81.3	5.0	81.2	81.5	7.0	80.1	81.9	9.0	77.9	81.4	10.0	76.5	80.8	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
4.4	81.5	80.9																																			
4.5	81.6	81.0																																			
4.8	81.4	81.3																																			
5.0	81.2	81.5																																			
7.0	80.1	81.9																																			
9.0	77.9	81.4																																			
10.0	76.5	80.8																																			
--	-	-																																			
--	-	-																																			
<div>Note: Slanted line shows the range of the rated input voltage.</div>																																					

Model		MGS6053R3	Temperature		25°C																																																			
Item		Efficiency (by Load Current)	Testing Circuitry		Figure A																																																			
Object																																																								
1.Graph																																																								
		—△—	Input Volt.	4.5V																																																				
		---□---	Input Volt.	5V																																																				
		-·-○-·-	Input Volt.	9V																																																				
																																																								
Note: Slanted line shows the range of the rated load current.																																																								
2.Values																																																								
<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 4.5[V]</th><th>Input Volt. 5[V]</th><th>Input Volt. 9[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.32</td><td>76.2</td><td>75.3</td><td>66.4</td></tr><tr><td>0.64</td><td>80.8</td><td>80.8</td><td>76.3</td></tr><tr><td>0.96</td><td>81.8</td><td>82.0</td><td>79.5</td></tr><tr><td>1.28</td><td>81.7</td><td>81.8</td><td>80.6</td></tr><tr><td>1.60</td><td>81.0</td><td>81.5</td><td>81.4</td></tr><tr><td>1.76</td><td>80.6</td><td>81.1</td><td>81.4</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>						Load Current [A]	Efficiency [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.00	-	-	-	0.32	76.2	75.3	66.4	0.64	80.8	80.8	76.3	0.96	81.8	82.0	79.5	1.28	81.7	81.8	80.6	1.60	81.0	81.5	81.4	1.76	80.6	81.1	81.4	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0.00	-	-	-																																																					
0.32	76.2	75.3	66.4																																																					
0.64	80.8	80.8	76.3																																																					
0.96	81.8	82.0	79.5																																																					
1.28	81.7	81.8	80.6																																																					
1.60	81.0	81.5	81.4																																																					
1.76	80.6	81.1	81.4																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Model	MGS6053R3																																
Item	Line Regulation	Temperature	25°C																														
Object	+3.3V1.6A	Testing Circuitry	Figure A																														
1.Graph		2.Values																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>---△---</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Output Voltage [V] Load 50%</th><th>Output Voltage [V] Load 100%</th></tr></thead><tbody><tr><td>4.4</td><td>3.305</td><td>3.304</td></tr><tr><td>4.5</td><td>3.305</td><td>3.304</td></tr><tr><td>4.8</td><td>3.305</td><td>3.304</td></tr><tr><td>5.0</td><td>3.305</td><td>3.304</td></tr><tr><td>7.0</td><td>3.305</td><td>3.304</td></tr><tr><td>9.0</td><td>3.305</td><td>3.304</td></tr><tr><td>10.0</td><td>3.305</td><td>3.304</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%	4.4	3.305	3.304	4.5	3.305	3.304	4.8	3.305	3.304	5.0	3.305	3.304	7.0	3.305	3.304	9.0	3.305	3.304	10.0	3.305	3.304	--	-	-	--	-	-		
Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%																															
4.4	3.305	3.304																															
4.5	3.305	3.304																															
4.8	3.305	3.304																															
5.0	3.305	3.304																															
7.0	3.305	3.304																															
9.0	3.305	3.304																															
10.0	3.305	3.304																															
--	-	-																															
--	-	-																															



Model	MGS6053R3																																																					
Item	Load Regulation	Temperature	25°C																																																			
Object	+3.3V1.6A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>4.5V</div></div><div><div>---□---</div><div>Input Volt.</div><div>5V</div></div><div><div>---○---</div><div>Input Volt.</div><div>9V</div></div></div> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 4.5[V]</th><th>Input Volt. 5[V]</th><th>Input Volt. 9[V]</th></tr><tr><td>0.00</td><td>3.307</td><td>3.307</td><td>3.307</td></tr><tr><td>0.32</td><td>3.306</td><td>3.306</td><td>3.307</td></tr><tr><td>0.64</td><td>3.306</td><td>3.306</td><td>3.306</td></tr><tr><td>0.96</td><td>3.305</td><td>3.305</td><td>3.305</td></tr><tr><td>1.28</td><td>3.304</td><td>3.304</td><td>3.304</td></tr><tr><td>1.60</td><td>3.304</td><td>3.304</td><td>3.304</td></tr><tr><td>1.76</td><td>3.303</td><td>3.303</td><td>3.303</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.00	3.307	3.307	3.307	0.32	3.306	3.306	3.307	0.64	3.306	3.306	3.306	0.96	3.305	3.305	3.305	1.28	3.304	3.304	3.304	1.60	3.304	3.304	3.304	1.76	3.303	3.303	3.303	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0.00	3.307	3.307	3.307																																																			
0.32	3.306	3.306	3.307																																																			
0.64	3.306	3.306	3.306																																																			
0.96	3.305	3.305	3.305																																																			
1.28	3.304	3.304	3.304																																																			
1.60	3.304	3.304	3.304																																																			
1.76	3.303	3.303	3.303																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	MGS6053R3	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+3.3V1.6A	

Input Volt. 5 V
Cycle 100 ms



$t_1, t_2 = 100 \mu s$



Min.Load (0A) ←→
Load 100% (1.6A)

200 mV/div

100 μs /div





100 μs /div

Min.Load (0A) ←→
Load 50% (0.8A)

200 mV/div

100 μs /div





100 μs /div

Load 50% (0.8A) ←→
Load 100% (1.6A)

200 mV/div

100 μs /div




100 μs /div

- 9 -

Model		MGS6053R3	Temperature		25°C																																						
Item		Ripple-Noise	Testing Circuitry		Figure B																																						
Object		+3.3V1.6A																																									
1.Graph			2.Values																																								
<div><div><div><div><div></div><div>—△—</div><div>Input Volt.</div><div>4.5V</div></div><div><div>- -○- -</div><div>Input Volt.</div><div>9V</div></div></div><div><p>Ripple Voltage [mV]</p><p>Load Current [A]</p></div></div><div><p>Measured by 100 MHz Oscilloscope.</p><p>Ripple-Noise is shown as p-p in the figure below.</p><p>Note: Slanted line shows the range of the rated load current.</p><p>Ripple Noise[mVp-p]</p><div></div><p>Fig.Complex Ripple Noise Wave Form</p></div></div>			<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple-Noise [mV]</th></tr><tr><th>Input Volt. 4.5 [V]</th><th>Input Volt. 9 [V]</th></tr><tr><td>0.00</td><td>10</td><td>30</td></tr><tr><td>0.32</td><td>5</td><td>5</td></tr><tr><td>0.64</td><td>5</td><td>10</td></tr><tr><td>0.96</td><td>5</td><td>5</td></tr><tr><td>1.28</td><td>10</td><td>5</td></tr><tr><td>1.60</td><td>10</td><td>10</td></tr><tr><td>1.76</td><td>10</td><td>10</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.00	10	30	0.32	5	5	0.64	5	10	0.96	5	5	1.28	10	5	1.60	10	10	1.76	10	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																										
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																									
0.00	10	30																																									
0.32	5	5																																									
0.64	5	10																																									
0.96	5	5																																									
1.28	10	5																																									
1.60	10	10																																									
1.76	10	10																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									

Testing Circuitry Figure B

2.Values



Note: Slanted line shows the range of the rated ambient temperature.

Model		MGS6053R3																																																					
Item		Ambient Temperature Drift	Testing Circuitry Figure A																																																				
Object		+3.3V1.6A																																																					
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>4.5V</div></div><div><div>---□---</div><div>Input Volt.</div><div>5V</div></div><div><div>---○---</div><div>Input Volt.</div><div>9V</div></div></div> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>	2.Values																																																				
		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 4.5[V]</th><th>Input Volt. 5[V]</th><th>Input Volt. 9[V]</th></tr><tr><td>-60</td><td>3.298</td><td>3.296</td><td>3.296</td></tr><tr><td>-40</td><td>3.299</td><td>3.299</td><td>3.299</td></tr><tr><td>-20</td><td>3.300</td><td>3.300</td><td>3.300</td></tr><tr><td>0</td><td>3.300</td><td>3.300</td><td>3.300</td></tr><tr><td>25</td><td>3.304</td><td>3.304</td><td>3.304</td></tr><tr><td>70</td><td>3.306</td><td>3.306</td><td>3.306</td></tr><tr><td>80</td><td>3.306</td><td>3.306</td><td>3.306</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	3.298	3.296	3.296	-40	3.299	3.299	3.299	-20	3.300	3.300	3.300	0	3.300	3.300	3.300	25	3.304	3.304	3.304	70	3.306	3.306	3.306	80	3.306	3.306	3.306	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																				
-60	3.298	3.296	3.296																																																				
-40	3.299	3.299	3.299																																																				
-20	3.300	3.300	3.300																																																				
0	3.300	3.300	3.300																																																				
25	3.304	3.304	3.304																																																				
70	3.306	3.306	3.306																																																				
80	3.306	3.306	3.306																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

COSEL

		Testing Circuitry Figure A
Model	MGS6053R3	
Item	Output Voltage Accuracy	
Object	+3.3V1.6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 70°C

Input Voltage : 4.5 - 9V

Load Current : 0 - 1.6A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) =
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	70	9	0	3.310	±6	±0.2
Minimum Voltage	-40	4.5	1.6	3.299		




Model	MGS6053R3																								
Item	Time Lapse Drift	Temperature	25°C																						
Object	+3.3V1.6A	Testing Circuitry	Figure A																						
1.Graph		2.Values																							
<div><p>Output Voltage [V]</p><p>Time [H]</p><p>Input Volt. 5V</p><p>Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>3.302</td></tr><tr><td>0.5</td><td>3.304</td></tr><tr><td>1.0</td><td>3.304</td></tr><tr><td>2.0</td><td>3.304</td></tr><tr><td>3.0</td><td>3.304</td></tr><tr><td>4.0</td><td>3.304</td></tr><tr><td>5.0</td><td>3.304</td></tr><tr><td>6.0</td><td>3.304</td></tr><tr><td>7.0</td><td>3.304</td></tr><tr><td>8.0</td><td>3.304</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	3.302	0.5	3.304	1.0	3.304	2.0	3.304	3.0	3.304	4.0	3.304	5.0	3.304	6.0	3.304	7.0	3.304	8.0	3.304
Time since start [H]	Output Voltage [V]																								
0.0	3.302																								
0.5	3.304																								
1.0	3.304																								
2.0	3.304																								
3.0	3.304																								
4.0	3.304																								
5.0	3.304																								
6.0	3.304																								
7.0	3.304																								
8.0	3.304																								

COSEL


Model	MGS6053R3	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+3.3V1.6A		

1.Graph



2.Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	1.2	0.3	1.5	0.1	0.8
100 %	1.2	0.2	1.4	0.1	0.4



1. Graph

The graph plots Input Voltage [V] on the Y-axis (0 to 10) against Ambient Temperature [°C] on the X-axis (-60 to 100). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a constant input voltage of approximately 3.7V across the temperature range. Slanted lines indicate the range of rated ambient temperature, which is approximately -40°C to 70°C.

Ambient Temperature [°C]	Input Voltage [V] (Load 50%)	Input Voltage [V] (Load 100%)
-60	3.7	3.7
-40	3.7	3.7
-20	3.7	3.7
0	3.7	3.7
20	3.7	3.7
40	3.7	3.7
60	3.7	3.7
70	3.7	3.7
80	3.7	3.7
100	3.7	3.7

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.8	3.8
-40	3.8	3.8
-20	3.8	3.8
0	3.7	3.8
25	3.7	3.8
70	3.7	3.8
80	3.7	3.7
--	-	-
--	-	-
--	-	-
--	-	-

Model		MGS6053R3	
Item		Overcurrent Protection	
Object		+3.3V1.6A	

1.Graph

Input Volt. 4.5V

Input Volt. 5V

Input Volt. 9V

Output Voltage [V]

<

Model	MGS6053R3		
Item	Switching Frequency (by Load Current)	Temperature	25°C
Object	+3.3V1.6A	Testing Circuitry	Figure A
<p>1.Graph</p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○ </p> <p> △□○<</p>			




Figure A




Figure B (Ripple and Ripple noise Characteristic)