

TEST DATA OF MUS1R52405

Regulated DC Power Supply
February 4, 2025

Approved by : Kenichi Tsukada
Design Manager

Prepared by : Soichiro Kawaguchi
Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Load Regulation	4
5.Ripple-Noise	4
6.Dynamic Load Response	5
7.Rise and Fall Time	6
8.Overcurrent Protection	7
9.Ambient Temperature Drift	8
10.Minimum Input Voltage for Regulated Output Voltage	8
11.Figure of Testing Circuitry	9

(Final Page 9)

Model		MUS1R52405		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>18V</div></div><div><div>---□---</div><div>Input Volt.</div><div>24V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>36V</div></div></div> <div>Input Current [A]</div> <div>Load Current [A]</div> <div>Note: Slanted line shows the range of the rated load current.</div>		2.Values																																																				
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>0.00</td><td>0.004</td><td>0.003</td><td>0.002</td></tr><tr><td>0.06</td><td>0.026</td><td>0.021</td><td>0.013</td></tr><tr><td>0.12</td><td>0.042</td><td>0.032</td><td>0.025</td></tr><tr><td>0.18</td><td>0.063</td><td>0.048</td><td>0.033</td></tr><tr><td>0.24</td><td>0.085</td><td>0.063</td><td>0.042</td></tr><tr><td>0.30</td><td>0.102</td><td>0.079</td><td>0.053</td></tr><tr><td>0.33</td><td>0.115</td><td>0.085</td><td>0.059</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.004	0.003	0.002	0.06	0.026	0.021	0.013	0.12	0.042	0.032	0.025	0.18	0.063	0.048	0.033	0.24	0.085	0.063	0.042	0.30	0.102	0.079	0.053	0.33	0.115	0.085	0.059	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
0.00	0.004	0.003	0.002																																																					
0.06	0.026	0.021	0.013																																																					
0.12	0.042	0.032	0.025																																																					
0.18	0.063	0.048	0.033																																																					
0.24	0.085	0.063	0.042																																																					
0.30	0.102	0.079	0.053																																																					
0.33	0.115	0.085	0.059																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					

COSEL

Model		MUS1R52405																																																				
Item		Efficiency (by Load Current)																																																				
Object																																																						
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>18V</div></div><div><div>---□---</div><div>Input Volt.</div><div>24V</div></div><div><div>---○---</div><div>Input Volt.</div><div>36V</div></div></div> <div>Note: Slanted line shows the range of the rated load current.</div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.06</td><td>63.8</td><td>60.2</td><td>63.3</td></tr><tr><td>0.12</td><td>79.8</td><td>76.4</td><td>67.0</td></tr><tr><td>0.18</td><td>77.9</td><td>79.7</td><td>75.9</td></tr><tr><td>0.24</td><td>79.8</td><td>78.7</td><td>80.1</td></tr><tr><td>0.30</td><td>80.7</td><td>80.1</td><td>78.5</td></tr><tr><td>0.33</td><td>81.0</td><td>80.5</td><td>78.8</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	-	-	-	0.06	63.8	60.2	63.3	0.12	79.8	76.4	67.0	0.18	77.9	79.7	75.9	0.24	79.8	78.7	80.1	0.30	80.7	80.1	78.5	0.33	81.0	80.5	78.8	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	-	-	-																																																			
0.06	63.8	60.2	63.3																																																			
0.12	79.8	76.4	67.0																																																			
0.18	77.9	79.7	75.9																																																			
0.24	79.8	78.7	80.1																																																			
0.30	80.7	80.1	78.5																																																			
0.33	81.0	80.5	78.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

- 2 -

BC-12042



Model	MUS1R52405																																		
Item	Line Regulation	Temperature	25°C																																
Object	+5V0.3A	Testing Circuitry	Figure A																																
1.Graph		2.Values																																	
<div><div><div>---□--- Load 50%</div><div>—△— Load 100%</div></div><p>Note: Slanted line shows the range of the rated input voltage.</p></div>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>16</td><td>5.107</td><td>5.108</td></tr><tr><td>18</td><td>5.107</td><td>5.108</td></tr><tr><td>20</td><td>5.107</td><td>5.108</td></tr><tr><td>24</td><td>5.107</td><td>5.108</td></tr><tr><td>30</td><td>5.107</td><td>5.108</td></tr><tr><td>36</td><td>5.107</td><td>5.108</td></tr><tr><td>40</td><td>5.107</td><td>5.108</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	16	5.107	5.108	18	5.107	5.108	20	5.107	5.108	24	5.107	5.108	30	5.107	5.108	36	5.107	5.108	40	5.107	5.108	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
16	5.107	5.108																																	
18	5.107	5.108																																	
20	5.107	5.108																																	
24	5.107	5.108																																	
30	5.107	5.108																																	
36	5.107	5.108																																	
40	5.107	5.108																																	
--	-	-																																	
--	-	-																																	



Model	MUS1R52405																																																					
Item	Load Regulation	Temperature	25°C																																																			
Object	+5V0.3A	Testing Circuitry	Figure A																																																			
1.Graph <div><div><div>—△—</div><div>Input Volt.</div><div>18V</div></div><div><div>---□---</div><div>Input Volt.</div><div>24V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>36V</div></div></div> <p>Note: Slanted line shows the range of the rated load current.</p>		2.Values <table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>0.00</td><td>5.108</td><td>5.107</td><td>5.107</td></tr><tr><td>0.06</td><td>5.107</td><td>5.107</td><td>5.107</td></tr><tr><td>0.12</td><td>5.107</td><td>5.107</td><td>5.107</td></tr><tr><td>0.18</td><td>5.107</td><td>5.107</td><td>5.107</td></tr><tr><td>0.24</td><td>5.107</td><td>5.107</td><td>5.107</td></tr><tr><td>0.30</td><td>5.107</td><td>5.107</td><td>5.107</td></tr><tr><td>0.33</td><td>5.107</td><td>5.107</td><td>5.107</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></table>		Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	5.108	5.107	5.107	0.06	5.107	5.107	5.107	0.12	5.107	5.107	5.107	0.18	5.107	5.107	5.107	0.24	5.107	5.107	5.107	0.30	5.107	5.107	5.107	0.33	5.107	5.107	5.107	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	5.108	5.107	5.107																																																			
0.06	5.107	5.107	5.107																																																			
0.12	5.107	5.107	5.107																																																			
0.18	5.107	5.107	5.107																																																			
0.24	5.107	5.107	5.107																																																			
0.30	5.107	5.107	5.107																																																			
0.33	5.107	5.107	5.107																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+5V0.3A	Testing Circuitry	Figure B																																																			
1.Graph <div><div>Input Voltage</div><div>24V</div><div>Load</div><div>100%</div></div>																																																						

-


4

-

BC-12042




Model	MUS1R52405		
Item	Dynamic Load Response	Temperature	25°C
		Testing Circuitry	Figure A
Object	+5V0.3A		






Model		MUS1R52405	Temperature 25°C Testing Circuitry Figure A
Item		Rise and Fall Time	
Object		+5V0.3A	

1.Graph



2.Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.6	2.9	3.5	0.1	1.5
100 %		0.6	3.5	4.1	0.1	0.5



COSEL

<div>COSEL</div>																																																										
Model	MUS1R52405																																																									
Item	Overcurrent Protection	Temperature	25°C																																																							
Object	+5V0.3A	Testing Circuitry	Figure A																																																							
1.Graph		2.Values																																																								
<div><div><div></div>Input Volt.18V</div><div><div></div>Input Volt.24V</div><div><div></div>Input Volt.36V</div></div> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>4.75</td><td>0.46</td><td>0.51</td><td>0.56</td></tr><tr><td>4.50</td><td>0.48</td><td>0.53</td><td>0.58</td></tr><tr><td>4.00</td><td>0.52</td><td>0.56</td><td>0.63</td></tr><tr><td>3.50</td><td>0.56</td><td>0.61</td><td>0.67</td></tr><tr><td>3.00</td><td>0.60</td><td>0.66</td><td>0.73</td></tr><tr><td>2.50</td><td>0.66</td><td>0.71</td><td>0.79</td></tr><tr><td>2.00</td><td>0.72</td><td>0.78</td><td>0.85</td></tr><tr><td>1.50</td><td>0.79</td><td>0.85</td><td>0.92</td></tr><tr><td>1.00</td><td>0.87</td><td>0.93</td><td>1.00</td></tr><tr><td>0.50</td><td>0.97</td><td>1.02</td><td>1.07</td></tr><tr><td>0.00</td><td>1.10</td><td>1.11</td><td>1.12</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	4.75	0.46	0.51	0.56	4.50	0.48	0.53	0.58	4.00	0.52	0.56	0.63	3.50	0.56	0.61	0.67	3.00	0.60	0.66	0.73	2.50	0.66	0.71	0.79	2.00	0.72	0.78	0.85	1.50	0.79	0.85	0.92	1.00	0.87	0.93	1.00	0.50	0.97	1.02	1.07	0.00	1.10	1.11	1.12	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
4.75	0.46	0.51	0.56																																																							
4.50	0.48	0.53	0.58																																																							
4.00	0.52	0.56	0.63																																																							
3.50	0.56	0.61	0.67																																																							
3.00	0.60	0.66	0.73																																																							
2.50	0.66	0.71	0.79																																																							
2.00	0.72	0.78	0.85																																																							
1.50	0.79	0.85	0.92																																																							
1.00	0.87	0.93	1.00																																																							
0.50	0.97	1.02	1.07																																																							
0.00	1.10	1.11	1.12																																																							
--	-	-	-																																																							

-7-

BC-12042



		Testing Circuitry Figure A																			
Model	MUS1R52405																				
Item	Ambient Temperature Drift																				
Object	+5V0.3A																				
1.Values <div>Load 100%</div> <table><tr><th rowspan="2">Ambient Temperature[°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 18V</th><th>Input Volt. 24V</th><th>Input Volt. 36V</th></tr><tr><td>-40</td><td>5.057</td><td>5.058</td><td>5.059</td></tr><tr><td>25</td><td>5.110</td><td>5.111</td><td>5.111</td></tr><tr><td>85</td><td>5.122</td><td>5.122</td><td>5.122</td></tr></table>			Ambient Temperature[°C]	Output Voltage [V]			Input Volt. 18V	Input Volt. 24V	Input Volt. 36V	-40	5.057	5.058	5.059	25	5.110	5.111	5.111	85	5.122	5.122	5.122
Ambient Temperature[°C]	Output Voltage [V]																				
	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V																		
-40	5.057	5.058	5.059																		
25	5.110	5.111	5.111																		
85	5.122	5.122	5.122																		
		Testing Circuitry Figure A																			
Item	Minimum Input Voltage for Regulated Output Voltage																				
Object	+5V0.3A																				
1.Values <table><tr><th rowspan="2">Ambient Temperature[°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>-40</td><td>14.0</td><td>13.9</td></tr><tr><td>25</td><td>13.9</td><td>14.0</td></tr><tr><td>85</td><td>13.9</td><td>14.0</td></tr></table>			Ambient Temperature[°C]	Input Voltage [V]		Load 50%	Load 100%	-40	14.0	13.9	25	13.9	14.0	85	13.9	14.0					
Ambient Temperature[°C]	Input Voltage [V]																				
	Load 50%	Load 100%																			
-40	14.0	13.9																			
25	13.9	14.0																			
85	13.9	14.0																			

- 8 -

BC-12042




Figure A




Figure B