

Temperature increase of main components: 主要部品温度上昇


Model: PBA100F

1. Conditions

- (1) Input :AC 85 ~ 264 [V]
 (2) Output :Rated output
 (3) Mounting method :Shown as Fig.1.1

2. Result

No.	Parts name	Symbol No.	Increase (ΔT)								Rated temp. [°C]	Reference
			[deg]									
			3.3V	5V	9V	12V	15V	24V	36V	48V		
1	Line Filter	L101	40	62	62	62	62	62	62	62	130	
2	Rectifier(Input)	SS101	65	76	76	76	76	76	76	76	150	Junction Temp.
3	Choke coil(PFC)	L103	39	53	53	53	53	53	53	53	120	
4	Transistor(PFC)	TR102	52	58	58	58	58	58	58	58	150	Junction Temp.
5	Rectified diode(PFC)	D102	45	57	57	57	57	57	57	57	150	Junction Temp.
6	Input Capacitor	C119	28	28	16	32	28	27	32	30	105	
7	Switching Transistor	TR201	56	67	67	67	67	67	67	67	150	Junction Temp.
8	Transformer	T201	51	50	48	53	53	54	50	51	130	
9	Rectified MOS-FET(Output)	TR502	62	70	-	-	-	-	-	-	150	Junction Temp.
10	Rectified Diode(Output)	SS502	-	-	77	72	65	58	54	51	150	Junction Temp.
11	Output Choke	L507	53	63	39	51	50	47	44	64	130	
12	Output Capacitor	C505	29	32	28	26	28	36	21	24	105	
13												
14												
15												
16												
17												
18												
19												
20												

Fig.1.1 Mounting method
(position A)

※This is reference data and the value is not guaranteed.
 本内容は参考データであり、その内容を保証するものではありません。