





PBA600F EMI/EMS Test result

 September 16, 2004
 Design engineering dep.

 Approved : Takahiro Umeda

 Prepared : Haruki Morita

No.	Test item	Conditions	Conditions of Acceptability	Result
1	Line conduction	(1) Rated input(AC100V,120V,230V) (2) Rated load (3) Ambient temp. $25 \pm 10^{\circ}\text{C}$	(1)Meets the undermentioned standard. FCC Part15 classB , VCCI classB CISPR22 classB , EN55022-B	OK
2	Radiated emission	(1) Rated input(AC100V,120V,230V) (2) Rated load (3) Ambient temp. $25 \pm 10^{\circ}\text{C}$	(1)Meets the undermentioned standard. FCC Part15 classB , VCCI classB CISPR22 classB , EN55022-B	OK
3	Harmonic current (EN61000-3-2)	(1) Rated input (AC100V,230V) (2) Load 0 - Rated load (3) Ambient temp. $25 \pm 10^{\circ}\text{C}$	(1)Meets the undermentioned standard. EN61000-3-2 classA	OK
4	Static electricity immunity test (EN61000-4-2)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. $25 \pm 10^{\circ}\text{C}$ (4) Contact discharge voltage 8[kV] (Level 4)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	OK
5	Radiated, radio-frequency, electromagnetic field immunity test (EN61000-4-3)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. $25 \pm 10^{\circ}\text{C}$ (4)Testing field strength 10[V/m] (Level 3)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	OK
6	Electrical fast transient/ burst immunity test (EN61000-4-4)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. $25 \pm 10^{\circ}\text{C}$ (4) Test peak voltage 4[kV] (Level 4)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	OK
7	Surge immunity test (EN61000-4-5)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. $25 \pm 10^{\circ}\text{C}$ (4) Test voltage Line to line 2[kV] (Level 3) Line to earth 4[kV] (Level 4)	(1)The power supply is not stop (2)Circuit does not malfunction. (3)No abnormality of the insulation destruction etc. (4)Parts are no damaged.	OK
8	Immunity to conducted disturbances, induced by radio-frequency fields (EN61000-4-6)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. $25 \pm 10^{\circ}\text{C}$ (4) Voltage level (e.m.f.) 10[V] (Level 3)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	OK
9	Power frequency magnetic field immunity test (EN61000-4-8)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. $25 \pm 10^{\circ}\text{C}$ (4) Magnetic field 30A/m (Level 4)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	OK
10	Voltage dips, short interruptions and voltage variations immunity test (EN61000-4-11)	(1) Rated input (AC230V) •30% reduction at 10mS min. •60% reduction at 100mS min •95% reduction at 5S min. • $\pm 10\%$ variation at 15 minutes (2) Rated load (3) Ambient temp. $25 \pm 10^{\circ}\text{C}$	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	OK

DATA SHEET							Date	21-Aug-03				
Model	PBA600F-7R5						Temp.	25 degreeC				
Test	EMI Line conduction & Radiated emission						Humid.	45 %RH				
							Tested by	H.Morita				
LINE CONDUCTION												
Model Name : PBA600F-7R5							Temp. : 25					
Model No. :							Humi. : 45					
Serial No. :							Date : 2003/8/21 20:29					
Points : 3							Test Equip. : R3132,ESPC					
Detector : PEAK/QP/Ave.							Comment : H.Morita					
Line Mode : VA							+7.5V 80A					
Power Supply : AC 230V 50Hz												
Limit1: [EN 55022] Class B(QP)												
Limit2: [EN 55022] Class B(Ave.)												
							Limit1(QP) Limit2(Ave.) VA(PEAK) VB(PEAK) VA(QP) VA(Ave.)					
							AC 230V 50Hz +7.5V 80A					
Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]		
0.1503	33.3	37.6	9.8	43.1	47.4	VA	56	66	12.9	18.6		
0.2781	31.5	34.5	9.8	41.3	44.3	VA	50.9	60.9	9.6	16.6		
0.3423	33.1	32.5	9.8	42.9	42.3	VA	49.2	59.2	6.3	16.9		
RADIATED EMISSION												
Model Name : PBA600F-7R5							Temp. : 25					
Model No. :							Humi. : 45					
Serial No. :							Date : 2003/8/21 20:07					
Points : 3							Test Equip. : R3132,ESPC					
Detector : PEAK/QP							Comment : H.Morita					
Polarization : Hori. & Vert.							+7.5V 80A					
Power Supply : AC 230V 50Hz												
Limit: [EN 55022] Class B<3m>												
							Limit(QP) Horizontal(PEAK) Vertical(PEAK) Horizontal(QP) Vertical(QP)					
							AC 230V 50Hz +7.5V 80A					
Frequency [MHz]	MeterReading (QP)[dBuV]	Ant. Type	Antenna Factor[dB/m]	Cable & Preamp[dB]	Level(QP) [dBuV/m]	Angle [°]	Height[cm]	Polar.	Limit [dBuV/m]	Margin [dB]		
49.823	55.2	BL	7.8	-32.1	30.9	122	139	Hori.	40	9.1		
77.612	58.4	BL	6.7	-31.9	33.2	343	146	Vert.	40	6.8		
154.841	52.5	BL	10.3	-31.5	31.3	107	154	Hori.	40	8.7		