

TEST DATA OF PDA600F-15

Regulated DC Power Supply
May 27, 2025

Approved by : Yoshiaki Shimizu
Design Manager

Prepared by : Terumasa Araki
Design Engineer


COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple-Noise	7
9.Dynamic Load Response	8
10.Rise and Fall Time	9
11.Hold-Up Time	10
12.Instantaneous Interruption Compensation	11
13.Overcurrent Protection	12
14.Ambient Temperature Drift	13
15.Minimum Input Voltage for Regulated Output Voltage	13
16.Overvoltage Protection	13
17.Figure of Testing Circuitry	14

(Final Page 15)

COSEL

Model		PDA600F-15		Temperature 25°C																																																		
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																		
Object		_____																																																				
1.Graph		<div><div>—△—</div><div>---□---</div><div>---○---</div></div> <div><div>Input Volt. 100V</div><div>Input Volt. 200V</div><div>Input Volt. 230V</div></div>		2.Values																																																		
<div><div>Input Current [A]</div><div></div><div>Load Current [A]</div></div> <div>Note: Slanted line shows the range of the rated load current.</div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 100[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 230[V]</th></tr><tr><td>0.0</td><td>0.166</td><td>0.141</td><td>0.149</td></tr><tr><td>8.0</td><td>1.594</td><td>0.877</td><td>0.802</td></tr><tr><td>16.0</td><td>2.956</td><td>1.524</td><td>1.368</td></tr><tr><td>24.0</td><td>4.358</td><td>2.201</td><td>1.942</td></tr><tr><td>32.0</td><td>5.799</td><td>2.902</td><td>2.543</td></tr><tr><td>40.0</td><td>7.280</td><td>3.612</td><td>3.160</td></tr><tr><td>43.0</td><td>7.850</td><td>3.879</td><td>3.393</td></tr><tr><td>47.3</td><td>8.670</td><td>4.266</td><td>3.729</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.166	0.141	0.149	8.0	1.594	0.877	0.802	16.0	2.956	1.524	1.368	24.0	4.358	2.201	1.942	32.0	5.799	2.902	2.543	40.0	7.280	3.612	3.160	43.0	7.850	3.879	3.393	47.3	8.670	4.266	3.729	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.166	0.141	0.149																																																			
8.0	1.594	0.877	0.802																																																			
16.0	2.956	1.524	1.368																																																			
24.0	4.358	2.201	1.942																																																			
32.0	5.799	2.902	2.543																																																			
40.0	7.280	3.612	3.160																																																			
43.0	7.850	3.879	3.393																																																			
47.3	8.670	4.266	3.729																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model		PDA600F-15		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>100V</div></div><div><div>---□---</div><div>Input Volt.</div><div>200V</div></div><div><div>---○---</div><div>Input Volt.</div><div>230V</div></div></div> <p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		2.Values																																																				
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 100[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 230[V]</th></tr><tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>8.0</td><td>78.5</td><td>79.6</td><td>79.6</td></tr><tr><td>16.0</td><td>83.3</td><td>84.7</td><td>84.8</td></tr><tr><td>24.0</td><td>84.4</td><td>86.0</td><td>86.2</td></tr><tr><td>32.0</td><td>84.4</td><td>86.3</td><td>86.4</td></tr><tr><td>40.0</td><td>84.0</td><td>86.1</td><td>86.4</td></tr><tr><td>43.0</td><td>83.7</td><td>86.1</td><td>86.3</td></tr><tr><td>47.3</td><td>83.4</td><td>86.0</td><td>86.2</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	8.0	78.5	79.6	79.6	16.0	83.3	84.7	84.8	24.0	84.4	86.0	86.2	32.0	84.4	86.3	86.4	40.0	84.0	86.1	86.4	43.0	83.7	86.1	86.3	47.3	83.4	86.0	86.2	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																					
0.0	-	-	-																																																					
8.0	78.5	79.6	79.6																																																					
16.0	83.3	84.7	84.8																																																					
24.0	84.4	86.0	86.2																																																					
32.0	84.4	86.3	86.4																																																					
40.0	84.0	86.1	86.4																																																					
43.0	83.7	86.1	86.3																																																					
47.3	83.4	86.0	86.2																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					

- 2 -

BC-12156

COSEL




Model		PDA600F-15		Temperature 25°C																																																				
Item		Power Factor (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph				2.Values																																																				
<div><div><div>—△—</div><div>---□---</div><div>-·○-</div></div><div>Input Volt. 100V</div><div>Input Volt. 200V</div><div>Input Volt. 230V</div></div> <p>Power Factor</p> <p>Load Current [A]</p>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Power Factor</th></tr><tr><th>Input Volt. 100[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 230[V]</th></tr><tr><td>0.0</td><td>0.579</td><td>0.323</td><td>0.267</td></tr><tr><td>8.0</td><td>0.972</td><td>0.870</td><td>0.826</td></tr><tr><td>16.0</td><td>0.988</td><td>0.941</td><td>0.910</td></tr><tr><td>24.0</td><td>0.993</td><td>0.964</td><td>0.946</td></tr><tr><td>32.0</td><td>0.994</td><td>0.971</td><td>0.961</td></tr><tr><td>40.0</td><td>0.994</td><td>0.976</td><td>0.967</td></tr><tr><td>43.0</td><td>0.996</td><td>0.977</td><td>0.969</td></tr><tr><td>47.3</td><td>0.995</td><td>0.979</td><td>0.972</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.579	0.323	0.267	8.0	0.972	0.870	0.826	16.0	0.988	0.941	0.910	24.0	0.993	0.964	0.946	32.0	0.994	0.971	0.961	40.0	0.994	0.976	0.967	43.0	0.996	0.977	0.969	47.3	0.995	0.979	0.972	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																							
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																					
0.0	0.579	0.323	0.267																																																					
8.0	0.972	0.870	0.826																																																					
16.0	0.988	0.941	0.910																																																					
24.0	0.993	0.964	0.946																																																					
32.0	0.994	0.971	0.961																																																					
40.0	0.994	0.976	0.967																																																					
43.0	0.996	0.977	0.969																																																					
47.3	0.995	0.979	0.972																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								

- 3 -

BC-12156



Model		PDA600F-15	
Item		Inrush Current	
Object		_____	
Temperature		25°C	
Testing Circuitry		Figure A	





Model		PDA600F-15	Temperature 25°C Testing Circuitry Figure C
Item		Leakage Current	
Object		_____	

1.Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	240 [V]	
DEN-AN	Figure C-1	Both phases	0.16	0.43	0.45	Operation
		One of phases	0.31	0.81	0.85	Stand by
IEC62368-1	Figure C-2	Both phases	0.16	0.42	0.45	Operation
		One of phases	0.31	0.80	0.84	Stand by
	Figure C-3	Both phases	0.16	0.42	0.44	Operation
		One of phases	0.31	0.79	0.83	Stand by

The value for "One of phases" is the reference value only.

2.Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model		PDA600F-15	Temperature		25°C																																
Item		Line Regulation	Testing Circuitry		Figure A																																
Object		+15V43A																																			
1.Graph			2.Values																																		
<div><div><div><div><div></div><div></div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div>Load 50%</div><div><div><div><div></div><div></div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div>Load 100%</div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>15.246</td><td>15.243</td></tr><tr><td>90</td><td>15.247</td><td>15.245</td></tr><tr><td>100</td><td>15.247</td><td>15.245</td></tr><tr><td>120</td><td>15.248</td><td>15.246</td></tr><tr><td>200</td><td>15.248</td><td>15.246</td></tr><tr><td>230</td><td>15.248</td><td>15.247</td></tr><tr><td>264</td><td>15.248</td><td>15.247</td></tr><tr><td>280</td><td>15.249</td><td>15.247</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	15.246	15.243	90	15.247	15.245	100	15.247	15.245	120	15.248	15.246	200	15.248	15.246	230	15.248	15.247	264	15.248	15.247	280	15.249	15.247	--	-	-			
Input Voltage [V]	Output Voltage [V]																																				
	Load 50%	Load 100%																																			
85	15.246	15.243																																			
90	15.247	15.245																																			
100	15.247	15.245																																			
120	15.248	15.246																																			
200	15.248	15.246																																			
230	15.248	15.247																																			
264	15.248	15.247																																			
280	15.249	15.247																																			
--	-	-																																			

COSEL


Model	PDA600F-15																																																					
Item	Load Regulation	Temperature	25°C																																																			
		Testing Circuitry	Figure A																																																			
Object	+15V43A																																																					
1.Graph		2.Values																																																				
<div><div><div><div><div></div><div>△</div></div><div>—</div></div><div>Input Volt. 100V</div></div><div><div><div><div></div><div>□</div></div><div>---</div></div><div>Input Volt. 200V</div></div><div><div><div><div></div><div>○</div></div><div>---</div></div><div>Input Volt. 230V</div></div></div> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 100[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 230[V]</th></tr><tr><td>0.0</td><td>15.266</td><td>15.265</td><td>15.266</td></tr><tr><td>8.0</td><td>15.261</td><td>15.261</td><td>15.261</td></tr><tr><td>16.0</td><td>15.259</td><td>15.259</td><td>15.259</td></tr><tr><td>24.0</td><td>15.256</td><td>15.256</td><td>15.256</td></tr><tr><td>32.0</td><td>15.253</td><td>15.253</td><td>15.253</td></tr><tr><td>40.0</td><td>15.249</td><td>15.250</td><td>15.250</td></tr><tr><td>43.0</td><td>15.248</td><td>15.249</td><td>15.248</td></tr><tr><td>47.3</td><td>15.247</td><td>15.247</td><td>15.247</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></table>		Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	15.266	15.265	15.266	8.0	15.261	15.261	15.261	16.0	15.259	15.259	15.259	24.0	15.256	15.256	15.256	32.0	15.253	15.253	15.253	40.0	15.249	15.250	15.250	43.0	15.248	15.249	15.248	47.3	15.247	15.247	15.247	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	15.266	15.265	15.266																																																			
8.0	15.261	15.261	15.261																																																			
16.0	15.259	15.259	15.259																																																			
24.0	15.256	15.256	15.256																																																			
32.0	15.253	15.253	15.253																																																			
40.0	15.249	15.250	15.250																																																			
43.0	15.248	15.249	15.248																																																			
47.3	15.247	15.247	15.247																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Item	Ripple-Noise	Temperature	25°C																																																			
		Testing Circuitry	Figure B																																																			
Object	+15V43A																																																					
1.Graph																																																						
<div><div>Input Voltage230V</div><div>Load100%</div></div> <div>20[mV/div]</div> <div>4[μs/div]</div>																																																						

-7-

BC-12156




Model		PDA600F-15	Temperature 25°C Testing Circuitry Figure A
Item		Dynamic Load Response	
Object		+15V43A	






Model	PDA600F-15	Temperature 25°C Testing Circuitry Figure A
Item	Rise and Fall Time	
Object	+15V43A	

1.Graph



2.Values

		[ms]				
Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		268.5	10.0	278.5	42.5	23.0
230 V		264.0	10.0	274.0	42.8	22.8



COSEL

<div>LOREL</div>																																			
Model	PDA600F-15																																		
Item	Hold-Up Time	Temperature	25°C																																
		Testing Circuitry	Figure A																																
Object	+15V43A																																		
1.Graph		2.Values																																	
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <p>The graph shows Hold-Up Time [ms] on a logarithmic y-axis (1 to 1000) versus Input Voltage [V] on a linear x-axis (50 to 300). Two data series are plotted: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a constant hold-up time of approximately 80 ms for Load 50% and 38 ms for Load 100% across the input voltage range. Vertical shaded regions indicate the rated input voltage range (approximately 85V to 100V and 264V to 280V).</p> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Hold-Up Time [ms]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>80</td><td>38</td></tr><tr><td>90</td><td>80</td><td>38</td></tr><tr><td>100</td><td>80</td><td>38</td></tr><tr><td>120</td><td>80</td><td>38</td></tr><tr><td>200</td><td>80</td><td>38</td></tr><tr><td>230</td><td>80</td><td>38</td></tr><tr><td>264</td><td>80</td><td>38</td></tr><tr><td>280</td><td>85</td><td>39</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	80	38	90	80	38	100	80	38	120	80	38	200	80	38	230	80	38	264	80	38	280	85	39	--	-	-		
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	80	38																																	
90	80	38																																	
100	80	38																																	
120	80	38																																	
200	80	38																																	
230	80	38																																	
264	80	38																																	
280	85	39																																	
--	-	-																																	

COSEL

<div>LOREL</div>																																																						
Model	PDA600F-15	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+15V43A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>100V</div></div><div><div>---□---</div><div>Input Volt.</div><div>200V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>230V</div></div></div> <div><div>Instantaneous Compensation Time [ms]</div><div><div>Load Current [A]</div></div></div> <div>Note: Slanted line shows the range of the rated load current.</div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr><tr><th>Input Volt. 100[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 230[V]</th></tr><tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>8.0</td><td>156</td><td>213</td><td>213</td></tr><tr><td>16.0</td><td>56</td><td>105</td><td>105</td></tr><tr><td>24.0</td><td>31</td><td>70</td><td>70</td></tr><tr><td>32.0</td><td>22</td><td>49</td><td>52</td></tr><tr><td>40.0</td><td>17</td><td>40</td><td>40</td></tr><tr><td>43.0</td><td>17</td><td>37</td><td>36</td></tr><tr><td>47.3</td><td>17</td><td>23</td><td>22</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	8.0	156	213	213	16.0	56	105	105	24.0	31	70	70	32.0	22	49	52	40.0	17	40	40	43.0	17	37	36	47.3	17	23	22	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
8.0	156	213	213																																																			
16.0	56	105	105																																																			
24.0	31	70	70																																																			
32.0	22	49	52																																																			
40.0	17	40	40																																																			
43.0	17	37	36																																																			
47.3	17	23	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

- 11 -

BC-12156

COSEL

Model		PDA600F-15	Temperature		25°C																																												
Item		Overcurrent Protection	Testing Circuitry		Figure A																																												
Object		+15V43A																																															
1.Graph			2.Values																																														
<div><div><div></div><div>Input Volt. 100V</div></div><div><div></div><div>Input Volt. 230V</div></div></div> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 9.00V to 0V.</p>			<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="2">Load Current [A]</th></tr><tr><th>Input Volt. 100[V]</th><th>Input Volt. 230[V]</th></tr><tr><td>14.25</td><td>48.63</td><td>48.63</td></tr><tr><td>13.50</td><td>48.94</td><td>48.93</td></tr><tr><td>12.00</td><td>49.55</td><td>49.55</td></tr><tr><td>10.50</td><td>50.23</td><td>50.23</td></tr><tr><td>9.00</td><td>51.13</td><td>51.14</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>			Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	14.25	48.63	48.63	13.50	48.94	48.93	12.00	49.55	49.55	10.50	50.23	50.23	9.00	51.13	51.14	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																																
	Input Volt. 100[V]	Input Volt. 230[V]																																															
14.25	48.63	48.63																																															
13.50	48.94	48.93																																															
12.00	49.55	49.55																																															
10.50	50.23	50.23																																															
9.00	51.13	51.14																																															
--	-	-																																															
--	-	-																																															
--	-	-																																															
--	-	-																																															
--	-	-																																															
--	-	-																																															
--	-	-																																															
--	-	-																																															




Figure A




Figure B




Figure C-1 (DEN-AN)




Figure C-2 (IEC62368-1 refer to IEC60990 Fig.4)




Figure C-3 (IEC62368-1 refer to IEC60990 Fig.5)