



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|-----------|
| Model | PDA600F-5 |
|-------|-----------|

| No. | P a r t s | | Q' ty of Device | Failure rate [10 ⁻⁶ /H] | Reference |
|--|------------------------|---------------------|-----------------|------------------------------------|-----------|
| 1 | I C | M o n o l i t h i c | 10 | 0.6540 | |
| 2 | | H y b r i d | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 16 | 0.6050 | |
| 4 | D i o d e s | | 45 | 0.9235 | |
| 5 | LED•Optocouplers | | 6 | 0.4200 | |
| 6 | R e s i s t o r s | | 250 | 1.1115 | |
| 7 | C a p a c i t o r s | | 140 | 1.2421 | |
| 8 | Transformer•Choke Coil | | 18 | 0.2277 | |
| 9 | C o n n e c t o r s | | 1263 | 0.2942 | |
| 1 0 | O t h e r s | | 10 | 2.7310 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 8.2090 | |

| | | |
|---------------------|------|---------|
| M T B F | [H] | 122,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |