



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|--------------|
| Model | PJMA1000F-48 |
|-------|--------------|

| No. | P a r t s | | Q'ty of Device | Failure rate [10 ⁻⁶ /H] | R e f e r e n c e |
|--|------------------------|------------|----------------|------------------------------------|-------------------|
| 1 | I C | Monolithic | 6 | 0.2440 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 18 | 0.6072 | |
| 4 | D i o d e s | | 54 | 1.1760 | |
| 5 | LED•Optocouplers | | 3 | 0.1412 | |
| 6 | R e s i s t o r s | | 237 | 1.0810 | |
| 7 | C a p a c i t o r s | | 120 | 1.1637 | |
| 8 | Transformer•Choke Coil | | 29 | 0.2116 | |
| 9 | C o n n e c t o r s | | 1405 | 0.3068 | |
| 10 | O t h e r s | | 7 | 4.9780 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 9.9095 | |

| | | |
|---------------------|------|---------|
| M T B F | [H] | 101,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |