



M T B F (E I A J R C R - 9 1 0 2)

| | |
|-------|-------------|
| Model | PJMA600F-12 |
|-------|-------------|

| No. | P a r t s | | Q'ty of Device | Failure rate [10 ⁻⁶ /H] | R e f e r e n c e |
|--|------------------------|---------------------|----------------|------------------------------------|-------------------|
| 1 | I C | M o n o l i t h i c | 4 | 0.1960 | |
| 2 | | H y b r i d | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 13 | 0.5038 | |
| 4 | D i o d e s | | 39 | 0.9005 | |
| 5 | LED•Optocouplers | | 3 | 0.1412 | |
| 6 | R e s i s t o r s | | 212 | 0.9015 | |
| 7 | C a p a c i t o r s | | 64 | 0.6797 | |
| 8 | Transformer•Choke Coil | | 20 | 0.1702 | |
| 9 | C o n n e c t o r s | | 970 | 0.2357 | |
| 1 0 | O t h e r s | | 5 | 2.5640 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 6.2926 | |

| | |
|--------------------------|---------|
| M T B F [H] | 159,000 |
| Ambient Temperature [°C] | — |
| Load Factor [%] | — |