

TEST DATA OF PLA150F-24

Regulated DC Power Supply
May 23, 2013

Approved by : Katsumi Ishikawa
Katsumi Ishikawa Design Manager

Prepared by : Naoki Fujita
Naoki Fujita Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Overvoltage Protection	23
24.Figure of Testing Circuitry	24

(Final Page 25)

COSEL

Model

PLA150F-24

Item

Input Current (by Load Current)

Object

1.Graph

—△—

Input Volt.

100V

---□---

Input Volt.

115V

-○-

Input Volt.

230V

Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.00	0.046	0.047	0.046
1.00	0.332	0.270	0.178
2.00	0.604	0.503	0.290
3.00	0.842	0.740	0.407
4.00	1.112	0.968	0.512
5.00	1.384	1.196	0.630
6.00	1.662	1.436	0.740
6.40	1.777	1.533	0.788
7.04	-	1.688	0.858
--	-	-	-
--	-	-	-



Model		PLA150F-24		Temperature 25°C																																																		
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																		
Object																																																						
1.Graph		<div><div><div>—△—</div><div>---□---</div><div>---○---</div></div><div><div>Input Volt. 100V</div><div>Input Volt. 115V</div><div>Input Volt. 230V</div></div></div>		2.Values																																																		
<div><div>Input Power [W]</div><div>Load Current [A]</div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 100[V]</th><th>Input Volt. 115[V]</th><th>Input Volt. 230[V]</th></tr><tr><td>0.00</td><td>1.1</td><td>1.0</td><td>0.6</td></tr><tr><td>1.00</td><td>30.5</td><td>29.5</td><td>31.0</td></tr><tr><td>2.00</td><td>57.0</td><td>56.3</td><td>56.0</td></tr><tr><td>3.00</td><td>83.4</td><td>82.5</td><td>83.0</td></tr><tr><td>4.00</td><td>110.4</td><td>109.5</td><td>107.0</td></tr><tr><td>5.00</td><td>138.0</td><td>136.5</td><td>135.0</td></tr><tr><td>6.00</td><td>165.9</td><td>164.4</td><td>160.0</td></tr><tr><td>6.40</td><td>177.3</td><td>175.5</td><td>172.0</td></tr><tr><td>7.04</td><td>-</td><td>193.2</td><td>188.0</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	1.1	1.0	0.6	1.00	30.5	29.5	31.0	2.00	57.0	56.3	56.0	3.00	83.4	82.5	83.0	4.00	110.4	109.5	107.0	5.00	138.0	136.5	135.0	6.00	165.9	164.4	160.0	6.40	177.3	175.5	172.0	7.04	-	193.2	188.0	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	1.1	1.0	0.6																																																			
1.00	30.5	29.5	31.0																																																			
2.00	57.0	56.3	56.0																																																			
3.00	83.4	82.5	83.0																																																			
4.00	110.4	109.5	107.0																																																			
5.00	138.0	136.5	135.0																																																			
6.00	165.9	164.4	160.0																																																			
6.40	177.3	175.5	172.0																																																			
7.04	-	193.2	188.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

- 2 -

BC - 10756



Model

PLA150F-24

Item

Efficiency (by Input Voltage)

Object

1.Graph

□---

Load 50%

△---

Load 100%

Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
85	86.2	85.8 ※1
100	87.2	87.0 ※2
115	87.5	87.5
200	88.7	89.5
230	89.0	90.1
264	89.6	90.1
280	89.5	89.8
--	-	-
--	-	-

※1:Load 80%

※2:Load 90%



Model		PLA150F-24		Temperature Testing Circuitry	25°C Figure A																																																			
Item		Efficiency (by Load Current)																																																						
Object																																																								
1.Graph				2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>100V</div></div><div><div>---□---</div><div>Input Volt.</div><div>115V</div></div><div><div>---○---</div><div>Input Volt.</div><div>230V</div></div></div> <p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 100[V]</th><th>Input Volt. 115[V]</th><th>Input Volt. 230[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>1.00</td><td>80.2</td><td>83.0</td><td>78.9</td></tr><tr><td>2.00</td><td>85.2</td><td>85.9</td><td>86.4</td></tr><tr><td>3.00</td><td>87.2</td><td>87.4</td><td>88.9</td></tr><tr><td>4.00</td><td>87.2</td><td>87.9</td><td>89.2</td></tr><tr><td>5.00</td><td>87.0</td><td>87.8</td><td>89.4</td></tr><tr><td>6.00</td><td>87.0</td><td>87.6</td><td>90.0</td></tr><tr><td>6.40</td><td>86.6</td><td>87.5</td><td>90.1</td></tr><tr><td>7.04</td><td>-</td><td>87.4</td><td>89.8</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	-	-	-	1.00	80.2	83.0	78.9	2.00	85.2	85.9	86.4	3.00	87.2	87.4	88.9	4.00	87.2	87.9	89.2	5.00	87.0	87.8	89.4	6.00	87.0	87.6	90.0	6.40	86.6	87.5	90.1	7.04	-	87.4	89.8	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																					
0.00	-	-	-																																																					
1.00	80.2	83.0	78.9																																																					
2.00	85.2	85.9	86.4																																																					
3.00	87.2	87.4	88.9																																																					
4.00	87.2	87.9	89.2																																																					
5.00	87.0	87.8	89.4																																																					
6.00	87.0	87.6	90.0																																																					
6.40	86.6	87.5	90.1																																																					
7.04	-	87.4	89.8																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Model		PLA150F-24		Temperature		25°C																																	
Item		Power Factor (by Input Voltage)		Testing Circuitry		Figure A																																	
Object																																							
1.Graph				2.Values																																			
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>---△---</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Power Factor</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>0.996</td><td>0.995 ※1</td></tr><tr><td>100</td><td>0.983</td><td>0.995 ※2</td></tr><tr><td>115</td><td>0.966</td><td>0.994</td></tr><tr><td>200</td><td>0.916</td><td>0.965</td></tr><tr><td>230</td><td>0.879</td><td>0.952</td></tr><tr><td>264</td><td>0.475</td><td>0.537</td></tr><tr><td>280</td><td>0.460</td><td>0.483</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>				Input Voltage [V]	Power Factor		Load 50%	Load 100%	85	0.996	0.995 ※1	100	0.983	0.995 ※2	115	0.966	0.994	200	0.916	0.965	230	0.879	0.952	264	0.475	0.537	280	0.460	0.483	--	-	-	--	-	-	<div>※1:Load 80%</div> <div>※2:Load 90%</div>			
Input Voltage [V]	Power Factor																																						
	Load 50%	Load 100%																																					
85	0.996	0.995 ※1																																					
100	0.983	0.995 ※2																																					
115	0.966	0.994																																					
200	0.916	0.965																																					
230	0.879	0.952																																					
264	0.475	0.537																																					
280	0.460	0.483																																					
--	-	-																																					
--	-	-																																					
Note: Slanted line shows the range of the rated input voltage.																																							



Model		PLA150F-24		Temperature		25°C																																																		
Item		Power Factor (by Load Current)		Testing Circuitry		Figure A																																																		
Object																																																								
1.Graph		<div><div>—△—</div>Input Volt. 100V</div> <div><div>---□---</div>Input Volt. 115V</div> <div><div>---○---</div>Input Volt. 230V</div>		2.Values																																																				
<div><div><div>Power Factor</div><div>1.0</div><div>0.9</div><div>0.8</div><div>0.7</div><div>0.6</div><div>0.5</div><div>0.4</div><div>0.3</div><div>0.2</div><div>0.1</div><div>0.0</div></div><div><div>0</div><div>2</div><div>4</div><div>6</div><div>8</div></div><div><div>Load Current [A]</div></div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Power Factor</th></tr><tr><th>Input Volt. 100[V]</th><th>Input Volt. 115[V]</th><th>Input Volt. 230[V]</th></tr><tr><td>0.00</td><td>0.407</td><td>0.345</td><td>0.078</td></tr><tr><td>1.00</td><td>0.937</td><td>0.918</td><td>0.795</td></tr><tr><td>2.00</td><td>0.956</td><td>0.965</td><td>0.838</td></tr><tr><td>3.00</td><td>0.984</td><td>0.969</td><td>0.872</td></tr><tr><td>4.00</td><td>0.993</td><td>0.981</td><td>0.915</td></tr><tr><td>5.00</td><td>0.994</td><td>0.989</td><td>0.931</td></tr><tr><td>6.00</td><td>0.996</td><td>0.995</td><td>0.942</td></tr><tr><td>6.40</td><td>0.997</td><td>0.994</td><td>0.952</td></tr><tr><td>7.04</td><td>-</td><td>0.995</td><td>0.953</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	0.407	0.345	0.078	1.00	0.937	0.918	0.795	2.00	0.956	0.965	0.838	3.00	0.984	0.969	0.872	4.00	0.993	0.981	0.915	5.00	0.994	0.989	0.931	6.00	0.996	0.995	0.942	6.40	0.997	0.994	0.952	7.04	-	0.995	0.953	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																							
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																					
0.00	0.407	0.345	0.078																																																					
1.00	0.937	0.918	0.795																																																					
2.00	0.956	0.965	0.838																																																					
3.00	0.984	0.969	0.872																																																					
4.00	0.993	0.981	0.915																																																					
5.00	0.994	0.989	0.931																																																					
6.00	0.996	0.995	0.942																																																					
6.40	0.997	0.994	0.952																																																					
7.04	-	0.995	0.953																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								

-




6

-

BC - 10756

COSEL

Model		PLA150F-24	Temperature 25°C Testing Circuitry Figure A
Item		Inrush Current	
Object		_____	





Model		PLA150F-24	Temperature 25°C Testing Circuitry Figure B
Item		Leakage Current	
Object			

1.Results

[mA]

Standards		Input Volt.			Note
		100[V]	115[V]	240[V]	
DEN-AN	Both phases	0.45	0.50	0.65	Operation
	One of phases	0.30	0.35	0.78	Stand by
IEC60950-1	Both phases	0.30	0.31	0.55	Operation
	One of phases	0.27	0.31	0.72	Stand by

The value for "One of phases" is the reference value only.

2.Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.



Model

PLA150F-24

Item

Line Regulation

Object

+24V6.4A

1.Graph

□

Load 50%

△

Load 100%

Output Voltage [V]

24.400

24.300

24.200

24.100

24.000

23.900

23.800

23.700

Input Voltage [V]

50

100

150

200

250

300

Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	24.144	24.140 ※1
100	24.143	24.140 ※2
115	24.143	24.139
200	24.143	24.139
230	24.143	24.138
264	24.143	24.138
280	24.143	24.138
—	-	-
—	-	-

※1:Load 80%

※2:Load 90%



Model		PLA150F-24		Temperature 25°C																																																				
Item		Load Regulation		Testing Circuitry Figure A																																																				
Object		+24V6.4A																																																						
1.Graph		<div><div><div>—△—</div><div>Input Volt. 100V</div></div><div><div>---□---</div><div>Input Volt. 115V</div></div><div><div>---○---</div><div>Input Volt. 230V</div></div></div> <div><div><div>Output Voltage [V]</div><div>Load Current [A]</div></div></div>		2.Values																																																				
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 100[V]</th><th>Input Volt. 115[V]</th><th>Input Volt. 230[V]</th></tr><tr><td>0.00</td><td>24.261</td><td>24.262</td><td>24.264</td></tr><tr><td>1.00</td><td>24.156</td><td>24.157</td><td>24.162</td></tr><tr><td>2.00</td><td>24.144</td><td>24.145</td><td>24.145</td></tr><tr><td>3.00</td><td>24.143</td><td>24.143</td><td>24.143</td></tr><tr><td>4.00</td><td>24.141</td><td>24.142</td><td>24.142</td></tr><tr><td>5.00</td><td>24.141</td><td>24.141</td><td>24.140</td></tr><tr><td>6.00</td><td>24.140</td><td>24.139</td><td>24.138</td></tr><tr><td>6.40</td><td>24.140</td><td>24.139</td><td>24.138</td></tr><tr><td>7.04</td><td>-</td><td>24.137</td><td>24.137</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	24.261	24.262	24.264	1.00	24.156	24.157	24.162	2.00	24.144	24.145	24.145	3.00	24.143	24.143	24.143	4.00	24.141	24.142	24.142	5.00	24.141	24.141	24.140	6.00	24.140	24.139	24.138	6.40	24.140	24.139	24.138	7.04	-	24.137	24.137	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																					
0.00	24.261	24.262	24.264																																																					
1.00	24.156	24.157	24.162																																																					
2.00	24.144	24.145	24.145																																																					
3.00	24.143	24.143	24.143																																																					
4.00	24.141	24.142	24.142																																																					
5.00	24.141	24.141	24.140																																																					
6.00	24.140	24.139	24.138																																																					
6.40	24.140	24.139	24.138																																																					
7.04	-	24.137	24.137																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								

- 10 -


BC - 10756

COSEL

Model	PLA150F-24	Temperature Testing Circuitry	25° C Figure A
Item	Dynamic Load Response		
Object	+24V6.4A		


Input Volt. 115 V
Cycle 1000 ms

Response. $t_1=t_2=50\mu\text{s}$. Typ




Min. Load (0A) \longleftrightarrow
Load 100% (6.4A)

400 mV/div




200 ms/div




200 ms/div

Min. Load (0A) \longleftrightarrow
Load 50% (3.2A)

400 mV/div



200 ms/div



200 ms/div

COSEL


Model		PLA150F-24																																					
Item		Ripple Voltage (by Load Current)																																					
Object		+24V6.4A																																					
1.Graph		2.Values																																					
<div><div><div><div><div></div><div>—△—</div><div>Input Volt. 115V</div></div><div><div></div><div>- -○- -</div><div>Input Volt. 230V</div></div></div><div><table><thead><tr><th>Load Current [A]</th><th>Input Volt. 115 [V]</th><th>Input Volt. 230 [V]</th></tr></thead><tbody><tr><td>0.00</td><td>225</td><td>230</td></tr><tr><td>1.00</td><td>20</td><td>30</td></tr><tr><td>2.00</td><td>20</td><td>30</td></tr><tr><td>3.00</td><td>20</td><td>35</td></tr><tr><td>4.00</td><td>25</td><td>35</td></tr><tr><td>5.00</td><td>25</td><td>35</td></tr><tr><td>6.00</td><td>35</td><td>35</td></tr><tr><td>6.40</td><td>35</td><td>35</td></tr><tr><td>7.04</td><td>40</td><td>40</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table></div></div></div>		Load Current [A]	Input Volt. 115 [V]	Input Volt. 230 [V]	0.00	225	230	1.00	20	30	2.00	20	30	3.00	20	35	4.00	25	35	5.00	25	35	6.00	35	35	6.40	35	35	7.04	40	40	--	-	-	--	-	-		
Load Current [A]	Input Volt. 115 [V]	Input Volt. 230 [V]																																					
0.00	225	230																																					
1.00	20	30																																					
2.00	20	30																																					
3.00	20	35																																					
4.00	25	35																																					
5.00	25	35																																					
6.00	35	35																																					
6.40	35	35																																					
7.04	40	40																																					
--	-	-																																					
--	-	-																																					
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																							
<div><div><div>T1: Due to AC Input Line</div><div>T2: Due to Switching</div></div><div></div></div>																																							
Fig. Complex Ripple Wave Form																																							

COSEL

Model		PLA150F-24	Temperature 25°C Testing Circuitry Figure C																																						
Item		Ripple-Noise																																							
Object		+24V6.4A																																							
1.Graph																																									
<div><div><div>—△—</div><div>Input Volt. 115V</div></div><div><div>- - -○- - -</div><div>Input Volt. 230V</div></div></div> <p>Measured by 20 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
2.Values																																									
<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple-Noise [mV]</th></tr><tr><th>Input Volt. 115 [V]</th><th>Input Volt. 230 [V]</th></tr><tr><td>0.00</td><td>275</td><td>280</td></tr><tr><td>1.00</td><td>50</td><td>60</td></tr><tr><td>2.00</td><td>50</td><td>60</td></tr><tr><td>3.00</td><td>55</td><td>65</td></tr><tr><td>4.00</td><td>60</td><td>65</td></tr><tr><td>5.00</td><td>60</td><td>65</td></tr><tr><td>6.00</td><td>60</td><td>65</td></tr><tr><td>6.40</td><td>60</td><td>65</td></tr><tr><td>7.04</td><td>65</td><td>65</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Ripple-Noise [mV]		Input Volt. 115 [V]	Input Volt. 230 [V]	0.00	275	280	1.00	50	60	2.00	50	60	3.00	55	65	4.00	60	65	5.00	60	65	6.00	60	65	6.40	60	65	7.04	65	65	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 115 [V]	Input Volt. 230 [V]																																							
0.00	275	280																																							
1.00	50	60																																							
2.00	50	60																																							
3.00	55	65																																							
4.00	60	65																																							
5.00	60	65																																							
6.00	60	65																																							
6.40	60	65																																							
7.04	65	65																																							
--	-	-																																							
--	-	-																																							
<div><div>T1: Due to AC Input Line</div><div>T2: Due to Switching</div><div>Ripple-Noise [mVp-p]</div><p>Fig. Complex Ripple Wave Form</p></div>																																									

Testing Circuitry **Figure C**

2.Values



Note: Slanted line shows the range of the rated ambient temperature.



Model

PLA150F-24

Item

Ambient Temperature Drift

Object

+24V6.4A

1.Graph

—△—

Input Volt. 100V

---□---

Input Volt. 115V

---○---

Input Volt. 230V

Output Voltage [V]

Ambient Temperature [°C]

Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
-20	24.147	24.147	24.146
-10	24.145	24.144	24.144
0	24.144	24.143	24.142
10	24.143	24.142	24.141
20	24.141	24.140	24.139
25	24.140	24.139	24.138
35	24.135	24.133	24.132
45	24.125	24.124	24.123
55	24.117	24.116	24.115
65	24.103	24.102	24.101
---	-	-	-

Note: In case of Input Volt. 100V, Load 90%.
Other case Load 100%.



COSEL		Testing Circuitry Figure A
Model	PLA150F-24	
Item	Output Voltage Accuracy	
Object	+24V6.4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 45°C

Input Voltage : 115 - 264V

Load Current : 1.92 - 6.4A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-10	230	1.92	24.151	±14	±0.1
Minimum Voltage	45	264	6.4	24.123		

COSEL

Model		PLA150F-24	
Item		Time Lapse Drift	
Object		+24V6.4A	

1.Graph

Output Voltage [V]



COSEL

LOREL

Model	PLA150F-24
Item	Hold-Up Time
Object	+24V6.4A

1.Graph

---□--- Load 50%
 —△— Load 100%

Input Voltage [V]	Hold-Up Time [ms] (Load 50%)	Hold-Up Time [ms] (Load 100%)
85	63	39
100	63	35
115	64	31
200	64	31
230	75	35
264	81	39
280	93	45

Hold-Up Time [ms]

Input Voltage [V]

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
 Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
 Testing Circuitry Figure A

2.Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	63	39 ※1
100	63	35 ※2
115	64	31
200	64	31
230	75	35
264	81	39
280	93	45
—	—	—
—	—	—

※1:Load 80%
 ※2:Load 90%



Model

PLA150F-24

Item

Instantaneous Interruption Compensation

Object

+24V6.4A

1.Graph

—△—

Input Volt. 100V

---□---

Input Volt. 115V

---○---

Input Volt. 230V

Instantaneous Compensation Time [ms]

1000

100

10

1

0

2

4

6

8

Load Current [A]

Note: Slanted line shows the range of the rated load current.

Temperature

25°C

Testing Circuitry

Figure A

2.Values


Load Current [A]	Time [ms]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.0	-	-	-
1.2	185	185	184
2.4	82	82	85
3.6	54	54	57
4.8	43	42	41
6.0	32	32	33
6.4	31	29	28
7.0	23	24	26
--	-	-	-
--	-	-	-
--	-	-	-

20

BC - 10756

Testing Circuitry Figure A

2.Values



Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model		PLA150F-24	
Item		Overcurrent Protection	
Object		+24V6.4A	

1.Graph

Input Volt. 115V

Input Volt. 230V

Output Voltage [V]

</



</

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)




Figure C