

DATA SHEET		Date	Apr.18,2002
Model	RMB50A	Temp.	25 °C
Test	Vibration/impact test 振動・衝撃試験	Humid.	55 %Rh
		Tested by	Hamaguchi

1. Method
 Vibration/impact test complies with JIS C 0911 (Vibration), JIS C 0912 (Impact)
 JIS C 0911 (振動), JIS C 0912 (衝撃) に準ずる

2. Conditions
 - (1) Frequency : 10~55 Hz
 (Vibration) 3 minutes period
 周波数(振動)

 - (2) Direction・Time : 60 minutes along X, Y and Z axis (Vibration)
 方向・時間 11mS, once each X, Y and Z axis (Impact)

3. Conditions of Acceptability
 - (1) No degradation of performance or loss of function after test.
 試験後、諸機能が正常であること

 - (2) No remakably damage of appearance.
 外観上著しい損傷がないこと

 - (3) No looseness or a crack at solder joint.
 はんだ付け、圧着など電氣的接合部分にクラックや緩みの発生がないこと

4. Result
 - (1) Vibration limit test

No.	Gravity[m/s ²]	Result	Note
1	19.6	OK	
2		—	
3		—	

All are satisfactory to item 3: OK

 - (2) Impact test

No.	Gravity[m/s ²]	Result	Note
1	196.1	OK	
2		—	
3		—	

All are satisfactory to item 3: OK