

DATA SHEET		Date	Apr.18,2002
Model	RMC15A	Temp.	25 °C
Test	Vibration/impact test 振動・衝撃試験	Humid.	55 %Rh
		Tested by	Hamaguchi

  

1. Method  
 Vibration/impact test complies with JIS C 0911 (Vibration), JIS C 0912 (Impact)  
 JIS C 0911 (振動), JIS C 0912 (衝撃) に準ずる
  
2. Conditions
  - (1) Frequency : 10~55 Hz  
 (Vibration) 3 minutes period  
 周波数(振動)
  
  - (2) Direction・Time : 60 minutes along X, Y and Z axis (Vibration)  
 方向・時間 11mS, once each X, Y and Z axis (Impact)
  
3. Conditions of Acceptability
  - (1) No degradation of performance or loss of function after test.  
 試験後、諸機能が正常であること
  
  - (2) No remakably damage of appearance.  
 外観上著しい損傷がないこと
  
  - (3) No looseness or a crack at solder joint.  
 はんだ付け、圧着など電氣的接合部分にクラックや緩みの発生がないこと
  
4. Result
  - (1) Vibration limit test
 

No.	Gravity[m/s <sup>2</sup> ]	Result	Note
1	19.6	OK	
2		—	
3		—	

All are satisfactory to item 3:    OK
  
  - (2) Impact test
 

No.	Gravity[m/s <sup>2</sup> ]	Result	Note
1	196.1	OK	
2		—	
3		—	

All are satisfactory to item 3:    OK