



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|-------------|
| Model | SFCS15483R3 |
|-------|-------------|

| No. | P a r t s | | Q'ty of Device | Failure rate [10 ⁻⁶ /H] | Reference |
|--|------------------------|------------|----------------|------------------------------------|-----------|
| 1 | I C | Monolithic | 1 | 0.0410 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 27 | 0.8129 | |
| 4 | D i o d e s | | 16 | 0.2665 | |
| 5 | LED•Optocouplers | | 0 | 0.0000 | |
| 6 | R e s i s t o r s | | 95 | 0.0190 | |
| 7 | C a p a c i t o r s | | 34 | 0.2516 | |
| 8 | Transformer•Choke Coil | | 3 | 0.0690 | |
| 9 | C o n n e c t o r s | | 480 | 0.0661 | |
| 1 0 | O t h e r s | | 1 | 0.1100 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 1.6361 | |

| | | |
|---------------------|-----|---------|
| M T B F | [H] | 612,000 |
| Ambient Temperature | [] | - |
| Load Factor | [%] | - |