

DATA SHEET							Date	11-Oct-07																																														
Model	SFS20483R3						Temp.	25 degreeC																																														
Test	EMI Line conduction & Radiated emission						Humid.	45 %RH																																														
							Tested by	Y.Miyawaki																																														
LINE CONDUCTION																																																						
Model Name : SFS20483R3			Temp. : 25degreeC																																																			
Model No. :			Humi. : 45%																																																			
Serial No. :			Date : 2007/10/11 10:34																																																			
Points : 3			Test Equip. : R3132,ESPC																																																			
Detector : PEAK/QP/Ave.			Load Line : 100mm																																																			
Line Mode : VA/VB			Comment : Vo = 3.3V , Io = 6.0A																																																			
Power Supply : DC 48V																																																						
Limit1: [CISPR Pub11] Class A Gr.1(QP)																																																						
Limit2: [CISPR Pub11] Class A Gr.1(Ave.)																																																						
							Limit1(QP) Limit2(Ave.) VA(PEAK) VB(PEAK) VA(QP) VA(Ave.) VB(QP) VB(Ave.)																																															
<table><tr><th>Frequency [MHz]</th><th>Meter Reading (Ave.) [dBuV]</th><th>Meter Reading (QP) [dBuV]</th><th>Factor [dB]</th><th>Level(Ave.) [dBuV]</th><th>Level(QP) [dBuV]</th><th>Line</th><th>Limit(Ave.) [dBuV]</th><th>Limit(QP) [dBuV]</th><th>Margin(Ave.) [dB]</th><th>Margin(QP) [dB]</th></tr><tr><td>0.1619</td><td>34.9</td><td>39.8</td><td>9.8</td><td>44.7</td><td>49.6</td><td>VA</td><td>66</td><td>79</td><td>21.3</td><td>29.4</td></tr><tr><td>19.1588</td><td>30.8</td><td>30.5</td><td>10.3</td><td>41.1</td><td>40.8</td><td>VA</td><td>60</td><td>73</td><td>18.9</td><td>32.2</td></tr><tr><td>0.6381</td><td>32.1</td><td>32</td><td>9.9</td><td>42</td><td>41.9</td><td>VB</td><td>60</td><td>73</td><td>18</td><td>31.1</td></tr></table>											Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]	0.1619	34.9	39.8	9.8	44.7	49.6	VA	66	79	21.3	29.4	19.1588	30.8	30.5	10.3	41.1	40.8	VA	60	73	18.9	32.2	0.6381	32.1	32	9.9	42	41.9	VB	60	73	18	31.1
Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]																																												
0.1619	34.9	39.8	9.8	44.7	49.6	VA	66	79	21.3	29.4																																												
19.1588	30.8	30.5	10.3	41.1	40.8	VA	60	73	18.9	32.2																																												
0.6381	32.1	32	9.9	42	41.9	VB	60	73	18	31.1																																												
RADIATED EMISSION																																																						
Model Name : SFS20483R3			Temp. : 25degreeC																																																			
Model No. :			Humi. : 45%																																																			
Serial No. :			Date : 2007/10/11 10:45																																																			
Points : 3			Test Equip. : R3132,ESPC																																																			
Detector : PEAK/QP			Load Line : 100mm																																																			
Polarization : Vertical			Comment : Vo = 3.3V , Io = 6.0A																																																			
Power Supply : DC 48V																																																						
Limit: [CISPR 11] Class A Group 1<3m>																																																						
							Limit(QP) Horizontal(PEAK) Vertical(PEAK) Vertical(QP)																																															
<table><tr><th>Frequency [MHz]</th><th>MeterReading (QP) [dBuV]</th><th>Ant. Type</th><th>Antenna Factor [dB/m]</th><th>Cable &amp; Preamp [dB]</th><th>Level(QP) [dBuV/m]</th><th>Angle [°]</th><th>Height [cm]</th><th>Polar.</th><th>Limit [dBuV/m]</th><th>Margin [dB]</th></tr><tr><td>67.358</td><td>56.9</td><td>BL</td><td>5.1</td><td>-32</td><td>30</td><td>331</td><td>122</td><td>Vert.</td><td>50</td><td>20</td></tr><tr><td>123.161</td><td>52.8</td><td>BL</td><td>11</td><td>-31.7</td><td>32.1</td><td>9</td><td>157</td><td>Vert.</td><td>50</td><td>17.9</td></tr><tr><td>255.295</td><td>60.6</td><td>BL</td><td>13.1</td><td>-31.1</td><td>42.6</td><td>230</td><td>130</td><td>Vert.</td><td>57</td><td>14.4</td></tr></table>											Frequency [MHz]	MeterReading (QP) [dBuV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level(QP) [dBuV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]	67.358	56.9	BL	5.1	-32	30	331	122	Vert.	50	20	123.161	52.8	BL	11	-31.7	32.1	9	157	Vert.	50	17.9	255.295	60.6	BL	13.1	-31.1	42.6	230	130	Vert.	57	14.4
Frequency [MHz]	MeterReading (QP) [dBuV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level(QP) [dBuV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]																																												
67.358	56.9	BL	5.1	-32	30	331	122	Vert.	50	20																																												
123.161	52.8	BL	11	-31.7	32.1	9	157	Vert.	50	17.9																																												
255.295	60.6	BL	13.1	-31.1	42.6	230	130	Vert.	57	14.4																																												

DATA SHEET		Date	11-Oct-07
Model	SFS20483R3	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	45 %RH
		Tested by	Y.Miyawaki

## 1.Conditions

### (1)Photograph of Test Set-Up





Fig1. Photograph of Test Set-Up

### (2)Testing circuitry




C1: 1 $\mu$ F 100V Ceramic capacitor  
 C2: 2200pF 630V Ceramic capacitor  
 C3: 22 $\mu$ F 16V Ceramic capacitor  
 C4: 10 $\mu$ F 100V Electric capacitor

L1: 1 $\mu$ H 2.4A Inductor  
 L2: ZJYS51R5-2PT : TDK

Fig2. Testing circuitry

DATA SHEET		Date	11-Oct-07
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	45 %RH
		Tested by	Y.Miyawaki

1. Line conduction



2. Radiated emission

