

TEST DATA OF SNDHS250B05

Regulated DC Power Supply
June 30, 2011

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Tadashi Arai
Tadashi Arai Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)

Model		SNDHS250B05		
Item		Input Current (by Input Voltage)		
Object				
1.Graph				
		Load 100% Load 50% Load 0%		
Note: Slanted line shows the range of the rated input voltage.				
2.Values				
Input Voltage [V]		Input Current [A]		
		Load 0%	Load 50%	Load 100%
0		0.000	0.000	0.000
50		0.000	0.004	0.000
100		0.002	0.002	0.002
150		0.000	0.000	0.000
170		0.000	0.000	0.000
180		0.000	0.000	0.000
190		0.000	0.000	0.000
195		0.035	0.708	1.456
200		0.033	0.689	1.422
250		0.028	0.556	1.136
280		0.028	0.500	1.016
300		0.029	0.468	0.950
350		0.030	0.406	0.818
400		0.032	0.360	0.723
420		0.033	0.345	0.692
425		0.033	0.341	0.685
--		-	-	-
--		-	-	-

BC-10592

COSEL

Model		SNDHS250B05																																																				
Item		Input Current (by Load Current)																																																				
Object																																																						
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>200V</div></div><div><div>---□---</div><div>Input Volt.</div><div>280V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>400V</div></div></div> <p>Input Current [A]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>0</td><td>0.032</td><td>0.029</td><td>0.032</td></tr><tr><td>10</td><td>0.289</td><td>0.213</td><td>0.159</td></tr><tr><td>20</td><td>0.555</td><td>0.403</td><td>0.293</td></tr><tr><td>30</td><td>0.834</td><td>0.601</td><td>0.430</td></tr><tr><td>40</td><td>1.122</td><td>0.804</td><td>0.572</td></tr><tr><td>50</td><td>1.423</td><td>1.014</td><td>0.721</td></tr><tr><td>55</td><td>1.579</td><td>1.123</td><td>0.799</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	0.032	0.029	0.032	10	0.289	0.213	0.159	20	0.555	0.403	0.293	30	0.834	0.601	0.430	40	1.122	0.804	0.572	50	1.423	1.014	0.721	55	1.579	1.123	0.799	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0	0.032	0.029	0.032																																																			
10	0.289	0.213	0.159																																																			
20	0.555	0.403	0.293																																																			
30	0.834	0.601	0.430																																																			
40	1.122	0.804	0.572																																																			
50	1.423	1.014	0.721																																																			
55	1.579	1.123	0.799																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	SNDHS250B05																																																					
Item	Input Power (by Load Current)	Temperature	25°C																																																			
		Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt. 200V</div></div><div><div>---□---</div><div>Input Volt. 280V</div></div><div><div>-·-○-·-</div><div>Input Volt. 400V</div></div></div> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>0</td><td>6.5</td><td>8.0</td><td>13.1</td></tr><tr><td>10</td><td>57.7</td><td>59.6</td><td>63.7</td></tr><tr><td>20</td><td>111.0</td><td>112.9</td><td>117.2</td></tr><tr><td>30</td><td>166.6</td><td>168.4</td><td>172.2</td></tr><tr><td>40</td><td>224.5</td><td>225.2</td><td>229.0</td></tr><tr><td>50</td><td>284.4</td><td>284.2</td><td>288.7</td></tr><tr><td>55</td><td>315.6</td><td>314.9</td><td>319.9</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	6.5	8.0	13.1	10	57.7	59.6	63.7	20	111.0	112.9	117.2	30	166.6	168.4	172.2	40	224.5	225.2	229.0	50	284.4	284.2	288.7	55	315.6	314.9	319.9	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0	6.5	8.0	13.1																																																			
10	57.7	59.6	63.7																																																			
20	111.0	112.9	117.2																																																			
30	166.6	168.4	172.2																																																			
40	224.5	225.2	229.0																																																			
50	284.4	284.2	288.7																																																			
55	315.6	314.9	319.9																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model		SNDHS250B05																																	
Item		Efficiency (by Input Voltage)																																	
Object																																			
1.Graph		2.Values																																	
<div><div><div><div><div></div><div></div></div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div>Load 50%</div><div>Load 100%</div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Efficiency [%]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>195</td><td>91.3</td><td>88.8</td></tr><tr><td>200</td><td>91.4</td><td>88.8</td></tr><tr><td>240</td><td>90.8</td><td>89.0</td></tr><tr><td>280</td><td>90.2</td><td>88.9</td></tr><tr><td>320</td><td>89.5</td><td>88.7</td></tr><tr><td>360</td><td>88.6</td><td>88.3</td></tr><tr><td>400</td><td>87.6</td><td>87.5</td></tr><tr><td>420</td><td>87.2</td><td>87.2</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	195	91.3	88.8	200	91.4	88.8	240	90.8	89.0	280	90.2	88.9	320	89.5	88.7	360	88.6	88.3	400	87.6	87.5	420	87.2	87.2	--	-	-		
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
195	91.3	88.8																																	
200	91.4	88.8																																	
240	90.8	89.0																																	
280	90.2	88.9																																	
320	89.5	88.7																																	
360	88.6	88.3																																	
400	87.6	87.5																																	
420	87.2	87.2																																	
--	-	-																																	

Model		SNDHS250B05		Temperature		25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry		Figure A																																																				
Object																																																										
1.Graph				2.Values																																																						
<div><div><div>—△— Input Volt. 200V</div><div>---□--- Input Volt. 280V</div><div>-○- Input Volt. 400V</div></div><div>Efficiency [%]</div><div>Load Current [A]</div></div> <div>Note: Slanted line shows the range of the rated load current.</div>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>10</td><td>88.0</td><td>85.2</td><td>79.7</td></tr><tr><td>20</td><td>91.3</td><td>89.7</td><td>86.5</td></tr><tr><td>30</td><td>91.2</td><td>90.2</td><td>88.3</td></tr><tr><td>40</td><td>90.2</td><td>89.9</td><td>88.4</td></tr><tr><td>50</td><td>88.9</td><td>89.0</td><td>87.6</td></tr><tr><td>55</td><td>88.1</td><td>88.4</td><td>87.0</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Efficiency [%]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	-	-	-	10	88.0	85.2	79.7	20	91.3	89.7	86.5	30	91.2	90.2	88.3	40	90.2	89.9	88.4	50	88.9	89.0	87.6	55	88.1	88.4	87.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																							
0	-	-	-																																																							
10	88.0	85.2	79.7																																																							
20	91.3	89.7	86.5																																																							
30	91.2	90.2	88.3																																																							
40	90.2	89.9	88.4																																																							
50	88.9	89.0	87.6																																																							
55	88.1	88.4	87.0																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
				- 5 -																																																						
				BC-10592																																																						

Model	SNDHS250B05																																
Item	Line Regulation	Temperature	25°C																														
Object	+5V50A	Testing Circuitry	Figure A																														
1.Graph		2.Values																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Output Voltage [V] Load 50%</th><th>Output Voltage [V] Load 100%</th></tr></thead><tbody><tr><td>195</td><td>5.068</td><td>5.061</td></tr><tr><td>200</td><td>5.068</td><td>5.062</td></tr><tr><td>240</td><td>5.068</td><td>5.062</td></tr><tr><td>280</td><td>5.068</td><td>5.062</td></tr><tr><td>320</td><td>5.069</td><td>5.063</td></tr><tr><td>360</td><td>5.069</td><td>5.063</td></tr><tr><td>400</td><td>5.069</td><td>5.064</td></tr><tr><td>420</td><td>5.069</td><td>5.064</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%	195	5.068	5.061	200	5.068	5.062	240	5.068	5.062	280	5.068	5.062	320	5.069	5.063	360	5.069	5.063	400	5.069	5.064	420	5.069	5.064	--	-	-		
Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%																															
195	5.068	5.061																															
200	5.068	5.062																															
240	5.068	5.062																															
280	5.068	5.062																															
320	5.069	5.063																															
360	5.069	5.063																															
400	5.069	5.064																															
420	5.069	5.064																															
--	-	-																															

COSEL

Model	SNDHS250B05																																																					
Item	Load Regulation	Temperature	25°C																																																			
Object	+5V50A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>200V</div></div><div><div>---□---</div><div>Input Volt.</div><div>280V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>400V</div></div></div> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>0</td><td>5.077</td><td>5.076</td><td>5.077</td></tr><tr><td>10</td><td>5.074</td><td>5.074</td><td>5.074</td></tr><tr><td>20</td><td>5.071</td><td>5.071</td><td>5.071</td></tr><tr><td>30</td><td>5.068</td><td>5.068</td><td>5.069</td></tr><tr><td>40</td><td>5.066</td><td>5.065</td><td>5.066</td></tr><tr><td>50</td><td>5.063</td><td>5.063</td><td>5.064</td></tr><tr><td>55</td><td>5.062</td><td>5.062</td><td>5.063</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	5.077	5.076	5.077	10	5.074	5.074	5.074	20	5.071	5.071	5.071	30	5.068	5.068	5.069	40	5.066	5.065	5.066	50	5.063	5.063	5.064	55	5.062	5.062	5.063	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0	5.077	5.076	5.077																																																			
10	5.074	5.074	5.074																																																			
20	5.071	5.071	5.071																																																			
30	5.068	5.068	5.069																																																			
40	5.066	5.065	5.066																																																			
50	5.063	5.063	5.064																																																			
55	5.062	5.062	5.063																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

-

7

-

BC-10592




Model	SNDHS250B05		
Item	Dynamic Load Response	Temperature	25°C
Object	+5V50A	Testing Circuitry	Figure A

Input Volt. 280 V
Cycle 1000 ms


Load Current  50A/50 μ s

Min. Load (0A) \longleftrightarrow
Load 100% (50A)

0.2 V/div




200us/div




400us/div

Min. Load (0A) \longleftrightarrow
Load 50% (25A)

0.2 V/div




200us/div




400us/div

Load 10% (5A) \longleftrightarrow
Load 100% (50A)

0.2 V/div



200us/div




400us/div

Model	SNDHS250B05																																								
Item	Ripple Voltage (by Load Current)	Temperature	25°C																																						
Object	+5V50A	Testing Circuitry	Figure B																																						
1.Graph		2.Values																																							
<div><div><div><div></div><div>—△—</div><div>Input Volt. 200V</div></div><div><div></div><div>-○-</div><div>Input Volt. 400V</div></div></div><div><p>Ripple Voltage [mV]</p><p>Load Current [A]</p></div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 200 [V]</th><th>Input Volt. 400 [V]</th></tr><tr><td>0</td><td>20</td><td>20</td></tr><tr><td>10</td><td>15</td><td>25</td></tr><tr><td>20</td><td>15</td><td>20</td></tr><tr><td>30</td><td>15</td><td>25</td></tr><tr><td>40</td><td>15</td><td>20</td></tr><tr><td>50</td><td>15</td><td>20</td></tr><tr><td>55</td><td>15</td><td>20</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0	20	20	10	15	25	20	15	20	30	15	25	40	15	20	50	15	20	55	15	20	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 200 [V]	Input Volt. 400 [V]																																							
0	20	20																																							
10	15	25																																							
20	15	20																																							
30	15	25																																							
40	15	20																																							
50	15	20																																							
55	15	20																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope.</p> <p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																									
<div><div><div></div><div>Ripple [mVp-p]</div></div><div><p>Fig.Complex Ripple Wave Form</p></div></div>																																									

Model	SNDHS250B05																																								
Item	Ripple-Noise	Temperature	25°C																																						
Object	+5V50A	Testing Circuitry	Figure B																																						
1.Graph		2.Values																																							
<div><div><div><div></div><div>Input Volt. 200V</div></div><div><div></div><div>Input Volt. 400V</div></div></div><div></div></div> <div><div>Measured by 100 MHz Oscilloscope.</div><div>Ripple-Noise is shown as p-p in the figure below.</div><div>Note: Slanted line shows the range of the rated load current.</div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple-Noise [mV]</th></tr><tr><th>Input Volt. 200 [V]</th><th>Input Volt. 400 [V]</th></tr><tr><td>0</td><td>30</td><td>40</td></tr><tr><td>10</td><td>50</td><td>40</td></tr><tr><td>20</td><td>50</td><td>65</td></tr><tr><td>30</td><td>50</td><td>70</td></tr><tr><td>40</td><td>50</td><td>70</td></tr><tr><td>50</td><td>60</td><td>70</td></tr><tr><td>55</td><td>70</td><td>75</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0	30	40	10	50	40	20	50	65	30	50	70	40	50	70	50	60	70	55	70	75	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 200 [V]	Input Volt. 400 [V]																																							
0	30	40																																							
10	50	40																																							
20	50	65																																							
30	50	70																																							
40	50	70																																							
50	60	70																																							
55	70	75																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<div><div><div></div><div>Ripple Noise[mVp-p]</div></div><div></div></div> <div>Fig.Complex Ripple Noise Wave Form</div>																																									

Testing Circuitry Figure B

2.Values



Note: Slanted line shows the range of the rated ambient temperature.

Model	SNDHS250B05																																																						
Item	Ambient Temperature Drift		Testing Circuitry Figure A																																																				
Object	+5V50A																																																						
1.Graph		2.Values																																																					
<div><div><div>—△—</div><div>---□---</div><div>-·-○-·-</div></div><div>Input Volt. 200V</div><div>Input Volt. 280V</div><div>Input Volt. 400V</div></div> <div><p>Output Voltage [V]</p><p>Ambient Temperature [°C]</p><p>Load 100%</p></div>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>-40</td><td>5.035</td><td>5.036</td><td>5.038</td></tr><tr><td>-20</td><td>5.044</td><td>5.045</td><td>5.046</td></tr><tr><td>0</td><td>5.053</td><td>5.054</td><td>5.055</td></tr><tr><td>25</td><td>5.061</td><td>5.062</td><td>5.063</td></tr><tr><td>40</td><td>5.066</td><td>5.067</td><td>5.067</td></tr><tr><td>55</td><td>5.070</td><td>5.070</td><td>5.071</td></tr><tr><td>70</td><td>5.071</td><td>5.072</td><td>5.072</td></tr><tr><td>85</td><td>5.072</td><td>5.072</td><td>5.073</td></tr><tr><td>95</td><td>5.074</td><td>5.074</td><td>5.075</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	-40	5.035	5.036	5.038	-20	5.044	5.045	5.046	0	5.053	5.054	5.055	25	5.061	5.062	5.063	40	5.066	5.067	5.067	55	5.070	5.070	5.071	70	5.071	5.072	5.072	85	5.072	5.072	5.073	95	5.074	5.074	5.075	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																				
-40	5.035	5.036	5.038																																																				
-20	5.044	5.045	5.046																																																				
0	5.053	5.054	5.055																																																				
25	5.061	5.062	5.063																																																				
40	5.066	5.067	5.067																																																				
55	5.070	5.070	5.071																																																				
70	5.071	5.072	5.072																																																				
85	5.072	5.072	5.073																																																				
95	5.074	5.074	5.075																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note: Slanted line shows the range of the rated ambient temperature.																																																							

- 12 -

BC-10592

		Testing Circuitry Figure A
Model	SNDHS250B05	
Item	Output Voltage Accuracy	
Object	+5V50A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 200 - 400V

Load Current : 0 - 50A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	95	200	0	5.090	±23	±0.5
Minimum Voltage	-20	200	50	5.044		


COSEL

Model	SNDHS250B05																								
Item	Time Lapse Drift	Temperature	25°C																						
		Testing Circuitry	Figure A																						
Object	+5V50A																								
1.Graph		2.Values																							
<div><div><div>5.12</div><div>5.10</div><div>5.08</div><div>5.06</div><div>5.04</div><div>5.02</div><div>5.00</div><div>4.98</div></div><div></div><div>0246810</div><div>Time [H]</div></div> <div><div>Input Volt.</div><div>280V</div><div>Load</div><div>100%</div></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>5.062</td></tr><tr><td>0.5</td><td>5.065</td></tr><tr><td>1.0</td><td>5.065</td></tr><tr><td>2.0</td><td>5.065</td></tr><tr><td>3.0</td><td>5.065</td></tr><tr><td>4.0</td><td>5.065</td></tr><tr><td>5.0</td><td>5.065</td></tr><tr><td>6.0</td><td>5.065</td></tr><tr><td>7.0</td><td>5.065</td></tr><tr><td>8.0</td><td>5.065</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	5.062	0.5	5.065	1.0	5.065	2.0	5.065	3.0	5.065	4.0	5.065	5.0	5.065	6.0	5.065	7.0	5.065	8.0	5.065
Time since start [H]	Output Voltage [V]																								
0.0	5.062																								
0.5	5.065																								
1.0	5.065																								
2.0	5.065																								
3.0	5.065																								
4.0	5.065																								
5.0	5.065																								
6.0	5.065																								
7.0	5.065																								
8.0	5.065																								

Model	SNDHS250B05	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+5V50A		


1.Graph

Input Volt. 280 V




2.Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	52.0	6.3	58.3	0.6	4.0
100 %	52.0	6.3	58.3	0.4	1.9



Testing Circuitry Figure A

2.Values



Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	SNDHS250B05																																																													
Item	Overcurrent Protection	Temperature	25°C																																																											
Object	+5V50A	Testing Circuitry	Figure A																																																											
1.Graph		2.Values																																																												
<div><div><div></div><div></div><div></div></div><div><div>Input Volt. 200V</div><div>Input Volt. 280V</div><div>Input Volt. 400V</div></div></div> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>4.75</td><td>60.98</td><td>61.62</td><td>60.78</td></tr><tr><td>4.50</td><td>61.41</td><td>62.06</td><td>61.78</td></tr><tr><td>4.00</td><td>62.30</td><td>63.05</td><td>62.11</td></tr><tr><td>3.50</td><td>63.11</td><td>64.00</td><td>62.89</td></tr><tr><td>3.00</td><td>64.54</td><td>64.98</td><td>64.36</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	4.75	60.98	61.62	60.78	4.50	61.41	62.06	61.78	4.00	62.30	63.05	62.11	3.50	63.11	64.00	62.89	3.00	64.54	64.98	64.36	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																													
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																											
4.75	60.98	61.62	60.78																																																											
4.50	61.41	62.06	61.78																																																											
4.00	62.30	63.05	62.11																																																											
3.50	63.11	64.00	62.89																																																											
3.00	64.54	64.98	64.36																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
Intermittent operation occurs when the output voltage is from 3V to 0V.																																																														

Model	SNDHS250B05																																								
Item	Overvoltage Protection	Testing Circuitry Figure A																																							
Object	+5V50A																																								
1.Graph		2.Values																																							
<div><div><div>—△—</div><div>Input Volt. 200V</div></div><div><div>---□---</div><div>Input Volt. 400V</div></div></div> <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Operating Point [V]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>-40</td><td>6.81</td><td>6.81</td></tr><tr><td>-20</td><td>6.82</td><td>6.82</td></tr><tr><td>0</td><td>6.83</td><td>6.83</td></tr><tr><td>25</td><td>6.84</td><td>6.84</td></tr><tr><td>40</td><td>6.84</td><td>6.84</td></tr><tr><td>55</td><td>6.84</td><td>6.84</td></tr><tr><td>70</td><td>6.84</td><td>6.84</td></tr><tr><td>85</td><td>6.84</td><td>6.84</td></tr><tr><td>95</td><td>6.84</td><td>6.84</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Operating Point [V]		Input Volt. 200[V]	Input Volt. 400[V]	-40	6.81	6.81	-20	6.82	6.82	0	6.83	6.83	25	6.84	6.84	40	6.84	6.84	55	6.84	6.84	70	6.84	6.84	85	6.84	6.84	95	6.84	6.84	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 200[V]	Input Volt. 400[V]																																							
-40	6.81	6.81																																							
-20	6.82	6.82																																							
0	6.83	6.83																																							
25	6.84	6.84																																							
40	6.84	6.84																																							
55	6.84	6.84																																							
70	6.84	6.84																																							
85	6.84	6.84																																							
95	6.84	6.84																																							
--	-	-																																							
--	-	-																																							




Figure A




Figure B (Ripple and Ripple noise Characteristic)