

TEST DATA OF SNDHS50B03

Regulated DC Power Supply
June 30, 2011

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager


Prepared by : Tadashi Arai
Tadashi Arai Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)

Model		SNDHS50B03																																																																																
Item		Input Current (by Input Voltage)																																																																																
Object																																																																																		
1.Graph		<div><div><div><div>—△—</div><div>Load 100%</div></div><div><div>---□---</div><div>Load 50%</div></div><div><div>---○---</div><div>Load 0%</div></div></div><p>Note: Slanted line shows the range of the rated input voltage.</p></div>																																																																																
2.Values		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Load 0%</th><th>Load 50%</th><th>Load 100%</th></tr><tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>150</td><td>0.002</td><td>0.002</td><td>0.002</td></tr><tr><td>170</td><td>0.003</td><td>0.003</td><td>0.003</td></tr><tr><td>180</td><td>0.024</td><td>0.127</td><td>0.240</td></tr><tr><td>200</td><td>0.023</td><td>0.114</td><td>0.215</td></tr><tr><td>250</td><td>0.019</td><td>0.092</td><td>0.174</td></tr><tr><td>280</td><td>0.016</td><td>0.084</td><td>0.157</td></tr><tr><td>300</td><td>0.014</td><td>0.080</td><td>0.148</td></tr><tr><td>350</td><td>0.012</td><td>0.072</td><td>0.130</td></tr><tr><td>400</td><td>0.011</td><td>0.066</td><td>0.117</td></tr><tr><td>420</td><td>0.011</td><td>0.064</td><td>0.113</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.000	0.000	0.000	150	0.002	0.002	0.002	170	0.003	0.003	0.003	180	0.024	0.127	0.240	200	0.023	0.114	0.215	250	0.019	0.092	0.174	280	0.016	0.084	0.157	300	0.014	0.080	0.148	350	0.012	0.072	0.130	400	0.011	0.066	0.117	420	0.011	0.064	0.113	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0	0.000	0.000	0.000																																																																															
50	0.000	0.000	0.000																																																																															
100	0.000	0.000	0.000																																																																															
150	0.002	0.002	0.002																																																																															
170	0.003	0.003	0.003																																																																															
180	0.024	0.127	0.240																																																																															
200	0.023	0.114	0.215																																																																															
250	0.019	0.092	0.174																																																																															
280	0.016	0.084	0.157																																																																															
300	0.014	0.080	0.148																																																																															
350	0.012	0.072	0.130																																																																															
400	0.011	0.066	0.117																																																																															
420	0.011	0.064	0.113																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

COSEL

Model	SNDHS50B03																																																					
Item	Input Current (by Load Current)	Temperature	25°C																																																			
		Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>200V</div></div><div><div>---□---</div><div>Input Volt.</div><div>280V</div></div><div><div>---○---</div><div>Input Volt.</div><div>400V</div></div></div> <p>Input Current [A]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>0.0</td><td>0.023</td><td>0.015</td><td>0.011</td></tr><tr><td>1.5</td><td>0.048</td><td>0.036</td><td>0.030</td></tr><tr><td>3.0</td><td>0.076</td><td>0.057</td><td>0.047</td></tr><tr><td>4.5</td><td>0.105</td><td>0.078</td><td>0.062</td></tr><tr><td>6.0</td><td>0.134</td><td>0.099</td><td>0.077</td></tr><tr><td>7.5</td><td>0.164</td><td>0.121</td><td>0.092</td></tr><tr><td>9.0</td><td>0.195</td><td>0.143</td><td>0.107</td></tr><tr><td>10.0</td><td>0.216</td><td>0.157</td><td>0.117</td></tr><tr><td>11.0</td><td>0.236</td><td>0.172</td><td>0.128</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	0.023	0.015	0.011	1.5	0.048	0.036	0.030	3.0	0.076	0.057	0.047	4.5	0.105	0.078	0.062	6.0	0.134	0.099	0.077	7.5	0.164	0.121	0.092	9.0	0.195	0.143	0.107	10.0	0.216	0.157	0.117	11.0	0.236	0.172	0.128	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0.0	0.023	0.015	0.011																																																			
1.5	0.048	0.036	0.030																																																			
3.0	0.076	0.057	0.047																																																			
4.5	0.105	0.078	0.062																																																			
6.0	0.134	0.099	0.077																																																			
7.5	0.164	0.121	0.092																																																			
9.0	0.195	0.143	0.107																																																			
10.0	0.216	0.157	0.117																																																			
11.0	0.236	0.172	0.128																																																			
--	-	-	-																																																			
--	-	-	-																																																			

-

2

-

BC-10579

Model		SNDHS50B03		Temperature		25°C																																																																																																				
Item		Input Power (by Load Current)		Testing Circuitry		Figure A																																																																																																				
Object																																																																																																										
1.Graph				2.Values																																																																																																						
<div><div><div><div><div></div><div>△</div></div><div>—</div><div>Input Volt.</div><div>200V</div></div><div><div><div></div><div>□</div></div><div>- - -</div><div>Input Volt.</div><div>280V</div></div><div><div><div></div><div>○</div></div><div>- · - · -</div><div>Input Volt.</div><div>400V</div></div></div><div><table><thead><tr><th>Load Current [A]</th><th>Input Power [W] (200V)</th><th>Input Power [W] (280V)</th><th>Input Power [W] (400V)</th></tr></thead><tbody><tr><td>0.0</td><td>4.60</td><td>4.30</td><td>4.40</td></tr><tr><td>1.5</td><td>9.60</td><td>10.20</td><td>12.10</td></tr><tr><td>3.0</td><td>15.30</td><td>15.90</td><td>18.70</td></tr><tr><td>4.5</td><td>21.00</td><td>21.70</td><td>24.70</td></tr><tr><td>6.0</td><td>26.90</td><td>27.80</td><td>30.70</td></tr><tr><td>7.5</td><td>32.90</td><td>33.80</td><td>36.70</td></tr><tr><td>9.0</td><td>39.00</td><td>40.00</td><td>42.80</td></tr><tr><td>10.0</td><td>43.10</td><td>44.10</td><td>47.00</td></tr><tr><td>11.0</td><td>47.30</td><td>48.30</td><td>51.10</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table></div></div> <div><div>Note: Slanted line shows the range of the rated load current.</div></div>				Load Current [A]	Input Power [W] (200V)	Input Power [W] (280V)	Input Power [W] (400V)	0.0	4.60	4.30	4.40	1.5	9.60	10.20	12.10	3.0	15.30	15.90	18.70	4.5	21.00	21.70	24.70	6.0	26.90	27.80	30.70	7.5	32.90	33.80	36.70	9.0	39.00	40.00	42.80	10.0	43.10	44.10	47.00	11.0	47.30	48.30	51.10	--	-	-	-	--	-	-	-	<table><thead><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr></thead><tbody><tr><td>0.0</td><td>4.60</td><td>4.30</td><td>4.40</td></tr><tr><td>1.5</td><td>9.60</td><td>10.20</td><td>12.10</td></tr><tr><td>3.0</td><td>15.30</td><td>15.90</td><td>18.70</td></tr><tr><td>4.5</td><td>21.00</td><td>21.70</td><td>24.70</td></tr><tr><td>6.0</td><td>26.90</td><td>27.80</td><td>30.70</td></tr><tr><td>7.5</td><td>32.90</td><td>33.80</td><td>36.70</td></tr><tr><td>9.0</td><td>39.00</td><td>40.00</td><td>42.80</td></tr><tr><td>10.0</td><td>43.10</td><td>44.10</td><td>47.00</td></tr><tr><td>11.0</td><td>47.30</td><td>48.30</td><td>51.10</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>				Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	4.60	4.30	4.40	1.5	9.60	10.20	12.10	3.0	15.30	15.90	18.70	4.5	21.00	21.70	24.70	6.0	26.90	27.80	30.70	7.5	32.90	33.80	36.70	9.0	39.00	40.00	42.80	10.0	43.10	44.10	47.00	11.0	47.30	48.30	51.10	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W] (200V)	Input Power [W] (280V)	Input Power [W] (400V)																																																																																																							
0.0	4.60	4.30	4.40																																																																																																							
1.5	9.60	10.20	12.10																																																																																																							
3.0	15.30	15.90	18.70																																																																																																							
4.5	21.00	21.70	24.70																																																																																																							
6.0	26.90	27.80	30.70																																																																																																							
7.5	32.90	33.80	36.70																																																																																																							
9.0	39.00	40.00	42.80																																																																																																							
10.0	43.10	44.10	47.00																																																																																																							
11.0	47.30	48.30	51.10																																																																																																							
--	-	-	-																																																																																																							
--	-	-	-																																																																																																							
Load Current [A]	Input Power [W]																																																																																																									
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																																																																							
0.0	4.60	4.30	4.40																																																																																																							
1.5	9.60	10.20	12.10																																																																																																							
3.0	15.30	15.90	18.70																																																																																																							
4.5	21.00	21.70	24.70																																																																																																							
6.0	26.90	27.80	30.70																																																																																																							
7.5	32.90	33.80	36.70																																																																																																							
9.0	39.00	40.00	42.80																																																																																																							
10.0	43.10	44.10	47.00																																																																																																							
11.0	47.30	48.30	51.10																																																																																																							
--	-	-	-																																																																																																							
--	-	-	-																																																																																																							

COSEL

Model		SNDHS50B03																																	
Item		Efficiency (by Input Voltage)																																	
Object																																			
1.Graph		2.Values																																	
<div><div><div><div></div><div></div><div></div></div><div>Load 50%</div></div><div><div><div></div><div></div><div></div></div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Efficiency [%]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>195</td><td>73.7</td><td>77.8</td></tr><tr><td>200</td><td>73.7</td><td>77.8</td></tr><tr><td>240</td><td>73.0</td><td>77.4</td></tr><tr><td>280</td><td>71.5</td><td>76.2</td></tr><tr><td>320</td><td>68.9</td><td>74.7</td></tr><tr><td>360</td><td>66.2</td><td>73.2</td></tr><tr><td>400</td><td>63.7</td><td>71.5</td></tr><tr><td>420</td><td>62.3</td><td>70.7</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	195	73.7	77.8	200	73.7	77.8	240	73.0	77.4	280	71.5	76.2	320	68.9	74.7	360	66.2	73.2	400	63.7	71.5	420	62.3	70.7	--	-	-		
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
195	73.7	77.8																																	
200	73.7	77.8																																	
240	73.0	77.4																																	
280	71.5	76.2																																	
320	68.9	74.7																																	
360	66.2	73.2																																	
400	63.7	71.5																																	
420	62.3	70.7																																	
--	-	-																																	

COSEL

Model		SNDHS50B03		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object																																																								
1.Graph		<div><div>—△—</div>Input Volt. 200V</div> <div><div>- - □ - -</div>Input Volt. 280V</div> <div><div>- · - ○ - · -</div>Input Volt. 400V</div> <p>Efficiency [%]</p> <p>Load Current [A]</p>		2.Values																																																				
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>1.5</td><td>53.5</td><td>50.4</td><td>42.5</td></tr><tr><td>3.0</td><td>66.5</td><td>64.0</td><td>54.4</td></tr><tr><td>4.5</td><td>72.4</td><td>70.1</td><td>61.6</td></tr><tr><td>6.0</td><td>75.2</td><td>72.7</td><td>65.9</td></tr><tr><td>7.5</td><td>76.7</td><td>74.6</td><td>68.7</td></tr><tr><td>9.0</td><td>77.5</td><td>75.5</td><td>70.6</td></tr><tr><td>10.0</td><td>77.8</td><td>76.0</td><td>71.4</td></tr><tr><td>11.0</td><td>77.9</td><td>76.3</td><td>72.1</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Efficiency [%]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	-	-	-	1.5	53.5	50.4	42.5	3.0	66.5	64.0	54.4	4.5	72.4	70.1	61.6	6.0	75.2	72.7	65.9	7.5	76.7	74.6	68.7	9.0	77.5	75.5	70.6	10.0	77.8	76.0	71.4	11.0	77.9	76.3	72.1	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.0	-	-	-																																																					
1.5	53.5	50.4	42.5																																																					
3.0	66.5	64.0	54.4																																																					
4.5	72.4	70.1	61.6																																																					
6.0	75.2	72.7	65.9																																																					
7.5	76.7	74.6	68.7																																																					
9.0	77.5	75.5	70.6																																																					
10.0	77.8	76.0	71.4																																																					
11.0	77.9	76.3	72.1																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								

- 5 -

BC-10579

COSEL

Model	SNDHS50B03																																
Item	Line Regulation	Temperature	25°C																														
Object	+3.3V10A	Testing Circuitry	Figure A																														
1.Graph		2.Values																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Output Voltage [V] Load 50%</th><th>Output Voltage [V] Load 100%</th></tr></thead><tbody><tr><td>195</td><td>3.364</td><td>3.350</td></tr><tr><td>200</td><td>3.364</td><td>3.350</td></tr><tr><td>240</td><td>3.364</td><td>3.350</td></tr><tr><td>280</td><td>3.364</td><td>3.351</td></tr><tr><td>320</td><td>3.365</td><td>3.351</td></tr><tr><td>360</td><td>3.365</td><td>3.351</td></tr><tr><td>400</td><td>3.365</td><td>3.351</td></tr><tr><td>420</td><td>3.365</td><td>3.351</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%	195	3.364	3.350	200	3.364	3.350	240	3.364	3.350	280	3.364	3.351	320	3.365	3.351	360	3.365	3.351	400	3.365	3.351	420	3.365	3.351	--	-	-		
Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%																															
195	3.364	3.350																															
200	3.364	3.350																															
240	3.364	3.350																															
280	3.364	3.351																															
320	3.365	3.351																															
360	3.365	3.351																															
400	3.365	3.351																															
420	3.365	3.351																															
--	-	-																															

COSEL

Model	SNDHS50B03																																																					
Item	Load Regulation	Temperature	25°C																																																			
		Testing Circuitry	Figure A																																																			
Object	+3.3V10A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>200V</div></div><div><div>---□---</div><div>Input Volt.</div><div>280V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>400V</div></div></div> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>0.0</td><td>3.380</td><td>3.380</td><td>3.380</td></tr><tr><td>1.5</td><td>3.374</td><td>3.375</td><td>3.375</td></tr><tr><td>3.0</td><td>3.370</td><td>3.370</td><td>3.371</td></tr><tr><td>4.5</td><td>3.366</td><td>3.366</td><td>3.367</td></tr><tr><td>6.0</td><td>3.362</td><td>3.362</td><td>3.362</td></tr><tr><td>7.5</td><td>3.358</td><td>3.358</td><td>3.358</td></tr><tr><td>9.0</td><td>3.353</td><td>3.354</td><td>3.354</td></tr><tr><td>10.0</td><td>3.350</td><td>3.351</td><td>3.351</td></tr><tr><td>11.0</td><td>3.348</td><td>3.348</td><td>3.348</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	3.380	3.380	3.380	1.5	3.374	3.375	3.375	3.0	3.370	3.370	3.371	4.5	3.366	3.366	3.367	6.0	3.362	3.362	3.362	7.5	3.358	3.358	3.358	9.0	3.353	3.354	3.354	10.0	3.350	3.351	3.351	11.0	3.348	3.348	3.348	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0.0	3.380	3.380	3.380																																																			
1.5	3.374	3.375	3.375																																																			
3.0	3.370	3.370	3.371																																																			
4.5	3.366	3.366	3.367																																																			
6.0	3.362	3.362	3.362																																																			
7.5	3.358	3.358	3.358																																																			
9.0	3.353	3.354	3.354																																																			
10.0	3.350	3.351	3.351																																																			
11.0	3.348	3.348	3.348																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL


Model	SNDHS50B03	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+3.3V10A	

Input Volt. 280 V
Cycle 1000 ms


Load Current 10A/50 μ s

Min. Load (0A) \longleftrightarrow
Load 100% (10A)

0.5 V/div




1ms/div



20ms/div

Min. Load (0A) \longleftrightarrow
Load 50% (5A)

0.5 V/div




1ms/div




20ms/div

Load 10% (1A) \longleftrightarrow
Load 100% (10A)

0.5 V/div



1ms/div



20ms/div

Model		SNDHS50B03		Temperature Testing Circuitry	25°C Figure B																																						
Item		Ripple Voltage (by Load Current)																																									
Object		+3.3V10A																																									
1.Graph				2.Values																																							
<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>Input Volt. 200V</div><div>Input Volt. 400V</div></div></div><p>Ripple Voltage [mV]</p><p>Load Current [A]</p></div>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 200 [V]</th><th>Input Volt. 400 [V]</th></tr><tr><td>0.0</td><td>5</td><td>5</td></tr><tr><td>1.5</td><td>10</td><td>10</td></tr><tr><td>3.0</td><td>10</td><td>10</td></tr><tr><td>4.5</td><td>10</td><td>10</td></tr><tr><td>6.0</td><td>10</td><td>10</td></tr><tr><td>7.5</td><td>10</td><td>10</td></tr><tr><td>9.0</td><td>10</td><td>10</td></tr><tr><td>10.0</td><td>10</td><td>10</td></tr><tr><td>11.0</td><td>10</td><td>15</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.0	5	5	1.5	10	10	3.0	10	10	4.5	10	10	6.0	10	10	7.5	10	10	9.0	10	10	10.0	10	10	11.0	10	15	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																										
	Input Volt. 200 [V]	Input Volt. 400 [V]																																									
0.0	5	5																																									
1.5	10	10																																									
3.0	10	10																																									
4.5	10	10																																									
6.0	10	10																																									
7.5	10	10																																									
9.0	10	10																																									
10.0	10	10																																									
11.0	10	15																																									
--	-	-																																									
--	-	-																																									
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																											
<div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><p>Ripple [mVp-p]</p><p>Fig.Complex Ripple Wave Form</p></div>																																											

- 9 -

BC-10579


Model	SNDHS50B03																																								
Item	Ripple-Noise	Temperature	25°C																																						
Object	+3.3V10A	Testing Circuitry	Figure B																																						
1.Graph		2.Values																																							
<div><div><div>—△—</div><div>Input Volt. 200V</div></div><div><div>- -○- -</div><div>Input Volt. 400V</div></div></div> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple-Noise [mV]</th></tr><tr><th>Input Volt. 200 [V]</th><th>Input Volt. 400 [V]</th></tr><tr><td>0.0</td><td>10</td><td>15</td></tr><tr><td>1.5</td><td>20</td><td>25</td></tr><tr><td>3.0</td><td>20</td><td>25</td></tr><tr><td>4.5</td><td>15</td><td>25</td></tr><tr><td>6.0</td><td>20</td><td>30</td></tr><tr><td>7.5</td><td>20</td><td>30</td></tr><tr><td>9.0</td><td>25</td><td>30</td></tr><tr><td>10.0</td><td>25</td><td>30</td></tr><tr><td>11.0</td><td>25</td><td>30</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.0	10	15	1.5	20	25	3.0	20	25	4.5	15	25	6.0	20	30	7.5	20	30	9.0	25	30	10.0	25	30	11.0	25	30	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 200 [V]	Input Volt. 400 [V]																																							
0.0	10	15																																							
1.5	20	25																																							
3.0	20	25																																							
4.5	15	25																																							
6.0	20	30																																							
7.5	20	30																																							
9.0	25	30																																							
10.0	25	30																																							
11.0	25	30																																							
--	-	-																																							
--	-	-																																							
<p>Fig.Complex Ripple Noise Wave Form</p>																																									

- 10 -

BC-10579

Testing Circuitry Figure B

2.Values



Note: Slanted line shows the range of the rated ambient temperature.

Model	SNDHS50B03																																																					
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																				
Object	+3.3V10A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt. 200V</div></div><div><div>---□---</div><div>Input Volt. 280V</div></div><div><div>-·-○-·-</div><div>Input Volt. 400V</div></div></div> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>-40</td><td>3.353</td><td>3.353</td><td>3.353</td></tr><tr><td>-20</td><td>3.351</td><td>3.351</td><td>3.351</td></tr><tr><td>0</td><td>3.349</td><td>3.349</td><td>3.349</td></tr><tr><td>25</td><td>3.350</td><td>3.350</td><td>3.350</td></tr><tr><td>40</td><td>3.351</td><td>3.351</td><td>3.352</td></tr><tr><td>55</td><td>3.352</td><td>3.352</td><td>3.352</td></tr><tr><td>70</td><td>3.352</td><td>3.352</td><td>3.352</td></tr><tr><td>85</td><td>3.351</td><td>3.351</td><td>3.351</td></tr><tr><td>95</td><td>3.350</td><td>3.350</td><td>3.350</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	-40	3.353	3.353	3.353	-20	3.351	3.351	3.351	0	3.349	3.349	3.349	25	3.350	3.350	3.350	40	3.351	3.351	3.352	55	3.352	3.352	3.352	70	3.352	3.352	3.352	85	3.351	3.351	3.351	95	3.350	3.350	3.350	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
-40	3.353	3.353	3.353																																																			
-20	3.351	3.351	3.351																																																			
0	3.349	3.349	3.349																																																			
25	3.350	3.350	3.350																																																			
40	3.351	3.351	3.352																																																			
55	3.352	3.352	3.352																																																			
70	3.352	3.352	3.352																																																			
85	3.351	3.351	3.351																																																			
95	3.350	3.350	3.350																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated ambient temperature.																																																						

- 12 -

BC-10579



		Testing Circuitry Figure A
Model	SNDHS50B03	
Item	Output Voltage Accuracy	
Object	+3.3V10A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 200 - 400V

Load Current : 0 - 10A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	95	400	0	3.387	±19	±0.6
Minimum Voltage	0	200	10	3.349		

COSEL

Model	SNDHS50B03																								
Item	Time Lapse Drift	Temperature	25°C																						
		Testing Circuitry	Figure A																						
Object	+3.3V10A																								
1.Graph		2.Values																							
<div><p>Output Voltage [V]</p><p>Time [H]</p><p>Input Volt. 280V</p><p>Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>3.353</td></tr><tr><td>0.5</td><td>3.353</td></tr><tr><td>1.0</td><td>3.353</td></tr><tr><td>2.0</td><td>3.353</td></tr><tr><td>3.0</td><td>3.353</td></tr><tr><td>4.0</td><td>3.353</td></tr><tr><td>5.0</td><td>3.353</td></tr><tr><td>6.0</td><td>3.353</td></tr><tr><td>7.0</td><td>3.353</td></tr><tr><td>8.0</td><td>3.353</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	3.353	0.5	3.353	1.0	3.353	2.0	3.353	3.0	3.353	4.0	3.353	5.0	3.353	6.0	3.353	7.0	3.353	8.0	3.353
Time since start [H]	Output Voltage [V]																								
0.0	3.353																								
0.5	3.353																								
1.0	3.353																								
2.0	3.353																								
3.0	3.353																								
4.0	3.353																								
5.0	3.353																								
6.0	3.353																								
7.0	3.353																								
8.0	3.353																								


Model	SNDHS50B03	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+3.3V10A		

1. Graph



2. Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	18.0	3.5	21.5	3.3	14.1
100 %	18.0	4.0	22.0	1.7	7.5




Model	SNDHS50B03																																								
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																							
Object	+3.3V10A																																								
1.Graph		2.Values																																							
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>-40</td><td>153</td><td>160</td></tr><tr><td>-20</td><td>154</td><td>161</td></tr><tr><td>0</td><td>154</td><td>162</td></tr><tr><td>25</td><td>155</td><td>164</td></tr><tr><td>40</td><td>155</td><td>164</td></tr><tr><td>55</td><td>155</td><td>165</td></tr><tr><td>70</td><td>155</td><td>165</td></tr><tr><td>85</td><td>154</td><td>165</td></tr><tr><td>95</td><td>153</td><td>164</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	153	160	-20	154	161	0	154	162	25	155	164	40	155	164	55	155	165	70	155	165	85	154	165	95	153	164	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-40	153	160																																							
-20	154	161																																							
0	154	162																																							
25	155	164																																							
40	155	164																																							
55	155	165																																							
70	155	165																																							
85	154	165																																							
95	153	164																																							
--	-	-																																							
--	-	-																																							

COSEL

Model	SNDHS50B03																																																													
Item	Overcurrent Protection	Temperature	25°C																																																											
		Testing Circuitry	Figure A																																																											
Object	+3.3V10A																																																													
1.Graph		2.Values																																																												
<div><div><div></div><div>Input Volt. 200V</div></div><div><div></div><div>Input Volt. 280V</div></div><div><div></div><div>Input Volt. 400V</div></div></div> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 2.31V to 0V.</p>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 280[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>3.14</td><td>11.76</td><td>12.25</td><td>12.96</td></tr><tr><td>2.97</td><td>11.81</td><td>12.38</td><td>12.99</td></tr><tr><td>2.64</td><td>12.06</td><td>12.65</td><td>13.17</td></tr><tr><td>2.31</td><td>12.29</td><td>13.00</td><td>13.33</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	3.14	11.76	12.25	12.96	2.97	11.81	12.38	12.99	2.64	12.06	12.65	13.17	2.31	12.29	13.00	13.33	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																													
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																											
3.14	11.76	12.25	12.96																																																											
2.97	11.81	12.38	12.99																																																											
2.64	12.06	12.65	13.17																																																											
2.31	12.29	13.00	13.33																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											

- 17 -

BC-10579

Model	SNDHS50B03																																								
Item	Overvoltage Protection	Testing Circuitry Figure A																																							
Object	+3.3V10A																																								
1.Graph		2.Values																																							
<div><div>—△— Input Volt. 200V</div><div>---□--- Input Volt. 400V</div><p>Operating Point [V]</p><p>Ambient Temperature [°C]</p><p>Load 0%</p></div>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Operating Point [V]</th></tr><tr><th>Input Volt. 200[V]</th><th>Input Volt. 400[V]</th></tr><tr><td>-40</td><td>4.96</td><td>4.96</td></tr><tr><td>-20</td><td>4.96</td><td>4.84</td></tr><tr><td>0</td><td>4.84</td><td>4.84</td></tr><tr><td>25</td><td>4.72</td><td>4.72</td></tr><tr><td>40</td><td>4.66</td><td>4.66</td></tr><tr><td>55</td><td>4.55</td><td>4.55</td></tr><tr><td>70</td><td>4.55</td><td>4.55</td></tr><tr><td>85</td><td>4.43</td><td>4.43</td></tr><tr><td>95</td><td>4.43</td><td>4.43</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Operating Point [V]		Input Volt. 200[V]	Input Volt. 400[V]	-40	4.96	4.96	-20	4.96	4.84	0	4.84	4.84	25	4.72	4.72	40	4.66	4.66	55	4.55	4.55	70	4.55	4.55	85	4.43	4.43	95	4.43	4.43	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 200[V]	Input Volt. 400[V]																																							
-40	4.96	4.96																																							
-20	4.96	4.84																																							
0	4.84	4.84																																							
25	4.72	4.72																																							
40	4.66	4.66																																							
55	4.55	4.55																																							
70	4.55	4.55																																							
85	4.43	4.43																																							
95	4.43	4.43																																							
--	-	-																																							
--	-	-																																							
Note: Slanted line shows the range of the rated ambient temperature.																																									

- 18 -

BC-10579




Figure A




Figure B (Ripple and Ripple noise Characteristic)