



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|-------------|
| Model | SUCW1R52415 |
|-------|-------------|

| No. | P a r t s | | Q'ty of Device | Failure rate [10 ⁻⁶ /H] | R e f e r e n c e |
|--|------------------------|------------|----------------|------------------------------------|-------------------|
| 1 | I C | Monolithic | 1 | 0.0240 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | Transistors | | 3 | 0.1012 | |
| 4 | Diodes | | 10 | 0.1740 | |
| 5 | LED•Optocouplers | | 1 | 0.0700 | |
| 6 | Resistors | | 24 | 0.0048 | |
| 7 | Capacitors | | 11 | 0.0814 | |
| 8 | Transformer•Choke Coil | | 4 | 0.0920 | |
| 9 | Connectors | | 93 | 0.0127 | |
| 10 | Others | | 2 | 0.1300 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 0.6901 | |

| | | |
|---------------------|-----|-----------|
| M T B F | [H] | 1,450,000 |
| Ambient Temperature | [℃] | — |
| Load Factor | [%] | — |