



TEST DATA OF SUS34805

Regulated DC Power Supply
Mar 7, 2005

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Hayato Nakatsubo
Hayato Nakatsubo Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Figure of Testing Circuitry	18

(Final Page 18)


COSEL

Model		SUS34805																																																																																
Item		Input Current (by Input Voltage)																																																																																
Object																																																																																		
1.Graph		2.Values																																																																																
<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>—△—</div><div>Load 100%</div></div><div><div>---□---</div><div>Load 50%</div></div><div><div>---○---</div><div>Load 0%</div></div></div><div><div><div><div>0.200</div><div>0.150</div><div>0.100</div><div>0.050</div><div>0.000</div></div><div><div>0</div><div>20</div><div>40</div><div>60</div><div>80</div></div></div><div><div>Input Current [A]</div><div>Input Voltage [V]</div></div></div><div><div>Note: Slanted line shows the range of the rated input voltage.</div></div></div>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Load 0%</th><th>Load 50%</th><th>Load 100%</th></tr><tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>19.2</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>21.6</td><td>0.007</td><td>0.092</td><td>0.175</td></tr><tr><td>24.0</td><td>0.007</td><td>0.082</td><td>0.165</td></tr><tr><td>33.0</td><td>0.006</td><td>0.060</td><td>0.117</td></tr><tr><td>36.0</td><td>0.006</td><td>0.055</td><td>0.107</td></tr><tr><td>40.0</td><td>0.006</td><td>0.050</td><td>0.096</td></tr><tr><td>48.0</td><td>0.006</td><td>0.042</td><td>0.080</td></tr><tr><td>60.0</td><td>0.006</td><td>0.035</td><td>0.064</td></tr><tr><td>70.0</td><td>0.006</td><td>0.031</td><td>0.056</td></tr><tr><td>76.0</td><td>0.007</td><td>0.029</td><td>0.052</td></tr><tr><td>80.0</td><td>0.007</td><td>0.028</td><td>0.050</td></tr><tr><td>84.8</td><td>0.008</td><td>0.027</td><td>0.048</td></tr><tr><td>88.0</td><td>0.008</td><td>0.027</td><td>0.046</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	19.2	0.000	0.000	0.000	21.6	0.007	0.092	0.175	24.0	0.007	0.082	0.165	33.0	0.006	0.060	0.117	36.0	0.006	0.055	0.107	40.0	0.006	0.050	0.096	48.0	0.006	0.042	0.080	60.0	0.006	0.035	0.064	70.0	0.006	0.031	0.056	76.0	0.007	0.029	0.052	80.0	0.007	0.028	0.050	84.8	0.008	0.027	0.048	88.0	0.008	0.027	0.046	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
8.0	0.000	0.000	0.000																																																																															
16.0	0.000	0.000	0.000																																																																															
19.2	0.000	0.000	0.000																																																																															
21.6	0.007	0.092	0.175																																																																															
24.0	0.007	0.082	0.165																																																																															
33.0	0.006	0.060	0.117																																																																															
36.0	0.006	0.055	0.107																																																																															
40.0	0.006	0.050	0.096																																																																															
48.0	0.006	0.042	0.080																																																																															
60.0	0.006	0.035	0.064																																																																															
70.0	0.006	0.031	0.056																																																																															
76.0	0.007	0.029	0.052																																																																															
80.0	0.007	0.028	0.050																																																																															
84.8	0.008	0.027	0.048																																																																															
88.0	0.008	0.027	0.046																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

1

BC-3760

COSEL



COSEL

Model		SUS34805																																																				
Item		Input Power (by Load Current)																																																				
Object																																																						
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>---□---</div><div>---○---</div></div><div><div>Input Volt.</div><div>Input Volt.</div><div>Input Volt.</div></div><div><div>36V</div><div>48V</div><div>76V</div></div></div> <div><p>Note: Slanted line shows the range of the rated load current.</p></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>0.00</td><td>0.22</td><td>0.27</td><td>0.52</td></tr><tr><td>0.12</td><td>0.92</td><td>0.97</td><td>1.20</td></tr><tr><td>0.24</td><td>1.63</td><td>1.67</td><td>1.89</td></tr><tr><td>0.36</td><td>2.35</td><td>2.38</td><td>2.58</td></tr><tr><td>0.48</td><td>3.09</td><td>3.11</td><td>3.28</td></tr><tr><td>0.60</td><td>3.85</td><td>3.84</td><td>3.99</td></tr><tr><td>0.66</td><td>4.24</td><td>4.21</td><td>4.35</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.22	0.27	0.52	0.12	0.92	0.97	1.20	0.24	1.63	1.67	1.89	0.36	2.35	2.38	2.58	0.48	3.09	3.11	3.28	0.60	3.85	3.84	3.99	0.66	4.24	4.21	4.35	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	0.22	0.27	0.52																																																			
0.12	0.92	0.97	1.20																																																			
0.24	1.63	1.67	1.89																																																			
0.36	2.35	2.38	2.58																																																			
0.48	3.09	3.11	3.28																																																			
0.60	3.85	3.84	3.99																																																			
0.66	4.24	4.21	4.35																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL


Model SUS34805

Item Efficiency (by Input Voltage)

Object

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
30	76.7	78.0
36	76.2	78.7
40	75.7	78.9
48	74.7	78.9
55	73.5	78.6
60	72.4	78.2
70	69.7	76.9
76	68.0	76.1
80	66.8	75.4

COSEL

Model		SUS34805																																																				
Item		Efficiency (by Load Current)																																																				
Object																																																						
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>---□---</div><div>---○---</div></div><div><div>Input Volt.</div><div>Input Volt.</div><div>Input Volt.</div></div><div><div>36V</div><div>48V</div><div>76V</div></div></div> <div><div><div>86</div><div>78</div><div>70</div><div>62</div><div>54</div><div>46</div><div>38</div><div>30</div></div><div><div>0.0</div><div>0.2</div><div>0.4</div><div>0.6</div></div><div><div>Efficiency [%]</div><div>Load Current [A]</div></div></div> <div><div>Note: Slanted line shows the range of the rated load current.</div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.12</td><td>66.2</td><td>62.6</td><td>50.6</td></tr><tr><td>0.24</td><td>74.4</td><td>72.5</td><td>64.3</td></tr><tr><td>0.36</td><td>77.3</td><td>76.2</td><td>70.6</td></tr><tr><td>0.48</td><td>78.4</td><td>78.1</td><td>74.0</td></tr><tr><td>0.60</td><td>78.7</td><td>78.9</td><td>76.0</td></tr><tr><td>0.66</td><td>78.7</td><td>79.2</td><td>76.7</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	0.12	66.2	62.6	50.6	0.24	74.4	72.5	64.3	0.36	77.3	76.2	70.6	0.48	78.4	78.1	74.0	0.60	78.7	78.9	76.0	0.66	78.7	79.2	76.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	-	-	-																																																			
0.12	66.2	62.6	50.6																																																			
0.24	74.4	72.5	64.3																																																			
0.36	77.3	76.2	70.6																																																			
0.48	78.4	78.1	74.0																																																			
0.60	78.7	78.9	76.0																																																			
0.66	78.7	79.2	76.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

-

5

-

BC-3760

COSEL


Model SUS34805

Item Line Regulation

Object +5V0.6A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
30	5.051	5.049
36	5.051	5.049
40	5.051	5.049
48	5.051	5.049
55	5.051	5.049
60	5.051	5.049
70	5.051	5.049
76	5.051	5.049
80	5.051	5.049

COSEL

Model SUS34805


Item Load Regulation

Object +5V0.6A

Temperature 25°C
Testing Circuitry Figure A

1. Graph

—△— Input Volt. 36V
 ---□--- Input Volt. 48V
 ---○--- Input Volt. 76V



Note: Slanted line shows the range of the rated load current.


2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.00	5.053	5.053	5.053
0.12	5.052	5.052	5.052
0.24	5.051	5.051	5.051
0.36	5.050	5.050	5.050
0.48	5.050	5.050	5.050
0.60	5.049	5.049	5.049
0.66	5.049	5.049	5.049
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL


Model	SUS34805	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+5V0.6A		

Input Volt. 48 V
Cycle 100 mS



Min. Load (0A) \longleftrightarrow
Load 100% (0.6A)

100mV/div




200µs/div




200µs/div

Min. Load (0A) \longleftrightarrow
Load 50% (0.3A)

100mV/div




200µs/div




200µs/div

Load 50% (0.3A) \longleftrightarrow
Load 100% (0.6A)

100mV/div



200µs/div



200µs/div

COSEL

Model	SUS34805	Temperature 25°C Testing Circuitry Figure B																																							
Item	Ripple Voltage (by Load Current)																																								
Object	+5V0.6A																																								
1.Graph		2.Values																																							
<div><div><div>—△— Input Volt. 36V - - -○- - - Input Volt. 76V</div><div>Ripple Voltage [mV]</div><div>Load Current [A]</div></div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 36 [V]</th><th>Input Volt. 76 [V]</th></tr><tr><td>0.00</td><td>2</td><td>2</td></tr><tr><td>0.12</td><td>3</td><td>2</td></tr><tr><td>0.24</td><td>4</td><td>3</td></tr><tr><td>0.36</td><td>6</td><td>3</td></tr><tr><td>0.48</td><td>10</td><td>4</td></tr><tr><td>0.60</td><td>13</td><td>5</td></tr><tr><td>0.66</td><td>15</td><td>5</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	2	2	0.12	3	2	0.24	4	3	0.36	6	3	0.48	10	4	0.60	13	5	0.66	15	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 36 [V]	Input Volt. 76 [V]																																							
0.00	2	2																																							
0.12	3	2																																							
0.24	4	3																																							
0.36	6	3																																							
0.48	10	4																																							
0.60	13	5																																							
0.66	15	5																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<div>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</div>																																									
<div><div>Ripple [mVp-p]</div><div>Fig.Complex Ripple Wave Form</div></div>																																									

- 9 -


BC-3760

COSEL

Model		SUS34805	
Item		Ripple-Noise	
Object		+5V0.6A	
1.Graph		2.Values	

</

COSEL

Model		SUS34805																																																				
Item		Ambient Temperature Drift																																																				
Object		+5V0.6A																																																				
1.Graph		<div><div><div><div>—△—</div><div>Input Volt.</div><div>36V</div></div><div><div>---□---</div><div>Input Volt.</div><div>48V</div></div><div><div>---○---</div><div>Input Volt.</div><div>76V</div></div></div><p>Output Voltage [V]</p><p>Ambient Temperature [°C]</p><p>Load 100%</p><p>Note: Slanted line shows the range of the rated ambient temperature.</p></div>																																																				
2.Values		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>-60</td><td>5.017</td><td>5.018</td><td>5.019</td></tr><tr><td>-40</td><td>5.028</td><td>5.029</td><td>5.029</td></tr><tr><td>-20</td><td>5.037</td><td>5.038</td><td>5.038</td></tr><tr><td>0</td><td>5.044</td><td>5.044</td><td>5.044</td></tr><tr><td>25</td><td>5.049</td><td>5.049</td><td>5.049</td></tr><tr><td>55</td><td>5.051</td><td>5.051</td><td>5.051</td></tr><tr><td>60</td><td>5.050</td><td>5.050</td><td>5.050</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-60	5.017	5.018	5.019	-40	5.028	5.029	5.029	-20	5.037	5.038	5.038	0	5.044	5.044	5.044	25	5.049	5.049	5.049	55	5.051	5.051	5.051	60	5.050	5.050	5.050	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
-60	5.017	5.018	5.019																																																			
-40	5.028	5.029	5.029																																																			
-20	5.037	5.038	5.038																																																			
0	5.044	5.044	5.044																																																			
25	5.049	5.049	5.049																																																			
55	5.051	5.051	5.051																																																			
60	5.050	5.050	5.050																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

- 12 -

BC-3760

COSEL

		Testing Circuitry Figure A
Model	SUS34805	
Item	Output Voltage Accuracy	
Object	+5V0.6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current : 0 - 0.6A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	55	76	0	5.055	±14	±0.3
Minimum Voltage	-40	36	0.6	5.028		

COSEL


Model	SUS34805																								
Item	Time Lapse Drift	Temperature	25°C																						
Object	+5V0.6A	Testing Circuitry	Figure A																						
1.Graph		2.Values																							
<div><p>Output Voltage [V]</p><p>Time [H]</p><p>Input Volt. 48V</p><p>Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>5.048</td></tr><tr><td>0.5</td><td>5.049</td></tr><tr><td>1.0</td><td>5.049</td></tr><tr><td>2.0</td><td>5.049</td></tr><tr><td>3.0</td><td>5.049</td></tr><tr><td>4.0</td><td>5.049</td></tr><tr><td>5.0</td><td>5.049</td></tr><tr><td>6.0</td><td>5.049</td></tr><tr><td>7.0</td><td>5.049</td></tr><tr><td>8.0</td><td>5.049</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	5.048	0.5	5.049	1.0	5.049	2.0	5.049	3.0	5.049	4.0	5.049	5.0	5.049	6.0	5.049	7.0	5.049	8.0	5.049
Time since start [H]	Output Voltage [V]																								
0.0	5.048																								
0.5	5.049																								
1.0	5.049																								
2.0	5.049																								
3.0	5.049																								
4.0	5.049																								
5.0	5.049																								
6.0	5.049																								
7.0	5.049																								
8.0	5.049																								

COSEL

Model	SUS34805	Temperature 25°C Testing Circuitry Figure A
Item	Rise and Fall Time	
Object	+5V0.6A	

1.Graph


Input Volt. 48 V



2.Values

[mS]

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	0.1	0.8	0.9	0.1	0.6
100 %	0.1	0.9	1.0	0.1	0.3



COSEL

Model		SUS34805
Item		Minimum Input Voltage for Regulated Output Voltage
Object		+5V0.6A

1.Graph

□

Load 50%

—

△

—

Load 100%

Input Voltage [V]

32

24

16

8

0

-60

-20

20

60

Ambient Temperature [°C]

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	17.2	21.5
-40	16.8	21.7
-20	16.4	22.0
0	15.9	22.3
25	15.7	22.8
55	15.9	23.4
60	15.9	23.5
—	-	-
—	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

- 16 -

BC-3760

COSEL

Model	SUS34805																																																									
Item	Overcurrent Protection	Temperature	25°C																																																							
Object	+5V0.6A	Testing Circuitry	Figure A																																																							
1.Graph		2.Values																																																								
<div><div><div></div>Input Volt. 36V</div><div><div></div>Input Volt. 48V</div><div><div></div>Input Volt. 76V</div></div> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>5.00</td><td>0.60</td><td>0.60</td><td>0.60</td></tr><tr><td>4.75</td><td>0.92</td><td>0.98</td><td>0.96</td></tr><tr><td>4.50</td><td>0.95</td><td>1.00</td><td>0.98</td></tr><tr><td>4.00</td><td>1.02</td><td>1.06</td><td>1.02</td></tr><tr><td>3.50</td><td>1.08</td><td>1.12</td><td>1.05</td></tr><tr><td>3.00</td><td>1.16</td><td>1.18</td><td>1.09</td></tr><tr><td>2.50</td><td>1.24</td><td>1.23</td><td>1.11</td></tr><tr><td>2.00</td><td>1.32</td><td>1.28</td><td>1.13</td></tr><tr><td>1.50</td><td>1.39</td><td>1.32</td><td>1.13</td></tr><tr><td>1.00</td><td>1.45</td><td>1.31</td><td>1.09</td></tr><tr><td>0.50</td><td>1.44</td><td>1.22</td><td>1.00</td></tr><tr><td>0.00</td><td>1.89</td><td>1.36</td><td>1.05</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	5.00	0.60	0.60	0.60	4.75	0.92	0.98	0.96	4.50	0.95	1.00	0.98	4.00	1.02	1.06	1.02	3.50	1.08	1.12	1.05	3.00	1.16	1.18	1.09	2.50	1.24	1.23	1.11	2.00	1.32	1.28	1.13	1.50	1.39	1.32	1.13	1.00	1.45	1.31	1.09	0.50	1.44	1.22	1.00	0.00	1.89	1.36	1.05
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																							
5.00	0.60	0.60	0.60																																																							
4.75	0.92	0.98	0.96																																																							
4.50	0.95	1.00	0.98																																																							
4.00	1.02	1.06	1.02																																																							
3.50	1.08	1.12	1.05																																																							
3.00	1.16	1.18	1.09																																																							
2.50	1.24	1.23	1.11																																																							
2.00	1.32	1.28	1.13																																																							
1.50	1.39	1.32	1.13																																																							
1.00	1.45	1.31	1.09																																																							
0.50	1.44	1.22	1.00																																																							
0.00	1.89	1.36	1.05																																																							




Figure A




Figure B (Ripple and Ripple noise Characteristic)