



# M T B F

(E I A J R C R - 9 1 0 2)

|       |           |
|-------|-----------|
| Model | SUS6243R3 |
|-------|-----------|

| No.                                      | P a r t s              |            | Q' ty of Device | Failure rate [10 <sup>-6</sup> /H] | R e f e r e n c e |
|--|------------------------|------------|-----------------|------------------------------------|-------------------|
| 1  | I C                    | Monolithic | 1               | 0.0240                             |                   |
| 2  |                        | Hybrid     | 0               | 0.0000                             |                   |
| 3  | Transistors            |            | 10              | 0.1089                             |                   |
| 4  | Diodes                 |            | 13              | 0.1925                             |                   |
| 5  | LED•Optocouplers       |            | 1               | 0.0700                             |                   |
| 6  | Resistors              |            | 56              | 0.0112                             |                   |
| 7  | Capacitors             |            | 14              | 0.1036                             |                   |
| 8  | Transformer•Choke Coil |            | 3               | 0.0690                             |                   |
| 9  | Connectors             |            | 230             | 0.0316                             |                   |
| 10                                       | Others                 |            | 2               | 0.1300                             |                   |
| Total Failure Rate [10 <sup>-6</sup> /H] |                        |            |                 | 0.7408                             |                   |

|                     |      |           |
|---------------------|------|-----------|
| M T B F             | [H]  | 1,350,000 |
| Ambient Temperature | [°C] | —         |
| Load Factor         | [%]  | —         |