

TEST DATA OF TAC-300-□□□

Noise Filter

March. 19. 2009

Approved by : Toshio Watanabe
Toshio Watanabe Design Manager

Prepared by : Yuichi Uozu
Yuichi Uozu Design Engineer

COSEL CO.,LTD.





CONTENTS

1. Attenuation Characteristics	1
2. Leakage Current	3
3. Figure of Testing Circuitry	4
(Final Page 4)	


COSEL

Model	TAC-300-□□□	Temperature	25°C
Item	Attenuation Characteristics	Testing Circuitry	Figure A
Object			



COSEL

Model	TAC-300-□□□	Temperature	25°C
Item	Attenuation Characteristics	Testing Circuitry	Figure A
Object	_____		





Model		TAC-300-□□□	Temperature 25°C Testing Circuitry Figure B
Item		Leakage Current	
Object		_____	

1.Results

[mA]

Model	Standards	Input Volt.					Note
		200 [V]	250 [V]	400 [V]	480 [V]	500 [V]	
TAC-300-103	UL1283	0.62	0.77	1.3	1.5	1.6	
TAC-300-223	UL1283	1.4	1.7	2.8	3.3	3.4	
TAC-300-333	UL1283	2.1	2.6	4.1	4.9	5.2	

2.Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.




Figure A - 1 Differential mode attenuation measurement




Figure A - 2 Common mode attenuation measurement




Figure B Leakage current measurement (UL1283)