



M T B F

(MIL-HDBK217F NOTICE 2)

Model	UMA120F-48-Y
-------	--------------

No.	P a r t s		Q' ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	M o n o l i t h i c	3	4.2900	
2		H y b r i d	0	0.0000	
3	T r a n s i s t o r s		8	7.6520	
4	D i o d e s		19	0.7580	
5	LED•Optocouplers		2	0.5830	
6	R e s i s t o r s		80	0.3090	
7	C a p a c i t o r s		43	3.0780	
8	Transformer•Choke Coil		9	0.4630	
9	C o n n e c t o r s		247	0.0130	
1 0	O t h e r s		5	0.0350	
Total Failure Rate [10 ⁻⁶ /H]				17.1810	

M T B F	[H]	58,200
Ambient Temperature	[°C]	40.0
Load Factor	[%]	100



M T B F

(E I A J R C R - 9 1 0 2)

Model	UMA120F-48-Y
-------	--------------

No.	P a r t s		Q'ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	M o n o l i t h i c	3	0.1220	
2		H y b r i d	0	0.0000	
3	T r a n s i s t o r s		8	0.4983	
4	D i o d e s		19	0.3230	
5	LED・Optocouplers		2	0.1400	
6	R e s i s t o r s		80	0.4356	
7	C a p a c i t o r s		43	0.4339	
8	Transformer・Choke Coil		9	0.1242	
9	C o n n e c t o r s		247	0.0594	
10	O t h e r s		5	0.1850	
Total Failure Rate [10 ⁻⁶ /H]				2.3214	

M T B F	[H]	431,000
Ambient Temperature	[°C]	—
Load Factor	[%]	—

* BD-9376