



M T B F

(MIL-HDBK217F NOTICE 2)

Model	UMA60F-36
-------	-----------

No.	P a r t s		Q' ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	M o n o l i t h i c	2	3.5060	
2		H y b r i d	0	0.0000	
3	T r a n s i s t o r s		3	1.8230	
4	D i o d e s		9	0.3580	
5	LED•Optocouplers		2	0.7800	
6	R e s i s t o r s		40	0.2430	
7	C a p a c i t o r s		25	3.2580	
8	Transformer•Choke Coil		6	0.3850	
9	C o n n e c t o r s		231	0.0110	
1 0	O t h e r s		5	0.0400	
Total Failure Rate [10 ⁻⁶ /H]				10.4040	

M T B F	[H]	96,100
Ambient Temperature	[°C]	50.0
Load Factor	[%]	100



M T B F

(E I A J R C R - 9 1 0 2)

Model	UMA60F-36
-------	-----------

No.	P a r t s		Q' ty of Device	Failure rate [10 ⁻⁶ /H]	Re f e r e n c e
1	I C	Monolithic	2	0.0980	
2		Hybrid	0	0.0000	
3	Transistors		3	0.1012	
4	Diodes		9	0.2272	
5	LED•Optocouplers		2	0.1400	
6	Resistors		40	0.3278	
7	Capacitors		25	0.2772	
8	Transformer•Choke Coil		6	0.1173	
9	Connectors		231	0.0598	
10	Others		5	0.1850	
Total Failure Rate [10 ⁻⁶ /H]				1.5335	

M T B F	[H]	652,000
Ambient Temperature	[°C]	—
Load Factor	[%]	—