



M T B F

(MIL-HDBK217F NOTICE 2)

Model	UMCS60F-48-E
-------	--------------

No.	P a r t s		Q' ty of Device	Failure rate [10 ⁻⁶ /H]	Reference
1	I C	Monolithic	2	1.0270	
2		Hybrid	0	0.0000	
3	Transistors		3	1.2570	
4	Diodes		9	0.5870	
5	LED•Optocouplers		2	0.4770	
6	Resistors		40	0.2460	
7	Capacitors		25	1.7830	
8	Transformer•Choke Coil		6	0.3030	
9	Connectors		240	0.0220	
10	Others		6	0.0380	
Total Failure Rate [10 ⁻⁶ /H]				5.7400	

M T B F	[H]	174,200
Ambient Temperature	[°C]	40.0
Load Factor	[%]	100



M T B F

(E I A J R C R - 9 1 0 2)

Model	UMCS60F-48-E
-------	--------------

No.	P a r t s		Q' ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	M o n o l i t h i c	2	0.0980	
2		H y b r i d	0	0.0000	
3	T r a n s i s t o r s		3	0.1012	
4	D i o d e s		9	0.2272	
5	LED•Optocouplers		2	0.1400	
6	R e s i s t o r s		40	0.3278	
7	C a p a c i t o r s		25	0.2772	
8	Transformer•Choke Coil		6	0.1173	
9	C o n n e c t o r s		240	0.1014	
1 0	O t h e r s		6	0.1880	
Total Failure Rate [10 ⁻⁶ /H]				1.5781	

M T B F	[H]	634,000
Ambient Temperature	[°C]	—
Load Factor	[%]	—