



M T B F

(MIL-HDBK217F NOTICE 2)

Model	WBA150B-24
-------	------------

No.	P a r t s		Q'ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	Monolithic	2	1.4270	
2		Hybrid	0	0.0000	
3	T r a n s i s t o r s		2	1.5420	
4	D i o d e s		9	0.2640	
5	LED•Optocouplers		3	0.6340	
6	R e s i s t o r s		68	0.3440	
7	C a p a c i t o r s		30	3.6890	
8	Transformer•Choke Coil		3	0.3920	
9	C o n n e c t o r s		345	0.4760	
10	O t h e r s		2	0.0130	
Total Failure Rate [10 ⁻⁶ /H]				8.7810	

M T B F	[H]	113,900
Ambient Temperature	[°C]	50.0
Load Factor	[%]	100



M T B F

(E I A J R C R - 9 1 0 2)

Model	WBA150B-24
-------	------------

No.	P a r t s		Q' ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	Monolithic	2	0.0980	
2		Hybrid	0	0.0000	
3	T r a n s i s t o r s		2	0.1001	
4	D i o d e s		9	0.2795	
5	LED•Optocouplers		3	0.1412	
6	R e s i s t o r s		68	0.7530	
7	C a p a c i t o r s		30	0.4055	
8	Transformer•Choke Coil		3	0.0690	
9	C o n n e c t o r s		345	0.2477	
10	O t h e r s		2	0.0230	
Total Failure Rate [10 ⁻⁶ /H]				2.1170	

M T B F	[H]	472,000
Ambient Temperature	[°C]	—
Load Factor	[%]	—