



M T B F

(MIL-HDBK217F NOTICE 2)

Model	WBA35B-48
-------	-----------

No.	P a r t s		Q'ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	Monolithic	2	1.4270	
2		Hybrid	0	0.0000	
3	T r a n s i s t o r s		2	1.2330	
4	D i o d e s		13	0.8160	
5	LED•Optocouplers		2	0.4540	
6	R e s i s t o r s		41	0.3020	
7	C a p a c i t o r s		21	3.0740	
8	Transformer•Choke Coil		3	0.4370	
9	C o n n e c t o r s		207	0.3200	
10	O t h e r s		2	0.0100	
Total Failure Rate [10 ⁻⁶ /H]				8.0730	

M T B F	[H]	123,900
Ambient Temperature	[°C]	50.0
Load Factor	[%]	100



M T B F

(E I A J R C R - 9 1 0 2)

Model	WBA35B-48
-------	-----------

No.	P a r t s		Q'ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	Monolithic	2	0.0980	
2		Hybrid	0	0.0000	
3	T r a n s i s t o r s		2	0.1980	
4	D i o d e s		13	0.3140	
5	LED•Optocouplers		2	0.0712	
6	R e s i s t o r s		41	0.4278	
7	C a p a c i t o r s		21	0.2250	
8	Transformer•Choke Coil		3	0.0690	
9	C o n n e c t o r s		207	0.0772	
10	O t h e r s		2	0.0230	
Total Failure Rate [10 ⁻⁶ /H]				1.5032	

M T B F	[H]	665,000
Ambient Temperature	[°C]	—
Load Factor	[%]	—