



DATA SHEET		Date	16-Jul-21
Model	WBA75B-12	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	R.Takahashi




Frequency	Line	Level		Limit		Margin		Pass/Fail	Remark
MHz		dB(μV)		dB(μV)		dB			
		QP	AV	QP	AV	QP	AV		
0.15	L1	61.9	43.9	66	56	4.1	12.1	Pass	
0.815	L1	42	34.4	56	46	14	11.6	Pass	
0.15	N	61.5	45.5	66	56	4.5	10.5	Pass	




Frequency MHz	Polarization	Stability	Level	Limit	Margin	Pass/Fail	Height cm	Angle deg	Remark
			dB(μV/m)	dB(μV/m)	dB				
146.005	V	Stable	26.1	40	13.9	Pass	100.2	243.9	

DATA SHEET		Date	16-Jul-21
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	R.Takahashi

1. Line conduction



2. Radiated emission




Conditions

Test : EMI
Model Name: WBA75B

○Photographs of Test Set-Up

1. LINE CONDUCTION



2. RADIATED EMISSION

