



M T B F

(MIL-HDBK217F NOTICE 2)

Model	WMA75F-24
-------	-----------

No.	P a r t s		Q'ty of Device	Failure rate [10 ⁻⁶ /H]	Reference
1	I C	M o n o l i t h i c	2	1.4270	
2		H y b r i d	0	0.0000	
3	T r a n s i s t o r s		3	1.7770	
4	D i o d e s		12	0.2930	
5	LED•Optocouplers		2	0.3210	
6	R e s i s t o r s		47	0.2600	
7	C a p a c i t o r s		24	3.9330	
8	Transformer•Choke Coil		4	0.5110	
9	C o n n e c t o r s		225	0.3210	
1 0	O t h e r s		3	0.0200	
Total Failure Rate [10 ⁻⁶ /H]				8.8630	

M T B F	[H]	112,800
Ambient Temperature	[°C]	50.0
Load Factor	[%]	100



M T B F

(E I A J R C R - 9 1 0 2)

Model	WMA75F-24
-------	-----------

No.	P a r t s		Q' ty of Device	Failure rate [10 ⁻⁶ /H]	Re f e r e n c e
1	I C	M o n o l i t h i c	2	0.0980	
2		H y b r i d	0	0.0000	
3	T r a n s i s t o r s		3	0.1991	
4	D i o d e s		12	0.2735	
5	LED•Optocouplers		2	0.0712	
6	R e s i s t o r s		47	0.4290	
7	C a p a c i t o r s		24	0.2698	
8	Transformer•Choke Coil		4	0.0713	
9	C o n n e c t o r s		225	0.0816	
1 0	O t h e r s		3	0.0430	
Total Failure Rate [10 ⁻⁶ /H]				1.5365	

M T B F	[H]	651,000
Ambient Temperature	[°C]	—
Load Factor	[%]	—