



# M T B F

(MIL-HDBK217F NOTICE 2)

Model	WMA75F-48
-------	-----------

No.	P a r t s		Q'ty of Device	Failure rate [10 <sup>-6</sup> /H]	Reference
1	I C	M o n o l i t h i c	2	1.4270	
2		H y b r i d	0	0.0000	
3	T r a n s i s t o r s		3	1.8530	
4	D i o d e s		14	0.8690	
5	LED•Optocouplers		2	0.3210	
6	R e s i s t o r s		48	0.3210	
7	C a p a c i t o r s		23	3.5490	
8	Transformer•Choke Coil		4	0.4860	
9	C o n n e c t o r s		129	0.3150	
1 0	O t h e r s		3	0.0200	
Total Failure Rate [10 <sup>-6</sup> /H]				9.1610	

M T B F	[H]	109,200
Ambient Temperature	[°C]	50.0
Load Factor	[%]	100



# M T B F

(E I A J R C R - 9 1 0 2)

Model	WMA75F-48
-------	-----------

No.	P a r t s		Q'ty of Device	Failure rate [10 <sup>-6</sup> /H]	Reference
1	I C	M o n o l i t h i c	2	0.0980	
2		H y b r i d	0	0.0000	
3	T r a n s i s t o r s		3	0.1991	
4	D i o d e s		14	0.3215	
5	LED•Optocouplers		2	0.0712	
6	R e s i s t o r s		48	0.4292	
7	C a p a c i t o r s		23	0.2398	
8	Transformer•Choke Coil		4	0.0713	
9	C o n n e c t o r s		129	0.0676	
1 0	O t h e r s		3	0.0430	
Total Failure Rate [10 <sup>-6</sup> /H]				1.5407	

M T B F	[H]	649,000
Ambient Temperature	[°C]	—
Load Factor	[%]	—