



# TEST DATA OF ZTW1R50512

(5.0V INPUT)

Regulated DC Power Supply

Date : Mar. 5. 1998

Approved by : N. Shiraiishi  
Design Manager

Prepared by : T. Tsuru  
Design Engineer

**コーセル株式会社**  
**COSEL CO., LTD.**

CONTENTS

1. Line Regulation . . . . .	1
静的入力変動	
2. Efficiency . . . . .	2
効率	
3. Load Regulation . . . . .	3
静的負荷変動	
4. Ripple Voltage (by Load Current) . . . . .	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise . . . . .	6
リップルノイズ	
6. Overcurrent Protection . . . . .	8
過電流保護	
7. Dynamic Load Responce . . . . .	9
動的負荷変動	
8. Rise and Fall Time . . . . .	11
立上り、立下がり時間	
9. Ambient Temperature Drift . . . . .	13
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage . . .	14
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature) . . . . .	15
リップル電圧(周囲温度特性)	
12. Time Lapse Drift . . . . .	16
経時ドリフト	
13. Output Voltage Accuracy . . . . .	17
定電圧精度	
14. Condensation . . . . .	18
結露特性	
15. Figure of Testing Circuitry . . . . .	20
測定回路図	

(Final Page 20 )

**COSEL**

Model		ZTW1R50512																																								
Item		Line Regulation  静的入力変動																																								
Object		+12V0.065A																																								
1. Graph		-----□----- Load 50% -----△----- Load 100%																																								
<p>[V]</p> <p>Output Voltage</p> <p>Input Voltage</p>		2. Values																																								
		<table><tr><th>Input Voltage [V]</th><th>Load 50% Output Volt. [V]</th><th>Load 100% Output Volt. [V]</th></tr><tr><td>4.0</td><td>12.130</td><td>11.998</td></tr><tr><td>4.5</td><td>12.120</td><td>12.000</td></tr><tr><td>5.0</td><td>12.113</td><td>12.001</td></tr><tr><td>6.0</td><td>12.103</td><td>12.001</td></tr><tr><td>7.0</td><td>12.096</td><td>12.000</td></tr><tr><td>8.0</td><td>12.092</td><td>11.998</td></tr><tr><td>9.0</td><td>12.088</td><td>11.998</td></tr><tr><td>9.5</td><td>12.086</td><td>11.998</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	4.0	12.130	11.998	4.5	12.120	12.000	5.0	12.113	12.001	6.0	12.103	12.001	7.0	12.096	12.000	8.0	12.092	11.998	9.0	12.088	11.998	9.5	12.086	11.998	—	—	—	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]																																								
4.0	12.130	11.998																																								
4.5	12.120	12.000																																								
5.0	12.113	12.001																																								
6.0	12.103	12.001																																								
7.0	12.096	12.000																																								
8.0	12.092	11.998																																								
9.0	12.088	11.998																																								
9.5	12.086	11.998																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
Object		-12V0.065A																																								
1. Graph		-----□----- Load 50% -----△----- Load 100%																																								
<p>[V]</p> <p>Output Voltage</p> <p>Input Voltage</p>		2. Values																																								
		<table><tr><th>Input Voltage [V]</th><th>Load 50% Output Volt. [V]</th><th>Load 100% Output Volt. [V]</th></tr><tr><td>4.0</td><td>-12.115</td><td>-11.983</td></tr><tr><td>4.5</td><td>-12.106</td><td>-11.985</td></tr><tr><td>5.0</td><td>-12.099</td><td>-11.986</td></tr><tr><td>6.0</td><td>-12.090</td><td>-11.986</td></tr><tr><td>7.0</td><td>-12.083</td><td>-11.985</td></tr><tr><td>8.0</td><td>-12.079</td><td>-11.985</td></tr><tr><td>9.0</td><td>-12.076</td><td>-11.984</td></tr><tr><td>9.5</td><td>-12.074</td><td>-11.984</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	4.0	-12.115	-11.983	4.5	-12.106	-11.985	5.0	-12.099	-11.986	6.0	-12.090	-11.986	7.0	-12.083	-11.985	8.0	-12.079	-11.985	9.0	-12.076	-11.984	9.5	-12.074	-11.984	—	—	—	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]																																								
4.0	-12.115	-11.983																																								
4.5	-12.106	-11.985																																								
5.0	-12.099	-11.986																																								
6.0	-12.090	-11.986																																								
7.0	-12.083	-11.985																																								
8.0	-12.079	-11.985																																								
9.0	-12.076	-11.984																																								
9.5	-12.074	-11.984																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
Note: Slanted line shows the range of the rated input voltage. (注)斜線は定格入力電圧範囲を示す。																																										

**COSEL**


Model ZTW1R50512

Item Efficiency 効率

Object

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph




Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。


## 2. Values

Input Voltage [V]	Load 50%	Load 100%
	Efficiency [%]	Efficiency [%]
4.0	59.2	64.8
4.5	58.5	65.6
5.0	57.0	65.7
6.0	54.2	65.2
7.0	50.9	63.1
8.0	47.9	61.3
9.0	45.0	58.6
9.5	43.3	57.5
—	—	—
—	—	—
—	—	—
—	—	—


# COSEL




# COSEL



# COSEL




# COSEL







# COSEL



**COSEL**

Model ZTW1R50512		Temperature 25°C																																																								
Item Overcurrent Protection 過電流保護		Testing Circuitry Figure A																																																								
Object +12V0.065A																																																										
1. Graph [V] 		2. Values <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th><th>Input Volt. 4.5[V]</th><th>Input Volt. 5.0[V]</th><th>Input Volt. 9.0[V]</th></tr> <tr> <th>Load Current [A]</th><th>Load Current [A]</th><th>Load Current [A]</th></tr> </thead> <tbody> <tr><td>12.00</td><td>0.073</td><td>0.056</td><td>0.052</td></tr> <tr><td>11.40</td><td>0.129</td><td>0.132</td><td>0.120</td></tr> <tr><td>10.80</td><td>0.135</td><td>0.139</td><td>0.124</td></tr> <tr><td>9.60</td><td>0.150</td><td>0.151</td><td>0.132</td></tr> <tr><td>8.40</td><td>0.165</td><td>0.165</td><td>0.140</td></tr> <tr><td>7.20</td><td>0.178</td><td>0.177</td><td>0.147</td></tr> <tr><td>6.00</td><td>0.194</td><td>0.190</td><td>0.153</td></tr> <tr><td>4.80</td><td>0.207</td><td>0.200</td><td>0.157</td></tr> <tr><td>3.60</td><td>0.219</td><td>0.208</td><td>0.161</td></tr> <tr><td>2.40</td><td>0.230</td><td>0.215</td><td>0.165</td></tr> <tr><td>1.20</td><td>0.244</td><td>0.225</td><td>0.175</td></tr> <tr><td>0.00</td><td>0.295</td><td>0.274</td><td>0.175</td></tr> </tbody> </table>		Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	Load Current [A]	Load Current [A]	Load Current [A]	12.00	0.073	0.056	0.052	11.40	0.129	0.132	0.120	10.80	0.135	0.139	0.124	9.60	0.150	0.151	0.132	8.40	0.165	0.165	0.140	7.20	0.178	0.177	0.147	6.00	0.194	0.190	0.153	4.80	0.207	0.200	0.157	3.60	0.219	0.208	0.161	2.40	0.230	0.215	0.165	1.20	0.244	0.225	0.175	0.00	0.295	0.274	0.175
Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																																							
	Load Current [A]	Load Current [A]	Load Current [A]																																																							
12.00	0.073	0.056	0.052																																																							
11.40	0.129	0.132	0.120																																																							
10.80	0.135	0.139	0.124																																																							
9.60	0.150	0.151	0.132																																																							
8.40	0.165	0.165	0.140																																																							
7.20	0.178	0.177	0.147																																																							
6.00	0.194	0.190	0.153																																																							
4.80	0.207	0.200	0.157																																																							
3.60	0.219	0.208	0.161																																																							
2.40	0.230	0.215	0.165																																																							
1.20	0.244	0.225	0.175																																																							
0.00	0.295	0.274	0.175																																																							
Object -12V0.065A																																																										
1. Graph [V] 		2. Values <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th><th>Input Volt. 4.5[V]</th><th>Input Volt. 5.0[V]</th><th>Input Volt. 9.0[V]</th></tr> <tr> <th>Load Current [A]</th><th>Load Current [A]</th><th>Load Current [A]</th></tr> </thead> <tbody> <tr><td>-12.00</td><td>0.081</td><td>0.084</td><td>0.091</td></tr> <tr><td>-11.40</td><td>0.132</td><td>0.135</td><td>0.123</td></tr> <tr><td>-10.80</td><td>0.138</td><td>0.141</td><td>0.127</td></tr> <tr><td>-9.60</td><td>0.152</td><td>0.154</td><td>0.135</td></tr> <tr><td>-8.40</td><td>0.167</td><td>0.168</td><td>0.144</td></tr> <tr><td>-7.20</td><td>0.183</td><td>0.181</td><td>0.151</td></tr> <tr><td>-6.00</td><td>0.197</td><td>0.194</td><td>0.158</td></tr> <tr><td>-4.80</td><td>0.212</td><td>0.205</td><td>0.162</td></tr> <tr><td>-3.60</td><td>0.225</td><td>0.214</td><td>0.166</td></tr> <tr><td>-2.40</td><td>0.237</td><td>0.222</td><td>0.170</td></tr> <tr><td>-1.20</td><td>0.253</td><td>0.233</td><td>0.182</td></tr> <tr><td>0.00</td><td>0.300</td><td>0.277</td><td>0.193</td></tr> </tbody> </table>		Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	Load Current [A]	Load Current [A]	Load Current [A]	-12.00	0.081	0.084	0.091	-11.40	0.132	0.135	0.123	-10.80	0.138	0.141	0.127	-9.60	0.152	0.154	0.135	-8.40	0.167	0.168	0.144	-7.20	0.183	0.181	0.151	-6.00	0.197	0.194	0.158	-4.80	0.212	0.205	0.162	-3.60	0.225	0.214	0.166	-2.40	0.237	0.222	0.170	-1.20	0.253	0.233	0.182	0.00	0.300	0.277	0.193
Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																																							
	Load Current [A]	Load Current [A]	Load Current [A]																																																							
-12.00	0.081	0.084	0.091																																																							
-11.40	0.132	0.135	0.123																																																							
-10.80	0.138	0.141	0.127																																																							
-9.60	0.152	0.154	0.135																																																							
-8.40	0.167	0.168	0.144																																																							
-7.20	0.183	0.181	0.151																																																							
-6.00	0.197	0.194	0.158																																																							
-4.80	0.212	0.205	0.162																																																							
-3.60	0.225	0.214	0.166																																																							
-2.40	0.237	0.222	0.170																																																							
-1.20	0.253	0.233	0.182																																																							
0.00	0.300	0.277	0.193																																																							
Note: Slanted line shows the range of the rated load current. (注) 斜線は定格負荷電流範囲を示す。																																																										

# COSEL

Model	ZTW1R50512	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Responce 動的負荷変動	
Object	+12V0.065A	



Input Volt. 5.0 V

Cycle 100 mS

Load Current



Min. Load ↔  
Load 100 %

200 mV/div





Min. Load ↔  
Load 50 %

200 mV/div



Load 50% ↔  
Load 100 %

200 mV/div



1 mS/div

# COSEL

Model	ZTW1R50512	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Responce 動的負荷変動	
Object	-12V0.065A	

Input Volt. 5.0 V



Cycle 100 mS

Load Current

Min. Load ↔

Load 100 %



200 mV/div



Min. Load ↔

Load 50 %



200 mV/div



Load 50% ↔

Load 100 %

200 mV/div




1 mS/div

**COSEL**

Model	ZTW1R50512	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+12V0.065A		

## 1. Graph


Input Volt. 4.5 V



## 2. Values

[mS]

Load \ Time	T <sub>d</sub>	T <sub>r</sub>	T <sub>s</sub>	T <sub>h</sub>	T <sub>f</sub>
50 %	0.05	1.25	1.30	0.49	1.64
100 %	0.05	1.30	1.35	0.30	1.19




**COSEL**

Model	ZTW1R50512	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	-12V0.065A		

## 1. Graph


Input Volt. 4.5 V



## 2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.40	0.85	1.25	0.48	1.16
100 %	0.40	0.90	1.30	0.30	1.15



# COSEL

Model ZTW1R50512		Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	+12V0.065A																																																						
1. Graph		2. Values																																																					
<div> <div> <div>—△—</div> <div>Input Volt. 4.5V</div> </div> <div> <div>- -□- -</div> <div>Input Volt. 5.0V</div> </div> <div> <div>—○—</div> <div>Input Volt. 9.0V</div> </div> </div>		<table> <tr> <th>Temperature</th><th>Input Volt. 4.5[V]</th><th>Input Volt. 5.0[V]</th><th>Input Volt. 9.0[V]</th></tr> <tr> <th></th><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr> <tr><td>-30</td><td>12.005</td><td>12.006</td><td>12.001</td></tr> <tr><td>-20</td><td>12.004</td><td>12.005</td><td>12.000</td></tr> <tr><td>-10</td><td>12.004</td><td>12.005</td><td>12.000</td></tr> <tr><td>0</td><td>12.003</td><td>12.004</td><td>11.999</td></tr> <tr><td>10</td><td>12.004</td><td>12.004</td><td>11.999</td></tr> <tr><td>25</td><td>12.004</td><td>12.004</td><td>12.001</td></tr> <tr><td>30</td><td>12.004</td><td>12.005</td><td>12.001</td></tr> <tr><td>40</td><td>12.004</td><td>12.005</td><td>12.002</td></tr> <tr><td>55</td><td>12.003</td><td>12.004</td><td>12.003</td></tr> <tr><td>60</td><td>12.002</td><td>12.003</td><td>12.003</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </table>		Temperature	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]		Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	-30	12.005	12.006	12.001	-20	12.004	12.005	12.000	-10	12.004	12.005	12.000	0	12.003	12.004	11.999	10	12.004	12.004	11.999	25	12.004	12.004	12.001	30	12.004	12.005	12.001	40	12.004	12.005	12.002	55	12.003	12.004	12.003	60	12.002	12.003	12.003	—	—	—	—
Temperature	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																																				
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
-30	12.005	12.006	12.001																																																				
-20	12.004	12.005	12.000																																																				
-10	12.004	12.005	12.000																																																				
0	12.003	12.004	11.999																																																				
10	12.004	12.004	11.999																																																				
25	12.004	12.004	12.001																																																				
30	12.004	12.005	12.001																																																				
40	12.004	12.005	12.002																																																				
55	12.003	12.004	12.003																																																				
60	12.002	12.003	12.003																																																				
—	—	—	—																																																				
Object -12V0.065A																																																							
1. Graph		2. Values																																																					
<div> <div>—△—</div> <div>Input Volt. 4.5V</div> </div> <div> <div>- -□- -</div> <div>Input Volt. 5.0V</div> </div> <div> <div>—○—</div> <div>Input Volt. 9.0V</div> </div>		<table> <tr> <th>Temperature</th><th>Input Volt. 4.5[V]</th><th>Input Volt. 5.0[V]</th><th>Input Volt. 9.0[V]</th></tr> <tr> <th></th><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr> <tr><td>-30</td><td>-11.989</td><td>-11.990</td><td>-11.986</td></tr> <tr><td>-20</td><td>-11.989</td><td>-11.990</td><td>-11.986</td></tr> <tr><td>-10</td><td>-11.989</td><td>-11.989</td><td>-11.986</td></tr> <tr><td>0</td><td>-11.989</td><td>-11.989</td><td>-11.986</td></tr> <tr><td>10</td><td>-11.989</td><td>-11.989</td><td>-11.986</td></tr> <tr><td>25</td><td>-11.988</td><td>-11.989</td><td>-11.986</td></tr> <tr><td>30</td><td>-11.987</td><td>-11.988</td><td>-11.986</td></tr> <tr><td>40</td><td>-11.987</td><td>-11.988</td><td>-11.986</td></tr> <tr><td>55</td><td>-11.985</td><td>-11.986</td><td>-11.987</td></tr> <tr><td>60</td><td>-11.984</td><td>-11.985</td><td>-11.987</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </table>		Temperature	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]		Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	-30	-11.989	-11.990	-11.986	-20	-11.989	-11.990	-11.986	-10	-11.989	-11.989	-11.986	0	-11.989	-11.989	-11.986	10	-11.989	-11.989	-11.986	25	-11.988	-11.989	-11.986	30	-11.987	-11.988	-11.986	40	-11.987	-11.988	-11.986	55	-11.985	-11.986	-11.987	60	-11.984	-11.985	-11.987	—	—	—	—
Temperature	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																																				
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
-30	-11.989	-11.990	-11.986																																																				
-20	-11.989	-11.990	-11.986																																																				
-10	-11.989	-11.989	-11.986																																																				
0	-11.989	-11.989	-11.986																																																				
10	-11.989	-11.989	-11.986																																																				
25	-11.988	-11.989	-11.986																																																				
30	-11.987	-11.988	-11.986																																																				
40	-11.987	-11.988	-11.986																																																				
55	-11.985	-11.986	-11.987																																																				
60	-11.984	-11.985	-11.987																																																				
—	—	—	—																																																				
Note: Slanted line shows the range of the rated ambient temperature. (注) 斜線は定格周囲温度範囲を示す。																																																							

# COSEL

Model

ZTW1R50512

Item

Minimum Input Voltage for Regulated Output Voltage  
最低レギュレーション電圧


Object

+12V0.065A

Testing Circuitry Figure A

## 1. Graph

[V]




## 2. Values

Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-30	3.2	3.6
-20	3.1	3.6
-10	3.0	3.5
0	3.0	3.4
10	2.9	3.4
25	2.9	3.3
30	2.9	3.3
40	2.8	3.3
55	2.8	3.2
60	2.8	3.2
—	—	—

Object

-12V0.065A

[V]




## 2. Values

Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-30	3.2	3.6
-20	3.1	3.6
-10	3.0	3.5
0	3.0	3.4
10	2.9	3.4
25	2.9	3.3
30	2.9	3.3
40	2.8	3.3
55	2.8	3.2
60	2.8	3.2
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。



Testing Circuitry      Figure A

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-30	20	40
-20	20	35
-10	20	35
0	15	35
10	15	35
25	15	30
30	15	30
40	15	25
55	10	25
60	10	20
—	—	—

## 2. Values



(注)斜線は定格周囲温度範囲を示す。

**COSEL**

# COSEL

Model	ZTW1R50512
Item	Time Lapse Drift 経時ドリフト
Object	+12V0.065A
1. Graph	<div> <div> <div>Output Voltage</div> <div>[V]</div> <div> <div>12.08</div> <div>12.06</div> <div>12.04</div> <div>12.02</div> <div>12.00</div> <div>11.98</div> <div>11.96</div> <div>0</div> </div> <div> <div>0</div> <div>1</div> <div>2</div> <div>3</div> <div>4</div> <div>5</div> <div>6</div> <div>7</div> <div>8</div> <div>9</div> <div>10</div> </div> <div>Time</div> <div>[H]</div> </div> <div> <div>Input Volt. 5.0V</div> <div>Load 100%</div> </div> </div>

Temperature

25 ℃

Testing Circuitry

Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	12.015
0.5	12.007
1.0	12.007
2.0	12.007
3.0	12.007
4.0	12.007
5.0	12.007
6.0	12.007
7.0	12.007
8.0	12.007

Object	-12V0.065A
1. Graph	<div> <div> <div>Output Voltage</div> <div>[V]</div> <div> <div>-12.05</div> <div>-12.03</div> <div>-12.01</div> <div>-11.99</div> <div>-11.97</div> <div>-11.95</div> <div>-11.93</div> <div>0</div> </div> <div> <div>0</div> <div>1</div> <div>2</div> <div>3</div> <div>4</div> <div>5</div> <div>6</div> <div>7</div> <div>8</div> <div>9</div> <div>10</div> </div> <div>Time</div> <div>[H]</div> </div> <div> <div>Input Volt. 5.0V</div> <div>Load 100%</div> </div> </div>

2.Values

Time since start [H]	Output Voltage [V]
0.0	-11.985
0.5	-11.980
1.0	-11.980
2.0	-11.980
3.0	-11.980
4.0	-11.980
5.0	-11.980
6.0	-11.980
7.0	-11.980
8.0	-11.980



**COSEL**

Model		ZTW1R50512	Testing Circuitry      Figure A
Item		Condensation    結露特性	
Object		+12V0.065A	
1. Condensation test Testing procedure is as follows. ① Keeping and cooling the unit in a tank at -10℃ for an hour with the input off. ② Taking it out of the tank and dewing itself in a room where the temperature is 25℃ and the humidity is 40%RH. ③ Testing electrical characteristics of the unit to confirm there be no fault.			
1. 結露特性試験 入力 を 切 っ た 状 態 で、 恒 温 槽 で - 1 0 ℃ に 冷 却 し て お き、 約 1 時 間 後 に 恒 温 槽 か ら 取 り 出 し、 室 温 2 5 ℃、 湿 度 4 0 %RH の 状 態 に お き 結 露 さ せ、 そ の 電 気 的 特 性 の 測 定 を 行 い、 異 常 の な い こ と を 確 認 す る。			

2. Values		
Item	Data	Testing Conditions
Output Voltage [V]	12.307	Input Volt.: 5V, Load Current:0.065A
Line Regulation [mV]	9	Input Volt.: 4.5~9V, Load Current:0.065A
Load Regulation [mV]	295	Input Volt.: 5V, Load Current:0~0.065A

# COSEL

COSEL

		Testing Circuitry      Figure A
Model	ZTW1R50512	
Item	Condensation    結露特性	
Object	−12V0.065A	

1. Condensation test

Testing procedure is as follows.

① Keeping and cooling the unit in a tank at −10℃ for an hour with the input off.

② Taking it out of the tank and dewing itself in a room where the temperature is 25℃ and the humidity is 40%RH.

③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で−10℃に冷却しておき、約1時間後に恒温槽から取り出し、室温25℃、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values		
Item	Data	Testing Conditions
Output Voltage [V]	−12.258	Input Volt.: 5V, Load Current:0.065A
Line Regulation [mV]	4	Input Volt.: 4.5~9V, Load Current:0.065A
Load Regulation [mV]	271	Input Volt.: 5V, Load Current:0~0.065A

−19−

BC−3118


**COSEL**

Figure A