



TEST DATA OF ZUS34815

(48.0V INPUT)

Regulated DC Power Supply

Date : Nov. 5. 1996

Approved by : T. Sugimori
Design Manager

Prepared by : y. Nagai
Design Engineer

コーセル株式会社
COSEL CO., LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Load Regulation	3
静的負荷変動	
4. Ripple Voltage (by Load Current)	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise	5
リップルノイズ	
6. Overcurrent Protection	6
過電流保護	
7. Dynamic Load Responce	7
動的負荷変動	
8. Rise and Fall Time	8
立上り、立下がり時間	
9. Ambient Temperature Drift	9
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage	10
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature)	11
リップル電圧(周囲温度特性)	
12. Time Lapse Drift	12
経時ドリフト	
13. Output Voltage Accuracy	13
定電圧精度	
14. Condensation	14
結露特性	
15. Figure of Testing Circuitry	15
測定回路図	

(Final Page 15)

COSEL

Model		ZUS34815	Temperature Testing Circuitry	25℃ Figure A
Item		Line Regulation 静的入力変動		
Object		+15V0.2A		

1. Graph

-----□----- Load 50%

-----△----- Load 100%

Output Voltage [V]

15.49

15.39

15.29

15.19

15.09

14.99

14.89

0

0

40

50

60

70

80

Input Voltage [V]

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。


2. Values

Input Voltage [V]	Load 50%	Load 100%
	Output Volt. [V]	Output Volt. [V]
33.0	15.140	15.139
36.0	15.140	15.139
42.0	15.140	15.139
48.0	15.140	15.139
54.0	15.140	15.139
60.0	15.140	15.138
66.0	15.140	15.138
72.0	15.141	15.138
75.0	15.140	15.138
—	—	—
—	—	—
—	—	—

COSEL

Model	ZUS34815
Item	Efficiency 効率
Object	

Temperature 25℃
Testing Circuitry Figure A



2. Values

Input Voltage [V]	Load 50%	Load 100%
	Efficiency [%]	Efficiency [%]
33.0	74.0	76.8
36.0	72.8	77.6
42.0	70.2	77.3
48.0	67.9	76.4
54.0	65.3	74.9
60.0	63.3	73.4
66.0	61.3	72.0
72.0	59.3	70.6
75.0	58.3	69.9
—	—	—
—	—	—
—	—	—

COSEL


Model	ZUS34815	Temperature	25°C																																															
Item	Load Regulation 静的負荷変動	Testing Circuitry	Figure A																																															
Object	+15V0.2A																																																	
1. Graph		2. Values																																																
<div> <div> <div>△</div> <div>Input Volt. 36.0V</div> </div> <div> <div>□</div> <div>Input Volt. 48.0V</div> </div> <div> <div>○</div> <div>Input Volt. 72.0V</div> </div> </div> <div> <div>Output Voltage [V]</div> <div>Load Current [A]</div> </div>		<table> <tr> <th rowspan="2">Load Current [A]</th><th>Input Volt. 36.0[V]</th><th>Input Volt. 48.0[V]</th><th>Input Volt. 72.0[V]</th></tr> <tr> <th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr> <tr><td>0.00</td><td>15.141</td><td>15.142</td><td>15.146</td></tr> <tr><td>0.04</td><td>15.140</td><td>15.141</td><td>15.141</td></tr> <tr><td>0.08</td><td>15.140</td><td>15.140</td><td>15.140</td></tr> <tr><td>0.12</td><td>15.139</td><td>15.140</td><td>15.140</td></tr> <tr><td>0.16</td><td>15.139</td><td>15.139</td><td>15.139</td></tr> <tr><td>0.20</td><td>15.139</td><td>15.139</td><td>15.138</td></tr> <tr><td>0.22</td><td>15.138</td><td>15.139</td><td>15.138</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </table>		Load Current [A]	Input Volt. 36.0[V]	Input Volt. 48.0[V]	Input Volt. 72.0[V]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	0.00	15.141	15.142	15.146	0.04	15.140	15.141	15.141	0.08	15.140	15.140	15.140	0.12	15.139	15.140	15.140	0.16	15.139	15.139	15.139	0.20	15.139	15.139	15.138	0.22	15.138	15.139	15.138	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 36.0[V]	Input Volt. 48.0[V]	Input Volt. 72.0[V]																																															
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																															
0.00	15.141	15.142	15.146																																															
0.04	15.140	15.141	15.141																																															
0.08	15.140	15.140	15.140																																															
0.12	15.139	15.140	15.140																																															
0.16	15.139	15.139	15.139																																															
0.20	15.139	15.139	15.138																																															
0.22	15.138	15.139	15.138																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															
Note: Slanted line shows the range of the rated load current. (注)斜線は定格負荷電流範囲を示す。																																																		

COSEL

Model	ZUS34815
Item	Ripple Voltage (by Load Current) リップル電圧(負荷電流特性)
Object	+15V 0.2A

Temperature 25°C
Testing Circuitry Figure A

1. Graph
- Input Volt. 36.0V
 -----△----- Input Volt. 72.0V



Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p-p 値で示される。

(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期
T2: Due to Switching
スイッチング周期





Fig. Complex Ripple Wave Form
図 リップル波形詳細図

2. Values

Load Current [A]	Input Volt. 36.0 [V]	Input Volt. 72.0 [V]
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
0.00	5	5
0.04	5	5
0.08	5	5
0.12	10	5
0.16	10	5
0.20	15	5
0.22	15	5
—	—	—
—	—	—
—	—	—
—	—	—

COSEL



COSEL

Model		ZUS34815		Temperature 25℃	
Item		Overcurrent Protection 過電流保護		Testing Circuitry Figure A	
Object		+15V0.2A			
1. Graph		Input Volt. 36.0V Input Volt. 48.0V Input Volt. 72.0V		2. Values	
[V]					
Note: Slanted line shows the range of the rated load current.					
(注)斜線は定格負荷電流範囲を示す。					

COSEL

Model	ZUS34815	Temperature	25°C
Item	Dynamic Load Responce 動的負荷変動	Testing Circuitry	Figure A
Object	+15V0.2A		

Input Volt. 48.0 V



Cycle 100 mS

Load Current

Min. Load ↔

Load 100 %



200 mV/div



Min. Load ↔

Load 50 %



200 mV/div



Load 50% ↔

Load 100 %

200 mV/div




1 mS/div

COSEL

Model	ZUS34815	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+15V 0.2A		

1. Graph


Input Volt. 36.0 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.10	3.30	3.40	0.59	5.96
100 %	0.10	3.30	3.40	0.26	2.27



COSEL


Model	ZUS34815	Testing Circuitry Figure A																																																	
Item	Ambient Temperature Drift 周囲温度変動																																																		
Object	+15V0.2A																																																		
1. Graph		2. Values																																																	
<div> <div> <div>—△—</div> <div>Input Volt. 36.0V</div> </div> <div> <div>---□---</div> <div>Input Volt. 48.0V</div> </div> <div> <div>---○---</div> <div>Input Volt. 72.0V</div> </div> </div> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注)斜線は定格周囲温度範囲を示す。</p>		<table> <tr> <th>Temperature [°C]</th><th>Input Volt. 36.0[V] Output Volt. [V]</th><th>Input Volt. 48.0[V] Output Volt. [V]</th><th>Input Volt. 72.0[V] Output Volt. [V]</th></tr> <tr><td>-30</td><td>15.160</td><td>15.161</td><td>15.160</td></tr> <tr><td>-20</td><td>15.157</td><td>15.157</td><td>15.157</td></tr> <tr><td>-10</td><td>15.154</td><td>15.154</td><td>15.154</td></tr> <tr><td>0</td><td>15.151</td><td>15.151</td><td>15.151</td></tr> <tr><td>10</td><td>15.148</td><td>15.148</td><td>15.148</td></tr> <tr><td>25</td><td>15.141</td><td>15.141</td><td>15.140</td></tr> <tr><td>30</td><td>15.136</td><td>15.136</td><td>15.136</td></tr> <tr><td>40</td><td>15.127</td><td>15.128</td><td>15.127</td></tr> <tr><td>55</td><td>15.111</td><td>15.111</td><td>15.110</td></tr> <tr><td>60</td><td>15.104</td><td>15.103</td><td>15.103</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </table>		Temperature [°C]	Input Volt. 36.0[V] Output Volt. [V]	Input Volt. 48.0[V] Output Volt. [V]	Input Volt. 72.0[V] Output Volt. [V]	-30	15.160	15.161	15.160	-20	15.157	15.157	15.157	-10	15.154	15.154	15.154	0	15.151	15.151	15.151	10	15.148	15.148	15.148	25	15.141	15.141	15.140	30	15.136	15.136	15.136	40	15.127	15.128	15.127	55	15.111	15.111	15.110	60	15.104	15.103	15.103	—	—	—	—
Temperature [°C]	Input Volt. 36.0[V] Output Volt. [V]	Input Volt. 48.0[V] Output Volt. [V]	Input Volt. 72.0[V] Output Volt. [V]																																																
-30	15.160	15.161	15.160																																																
-20	15.157	15.157	15.157																																																
-10	15.154	15.154	15.154																																																
0	15.151	15.151	15.151																																																
10	15.148	15.148	15.148																																																
25	15.141	15.141	15.140																																																
30	15.136	15.136	15.136																																																
40	15.127	15.128	15.127																																																
55	15.111	15.111	15.110																																																
60	15.104	15.103	15.103																																																
—	—	—	—																																																

COSEL

Model	ZUS34815
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+15V0.2A

Testing Circuitry Figure A

1. Graph
- Load 50%
- △----- Load 100%
- [V]



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-30	21.9	27.4
-20	21.4	26.9
-10	20.9	26.4
0	20.4	25.9
10	20.4	25.4
25	19.4	25.4
30	19.4	25.4
40	18.9	25.4
55	18.4	25.4
60	18.4	25.9
—	—	—

COSEL

Model		ZUS34815
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	
Object	+15V0.2A	

1. Graph

-----□-----

Load 50%

-----△-----

Load 100%

[mV]

60

40

20

0

Ripple Voltage

Ambient Temperature

[°C]

Input Volt. 36.0 V


Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-30	10	20
-20	10	20
-10	10	15
0	10	15
10	10	15
25	10	15
30	5	10
40	5	10
55	5	10
60	5	10
—	—	—

COSEL

Model	ZUS34815	Temperature Testing Circuitry	25 ℃ Figure A																						
Item	Time Lapse Drift 経時ドリフト																								
Object	+15V0.2A																								
1. Graph		2.Values																							
<p>[V]</p>  <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>		<table><thead><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr></thead><tbody><tr><td>0.0</td><td>15.139</td></tr><tr><td>0.5</td><td>15.133</td></tr><tr><td>1.0</td><td>15.133</td></tr><tr><td>2.0</td><td>15.133</td></tr><tr><td>3.0</td><td>15.133</td></tr><tr><td>4.0</td><td>15.134</td></tr><tr><td>5.0</td><td>15.134</td></tr><tr><td>6.0</td><td>15.134</td></tr><tr><td>7.0</td><td>15.134</td></tr><tr><td>8.0</td><td>15.134</td></tr></tbody></table>		Time since start [H]	Output Voltage [V]	0.0	15.139	0.5	15.133	1.0	15.133	2.0	15.133	3.0	15.133	4.0	15.134	5.0	15.134	6.0	15.134	7.0	15.134	8.0	15.134
Time since start [H]	Output Voltage [V]																								
0.0	15.139																								
0.5	15.133																								
1.0	15.133																								
2.0	15.133																								
3.0	15.133																								
4.0	15.134																								
5.0	15.134																								
6.0	15.134																								
7.0	15.134																								
8.0	15.134																								

COSEL

Model		ZUS34815	Testing Circuitry Figure A
Item		Output Voltage Accuracy 定電圧精度	
Object		+15V0.2A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~55 °C

Input Voltage : 36.0~72.0 V

Load Current : 0.0~0.2 A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) = $\frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -20~55 °C

入力電圧 : 36.0~72.0 V

負荷電流 : 0.0~0.2 A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

* 定電圧精度(変動率) = $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ratio) [%]
Maximum Voltage	-20	72.0	0.0	15.167	±30	±0.3
Minimum Voltage	55	72.0	0.2	15.107		

COSEL

COSEL

Model	ZUS34815
Item	Condensation 結露特性
Object	+15V0.2A

Testing Circuitry Figure A

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10℃ for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25℃ and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①,② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で－10℃に冷却しておき、約1時間後に恒温槽から取り出し、室温25℃、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	15.150	5	15
	2	15.153	5	15
	3	15.153	5	15
Load 100 %	1	15.148	10	25
	2	15.150	10	25
	3	15.151	10	25

Input Volt. 48.0 V

COSEL




Figure A