



TEST DATA OF ZUW100515

(5.0V INPUT)

Regulated DC Power Supply

Date : Sep 21. 1996

Approved by : T. Sugimori
Design Manager

Prepared by : M. Takashima
Design Engineer

コーセル株式会社
COSEL CO., LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Load Regulation	3
静的負荷変動	
4. Ripple Voltage (by Load Current)	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise	6
リップルノイズ	
6. Overcurrent Protection	8
過電流保護	
7. Dynamic Load Responce	9
動的負荷変動	
8. Rise and Fall Time	11
立上り、立下がり時間	
9. Ambient Temperature Drift	13
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage . . .	14
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature)	15
リップル電圧(周囲温度特性)	
12. Time Lapse Drift	16
経時ドリフト	
13. Output Voltage Accuracy	17
定電圧精度	
14. Condensation	18
結露特性	
15. Figure of Testing Circuitry	20
測定回路図	

(Final Page 20)

COSEL

Model	ZUW100515																																									
Item	Line Regulation 静的入力変動	Temperature	25℃																																							
Object	+15V0.300A	Testing Circuitry	Figure A																																							
1. Graph		2. Values																																								
<div>-----□----- Load 50%</div> <div>-----△----- Load 100%</div> <div><p>[V]</p><p>Output Voltage</p><p>Input Voltage [V]</p></div>		<table><tr><th>Input Voltage [V]</th><th>Load 50% Output Volt. [V]</th><th>Load 100% Output Volt. [V]</th></tr><tr><td>4.5</td><td>15.378</td><td>15.206</td></tr><tr><td>5.0</td><td>15.370</td><td>15.209</td></tr><tr><td>6.0</td><td>15.360</td><td>15.208</td></tr><tr><td>7.0</td><td>15.353</td><td>15.207</td></tr><tr><td>8.0</td><td>15.348</td><td>15.209</td></tr><tr><td>9.0</td><td>15.344</td><td>15.208</td></tr><tr><td>9.5</td><td>15.338</td><td>15.205</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	4.5	15.378	15.206	5.0	15.370	15.209	6.0	15.360	15.208	7.0	15.353	15.207	8.0	15.348	15.209	9.0	15.344	15.208	9.5	15.338	15.205	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]																																								
4.5	15.378	15.206																																								
5.0	15.370	15.209																																								
6.0	15.360	15.208																																								
7.0	15.353	15.207																																								
8.0	15.348	15.209																																								
9.0	15.344	15.208																																								
9.5	15.338	15.205																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
Object -15V0.300A																																										
1. Graph		2. Values																																								
<div>-----□----- Load 50%</div> <div>-----△----- Load 100%</div> <div><p>[V]</p><p>Output Voltage</p><p>Input Voltage [V]</p></div>		<table><tr><th>Input Voltage [V]</th><th>Load 50% Output Volt. [V]</th><th>Load 100% Output Volt. [V]</th></tr><tr><td>4.5</td><td>-15.431</td><td>-15.256</td></tr><tr><td>5.0</td><td>-15.422</td><td>-15.260</td></tr><tr><td>6.0</td><td>-15.413</td><td>-15.260</td></tr><tr><td>7.0</td><td>-15.407</td><td>-15.261</td></tr><tr><td>8.0</td><td>-15.402</td><td>-15.260</td></tr><tr><td>9.0</td><td>-15.398</td><td>-15.261</td></tr><tr><td>9.5</td><td>-15.396</td><td>-15.262</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	4.5	-15.431	-15.256	5.0	-15.422	-15.260	6.0	-15.413	-15.260	7.0	-15.407	-15.261	8.0	-15.402	-15.260	9.0	-15.398	-15.261	9.5	-15.396	-15.262	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]																																								
4.5	-15.431	-15.256																																								
5.0	-15.422	-15.260																																								
6.0	-15.413	-15.260																																								
7.0	-15.407	-15.261																																								
8.0	-15.402	-15.260																																								
9.0	-15.398	-15.261																																								
9.5	-15.396	-15.262																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
Note: Slanted line shows the range of the rated input voltage. (注)斜線は定格入力電圧範囲を示す。																																										

COSEL


Model ZUW100515

Item Efficiency 効率

Object

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	Load 50%	Load 100%
	Efficiency [%]	Efficiency [%]
4.0	77.5	77.7
4.5	77.4	78.4
5.0	77.4	78.7
6.0	76.8	79.5
7.0	77.2	79.7
8.0	77.7	79.9
9.0	76.1	79.6
9.5	75.9	79.1
—	—	—
—	—	—
—	—	—
—	—	—

COSEL

Model		ZUW100515		Temperature		25℃	
Item		Load Regulation 静的負荷変動		Testing Circuitry		Figure A	
Object		+15V0.300A					
1. Graph				2. Values			
<div><div><div>△</div><div>—</div></div><div>Input Volt. 4.5V</div><div><div>□</div><div>---</div></div><div>Input Volt. 5.0V</div><div><div>○</div><div>----</div></div><div>Input Volt. 9.0V</div></div> <div><div>Output Voltage [V]</div><div><div>16.06</div><div>15.86</div><div>15.66</div><div>15.46</div><div>15.26</div><div>15.06</div><div>14.86</div><div>0</div></div><div><div>0</div><div>0.1</div><div>0.2</div><div>0.3</div><div>0.4</div></div><div>Load Current [A]</div></div> <div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><</div>							

COSEL

Model		ZUW100515	
Item		Ripple Voltage (by Load Current) リップル電圧 (負荷電流特性)	
Object		+15V0.30A	

1. Graph

-----□----- Input Volt. 4.5V

-----△----- Input Volt. 9.0V

[mV]

100

80

60

40

20

0

0

0.1

0.2

0.3

0.4

Ripple Voltage

Load Current

[A]

2. Values

Load Current	Input Volt.	Input Volt.
	4.5 [V]	9.0 [V]
[A]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
0.00	5	5
0.06	5	5
0.12	5	5
0.18	6	5
0.24	9	7
0.30	10	7
0.33	11	8
—	—	—
—	—	—
—	—	—
—	—	—

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p-p 値で示される。

(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期

T2: Due to Switching
スイッチング周期

Ripple [mVp-p]

T1

T2

Fig. Complex Ripple Wave Form

図 リップル波形詳細図

COSEL

Model		ZUW100515	
Item		Ripple Voltage (by Load Current) リップル電圧 (負荷電流特性)	
Object		-15V0.30A	

1. Graph

-----□----- Input Volt. 4.5V

-----△----- Input Volt. 9.0V

[mV]

100

80

60

40

20

0

Ripple Voltage

0

0.1

0.2

0.3

0.4

[A]

2. Values

Load Current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
0.00	5	7
0.06	5	5
0.12	5	5
0.18	5	5
0.24	5	5
0.30	5	5
0.33	5	5
—	—	—
—	—	—
—	—	—
—	—	—

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p-p 値で示される。

(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期

T2: Due to Switching
スイッチング周期

Ripple [mVp-p]


T1

T2

Fig. Complex Ripple Wave Form


図 リップル波形詳細図

Temperature	25°C
Testing Circuitry	Figure A



Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated
load current.



T1: Due to AC Input Line
入力商用周期
T2: Due to Switching
スイッチング周期



Load current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple-Noise [mV]	Ripple-Noise [mV]
0.00	15	20
0.06	20	20
0.12	20	20
0.18	20	25
0.24	20	20
0.30	20	20
0.33	20	25
—	—	—
—	—	—
—	—	—
—	—	—

Fig. Complex Ripple Wave Form
図 リップル波形詳細図

COSEL

Model ZUW100515		Temperature 25°C																																																					
Item Overcurrent Protection 過電流保護		Testing Circuitry Figure A																																																					
Object +15V0.300A																																																							
1. Graph [V]  Load Current [A]		2. Values <table border="1"> <thead> <tr> <th>Output Voltage [V]</th><th>Input Volt. 4.5[V] Load Curr-ent [A]</th><th>Input Volt. 5.0[V] Load Curr-ent [A]</th><th>Input Volt. 9.0[V] Load Curr-ent [A]</th></tr> </thead> <tbody> <tr><td>15.00</td><td>0.441</td><td>0.459</td><td>0.464</td></tr> <tr><td>14.25</td><td>0.473</td><td>0.490</td><td>0.499</td></tr> <tr><td>13.50</td><td>0.501</td><td>0.521</td><td>0.531</td></tr> <tr><td>12.00</td><td>0.564</td><td>0.584</td><td>0.601</td></tr> <tr><td>10.50</td><td>0.638</td><td>0.658</td><td>0.678</td></tr> <tr><td>9.00</td><td>0.705</td><td>0.723</td><td>0.735</td></tr> <tr><td>7.50</td><td>0.757</td><td>0.771</td><td>0.757</td></tr> <tr><td>6.00</td><td>0.780</td><td>0.787</td><td>0.738</td></tr> <tr><td>4.50</td><td>0.779</td><td>0.783</td><td>0.723</td></tr> <tr><td>3.00</td><td>0.799</td><td>0.820</td><td>0.760</td></tr> <tr><td>1.50</td><td>0.833</td><td>0.872</td><td>0.824</td></tr> <tr><td>0.00</td><td>0.884</td><td>0.938</td><td>0.881</td></tr> </tbody> </table>		Output Voltage [V]	Input Volt. 4.5[V] Load Curr-ent [A]	Input Volt. 5.0[V] Load Curr-ent [A]	Input Volt. 9.0[V] Load Curr-ent [A]	15.00	0.441	0.459	0.464	14.25	0.473	0.490	0.499	13.50	0.501	0.521	0.531	12.00	0.564	0.584	0.601	10.50	0.638	0.658	0.678	9.00	0.705	0.723	0.735	7.50	0.757	0.771	0.757	6.00	0.780	0.787	0.738	4.50	0.779	0.783	0.723	3.00	0.799	0.820	0.760	1.50	0.833	0.872	0.824	0.00	0.884	0.938	0.881
Output Voltage [V]	Input Volt. 4.5[V] Load Curr-ent [A]	Input Volt. 5.0[V] Load Curr-ent [A]	Input Volt. 9.0[V] Load Curr-ent [A]																																																				
15.00	0.441	0.459	0.464																																																				
14.25	0.473	0.490	0.499																																																				
13.50	0.501	0.521	0.531																																																				
12.00	0.564	0.584	0.601																																																				
10.50	0.638	0.658	0.678																																																				
9.00	0.705	0.723	0.735																																																				
7.50	0.757	0.771	0.757																																																				
6.00	0.780	0.787	0.738																																																				
4.50	0.779	0.783	0.723																																																				
3.00	0.799	0.820	0.760																																																				
1.50	0.833	0.872	0.824																																																				
0.00	0.884	0.938	0.881																																																				
Object -15V0.300A																																																							
1. Graph [V]  Load Current [A]		2. Values <table border="1"> <thead> <tr> <th>Output Voltage [V]</th><th>Input Volt. 4.5[V] Load Curr-ent [A]</th><th>Input Volt. 5.0[V] Load Curr-ent [A]</th><th>Input Volt. 9.0[V] Load Curr-ent [A]</th></tr> </thead> <tbody> <tr><td>12.00</td><td>0.581</td><td>0.617</td><td>0.625</td></tr> <tr><td>11.40</td><td>0.671</td><td>0.712</td><td>0.709</td></tr> <tr><td>10.80</td><td>0.723</td><td>0.758</td><td>0.759</td></tr> <tr><td>9.60</td><td>0.823</td><td>0.874</td><td>0.885</td></tr> <tr><td>8.40</td><td>0.901</td><td>0.945</td><td>0.949</td></tr> <tr><td>7.20</td><td>0.963</td><td>0.999</td><td>0.989</td></tr> <tr><td>6.00</td><td>0.906</td><td>0.912</td><td>0.876</td></tr> <tr><td>4.80</td><td>0.820</td><td>0.797</td><td>0.732</td></tr> <tr><td>3.60</td><td>0.786</td><td>0.754</td><td>0.675</td></tr> <tr><td>2.40</td><td>0.861</td><td>0.834</td><td>0.788</td></tr> <tr><td>1.20</td><td>1.063</td><td>1.040</td><td>0.978</td></tr> <tr><td>0.00</td><td>1.225</td><td>1.165</td><td>0.950</td></tr> </tbody> </table>		Output Voltage [V]	Input Volt. 4.5[V] Load Curr-ent [A]	Input Volt. 5.0[V] Load Curr-ent [A]	Input Volt. 9.0[V] Load Curr-ent [A]	12.00	0.581	0.617	0.625	11.40	0.671	0.712	0.709	10.80	0.723	0.758	0.759	9.60	0.823	0.874	0.885	8.40	0.901	0.945	0.949	7.20	0.963	0.999	0.989	6.00	0.906	0.912	0.876	4.80	0.820	0.797	0.732	3.60	0.786	0.754	0.675	2.40	0.861	0.834	0.788	1.20	1.063	1.040	0.978	0.00	1.225	1.165	0.950
Output Voltage [V]	Input Volt. 4.5[V] Load Curr-ent [A]	Input Volt. 5.0[V] Load Curr-ent [A]	Input Volt. 9.0[V] Load Curr-ent [A]																																																				
12.00	0.581	0.617	0.625																																																				
11.40	0.671	0.712	0.709																																																				
10.80	0.723	0.758	0.759																																																				
9.60	0.823	0.874	0.885																																																				
8.40	0.901	0.945	0.949																																																				
7.20	0.963	0.999	0.989																																																				
6.00	0.906	0.912	0.876																																																				
4.80	0.820	0.797	0.732																																																				
3.60	0.786	0.754	0.675																																																				
2.40	0.861	0.834	0.788																																																				
1.20	1.063	1.040	0.978																																																				
0.00	1.225	1.165	0.950																																																				
Note: Slanted line shows the range of the rated load current. (注)斜線は定格負荷電流範囲を示す。																																																							

COSEL

Model	ZUW100515	Temperature	25°C
Item	Dynamic Load Responce 動的負荷変動	Testing Circuitry	Figure A
Object	+15V 0.300A		

Input Volt. \pm V



Cycle 100 mS

Load Current

Min. Load \longleftrightarrow

Load 100 %



200 mV/div



Min. Load \longleftrightarrow

Load 50 %



200 mV/div



Load 50% \longleftrightarrow

Load 100 %

200 mV/div



1 mS/div

COSEL

Model	ZUW100515	Temperature 25℃ Testing Circuitry Figure A
Item	Dynamic Load Responce 動的負荷変動	
Object	-15V0.300A	

Input Volt. 5 V


Cycle 100 mS

Load Current

Min. Load ↔

Load 100 %


200 mV/div



Min. Load ↔

Load 50 %


200 mV/div



Load 50% ↔

Load 100 %

200 mV/div




1 mS/div

COSEL

Model	ZUW100515	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+15V0.300A		

1. Graph


Input Volt. 4.5 V



2. Values

[mS]

Time	T d	T r	T s	T h	T f
Load 50 %	0.15	1.95	2.10	0.33	5.30
Load 100 %	0.15	2.10	2.25	0.19	2.76




COSEL

Model	ZUW100515	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	-15V0.300A		

1. Graph


Input Volt. 4.5 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.15	1.85	2.00	0.33	5.07
100 %	0.15	1.95	2.10	0.19	2.53



COSEL

Model ZUW100515		Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	+15V0.300A																																																						
1. Graph <div style="display: flex; align-items: center;"> <div style="flex: 1;"> </div> <div style="flex: 1;"> <p>—△— Input Volt. 4.5V</p> <p>- -□- - Input Volt. 5.0V</p> <p>...○... Input Volt. 9.0V</p> </div> </div>		2. Values <table border="1"> <thead> <tr> <th>Temperature</th><th>Input Volt. 4.5[V]</th><th>Input Volt. 5.0[V]</th><th>Input Volt. 9.0[V]</th></tr> <tr> <th>[°C]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr> </thead> <tbody> <tr><td>-30</td><td>15.160</td><td>15.161</td><td>15.159</td></tr> <tr><td>-20</td><td>15.169</td><td>15.168</td><td>15.167</td></tr> <tr><td>-10</td><td>15.178</td><td>15.179</td><td>15.178</td></tr> <tr><td>0</td><td>15.188</td><td>15.188</td><td>15.187</td></tr> <tr><td>10</td><td>15.197</td><td>15.198</td><td>15.194</td></tr> <tr><td>25</td><td>15.205</td><td>15.207</td><td>15.208</td></tr> <tr><td>30</td><td>15.209</td><td>15.209</td><td>15.208</td></tr> <tr><td>40</td><td>15.214</td><td>15.212</td><td>15.210</td></tr> <tr><td>55</td><td>15.215</td><td>15.213</td><td>15.212</td></tr> <tr><td>60</td><td>15.213</td><td>15.212</td><td>15.211</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Temperature	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	-30	15.160	15.161	15.159	-20	15.169	15.168	15.167	-10	15.178	15.179	15.178	0	15.188	15.188	15.187	10	15.197	15.198	15.194	25	15.205	15.207	15.208	30	15.209	15.209	15.208	40	15.214	15.212	15.210	55	15.215	15.213	15.212	60	15.213	15.212	15.211	—	—	—	—
Temperature	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																																				
[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
-30	15.160	15.161	15.159																																																				
-20	15.169	15.168	15.167																																																				
-10	15.178	15.179	15.178																																																				
0	15.188	15.188	15.187																																																				
10	15.197	15.198	15.194																																																				
25	15.205	15.207	15.208																																																				
30	15.209	15.209	15.208																																																				
40	15.214	15.212	15.210																																																				
55	15.215	15.213	15.212																																																				
60	15.213	15.212	15.211																																																				
—	—	—	—																																																				
Object -15V0.300A		2. Values <table border="1"> <thead> <tr> <th>Temperature</th><th>Input Volt. 4.5[V]</th><th>Input Volt. 5.0[V]</th><th>Input Volt. 9.0[V]</th></tr> <tr> <th>[°C]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr> </thead> <tbody> <tr><td>-30</td><td>-15.212</td><td>-15.213</td><td>-15.213</td></tr> <tr><td>-20</td><td>-15.220</td><td>-15.219</td><td>-15.221</td></tr> <tr><td>-10</td><td>-15.229</td><td>-15.230</td><td>-15.231</td></tr> <tr><td>0</td><td>-15.239</td><td>-15.238</td><td>-15.240</td></tr> <tr><td>10</td><td>-15.247</td><td>-15.248</td><td>-15.247</td></tr> <tr><td>25</td><td>-15.255</td><td>-15.257</td><td>-15.260</td></tr> <tr><td>30</td><td>-15.258</td><td>-15.258</td><td>-15.259</td></tr> <tr><td>40</td><td>-15.262</td><td>-15.261</td><td>-15.261</td></tr> <tr><td>55</td><td>-15.263</td><td>-15.262</td><td>-15.262</td></tr> <tr><td>60</td><td>-15.261</td><td>-15.261</td><td>-15.261</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Temperature	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	-30	-15.212	-15.213	-15.213	-20	-15.220	-15.219	-15.221	-10	-15.229	-15.230	-15.231	0	-15.239	-15.238	-15.240	10	-15.247	-15.248	-15.247	25	-15.255	-15.257	-15.260	30	-15.258	-15.258	-15.259	40	-15.262	-15.261	-15.261	55	-15.263	-15.262	-15.262	60	-15.261	-15.261	-15.261	—	—	—	—
Temperature	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																																				
[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
-30	-15.212	-15.213	-15.213																																																				
-20	-15.220	-15.219	-15.221																																																				
-10	-15.229	-15.230	-15.231																																																				
0	-15.239	-15.238	-15.240																																																				
10	-15.247	-15.248	-15.247																																																				
25	-15.255	-15.257	-15.260																																																				
30	-15.258	-15.258	-15.259																																																				
40	-15.262	-15.261	-15.261																																																				
55	-15.263	-15.262	-15.262																																																				
60	-15.261	-15.261	-15.261																																																				
—	—	—	—																																																				
1. Graph <div style="display: flex; align-items: center;"> <div style="flex: 1;"> </div> <div style="flex: 1;"> <p>—△— Input Volt. 4.5V</p> <p>- -□- - Input Volt. 5.0V</p> <p>...○... Input Volt. 9.0V</p> </div> </div>																																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注)斜線は定格周囲温度範囲を示す。</p>																																																							


COSEL

Model ZUW100515

Item Minimum Input Voltage for Regulated Output Voltage
最低レギュレーション電圧

Object +15V0.300A

1. Graph




Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-30	3.5	3.7
-20	3.6	3.7
-10	3.6	3.7
0	3.6	3.8
10	3.6	3.8
25	3.6	3.9
30	3.6	3.9
40	3.7	3.9
55	3.7	3.9
60	3.7	3.9
70	3.7	4.0

Object -15V0.300A



2. Values

Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-30	3.5	3.7
-20	3.6	3.7
-10	3.6	3.7
0	3.6	3.8
10	3.6	3.8
25	3.6	3.9
30	3.6	3.9
40	3.7	3.9
55	3.7	3.9
60	3.7	3.9
70	3.7	4.0

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL

Model		ZUW100515																																																																									
Item		Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)																																																																									
Object		+15V0.300A																																																																									
1. Graph		2. Values																																																																									
<div><div><div>-----□-----</div><div>Load 50%</div></div><div><div>-----△-----</div><div>Load 100%</div></div></div> <div><div><div>Ripple Voltage</div><div>[mV]</div></div><div><div><div>50</div><div>40</div><div>30</div><div>20</div><div>10</div><div>0</div></div><div><div><div>-40</div><div>-20</div><div>0</div><div>20</div><div>40</div><div>60</div></div><div><div>Ambient Temperature</div><div>[°C]</div></div></div></div><div><div>Input Volt. 4.5 V</div></div></div> <table><tr><th>Ambient Temp. [°C]</th><th>Load 50% Ripple Output Volt. [mV]</th><th>Load 100% Ripple Output Volt. [mV]</th></tr><tr><td>-30</td><td>10</td><td>25</td></tr><tr><td>-20</td><td>10</td><td>20</td></tr><tr><td>-10</td><td>10</td><td>15</td></tr><tr><td>0</td><td>5</td><td>10</td></tr><tr><td>10</td><td>5</td><td>10</td></tr><tr><td>25</td><td>5</td><td>10</td></tr><tr><td>30</td><td>5</td><td>10</td></tr><tr><td>40</td><td>5</td><td>10</td></tr><tr><td>55</td><td>5</td><td>10</td></tr><tr><td>60</td><td>5</td><td>10</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]	-30	10	25	-20	10	20	-10	10	15	0	5	10	10	5	10	25	5	10	30	5	10	40	5	10	55	5	10	60	5	10	—	—	—	<div><div><div>-----□-----</div><div>Load 50%</div></div><div><div>-----△-----</div><div>Load 100%</div></div></div> <div><div><div>Ripple Voltage</div><div>[mV]</div></div><div><div><div>50</div><div>40</div><div>30</div><div>20</div><div>10</div><div>0</div></div><div><div><div>-40</div><div>-20</div><div>0</div><div>20</div><div>40</div><div>60</div></div><div><div>Ambient Temperature</div><div>[°C]</div></div></div></div><div><div>Input Volt. 4.5 V</div></div></div> <table><tr><th>Ambient Temp. [°C]</th><th>Load 50% Ripple Output Volt. [mV]</th><th>Load 100% Ripple Output Volt. [mV]</th></tr><tr><td>-30</td><td>5</td><td>10</td></tr><tr><td>-20</td><td>5</td><td>10</td></tr><tr><td>-10</td><td>5</td><td>10</td></tr><tr><td>0</td><td>5</td><td>5</td></tr><tr><td>10</td><td>5</td><td>5</td></tr><tr><td>25</td><td>5</td><td>5</td></tr><tr><td>30</td><td>5</td><td>5</td></tr><tr><td>40</td><td>5</td><td>5</td></tr><tr><td>55</td><td>5</td><td>5</td></tr><tr><td>60</td><td>5</td><td>5</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]	-30	5	10	-20	5	10	-10	5	10	0	5	5	10	5	5	25	5	5	30	5	5	40	5	5	55	5	5	60	5	5	—	—	—
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]																																																																									
-30	10	25																																																																									
-20	10	20																																																																									
-10	10	15																																																																									
0	5	10																																																																									
10	5	10																																																																									
25	5	10																																																																									
30	5	10																																																																									
40	5	10																																																																									
55	5	10																																																																									
60	5	10																																																																									
—	—	—																																																																									
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]																																																																									
-30	5	10																																																																									
-20	5	10																																																																									
-10	5	10																																																																									
0	5	5																																																																									
10	5	5																																																																									
25	5	5																																																																									
30	5	5																																																																									
40	5	5																																																																									
55	5	5																																																																									
60	5	5																																																																									
—	—	—																																																																									
Object		-15V0.300A																																																																									
1. Graph		2. Values																																																																									
<div><div><div>-----□-----</div><div>Load 50%</div></div><div><div>-----△-----</div><div>Load 100%</div></div></div> <div><div><div>Ripple Voltage</div><div>[mV]</div></div><div><div><div>50</div><div>40</div><div>30</div><div>20</div><div>10</div><div>0</div></div><div><div><div>-40</div><div>-20</div><div>0</div><div>20</div><div>40</div><div>60</div></div><div><div>Ambient Temperature</div><div>[°C]</div></div></div></div><div><div>Input Volt. 4.5 V</div></div></div> <table><tr><th>Ambient Temp. [°C]</th><th>Load 50% Ripple Output Volt. [mV]</th><th>Load 100% Ripple Output Volt. [mV]</th></tr><tr><td>-30</td><td>5</td><td>10</td></tr><tr><td>-20</td><td>5</td><td>10</td></tr><tr><td>-10</td><td>5</td><td>10</td></tr><tr><td>0</td><td>5</td><td>5</td></tr><tr><td>10</td><td>5</td><td>5</td></tr><tr><td>25</td><td>5</td><td>5</td></tr><tr><td>30</td><td>5</td><td>5</td></tr><tr><td>40</td><td>5</td><td>5</td></tr><tr><td>55</td><td>5</td><td>5</td></tr><tr><td>60</td><td>5</td><td>5</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]	-30	5	10	-20	5	10	-10	5	10	0	5	5	10	5	5	25	5	5	30	5	5	40	5	5	55	5	5	60	5	5	—	—	—	<div><div><div>-----□-----</div><div>Load 50%</div></div><div><div>-----△-----</div><div>Load 100%</div></div></div> <div><div><div>Ripple Voltage</div><div>[mV]</div></div><div><div><div>50</div><div>40</div><div>30</div><div>20</div><div>10</div><div>0</div></div><div><div><div>-40</div><div>-20</div><div>0</div><div>20</div><div>40</div><div>60</div></div><div><div>Ambient Temperature</div><div>[°C]</div></div></div></div><div><div>Input Volt. 4.5 V</div></div></div> <table><tr><th>Ambient Temp. [°C]</th><th>Load 50% Ripple Output Volt. [mV]</th><th>Load 100% Ripple Output Volt. [mV]</th></tr><tr><td>-30</td><td>5</td><td>10</td></tr><tr><td>-20</td><td>5</td><td>10</td></tr><tr><td>-10</td><td>5</td><td>10</td></tr><tr><td>0</td><td>5</td><td>5</td></tr><tr><td>10</td><td>5</td><td>5</td></tr><tr><td>25</td><td>5</td><td>5</td></tr><tr><td>30</td><td>5</td><td>5</td></tr><tr><td>40</td><td>5</td><td>5</td></tr><tr><td>55</td><td>5</td><td>5</td></tr><tr><td>60</td><td>5</td><td>5</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]	-30	5	10	-20	5	10	-10	5	10	0	5	5	10	5	5	25	5	5	30	5	5	40	5	5	55	5	5	60	5	5	—	—	—
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]																																																																									
-30	5	10																																																																									
-20	5	10																																																																									
-10	5	10																																																																									
0	5	5																																																																									
10	5	5																																																																									
25	5	5																																																																									
30	5	5																																																																									
40	5	5																																																																									
55	5	5																																																																									
60	5	5																																																																									
—	—	—																																																																									
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]																																																																									
-30	5	10																																																																									
-20	5	10																																																																									
-10	5	10																																																																									
0	5	5																																																																									
10	5	5																																																																									
25	5	5																																																																									
30	5	5																																																																									
40	5	5																																																																									
55	5	5																																																																									
60	5	5																																																																									
—	—	—																																																																									
Note: Slanted line shows the range of the rated ambient temperature.																																																																											
(注) 斜線は定格周囲温度範囲を示す。																																																																											

COSEL

COSEL

Model ZUW100515

Item Time Lapse Drift 経時ドリフト

Object +15V0.300A

Temperature 25 ℃
Testing Circuitry Figure A

1. Graph

Output Voltage [V]

Time [H]

Input Volt. 5.0V
Load 100%

2. Values

Time since start [H]	Output Voltage [V]
0.0	15.205
0.5	15.202
1.0	15.203
2.0	15.203
3.0	15.203
4.0	15.203
5.0	15.203
6.0	15.204
7.0	15.203
8.0	15.203

Object -15V0.300A

1. Graph

Output Voltage [V]

Time [H]

Input Volt. 5.0V
Load 100%

2. Values

Time since start [H]	Output Voltage [V]
0.0	-15.250
0.5	-15.249
1.0	-15.249
2.0	-15.249
3.0	-15.249
4.0	-15.249
5.0	-15.249
6.0	-15.249
7.0	-15.249
8.0	-15.249

-16-

BC-2076

COSEL

LOREL

Model	ZUW100515
Item	Condensation 結露特性
Object	+15V0.300A

Testing Circuitry Figure A

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10℃ for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25℃ and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で－１０℃に冷却しておき、約１時間後に恒温槽から取り出し、室温２５℃、湿度４０％RHの状態におき結露させ、その電気的特性の測定を３度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	15.306	5	30
	2	15.338	5	30
	3	15.296	5	30
Load 100 %	1	15.133	10	35
	2	15.194	10	35
	3	15.156	10	35

Input Volt. 5.0 V

-18-

BC-2076

COSEL

COSEL

Model	ZUW100515		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	−15V0.300A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10℃ for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25℃ and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①,② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で－10℃に冷却しておき、約1時間後に恒温槽から取り出し、室温25℃、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	15.400	5	25
	2	15.367	5	25
	3	15.390	5	25
Load 100 %	1	15.245	10	35
	2	15.213	10	35
	3	15.237	10	35

Input Volt. 5.0 V


COSEL

Figure A