



TEST DATA OF ZUW31215

(12.0V INPUT)

Regulated DC Power Supply

Date : Nov. 5. 1996

Approved by : T. Sugimori
Design Manager

Prepared by : y. Nagai
Design Engineer

コーセル株式会社
COSEL CO., LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Load Regulation	3
静的負荷変動	
4. Ripple Voltage (by Load Current)	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise	6
リップルノイズ	
6. Overcurrent Protection	8
過電流保護	
7. Dynamic Load Responce	9
動的負荷変動	
8. Rise and Fall Time	11
立上り、立下がり時間	
9. Ambient Temperature Drift	13
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage . . .	14
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature)	15
リップル電圧(周囲温度特性)	
12. Time Lapse Drift	16
経時ドリフト	
13. Output Voltage Accuracy	17
定電圧精度	
14. Condensation	18
結露特性	
15. Figure of Testing Circuitry	20
測定回路図	

(Final Page 20)

COSEL

Model		ZUW31215	
Item	Line Regulation 静的入力変動		
Object	+15V0.1A		
1. Graph		-----□----- Load 50% -----△----- Load 100%	
[V]			
Output Voltage			
Input Voltage [V]			
2. Values			
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	
8.0	15.086	14.971	
9.0	15.084	14.978	
10.0	15.082	14.982	
12.0	15.080	14.986	
15.0	15.074	14.985	
18.0	15.068	14.979	
20.0	15.064	14.974	
—	—	—	
—	—	—	
—	—	—	
—	—	—	
—	—	—	

Object		-15V0.1A	
1. Graph		-----□----- Load 50% -----△----- Load 100%	
[V]			
Output Voltage			
Input Voltage [V]			
2. Values			
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	
8.0	-15.077	-14.959	
9.0	-15.074	-14.965	
10.0	-15.072	-14.970	
12.0	-15.069	-14.974	
15.0	-15.064	-14.973	
18.0	-15.057	-14.967	
20.0	-15.054	-14.962	
—	—	—	
—	—	—	
—	—	—	
—	—	—	
—	—	—	

Note: Slanted line shows the range of the rated input voltage.
(注)斜線は定格入力電圧範囲を示す。

COSEL


Model ZUW31215

Item Efficiency 効率

Object

Temperature 25°C
Testing Circuitry Figure A



1. Graph



2. Values

Input Voltage [V]	Load 50%	Load 100%
	Efficiency [%]	Efficiency [%]
8.0	71.4	75.6
9.0	70.3	76.1
10.0	69.7	76.0
12.0	67.3	75.8
15.0	64.7	73.5
18.0	61.3	72.1
20.0	58.8	70.2
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—


COSEL

Model		ZUW31215																																																					
Item	Load Regulation	静的負荷変動																																																					
Object	+15V0.1A																																																						
1. Graph		2. Values																																																					
<div><div><div>—△—</div><div>---□---</div><div>---○---</div></div><div>Input Volt. 9.0V</div><div>Input Volt. 12.0V</div><div>Input Volt. 18.0V</div></div> 		<table><tr><th>Load Current</th><th>Input Volt.</th><th>Input Volt.</th><th>Input Volt.</th></tr><tr><th></th><th>9.0[V]</th><th>12.0[V]</th><th>18.0[V]</th></tr><tr><th>[A]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr><tr><td>0.000</td><td>15.241</td><td>15.239</td><td>15.236</td></tr><tr><td>0.020</td><td>15.151</td><td>15.146</td><td>15.136</td></tr><tr><td>0.040</td><td>15.100</td><td>15.096</td><td>15.085</td></tr><tr><td>0.060</td><td>15.056</td><td>15.056</td><td>15.045</td></tr><tr><td>0.080</td><td>15.015</td><td>15.018</td><td>15.010</td></tr><tr><td>0.100</td><td>14.972</td><td>14.982</td><td>14.976</td></tr><tr><td>0.110</td><td>14.950</td><td>14.963</td><td>14.959</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>		Load Current	Input Volt.	Input Volt.	Input Volt.		9.0[V]	12.0[V]	18.0[V]	[A]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	0.000	15.241	15.239	15.236	0.020	15.151	15.146	15.136	0.040	15.100	15.096	15.085	0.060	15.056	15.056	15.045	0.080	15.015	15.018	15.010	0.100	14.972	14.982	14.976	0.110	14.950	14.963	14.959	—	—	—	—	—	—	—	—	—	—	—	—
Load Current	Input Volt.	Input Volt.	Input Volt.																																																				
	9.0[V]	12.0[V]	18.0[V]																																																				
[A]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
0.000	15.241	15.239	15.236																																																				
0.020	15.151	15.146	15.136																																																				
0.040	15.100	15.096	15.085																																																				
0.060	15.056	15.056	15.045																																																				
0.080	15.015	15.018	15.010																																																				
0.100	14.972	14.982	14.976																																																				
0.110	14.950	14.963	14.959																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
Object		-15V0.1A																																																					
1. Graph		2. Values																																																					
<div><div><div>—△—</div><div>---□---</div><div>---○---</div></div><div>Input Volt. 9.0V</div><div>Input Volt. 12.0V</div><div>Input Volt. 18.0V</div></div> 		<table><tr><th>Load Current</th><th>Input Volt.</th><th>Input Volt.</th><th>Input Volt.</th></tr><tr><th></th><th>9.0[V]</th><th>12.0[V]</th><th>18.0[V]</th></tr><tr><th>[A]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr><tr><td>0.000</td><td>-15.240</td><td>-15.240</td><td>-15.240</td></tr><tr><td>0.020</td><td>-15.136</td><td>-15.132</td><td>-15.123</td></tr><tr><td>0.040</td><td>-15.083</td><td>-15.079</td><td>-15.070</td></tr><tr><td>0.060</td><td>-15.039</td><td>-15.038</td><td>-15.029</td></tr><tr><td>0.080</td><td>-14.995</td><td>-14.999</td><td>-14.992</td></tr><tr><td>0.100</td><td>-14.952</td><td>-14.962</td><td>-14.957</td></tr><tr><td>0.110</td><td>-14.928</td><td>-14.943</td><td>-14.940</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>		Load Current	Input Volt.	Input Volt.	Input Volt.		9.0[V]	12.0[V]	18.0[V]	[A]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	0.000	-15.240	-15.240	-15.240	0.020	-15.136	-15.132	-15.123	0.040	-15.083	-15.079	-15.070	0.060	-15.039	-15.038	-15.029	0.080	-14.995	-14.999	-14.992	0.100	-14.952	-14.962	-14.957	0.110	-14.928	-14.943	-14.940	—	—	—	—	—	—	—	—	—	—	—	—
Load Current	Input Volt.	Input Volt.	Input Volt.																																																				
	9.0[V]	12.0[V]	18.0[V]																																																				
[A]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
0.000	-15.240	-15.240	-15.240																																																				
0.020	-15.136	-15.132	-15.123																																																				
0.040	-15.083	-15.079	-15.070																																																				
0.060	-15.039	-15.038	-15.029																																																				
0.080	-14.995	-14.999	-14.992																																																				
0.100	-14.952	-14.962	-14.957																																																				
0.110	-14.928	-14.943	-14.940																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
Note: Slanted line shows the range of the rated load current.																																																							
(注)斜線は定格負荷電流範囲を示す。																																																							

-3-

BC-2038

COSEL



COSEL

Model	ZUW31215	Temperature	25°C
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷電流特性)	Testing Circuitry	Figure A
Object	-15V 0.1A		

1. Graph

[mV]

-----□----- Input Volt. 9.0V

-----△----- Input Volt. 18.0V

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p-p 値で示される。
(注) 斜線は定格負荷電流範囲を示す。

2. Values


Load Current [A]	Input Volt. 9.0 [V]	Input Volt. 18.0 [V]
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
0.00	5	5
0.02	5	5
0.04	5	5
0.06	5	5
0.08	10	5
0.10	15	5
0.11	20	10
—	—	—
—	—	—
—	—	—
—	—	—

T1: Due to AC Input Line
入力商用周期


T2: Due to Switching
スイッチング周期

Fig. Complex Ripple Wave Form
図 リップル波形詳細図



COSEL



COSEL



COSEL

Model ZUW31215		Temperature 25°C																																																					
Item Overcurrent Protection 過電流保護		Testing Circuitry Figure A																																																					
Object +15V0.1A																																																							
1. Graph [V] 		2. Values <table border="1"> <thead> <tr> <th>Output Voltage [V]</th><th>Input Volt. 9.0[V] Load Curr-ent [A]</th><th>Input Volt. 12.0[V] Load Curr-ent [A]</th><th>Input Volt. 18.0[V] Load Curr-ent [A]</th></tr> </thead> <tbody> <tr><td>15.00</td><td>0.067</td><td>0.067</td><td>0.061</td></tr> <tr><td>14.25</td><td>0.196</td><td>0.226</td><td>0.189</td></tr> <tr><td>13.50</td><td>0.201</td><td>0.232</td><td>0.190</td></tr> <tr><td>12.00</td><td>0.215</td><td>0.241</td><td>0.195</td></tr> <tr><td>10.50</td><td>0.226</td><td>0.248</td><td>0.196</td></tr> <tr><td>9.00</td><td>0.236</td><td>0.253</td><td>0.194</td></tr> <tr><td>7.50</td><td>0.242</td><td>0.254</td><td>0.189</td></tr> <tr><td>6.00</td><td>0.241</td><td>0.245</td><td>0.180</td></tr> <tr><td>4.50</td><td>0.238</td><td>0.233</td><td>0.167</td></tr> <tr><td>3.00</td><td>0.225</td><td>0.210</td><td>0.153</td></tr> <tr><td>1.50</td><td>0.206</td><td>0.182</td><td>0.142</td></tr> <tr><td>0.00</td><td>0.227</td><td>0.207</td><td>0.184</td></tr> </tbody> </table>		Output Voltage [V]	Input Volt. 9.0[V] Load Curr-ent [A]	Input Volt. 12.0[V] Load Curr-ent [A]	Input Volt. 18.0[V] Load Curr-ent [A]	15.00	0.067	0.067	0.061	14.25	0.196	0.226	0.189	13.50	0.201	0.232	0.190	12.00	0.215	0.241	0.195	10.50	0.226	0.248	0.196	9.00	0.236	0.253	0.194	7.50	0.242	0.254	0.189	6.00	0.241	0.245	0.180	4.50	0.238	0.233	0.167	3.00	0.225	0.210	0.153	1.50	0.206	0.182	0.142	0.00	0.227	0.207	0.184
Output Voltage [V]	Input Volt. 9.0[V] Load Curr-ent [A]	Input Volt. 12.0[V] Load Curr-ent [A]	Input Volt. 18.0[V] Load Curr-ent [A]																																																				
15.00	0.067	0.067	0.061																																																				
14.25	0.196	0.226	0.189																																																				
13.50	0.201	0.232	0.190																																																				
12.00	0.215	0.241	0.195																																																				
10.50	0.226	0.248	0.196																																																				
9.00	0.236	0.253	0.194																																																				
7.50	0.242	0.254	0.189																																																				
6.00	0.241	0.245	0.180																																																				
4.50	0.238	0.233	0.167																																																				
3.00	0.225	0.210	0.153																																																				
1.50	0.206	0.182	0.142																																																				
0.00	0.227	0.207	0.184																																																				
Object -15V0.1A																																																							
1. Graph [V] 		2. Values <table border="1"> <thead> <tr> <th>Output Voltage [V]</th><th>Input Volt. 9.0[V] Load Curr-ent [A]</th><th>Input Volt. 12.0[V] Load Curr-ent [A]</th><th>Input Volt. 18.0[V] Load Curr-ent [A]</th></tr> </thead> <tbody> <tr><td>-15.00</td><td>0.078</td><td>0.080</td><td>0.075</td></tr> <tr><td>-14.25</td><td>0.200</td><td>0.231</td><td>0.194</td></tr> <tr><td>-13.50</td><td>0.207</td><td>0.236</td><td>0.196</td></tr> <tr><td>-12.00</td><td>0.220</td><td>0.246</td><td>0.200</td></tr> <tr><td>-10.50</td><td>0.232</td><td>0.254</td><td>0.201</td></tr> <tr><td>-9.00</td><td>0.242</td><td>0.259</td><td>0.199</td></tr> <tr><td>-7.50</td><td>0.247</td><td>0.258</td><td>0.194</td></tr> <tr><td>-6.00</td><td>0.248</td><td>0.252</td><td>0.185</td></tr> <tr><td>-4.50</td><td>0.244</td><td>0.239</td><td>0.174</td></tr> <tr><td>-3.00</td><td>0.231</td><td>0.215</td><td>0.159</td></tr> <tr><td>-1.50</td><td>0.213</td><td>0.188</td><td>0.148</td></tr> <tr><td>0.00</td><td>0.224</td><td>0.202</td><td>0.180</td></tr> </tbody> </table>		Output Voltage [V]	Input Volt. 9.0[V] Load Curr-ent [A]	Input Volt. 12.0[V] Load Curr-ent [A]	Input Volt. 18.0[V] Load Curr-ent [A]	-15.00	0.078	0.080	0.075	-14.25	0.200	0.231	0.194	-13.50	0.207	0.236	0.196	-12.00	0.220	0.246	0.200	-10.50	0.232	0.254	0.201	-9.00	0.242	0.259	0.199	-7.50	0.247	0.258	0.194	-6.00	0.248	0.252	0.185	-4.50	0.244	0.239	0.174	-3.00	0.231	0.215	0.159	-1.50	0.213	0.188	0.148	0.00	0.224	0.202	0.180
Output Voltage [V]	Input Volt. 9.0[V] Load Curr-ent [A]	Input Volt. 12.0[V] Load Curr-ent [A]	Input Volt. 18.0[V] Load Curr-ent [A]																																																				
-15.00	0.078	0.080	0.075																																																				
-14.25	0.200	0.231	0.194																																																				
-13.50	0.207	0.236	0.196																																																				
-12.00	0.220	0.246	0.200																																																				
-10.50	0.232	0.254	0.201																																																				
-9.00	0.242	0.259	0.199																																																				
-7.50	0.247	0.258	0.194																																																				
-6.00	0.248	0.252	0.185																																																				
-4.50	0.244	0.239	0.174																																																				
-3.00	0.231	0.215	0.159																																																				
-1.50	0.213	0.188	0.148																																																				
0.00	0.224	0.202	0.180																																																				
Note: Slanted line shows the range of the rated load current. (注)斜線は定格負荷電流範囲を示す。																																																							

COSEL

Model	ZUW31215		
Item	Dynamic Load Responce 動的負荷変動	Temperature	25℃
Object	+15V0.1A	Testing Circuitry	Figure A

Input Volt. 12.0 V


Cycle 100 mS

Load Current

Min. Load ←→

Load 100 %


200 mV/div



Min. Load ←→

Load 50 %


200 mV/div



Load 50%←→

Load 100 %

200 mV/div



1 mS/div

COSEL

Model	ZUW31215	Temperature	25°C
Item	Dynamic Load Responce 動的負荷変動	Testing Circuitry	Figure A
Object	-15V0.1A		

Input Volt. 12.0 V



Cycle 100 mS

Load Current

Min. Load ↔

Load 100 %



200 mV/div



Min. Load ↔

Load 50 %



200 mV/div



Load 50%↔

Load 100 %

200 mV/div




1 mS/div

COSEL

Model	ZUW31215		
Item	Rise and Fall Time 立上り、立下り時間	Temperature	25°C
Object	+15V0.1A	Testing Circuitry	Figure A

1. Graph


Input Volt. 9.0 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.55	2.10	2.65	0.22	3.23
100 %	0.55	2.30	2.85	0.13	1.46




COSEL

Model	ZUW31215	Temperature	25℃
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	-15V0.1A		

1. Graph


Input Volt. 9.0 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.55	2.15	2.70	0.22	2.91
100 %	0.55	2.35	2.90	0.13	1.14



COSEL

Model		ZUW31215																																																					
Item		Ambient Temperature Drift 周囲温度変動																																																					
Object		+15V0.1A																																																					
1. Graph		2. Values																																																					
<div><div>—△— Input Volt. 9.0V</div><div>- -□- - Input Volt. 12.0V</div><div>- -○- - Input Volt. 18.0V</div></div> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<table><tr><th>Temperature</th><th>Input Volt. 9.0[V]</th><th>Input Volt. 12.0[V]</th><th>Input Volt. 18.0[V]</th></tr><tr><th>[°C]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr><tr><td>-30</td><td>14.972</td><td>14.978</td><td>14.973</td></tr><tr><td>-20</td><td>14.975</td><td>14.981</td><td>14.976</td></tr><tr><td>-10</td><td>14.977</td><td>14.983</td><td>14.977</td></tr><tr><td>0</td><td>14.978</td><td>14.985</td><td>14.978</td></tr><tr><td>10</td><td>14.979</td><td>14.986</td><td>14.979</td></tr><tr><td>25</td><td>14.978</td><td>14.986</td><td>14.979</td></tr><tr><td>30</td><td>14.978</td><td>14.987</td><td>14.980</td></tr><tr><td>40</td><td>14.977</td><td>14.987</td><td>14.979</td></tr><tr><td>55</td><td>14.973</td><td>14.984</td><td>14.975</td></tr><tr><td>60</td><td>14.970</td><td>14.982</td><td>14.974</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>		Temperature	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]	[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	-30	14.972	14.978	14.973	-20	14.975	14.981	14.976	-10	14.977	14.983	14.977	0	14.978	14.985	14.978	10	14.979	14.986	14.979	25	14.978	14.986	14.979	30	14.978	14.987	14.980	40	14.977	14.987	14.979	55	14.973	14.984	14.975	60	14.970	14.982	14.974	—	—	—	—
Temperature	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]																																																				
[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
-30	14.972	14.978	14.973																																																				
-20	14.975	14.981	14.976																																																				
-10	14.977	14.983	14.977																																																				
0	14.978	14.985	14.978																																																				
10	14.979	14.986	14.979																																																				
25	14.978	14.986	14.979																																																				
30	14.978	14.987	14.980																																																				
40	14.977	14.987	14.979																																																				
55	14.973	14.984	14.975																																																				
60	14.970	14.982	14.974																																																				
—	—	—	—																																																				
Object		-15V0.1A																																																					
1. Graph		2. Values																																																					
<div><div>—△— Input Volt. 9.0V</div><div>- -□- - Input Volt. 12.0V</div><div>- -○- - Input Volt. 18.0V</div></div> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<table><tr><th>Temperature</th><th>Input Volt. 9.0[V]</th><th>Input Volt. 12.0[V]</th><th>Input Volt. 18.0[V]</th></tr><tr><th>[°C]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr><tr><td>-30</td><td>-14.960</td><td>-14.966</td><td>-14.960</td></tr><tr><td>-20</td><td>-14.962</td><td>-14.968</td><td>-14.962</td></tr><tr><td>-10</td><td>-14.964</td><td>-14.970</td><td>-14.964</td></tr><tr><td>0</td><td>-14.965</td><td>-14.972</td><td>-14.965</td></tr><tr><td>10</td><td>-14.965</td><td>-14.973</td><td>-14.966</td></tr><tr><td>25</td><td>-14.965</td><td>-14.973</td><td>-14.966</td></tr><tr><td>30</td><td>-14.965</td><td>-14.974</td><td>-14.967</td></tr><tr><td>40</td><td>-14.964</td><td>-14.974</td><td>-14.967</td></tr><tr><td>55</td><td>-14.960</td><td>-14.971</td><td>-14.963</td></tr><tr><td>60</td><td>-14.958</td><td>-14.970</td><td>-14.962</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>		Temperature	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]	[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	-30	-14.960	-14.966	-14.960	-20	-14.962	-14.968	-14.962	-10	-14.964	-14.970	-14.964	0	-14.965	-14.972	-14.965	10	-14.965	-14.973	-14.966	25	-14.965	-14.973	-14.966	30	-14.965	-14.974	-14.967	40	-14.964	-14.974	-14.967	55	-14.960	-14.971	-14.963	60	-14.958	-14.970	-14.962	—	—	—	—
Temperature	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]																																																				
[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
-30	-14.960	-14.966	-14.960																																																				
-20	-14.962	-14.968	-14.962																																																				
-10	-14.964	-14.970	-14.964																																																				
0	-14.965	-14.972	-14.965																																																				
10	-14.965	-14.973	-14.966																																																				
25	-14.965	-14.973	-14.966																																																				
30	-14.965	-14.974	-14.967																																																				
40	-14.964	-14.974	-14.967																																																				
55	-14.960	-14.971	-14.963																																																				
60	-14.958	-14.970	-14.962																																																				
—	—	—	—																																																				
Note: Slanted line shows the range of the rated ambient temperature.																																																							
(注)斜線は定格周囲温度範囲を示す。																																																							

COSEL


Model ZUW31215

Item Minimum Input Voltage for Regulated Output Voltage
最低レギュレーション電圧

Object +15V0.1A

1. Graph

-----□----- Load 50%
 -----△----- Load 100%




Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-30	6.1	6.9
-20	5.9	6.8
-10	5.8	6.6
0	5.7	6.5
10	5.6	6.3
25	5.5	6.2
30	5.5	6.1
40	5.4	6.0
55	5.2	5.9
60	5.2	5.9
—	—	—

Object -15V0.1A

-----□----- Load 50%
 -----△----- Load 100%




2. Values


Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-30	6.1	6.9
-20	5.9	6.8
-10	5.8	6.6
0	5.7	6.5
10	5.6	6.3
25	5.5	6.2
30	5.5	6.1
40	5.4	6.0
55	5.2	5.9
60	5.2	5.9
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。



COSEL

Model		ZUW31215
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	
Object	+15V0.1A	
1. Graph		
	-----□-----	Load 50%
	-----△-----	Load 100%
[mV]		
Input Volt. 9.0 V		
2. Values		
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]
-30	10	40
-20	10	35
-10	10	30
0	10	30
10	5	20
25	5	20
30	5	15
40	5	15
55	5	15
60	5	15
—	—	—

Object		-15V0.1A
1. Graph		
	-----□-----	Load 50%
	-----△-----	Load 100%
[mV]		
Input Volt. 9.0 V		
2. Values		
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]
-30	10	45
-20	10	40
-10	5	30
0	5	25
10	5	20
25	5	15
30	5	15
40	5	20
55	5	20
60	5	25
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.
(注)斜線は定格周囲温度範囲を示す。

COSEL

COSEL																									
Model	ZUW31215	Temperature 25 ℃ Testing Circuitry Figure A																							
Item	Time Lapse Drift 経時ドリフト																								
Object	+15V0.1A																								
1. Graph		2.Values																							
<div><p>[V]</p><p>Time [H]</p><p>Input Volt. 12.0V Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>15.003</td></tr><tr><td>0.5</td><td>15.001</td></tr><tr><td>1.0</td><td>15.001</td></tr><tr><td>2.0</td><td>15.001</td></tr><tr><td>3.0</td><td>15.001</td></tr><tr><td>4.0</td><td>15.001</td></tr><tr><td>5.0</td><td>15.002</td></tr><tr><td>6.0</td><td>15.001</td></tr><tr><td>7.0</td><td>15.002</td></tr><tr><td>8.0</td><td>15.002</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	15.003	0.5	15.001	1.0	15.001	2.0	15.001	3.0	15.001	4.0	15.001	5.0	15.002	6.0	15.001	7.0	15.002	8.0	15.002
Time since start [H]	Output Voltage [V]																								
0.0	15.003																								
0.5	15.001																								
1.0	15.001																								
2.0	15.001																								
3.0	15.001																								
4.0	15.001																								
5.0	15.002																								
6.0	15.001																								
7.0	15.002																								
8.0	15.002																								
Object -15V0.1A																									
1. Graph		2.Values																							
<div><p>[V]</p><p>Time [H]</p><p>Input Volt. 12.0V Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>-14.972</td></tr><tr><td>0.5</td><td>-14.970</td></tr><tr><td>1.0</td><td>-14.970</td></tr><tr><td>2.0</td><td>-14.970</td></tr><tr><td>3.0</td><td>-14.970</td></tr><tr><td>4.0</td><td>-14.970</td></tr><tr><td>5.0</td><td>-14.970</td></tr><tr><td>6.0</td><td>-14.970</td></tr><tr><td>7.0</td><td>-14.970</td></tr><tr><td>8.0</td><td>-14.970</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	-14.972	0.5	-14.970	1.0	-14.970	2.0	-14.970	3.0	-14.970	4.0	-14.970	5.0	-14.970	6.0	-14.970	7.0	-14.970	8.0	-14.970
Time since start [H]	Output Voltage [V]																								
0.0	-14.972																								
0.5	-14.970																								
1.0	-14.970																								
2.0	-14.970																								
3.0	-14.970																								
4.0	-14.970																								
5.0	-14.970																								
6.0	-14.970																								
7.0	-14.970																								
8.0	-14.970																								

-16-

BC-2038

COSEL

LOREL

Model	ZUW31215		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+15V0.1A		

1. Condensation test

Testing procedure is as follows.

① Keeping and cooling the unit in a tank at -10℃ for an hour with the input off.

② Taking it out of the tank and dewing itself in a room where the temperature is 25℃ and the humidity is 40%RH.

③ Testing electrical characteristics of the unit to confirm there be no fault.

④ Repeating ①,② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で－10℃に冷却しておき、約1時間後に恒温槽から取り出し、室温25℃、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values				
	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	14.912	5	10
	2	14.905	5	10
	3	14.902	5	10
Load 100 %	1	14.819	10	20
	2	14.811	10	20
	3	14.811	10	20

Input Volt. 12.0 V

COSEL

COSEL

		Testing Circuitry Figure A	
Model	ZUW31215		
Item	Condensation 結露特性		
Object	−15V0.1A		

1. Condensation test

Testing procedure is as follows.

① Keeping and cooling the unit in a tank at −10℃ for an hour with the input off.

② Taking it out of the tank and dewing itself in a room where the temperature is 25℃ and the humidity is 40%RH.

③ Testing electrical characteristics of the unit to confirm there be no fault.

④ Repeating ①,② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で−10℃に冷却しておき、約1時間後に恒温槽から取り出し、室温25℃、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

		2. Values		
	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	−14.884	5	25
	2	−14.890	5	25
	3	−14.888	5	25
Load 100 %	1	−14.784	15	25
	2	−14.794	15	25
	3	−14.799	15	25

Input Volt. 12.0 V

COSEL




Figure A